INCH-POUND


MIL-PRF-55339/18A
17 September 2004
SUPERSEDING
MIL-PRF-55339/18
6 May 1975

PERFORMANCE SPECIFICATION SHEET

ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE,
(BETWEEN SERIES BNC PLUG TO SERIES N PLUG), CLASS 2

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the document described herein shall
consist of this specification sheet and MIL-PRF-55339.



Reference	Series	Contact
A	BNC	Pin
B	N	Pin

Inches	mm
.827	21.01
1.562	39.67

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. All undimensioned pictorial representations are for reference purposes only.
4. Interface dimensions are in accordance with MIL-STD-348, series BNC pin contact and series N pin contact.

FIGURE 1. General configuration.

AMSC N/A FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:05Z
Check the source to verify that this is the current version before use.

DESIGN AND CONSTRUCTION

General configuration: See figure 1.

Impedance: 50 ohms, nom.

Working voltage: Sea level – 500 V rms.
70,000 feet (4.437 kPa) – 125 V rms.

Frequency range: 0 to 4 GHz.

Temperature range: -65° to +165°C.

PERFORMANCE (installation torque of 6 to 10 lb (0.68 to 1.13 Nm), series N)

Dimensions: See figure 1 and MIL-STD-348.

Center contact retention:	Series BNC	Series N
Axial force (lb. min)	6 (26.7 N)	6 (26.7 N)
Torque (in. oz, min)	N/A	N/A

Force to engage and disengage:	Series BNC	Series N
Longitudinal force (lb. max)	3.0 (13.3 N)	0
Torque (in. lb, max)	2.5 (0.34 Nm)	6.0 (0.68 Nm)

Coupling proof torque: 15 in.lb (1.69 Nm), min, series N.

Mating characteristics:
Center contact (socket): Not applicable

Outer contact:	Series BNC	Series N
Min test ring ID (in., max)	.319 (8.10 mm)	.316 (8.03 mm)
Ring finish (microinches)	16 (0.407 μm)	16 (0.407 μm)
Insertion force (lb, max)	5 (22.2 N)	5 (22.2 N)
Insertion depth (in, min)	.093 (2.36 mm)	.093 (2.36 mm)
Number of insertions	1	1
Max test ring ID (in., min)	.324 (8.23 mm)	.324 (8.23 mm)
Test ring finish (microinches)	16 (0.407 μm)	16 (0.407 μm)
Insertion depth (in., max)	.031 (0.79 mm)	.031 (0.79 mm)
Number of insertions	1	1

Permeability: <2.0.

Seal: Hermetic – Not applicable.
Pressurized – Not applicable.
Weatherproof – Not applicable.

Insulation resistance: 5,000 megohms, min.

VSWR: 1.35:1, max .5 to 4 GHz.

RF leakage (total): -55 dB, min, 2 to 3 GHz.

RF insertion loss: .1 dB, max, 3 GHz (.06 $\sqrt{F\ (GHz)}$ dB max tested at 3 GHz).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:05Z
Check the source to verify that this is the current version before use.

Durability: 500 cycles minimum at 12 cycles/min maximum. The connector shall meet the mating characteristics and force to engage and disengage requirements.

Dielectric withstanding: Test voltage – 1,500 V rms, min (sea level).

Contact resistance (milliohms, max).

Contact	Initial	After
Center	2.0	2.5
Outer	0.5	N/A
Outer (-70001)	1.0	N/A

Vibration, high frequency: Interruptions – 1 μs, max.

Shock: Test condition I.

Thermal shock: Test condition C.

Moisture resistance: 200 megohms, min.

Corona level: Voltage – 375 V, min.
Altitude - 70,000 feet (4.437 kPa), min.

RF high potential withstanding voltage: RF voltage – 1,000 V rms, min.
Frequency – 5 MHz, min.

Salt spray (corrosion): Applicable.

Coupling mechanism retention force: 100 lb (444.8 N), min.

Part or Identifying Number (PIN): M55339/18-01034.

PIN: M55339/18-70001. **CAUTION: THIS PART HAS A NICKEL PLATED BODY AND IS NOT FOR USE IN APPLICATIONS WHERE PASSIVE INTERMODULATION GENERATION (PIM) MAY BE A CONCERN.**

Cross reference: See table I.

TABLE I. Cross reference of PIN.

PIN	Superseded PIN or type designation 1/
M55339/18-01034	UG-1034/U

1/ The superseded PIN or the type designation is for cross reference only. Where a superseded PIN or type designation is not given, none was assigned or will be assigned. The PIN M55339/18-01034 shall be used in all cases for marking and identifying the adapter.

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:05Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-PRF-55339, this document references the following:

MIL-STD-348

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-4657-017)

Review activities:
Army – AR, AT, MI
Navy – AS, MC
Air Force – 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:05Z
Check the source to verify that this is the current version before use.