MILITARY SPECIFICATION

PROJECTILE, 20MM, HEIT-SD, M246; METAL PARTS

This amendment forms a part of Military Specification MIL-P-60679A(MU), 10 December 1969.

Para 2.1, under STANDARDS, delete "FEDERAL - Federal Test Method Standard No. 151 - Metals; Test Methods."

After para 2.1, add the following:

"2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM)
ASTM B117-64 -- Method of Test for Salt Spray (Fog) Testing

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103)

(Technical Society and Technical Association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using federal agencies.)"

Para 4.3.1.a, add the following:

"(5) 3 Test panels (see TT-C-490)"

Para 4.4.3.3, under Major defects, make the following changes:

"115" Delete in its entirety and substitute:

"115. Void at junction of rotating band and body ---------- Visual"

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:55Z
Check the source to verify that this is the current version before use.

Para 4.4.3.3, under Major defects, make the following changes:

"117" Delete in its entirety.

"125" Delete the word "Thickness" and substitute the word "Width"

Add the following defects:

"130. Concentricity, boss (tracer cavity) with datum surface ---- Gage"
"131. Length, boss (tracer cavity) to precision ball (igniter cavity) ---------- Gage"
"132. Igniter cavity angle (small angle) ---------- Gage"

Para 4.5.7, delete entire paragraph and substitute the following:

"4.5.7 Corrosion resistance.-The method of test shall be as prescribed in American Society for Testing and Materials (ASTM) ASTM B117. The paint shall not be disturbed, however, the rotating band and unpainted surfaces of the sample projectiles may be masked out by a wax coating or other suitable material. The salt spray solution and exposure time shall be as specified in 3.6.3."

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1305-A727

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:55Z
Check the source to verify that this is the current version before use.