MIL-V-51281C(EA)
AMENDMENT 1
6 April 1987

MILITARY SPECIFICATION

VOICEMITTER-OUTLET VALVE ASSEMBLY, CHEMICAL-BIOLOGICAL MASK, C29R5

This amendment forms a part of MIL-V-51281C(EA), dated 15 August 1983, and is approved for use within the Chemical Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

3.6.2: Change paragraph to "DOP smoke penetration of the voicemitter-outlet valve assembly, with the opening in the valve seat and the drink tube mouthpiece sealed, shall not exceed 0.001 percent when tested as specified in 4.4.4.9."

PAGE 7

4.4.1: Add new sentence after second sentence: "A lot of diaphragm material is the quantity represented by actual physical test data, and presented at one time to the Government for agent testing."

PAGE 12

4.4.4.9: Change from ". . . to its neutral or rest position. Mount the voicemitter . . ." to ". . .to its neutral or rest position. Seal the drink tube mouthpiece with a plug which is dimensionally the same as 5-81-101, plunger. Mount the voicemitter in the Q127 Penetrometer (D136-42-102-7) and test for smoke penetration. The plug shall be removed after the test."

Custodian:

Army - EA

Preparing activity:

Army - EA

(Project No. 4240-A883)

AMSC N/A

FSC 4240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:55Z
Check the source to verify that this is the current version before use.