INTERROGATOR SETS, COMPONENTS FOR

1. Paragraph 1.1 Scope - Add the following to the list of components "and Receiver-Transmitter, Radio RT-264( )/UPX-6."

2. Paragraph 2.1 - Delete the following:

   a. Under Specification, FEDERAL

   NN-B-591, NN-B-601, UU-T-111, NN-B-631, LLL-B-631, JAN-P-105, JAN-P-106, MIL-B-107, JAN-P-108, MIL-P-116, JAN-P-117, JAN-P-127, MIL-B-131.

   b. Delete the heading "U. S. ARMY" and "19-10.".

   c. Under STANDARDS, MILITARY add "MIL-STD-170", and "MIL-STD-169".

   d. Under DRAWINGS, SIGNAL CORPS delete the following:

   "460-11;" "460-12"; "460-13"; "460-14"; "SC-D-15914"; "SC-D-19999".

3. Paragraph 3.5.2a - Delete in its entirety and substitute the following:

"3.5.2a Temperature. - Exposure in the range of + 160°F to -80°F; however, exposure at the high temperature extreme not to exceed 72 hours and at the low temperature extreme not to exceed 24 hours at any one time."

4. Paragraph 3.5.3.1 Vibration. Add at the end of the sentence the following:

"If any peaks are found within that range, 10-55 cps, the equipment shall be vibrated for 15 minutes at each of these peak frequencies. At the completion of the test the equipment shall show no signs of damage and shall meet full specification requirements."

5. Paragraph 3.5.3.2, table II, delete "Shock test; drop."

6. Paragraph 3.9, add "and Receiver-Transmitter, "Radio RT-264( )/UPX-6," to the paragraph title.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:12Z
Check the source to verify that this is the current version before use.

7. Paragraph 3.9.5.2.6. Delete in its entirety and substitute the following:

"3.9.5.2.6 Duty cycle capability. - The power supply shall be capable of supplying power to the transmitter sufficient to permit pulse trains of one microseconds wide, pulses spaced 3 microseconds between leading edges at the rate of 100 trains per second and 16 pulses per train.

8. Paragraph 3.9.5.2.10, line one, replace "lower" with "power."

9. Paragraph 3.9.5.3.4, after "52 ohms add ± 2%."

10. Paragraph 3.9.5.3.8 Power Consumption - Delete in its entirety.

11. Paragraph 3.9.5.3.8.1 Power Supply. Delete the columns headed "Frequency in cycles per second" and substitute the following:

RT-211( )/TPX	RT-264( )/UPX-6
115 volts ± 10% 400 Cycles ± 10%	115 Volts ± 10 % 60 Cycles ± 10%

12. Paragraph 3.10.2.2.1 Triggering - Replace subparagraphs, (b), (c) and (d) with the following:

b. Pulse width: Minimum 0.3 microseconds at half amplitude.

c. Amplitude: Minimum requirements 5 to 50 volts measured across the 75 ohm terminating resistor at the input of the coder.

d. Pulse repetition frequency: Up to 4100 pps minimum requirements.

13. Add the following subparagraph:

"3.10.2.2.3.1 The louvered panel shall contain three access holes for the trigger delay, count down, and chop rate controls. The holes shall be large enough to permit insertion of a socket wrench, and shall include pressure type button plugs.

14. Paragraph 3.13 Seal test, provision for, delete in its entirety.

15. Delete paragraph 4.1.2 in its entirety and substitute the following:

"4.1.2 Group B inspection. Group B inspection (including sampling) shall conform to table IV and the Appendix to Standard MIL-STD-105. Unless otherwise specified herein, normal inspection shall be used at the start of the contract. The reduced inspection procedure shall be R-1. Disposition of rejected product (sample units and inspection lots) shall be in accordance with Standard MIL-STD-105 and 4.1.5."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:12Z
Check the source to verify that this is the current version before use.

16. Delete paragraph 4.1 2.2, Sampling procedure in its entirety and substitute the following:

"4.1.2.2 Group B sampling plans. The group B sampling plans, as listed in table IV, shall be in accordance with table III."

Table III

Group B plans	AQL	Inspection level for normal inspection	Inspection level for reduced inspection
B-1	4.0%	L-8	L-6
B-2	6.5%	L-7	L-5
B-3	10.0%	L-6	L-4
B-4	15.0%	L-5	L-3

17. Paragraph 4.1.2.3 - Delete table III.

Delete paragraphs 4.5, 4.5.1, 4.5.2 and 4.7.2.

18. In paragraph 4.8 delete "Drawing SC-D-19999" and substitute "Standard MIL-STD-169."

19. In paragraph 4.9.2 (d) delete "Drawing SC-D-15914" and substitute "Standard MIL-STD-170."

20. Paragraph 4.14.5. In the third line replace "thei" with "this."

21. Section 5 delete in its entirety and substitute the following:

"5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. -

5.1.1 Components of Interrogator Set AN/TPX-20( ) shall be preserved and packaged in accordance with Specification MIL-P-116, and the provisions below for the level specified in the bid request or contract.

5.1.1.1 Level A. - The components of Interrogator Set AN/TPX-20( ) shall be packaged in a manner that will afford protection against corrosion, deterioration and physical damage during shipment, handling, indeterminate storage, and world-wide distribution.

5.1.2 Level C. - The components of Interrogator Set AN/TPX-20( ) shall be packaged in accordance with commercial practice and in a manner that will afford protection against corrosion, deterioration and physical damage during direct shipment to the first receiving activity.

5.2 Packing. -

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:12Z
Check the source to verify that this is the current version before use.

5.2.1 Level A.- Components of Interrogator Set AN/TPX-20( ) shall be packed for shipment within overseas-class nailed wood boxes conforming to Specification PPP-B-621. Fabricate the boxes to fit the contents snugly. Box closure shall be in conformance with the referenced box specification.

5.2.1.1 Metal Strapping.- Shipping containers shall be strapped in conformance with the requirements of the appendix of the container specification, only for direct shipment to ports.

5.2.2 Level B.- Components of Interrogator Set AN/TPX-20( ) shall be packed for shipment as specified in 5.2.1 except the boxes shall be domestic class.

5.2.3 Level C.- The components of Interrogator Set AN/TPX-20( ) shall be packed for shipment in a manner conforming to the requirements of Uniform Freight Classification for rail shipment, National Motor Freight Classification for truck shipment, Parcel Post Regulations, and the regulations of other carriers as applicable to the mode of transportation employed at lowest transportation rates.

5.3 Marking.- Interior packages and exterior shipping containers shall be marked in accordance with the applicable provisions of Standard MIL-STD-129.

5.4 Pilot pack.- Upon determination of processes of cleaning and preservation of the method of packaging to be used in the unit protection of the components, pilot packs shall be prepared by the contractor and, prior to quantity production, tested in accordance with the applicable provisions of Specification MIL-P-116; except, that final approval and acceptance shall be made by a packaging representative of the procuring activity."

22. Add the following paragraph to Section 6:

"Certain provisions of this specification are the subject of international standardization agreement (ABC). When amendment, revision, or cancellation of this specification is proposed, the departmental custodians will inform their respective Departmental Standardization Offices so that appropriate action may be taken respecting the international agreement concerned."

23. Delete the NOTICE on page 40 of the basic specification.

24. Add the following at the bottom, left, of the last page of the specification:

"International Interest (See Section 6)."

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:12Z
Check the source to verify that this is the current version before use.