INCH-POUND
A-A-59656
31 August 2001
SUPERSEDING
FF-B-187/8
10 September 1993

COMMERCIAL ITEM DESCRIPTION

BEARING, ROLLER, TAPERED, DOUBLE ROW, NORMAL ANGLE, TWO SINGLE CONES, ONE DOUBLE CUP, NONADJUSTABLE (TYPE TNA)

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description (CID) establishes government acquisition requirements for double row, tapered, roller bearings with normal angle, two single cones, and one double cup, nonadjustable (type TNA) for general purpose use.

2. CLASSIFICATION. The roller bearings shall be of one type (TNA) and classified by the size codes listed in table I. The column headings in table I refer to bearing characteristics defined in figure 1.




FIGURE 1. Bearing configuration.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: Defense Supply Center Richmond (DSCR), ATTN: DSCR-VBD, 8000 Jefferson Davis Highway, Richmond, VA 23297-5610.

AMSC N/A FSC 3110

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

TABLE I. Size codes and dimensions.*

Size code	Part 1/ number	d	D	T	B	R 2/	r 2/	d a	D a	K factor	Basic dynamic load ratings (lb.)
	Cone-cup	Bore	Outside diameter	Bearing width over cups	Cone width	Max. shaft fillet radius	Max. housing fillet radius	Recommended shoulder diameter			Two row radial
								Shaft	Housing		
001	NA05075-05185D	0.7500	1.8504	0.9926	1.2500	0.05	0.03	1.00	1.67	1.64	7500
002	NA08125-08231D	1.2500	2.3125	0.9688	1.2812	0.06	0.02	1.52	2.17	1.23	8900
003	NA13687-13621D	1.5000	2.7170	1.5000	1.8124	0.08	0.03	1.83	2.56	1.45	15400
004	NA438-432D	1.7500	3.7500	2.0000	2.4376	0.14	0.03	2.24	3.43	2.05	35200
005	NA366-363D	1.9685	3.5433	1.6563	1.9789	0.14	0.03	2.40	3.31	1.83	14000
006	NA3780-3729D	2.0000	3.6718	2.0625	2.5625	0.14	0.03	2.52	3.46	1.73	19700
007	NA455-452D	2.0000	4.2500	2.1250	2.5626	0.14	0.03	2.56	3.94	1.74	21800
008	NA539-533D	2.1250	4.3750	2.5000	3.1250	0.14	0.06	2.68	3.94	1.97	27600
009	NA385-384D	2.1654	3.9370	1.6875	2.0625	0.14	0.03	2.64	3.66	1.65	14800
010	NA558-552D	2.3750	4.8750	2.5000	3.1250	0.14	0.06	2.99	4.53	1.69	30700
011	NA569-563D	2.6250	5.0000	2.5625	3.1875	0.14	0.06	3.23	4.69	1.61	50000
012	NA482-472D	2.7500	4.7244	2.1250	2.5626	0.14	0.03	3.27	4.49	1.52	23100
013	NA484-472D	2.7559	4.7244	2.1250	2.5626	0.14	0.03	3.27	4.49	1.52	23100
014	NA567-563D	2.8750	5.0000	2.5625	3.1875	0.27	0.06	3.70	4.69	1.61	32000
015	NA495A-493D	3.0000	5.3750	2.1250	2.7500	0.14	0.03	3.62	5.12	1.31	25000
016	NA659-654D	3.0000	6.0000	3.0000	3.7500	0.14	0.06	3.66	5.55	1.43	39600
017	NA580-572D	3.2500	5.5115	2.6250	3.2500	0.14	0.03	3.86	5.24	1.45	51100
018	NA749-742D	3.2500	6.1250	3.3750	4.0000	0.14	0.06	3.90	5.63	1.80	50800
019	NA0593-592D	3.5000	6.0000	2.5000	3.2500	0.14	0.03	4.09	5.67	1.32	34800
020	NA759-752D	3.5000	6.3750	3.3750	4.1250	0.14	0.06	4.17	5.91	1.71	52300

1/ Part numbers are for references only. Part numbers reflect the cup and cone numbers used by industry and the American Bearing Manufacturers Association (ABMA).

2/ These maximum fillet radii shall be cleared by the bearing corners.

* Column headings in the above table refer to bearing characteristics defined in figure 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

TABLE I. Size codes and dimensions (continued).*

Size code	Part 1/ number	d	D	T	B	R 2/	r 2/	d a	D a	K factor	Basic dynamic load ratings (lb.)
	Cone-cup	Bore	Outside diameter	Bearing width over cups	Cone width	Max. shaft fillet radius	Max. housing fillet radius	Recommended shoulder diameter			Two row radial
								Shaft	Housing		
021	NA52375-52637D	3.7500	6.3750	2.4375	3.2499	0.14	0.03	4.41	6.06	1.23	36100
022	NA0593-592D	3.7500	7.0866	3.3750	4.1250	0.14	0.03	4.49	6.61	1.51	88200
023	NA776-774D	3.7500	7.1250	3.3750	4.1250	0.14	0.06	4.49	6.61	1.51	88200
024	NA691-672D	4.0000	6.6250	2.7500	3.6250	0.14	0.03	4.65	6.30	1.24	68200
025	NA780-773D	4.0000	7.0866	3.3750	4.1250	0.14	0.03	4.69	6.61	1.51	88200
026	NA780-774D	4.0000	7.1250	3.3750	4.1250	0.14	0.06	4.69	6.61	1.51	88200
027	NA861-854D	4.0000	7.5000	4.0000	5.0000	0.14	0.06	4.72	6.85	1.74	125400
028	HH221449NA-HH221410D	4.0000	7.5000	4.1250	5.0000	0.14	0.06	4.80	7.05	1.74	85200
029	NA782-773D	4.1250	7.0866	3.3750	4.1250	0.14	0.03	4.80	6.61	1.51	88200
030	NA782-774D	4.1250	7.1250	3.3750	4.1250	0.14	0.06	4.80	6.61	1.51	88200
031	NA71450-71751D	4.5000	7.5000	3.1875	4.1875	0.14	0.06	5.20	7.13	1.40	58300
032	NA938-932D	4.5000	8.3750	4.6250	5.6250	0.14	0.06	5.28	7.60	1.79	142900
033	NA48291-48220D	5.0000	7.1875	2.8750	3.3750	0.14	0.03	5.55	6.93	1.91	43200
034	NA798-792D	5.0000	8.1250	3.2500	4.2500	0.14	0.03	5.71	7.80	1.27	97800
035	NA95500-95927D	5.0000	9.2500	4.5000	5.6250	0.14	0.06	5.87	8.54	1.58	153000
036	NA48390-48320D	5.3750	7.5000	2.8750	3.3750	0.14	0.03	5.94	7.24	1.82	75000
037	NA81550-81963D	5.5000	9.6250	3.1250	4.2500	0.14	0.06	6.34	9.02	1.66	111200
038	NA48686-48620D	5.6250	7.8750	2.8750	3.6876	0.14	0.03	6.22	7.60	1.74	74600
039	NA82576-82951D	5.7500	9.5000	4.1875	5.1875	0.14	0.06	6.54	8.90	1.32	82500
040	NA99600-99102D	6.0000	10.0000	4.3750	5.6250	0.14	0.06	6.85	9.37	1.43	156800
041	NA67787-67720D	6.8750	9.7500	3.3125	4.0625	0.14	0.03	7.56	9.45	1.33	66800

1/ Part numbers are for references only. Part numbers reflect the cup and cone numbers used by industry and the American Bearing Manufacturers Association (ABMA).
2/ These maximum fillet radii shall be cleared by the bearing corners.
* Column headings in the above table refer to bearing characteristics defined in figure 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

TABLE I. Size codes and dimensions (continued).*

Size code	Part 1/ number	d	D	T	B	R 2/	r 2/	d a	D a	K factor	Basic dynamic load ratings (lb.)
	Cone-cup	Bore	Outside diameter	Bearing width over cups	Cone width	Max. shaft fillet radius	Max. housing fillet radius	Recommended shoulder diameter			Two row radial
								Shaft	Housing		
042	NA87700-87112D	7.0000	11.1250	3.1250	4.2500	0.14	0.06	7.87	10.50	1.45	119700
043	NA94700-94114D	7.0000	11.3750	4.3750	5.6250	0.22	0.06	7.99	10.71	1.25	173800
044	HM237545NA-HM237510D	7.0000	11.3750	4.3750	5.6250	0.22	0.06	7.95	10.68	1.83	211900
045	NA94700-94118D	7.0000	11.7500	4.3750	5.6250	0.22	0.06	7.99	10.71	1.25	173800
046	H239649NA-H239612D	7.3750	12.6250	5.4375	7.3125	0.22	0.06	8.43	11.73	1.83	303000
047	NA93800-93127D	8.0000	12.5000	4.3750	5.7500	0.22	0.06	9.06	11.81	1.12	200400
048	NA130902-131401D	9.0000	14.0000	4.3750	5.7500	0.25	0.06	10.08	13.01	1.77	231800
049	NA170950-171451D	9.5000	14.5000	3.3750	4.7500	0.25	0.06	10.59	13.27	1.61	165300

1/ Part numbers are for references only. Part numbers reflect the cup and cone numbers used by industry and the American Bearing Manufacturers Association (ABMA).
2/ These maximum fillet radii shall be cleared by the bearing corners.
* Column headings in the above table refer to bearing characteristics defined in figure 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

3. SALIENT CHARACTERISTICS

3.1 Dimensions. Bearing dimensions (and dynamic load ratings, see 3.4) shall conform to the requirements specified in table I for each of the bearing part numbers. The listed dimensions conform to the requirements specified in American National Standards Institute/American Bearing Manufacturers Association (ANSI/ABMA) Standard 19.2, "Tapered Roller Bearings - Radial Inch Design" (DoD adopted). The bearing size shall be specified in the acquisition order (see 7.4(b)). For any unlisted bearing size codes, the associated dimensional and dynamic load rating requirements should also be specified in the acquisition order.

3.2 Materials.

3.2.1 Cones (inner rings), cups (outer rings), and rollers. The bearing cones, cups, and rollers shall be made of case carburized or through-hardened steel produced in accordance with the American Society for Testing and Materials (ASTM) A 295, "Standard Specification for High-Carbon Anti-Friction Bearing Steel" (DoD adopted), ASTM A 534, "Standard Specification for Carburizing Steels for Anti-Friction Bearings" (DoD adopted), or ASTM A 535, "Standard Specification for Special-Quality Ball and Roller Bearing Steel" (DoD adopted). The steel shall show a fine fracture grain size in accordance with ASTM E 112, "Standard Test Methods for Determining Average Grain Size" (DoD adopted). Material hardness shall be no less than 58 HRC and no more than 64 HRC as defined in ASTM E 18, "Standard Test Methods for Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials" (DoD adopted).

3.2.2 Cage. The bearing cage material shall be impervious to deterioration from any lubricant, preservative, solvent, or other chemical substance expected to contact the bearing during normal use or storage. Similarly, the material shall not cause any chemical deterioration of any other bearing component. The cages shall be made from carbon steel (one piece stamped). Materials shall operate from -65 to 230 °F.

3.3 Tolerance class. The tolerance limits for bearings shall conform to tolerance class 4 as tabulated in ABMA Standard 19.2. Allowable tolerances for bearing components and assembled bearings are listed in tables II through VI.

3.4 Dynamic load rating. The bearing dynamic load rating shall conform to the requirements specified in table I for each bearing size code. The listed ratings conform to the requirements specified in ABMA Standard 11, "Load Ratings and Fatigue Life for Roller Bearings".

3.5 Lubrication and preservation. The bearings shall be furnished without lubrication and shall be preserved for packaging in accordance with MIL-DTL-197, "Packaging of Bearings, Antifriction Associated Parts and Subassemblies". If a preservative compound is required for packing or storage, the compound name shall be specified in the acquisition order (see 7.4(c)).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

TABLE II. Running clearance.

Bearings manufactured with correct running clearance for these fits										
Size code (ref)	Live shaft diameter limits	Dead shaft diameter limits	Housing		Size code (ref)	Live shaft diameter limits	Dead shaft diameter limits	Housing	
	Tight fit	Split fit	Live shaft bore limits	Dead shaft bore limits		Tight fit	Split fit	Live shaft bore limits	Dead shaft bore limits
			Loose fit	Tight fit				Loose fit	Tight fit
001	0.7515 - 0.7510	0.7505 - 0.7500	1.8534 - 1.8524	1.8494 - 1.8484	026	4.0030 - 4.0020	4.0010 - 4.0000	7.1280 - 7.1270	7.1240 - 7.1230
002	1.2515 - 1.2510	1.2505 - 1.2500	2.3155 - 2.3145	2.3115 - 2.3100	027	4.0030 - 4.0020	4.0010 - 4.0000	7.5030 - 7.5020	7.4990 - 7.4980
003	1.5015 - 1.5010	1.5005 - 1.5000	2.7200 - 2.7190	2.7160 - 2.7150	028	4.0030 - 4.0020	4.0010 - 4.0000	7.5030 - 7.5020	7.4990 - 7.4980
004	1.7517 - 1.7510	1.7505 - 1.7500	3.7530 - 3.7520	3.7490 - 3.7480	029	4.1280 - 4.1270	4.1260 - 4.1250	7.0896 - 7.0886	7.0856 - 7.0846
005	1.9700 - 1.9695	1.9690 - 1.9685	3.5463 - 3.5453	3.5423 - 3.5413	030	4.1280 - 4.1270	4.1260 - 4.1250	7.1280 - 7.1270	7.1240 - 7.1230
006	2.0020 - 2.0010	2.0005 - 2.0000	3.6748 - 3.6738	3.6708 - 3.6698	031	4.5035 - 4.5025	4.5010 - 4.5000	7.5030 - 7.5020	7.4990 - 7.4980
007	2.0020 - 2.0010	2.0005 - 2.0000	4.2530 - 4.2520	4.2490 - 4.2480	032	4.5035 - 4.5025	4.5010 - 4.5000	8.3780 - 8.3770	8.3740 - 8.3730
008	2.1270 - 2.1260	2.1255 - 2.1250	4.3780 - 4.3770	4.3740 - 4.3730	033	5.0035 - 5.0025	5.0010 - 5.0000	7.1905 - 7.1895	7.1865 - 7.1855
009	2.1674 - 2.1664	2.1659 - 2.1654	3.9400 - 3.9390	3.9360 - 3.9350	034	5.0035 - 5.0025	5.0010 - 5.0000	8.1280 - 8.1270	8.1240 - 8.1230
010	2.3770 - 2.3760	2.3755 - 2.3750	4.8780 - 4.8770	4.8740 - 4.8730	035	5.0035 - 5.0025	5.0010 - 5.0000	9.2530 - 9.2520	9.2490 - 9.2480
011	2.6275 - 2.6265	2.6255 - 2.6250	5.0030 - 5.0020	4.9990 - 4.9980	036	5.3785 - 5.3775	-- --	7.5030 - 7.5020	--
012	2.7525 - 2.7515	2.7505 - 2.7500	4.7274 - 4.7264	4.7234 - 4.7224	037	5.5040 - 5.5030	-- --	9.6280 - 9.6270	--
013	2.7584 - 2.7574	2.7564 - 2.7559	4.7274 - 4.7264	4.7234 - 4.7224	038	5.6290 - 5.6280	-- --	7.8780 - 7.8770	--
014	2.8775 - 2.8765	2.8755 - 2.8750	5.0030 - 5.0020	4.9990 - 4.9980	039	5.7540 - 5.7530	-- --	9.5030 - 9.5020	--
015	3.0025 - 3.0015	3.0005 - 3.0000	5.3780 - 5.3770	5.3740 - 5.3730	040	6.0040 - 6.0030	-- --	10.0030 - 10.0020	--
016	3.0025 - 3.0015	3.0005 - 3.0000	6.0030 - 6.0020	5.9990 - 5.9980	041	6.8795 - 6.8785	-- --	9.7530 - 9.7520	--
017	3.2525 - 3.2515	3.2505 - 3.2500	5.5145 - 5.5135	5.5105 - 5.5095	042	7.0045 - 7.0035	-- --	11.1280 - 11.1270	--
018	3.2525 - 3.2515	3.2505 - 3.2500	6.1280 - 6.1270	6.1240 - 6.1230	043	7.0045 - 7.0035	-- --	11.3780 - 11.3770	--
019	3.5030 - 3.5020	3.5010 - 3.5000	6.0030 - 6.0020	5.9990 - 5.9980	044	7.0045 - 7.0035	-- --	11.3780 - 11.3770	--
020	3.5030 - 3.5020	3.5010 - 3.5000	6.3780 - 6.3770	6.3740 - 6.3730	045	7.0045 - 7.0035	-- --	11.7530 - 11.7520	--
021	3.7530 - 3.7520	3.7510 - 3.7500	6.3780 - 6.3770	6.3740 - 6.3730	046	7.3795 - 7.3785	-- --	12.6310 - 12.6290	--
022	3.7530 - 3.7520	3.7510 - 3.7500	7.0896 - 7.0886	7.0856 - 7.0846	047	8.0050 - 8.0040	-- --	12.5060 - 12.5040	--
023	3.7530 - 3.7520	3.7510 - 3.7500	7.1280 - 7.1270	7.1240 - 7.1230	048	9.0055 - 9.0045	-- --	14.0060 - 14.0040	--
024	4.0030 - 4.0020	4.0010 - 4.0000	6.6280 - 6.6270	6.6240 - 6.6230	049	9.5060 - 9.5050	-- --	14.5060 - 14.5040	--
025	4.0030 - 4.0020	4.0010 - 4.0000	7.0896 - 7.0886	7.0856 - 7.0846	--	--	-- --	--	--

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

3.6 Contact angle. All bearings are normal angle bearings having a contact angle between 10 and 19 degrees. The contact angle is the angle between the line of action of the roller load and a plane perpendicular to the bearing axis.

TABLE III. Cone bore tolerance.

Cone bore (d)			
Size range		Tolerance	
Over	Incl.	Plus	Minus
0	3.0000	5	0
3.0000	12.0000	10	0

Note: Allowable tolerances are in 0.0001 inch.

TABLE IV. Cup diameter tolerance.

Cup diameter (D)			
Size range		Tolerance	
Over	Incl.	Plus	Minus
0.0000	12.0000	10	0
12.0000	24.0000	20	0

Note: Allowable tolerances are in 0.0001 inch.

TABLE V. Bearing width tolerance.

Bearing width (T)			
Bore size range		Tolerance	
Over	Incl.	Plus	Minus
0	5.0000	100	0
5.0000	12.0000	300	0

Note: Allowable tolerances are in 0.0001 inch.

TABLE VI. Assembled bearing tolerance.

Assembled bearing maximum radial runout		
Cup OD (D)		Tolerance
Over	Incl.	
0	24.0	20

Note: Allowable tolerances are in 0.0001 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

4. REGULATORY REQUIREMENTS

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Unless otherwise indicated in the solicitation and resulting contract, the foreign acquisition restrictions in Section 225.7019 of the Defense Federal Acquisition Regulation Supplement (DFARS) apply to products described by this CID.

5. PRODUCT CONFORMANCE PROVISIONS

5.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The government reserves the right to require proof of such conformance.

5.2 Market acceptability. The product offered must have been previously sold either to the government or on the commercial market.

6. PACKAGING

6.1 Preservation, packing, and marking. For acquisition purposes, the bearings supplied shall be preserved, packed, and marked as specified in the acquisition order (see 7.4(d)).

7. NOTES

7.1 Sources of documents.

7.1.1 FAR and DFARS. Copies of the FAR and DFARS may be obtained from the Superintendent of Documents, P.O. Box 371954, Pittsburgh, PA 15250-7954. Electronic copies of the FAR may be obtained from http://www.arnet.gov/far/. Electronic copies of the DFARS may be obtained from http://www.acq.osd.mil/dp/dars/dfars.html.


7.1.2 Military details. Copies of military details may be obtained from Standardization Documents Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094. Electronic copies of military specifications and standards may be obtained from http://astimage.daps.dla.mil/quicksearch/.

7.1.3 ABMA standards. Copies of ABMA standards may be obtained from the American Bearing Manufacturers Association, 1200 19th Street, Suite 300, Washington, DC 20036-2401.

7.1.4 ASTM standards. Copies of ASTM standards may be obtained from the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

7.2 Part or identification number (PIN). The following part or identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.



AA59656 - 002 indicates: bearing bore 1.2500 inches; outside diameter 2.3125 inches; width 0.9688 inches.

7.3 Sources of supply. The manufacturers and/or suppliers listed below are known to supply products that meet the salient characteristics requirements of this document. Competition is not limited to the listed firms.

KOYO Corporation of U.S.A.
Westlake, OH 44145

FAG Bearings Corporation
Danbury, CT 06813

NTN Bearing Corporation
Mount Prospect, IL 60056

SKF Industries
Kulpsville, PA 19443

7.4 Ordering data. Acquisition documents shall specify the following information:

a. CID document number, revision, and CID PIN
b. Bearing size (with dimension/load requirements if size is unlisted) (see 3.1)
c. Preservative compound, if required (see 3.5)
d. Preservation, packing, and marking requirements (see 6.1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

7.5 Cross-reference information. Table VII relates the original specification slant sheets to the replacement CIDs.

TABLE VII. Cross-reference table.

FF-B-187B	Replacement CID	ABMA type
Specification sheet 1	A-A-59649	TS
Specification sheet 2	A-A-59650	TSF
Specification sheet 3	A-A-59651	TSS
Specification sheet 4	A-A-59652	TSSF
Specification sheet 5	A-A-59653	TDI & TDIS
Specification sheet 6	A-A-59654	TDO
Specification sheet 7	A-A-59655	TDOS
Specification sheet 8	A-A-59656	TNA (normal angle)
Specification sheet 9	A-A-59657	TNAS (steep angle)
Specification sheet 10	A-A-59658	TNASW
Specification sheet 11	A-A-59659	TNASWE

7.6 Subject term (key word) listing.

bore
cone
cup
load
width

MILITARY INTERESTS:

Custodians:
Army - AR
Navy - YD
Air Force - 99

Reviewers:
Navy - MC, OS
Air Force - 84

CIVIL AGENCY
COORDINATING ACTIVITY:

GSA - 7FXE

Preparing activity:
DLA - GS4

(Project 3110-1244)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.