INCH-POUND
A-A-59657
31 August 2001
SUPERSEDING
FF-B-187/9
10 September 1993

COMMERCIAL ITEM DESCRIPTION

BEARING, ROLLER, TAPERED, DOUBLE ROW, STEEP ANGLE, TWO SINGLE CONES, ONE DOUBLE CUP, NONADJUSTABLE (TYPE TNAS)

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description (CID) establishes government acquisition requirements for double row, tapered, roller bearings with steep angle, two single cones, and one double cup, nonadjustable (type TNAS) for general purpose use.

2. CLASSIFICATION. The roller bearings shall be of one type (TNAS) and classified by the size codes listed in table I. The column headings in table I refer to bearing characteristics defined in figure 1.



FIGURE 1. Bearing configuration.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: Defense Supply Center Richmond (DSCR), ATTN: DSCR-VBD, 8000 Jefferson Davis Highway, Richmond, VA 23297-5610.

AMSC N/A FSC 3110

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

TABLE I. Size codes and dimensions.*

Size code	Part 1/ number	d	D	T	B	R 2/	r 2/	d a	D a	K factor	Basic dynamic load ratings (lb.)
	Cone-cup	Bore	Outside diameter	Bearing width over cups	Cone width	Max. shaft fillet radius	Max. housing fillet radius	Recommended shoulder diameter			
								Shaft	Housing		Two row radial
001	NA21075 - 21226D	0.7500	2.2500	1.4375	1.9375	0.06	0.03	1.24	2.01	.99	12800
002	NA43131 - 43319D	1.3125	3.1875	1.5625	2.1875	0.09	0.06	1.91	2.91	.87	21500
003	NA44143 - 44363D	1.4375	3.6250	1.5625	2.1875	0.03	0.06	2.01	3.35	.75	23300
004	NA44163 - 44363D	1.6250	3.6250	1.5625	2.1875	0.03	0.06	2.13	3.35	.75	13600
005	NA53176 - 53390D	1.7500	3.8750	1.7500	2.5626	0.09	0.06	2.40	3.54	.79	27700
006	NA55200 - 55444D	2.0000	4.4375	1.8125	2.5625	0.09	0.06	2.72	4.13	.66	29400
007	NA66212 - 66462D	2.1250	4.6250	2.1250	2.8750	0.14	0.03	2.87	4.37	.93	41200
008	NA72212 - 72488D	2.1250	4.8750	2.1875	3.0625	0.09	0.06	2.91	4.53	.79	50000
009	NA9378 - 9320D	3.0000	7.0000	2.9375	4.3065	0.14	0.09	4.13	6.46	.76	49100
010	NA98350 - 98789D	3.5000	7.8750	3.1581	4.5625	0.14	0.09	4.65	7.40	.92	112100
011	NA97450 - 97901D	4.5000	9.0000	3.3125	4.5625	0.14	0.09	5.51	8.38	.79	102600

1/ Part numbers are for reference only. Part numbers reflect the cup and cone numbers used by industry and the American Bearing Manufacturers Association (ABMA).

2/ These maximum fillet radii shall be cleared by the bearing corners.

* Column headings in the above table refer to bearing characteristics defined in figure 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

3. SALIENT CHARACTERISTICS

3.1 Dimensions. Bearing dimensions (and dynamic load ratings, see 3.4) shall conform to the requirements specified in table I for each of the bearing part numbers. The listed dimensions conform to the requirements specified in American National Standards Institute/American Bearing Manufacturers Association (ANSI/ABMA) Standard 19.2, "Tapered Roller Bearings - Radial Inch Design" (DoD adopted). The bearing size shall be specified in the acquisition order (see 7.4(b)). For any unlisted bearing size codes, the associated dimensional and dynamic load rating requirements should also be specified in the acquisition order.

3.2 Materials.

3.2.1 Cones (inner rings), cups (outer rings), and rollers. The bearing cones, cups, and rollers shall be made of case carburized or through-hardened steel produced in accordance with the American Society for Testing and Materials (ASTM) A 295, "Standard Specification for High-Carbon Anti-Friction Bearing Steel" (DoD adopted), ASTM A 534, "Standard Specification for Carburizing Steels for Anti-Friction Bearings" (DoD adopted), or ASTM A 535, "Standard Specification for Special-Quality Ball and Roller Bearing Steel" (DoD adopted). The steel shall show a fine fracture grain size in accordance with ASTM E 112, "Standard Test Methods for Determining Average Grain Size" (DoD adopted). Material hardness shall be no less than 58 HRC and no more than 64 HRC as defined in ASTM E 18, "Standard Test Methods for Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials" (DoD adopted).

3.2.2 Cage. The bearing cage material shall be impervious to deterioration from any lubricant, preservative, solvent, or other chemical substance expected to contact the bearing during normal use or storage. Similarly, the material shall not cause any chemical deterioration of any other bearing component. The cages shall be made from carbon steel (one piece stamped). Materials shall operate from -65 to 230 °F.

3.3 Tolerance class. The tolerance limits for bearings shall conform to tolerance class 4 as tabulated in ABMA Standard 19.2. Allowable tolerances for bearing components and assembled bearings are listed in tables II through VI.

3.4 Dynamic load rating. The bearing dynamic load rating shall conform to the requirements specified in table I for each bearing size code. The listed ratings conform to the requirements specified in ABMA Standard 11, "Load Ratings and Fatigue Life for Roller Bearings".

3.5 Lubrication and preservation. The bearings shall be furnished without lubrication and shall be preserved for packaging in accordance with MIL-DTL-197, "Packaging of Bearings, Antifriction Associated Parts and Subassemblies". If a preservative compound is required for packing or storage, the compound name shall be specified in the acquisition order (see 7.4(c)).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

TABLE II. Running clearance.

Bearings manufactured with correct running clearance for these fits			
Size code (ref)	Live shaft diameter limits	Housing	
	Tight fit	Live shaft bore limits	Dead shaft bore limits
		Loose fit	Tight fit
001	0.7515 - 0.7510	2.2530 - 2.2520	2.2490 - 2.2480
002	1.3140 - 1.3135	3.1905 - 3.1895	3.1865 - 3.1855
003	1.4390 - 1.4385	3.6280 - 3.6270	3.6240 - 3.6230
004	1.6265 - 1.6260	3.6280 - 3.6270	3.6240 - 3.6230
005	1.7515 - 1.7510	3.8780 - 3.8770	3.8740 - 3.8730
006	2.0020 - 2.0010	4.4405 - 4.4395	4.4365 - 4.4355
007	2.1270 - 2.1260	4.6280 - 4.6270	4.6240 - 4.6230
008	2.1270 - 2.1260	4.8780 - 4.8770	4.8740 - 4.8730
009	3.0025 - 3.0015	7.0030 - 7.0020	6.9990 - 6.9980
010	3.5030 - 3.5020	7.8780 - 7.8770	7.8740 - 7.8730
011	4.5035 - 4.5025	9.0030 - 9.0020	8.9990 - 8.9980

TABLE III. Cone bore tolerance.

Cone bore (d)			
Size range		Tolerance	
Over	Incl.	Plus	Minus
0	3.0000	5	0
3.0000	6.0000	10	0

Note: Allowable tolerances are in 0.0001 inch.

TABLE IV. Cup diameter tolerance.

Cup diameter (D)			
Size range		Tolerance	
Over	Incl.	Plus	Minus
0.0000	12.0000	10	0
12.0000	24.0000	20	0

Note: Allowable tolerances are in 0.0001 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

TABLE V. Bearing width tolerance.

Bearing width (T)			
Bore size range		Tolerance	
Over	Incl.	Plus	Minus
0	5.0000	100	0
5.0000	12.0000	300	0

Note: Allowable tolerances are in 0.0001 inch.

TABLE VI. Assembled bearing tolerance.

Assembled bearing maximum radial runout		
Cup OD (D)		Tolerance
Over	Incl.	
0	24.0	20

Note: Allowable tolerances are in 0.0001 inch.

3.6 Contact angle. All bearings are steep angle bearings having a contact angle between 22 and 31 degrees. The contact angle is the angle between the line of action of the roller load and a plane perpendicular to the bearing axis.

4. REGULATORY REQUIREMENTS

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Unless otherwise indicated in the solicitation and resulting contract, the foreign acquisition restrictions in Section 225.7019 of the Defense Federal Acquisition Regulation Supplement (DFARS) apply to products described by this CID.

5. PRODUCT CONFORMANCE PROVISIONS

5.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The government reserves the right to require proof of such conformance.

5.2 Market acceptability. The product offered must have been previously sold either to the government or on the commercial market.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

6. PACKAGING

6.1 Preservation, packing, and marking. For acquisition purposes, the bearings supplied shall be preserved, packed, and marked as specified in the acquisition order (see 7.4(d)).

7. NOTES

7.1 Sources of documents.

7.1.1 FAR and DFARS. Copies of the FAR and DFARS may be obtained from the Superintendent of Documents, P.O. Box 371954, Pittsburgh, PA 15250-7954. Electronic copies of the FAR may be obtained from http://www.arnet.gov/far/. Electronic copies of the DFARS may be obtained from http://www.acq.osd.mil/dp/dars/dfars.html.

7.1.2 Military details. Copies of military details may be obtained from Standardization Documents Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094. Electronic copies of military specifications and standards may be obtained from http://astimage.daps.dla.mil/quicksearch/.

7.1.3 ABMA standards. Copies of ABMA standards may be obtained from the American Bearing Manufacturers Association, 1200 19th Street, Suite 300, Washington, DC 20036-2401.

7.1.4 ASTM standards. Copies of ASTM standards may be obtained from the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.

7.2 Part or identification number (PIN). The following part or identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.



AA59657 - 002 indicates: bearing bore 1.3125 inches; outside diameter 3.1875 inches; width 1.5625 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

7.3 Sources of supply. The manufacturers and/or suppliers listed below are known to supply products that meet the salient characteristics requirements of this document. Competition is not limited to the listed firms.

KOYO Corporation of U.S.A.
Westlake, OH 44145

FAG Bearings Corporation
Danbury, CT 06813

NTN Bearing Corporation
Mount Prospect, IL 60056

SKF Industries
Kulpsville, PA 19443

7.4 Ordering data. Acquisition documents shall specify the following information:

a. CID document number, revision, and CID PIN
b. Bearing size (with dimension/load requirements if size is unlisted) (see 3.1)
c. Preservative compound, if required (see 3.5)
d. Preservation, packing, and marking requirements (see 6.1)

7.5 Cross-reference information. Table VII relates the original specification slant sheets to the replacement CIDs.

TABLE VII. Cross-reference table.

FF-B-187B	Replacement CID	ABMA type
Specification sheet 1	A-A-59649	TS
Specification sheet 2	A-A-59650	TSF
Specification sheet 3	A-A-59651	TSS
Specification sheet 4	A-A-59652	TSSF
Specification sheet 5	A-A-59653	TDI & TDIS
Specification sheet 6	A-A-59654	TDO
Specification sheet 7	A-A-59655	TDOS
Specification sheet 8	A-A-59656	TNA (normal angle)
Specification sheet 9	A-A-59657	TNAS (steep angle)
Specification sheet 10	A-A-59658	TNASW
Specification sheet 11	A-A-59659	TNASWE

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

7.6 Subject term (key word) listing.

bore
cone
cup
load
width

MILITARY INTERESTS:

Custodians:
Army - AR
Navy - YD
Air Force - 99

Reviewers:
Navy - MC, OS
Air Force - 84

CIVIL AGENCY
COORDINATING ACTIVITY:

GSA - 7FXE

Preparing activity:
DLA - GS4

(Project 3110-1245)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.