MILITARY SPECIFICATION

SWITCHES, ELECTRICAL AND FIBER OPTIC, PACKAGING OF

1. SCOPE

* 1.1 Scope. This specification covers the requirements for the preservation, packing, and container marking for all types of electrical and fiber optic switches, switch assemblies, and associated accessories which are primarily in FSC's 5930 and 6021. As used in this specification, the term "switches" shall also include switch assemblies.

2. APPLICABLE DOCUMENTS

* 2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

QQ-S-781	-	Strapping, Steel, and Seals.
PPP-B-566	-	Boxes, Folding, Paperboard.
PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-B-676	-	Boxes, Setup.

MILITARY

MIL-P-116	-	Preservation, Methods of.

STANDARDS

FEDERAL

FED-STD-123	-	Marking for Shipment (Civil Agencies).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Electronics Supply Center, ATTN: DESC-ES, 1507 Wilmington Pike, Dayton Ohio 45444-5276, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:19Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-147	-	Palletized Unit Loads.
MIL-STD-202	-	Test Methods for Electronic and Electrical Component Parts.
* MIL-STD-2073-1	-	DoD materiel, Procedures for Development and Application of Packaging Requirements.
MIL-STD-45662	-	Calibration Systems Requirements.

* (Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

* 2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 General. The packaging terms used herein shall be in accordance with the definitions listed in MIL-STD-129 and MIL-STD-2073-1. The following general requirements apply, as applicable, to levels A, B, and C as well as to shipments of non-Government activities.

* 3.1.1 Hardware and switch accessories. Unmounted hardware and switch accessories such as boots, caps, filters, lenses, mounting brackets, panel seals, and screws supplied with certain switches shall be physically protected and enclosed in the unit packs in a manner that will not damage the switches or packaging materials. When practical, the hardware should be mounted on each switch.

* 3.1.2 Physical protection. Switches and accessories shall be packaged in a manner that will ensure compliance with the applicable requirements of MIL-P-116 as well as those specified herein. For shipments to non-Government activities, large quantity unit packs may be used.

3.1.2.1 Protection of fragile and delicate parts. Projecting terminals, ceramic wafers, glass tubes, and other fragile parts of switches shall be protected by means of suitable noncorrosive materials or devices such as die-cut inserts or semirigid cushioning materials. Die-cut or molded inserts shall be used to securely position delicate air and liquid flow switches and prevent movement of the vanes.

* 3.1.2.2 Wrapping and cushioning. All wrapping and cushioning materials used shall be noncorrosive and dry. In addition, materials used for fiber optic switches shall be nonstatic generating and shall not crumble, flake, powder, or shed. Cushioning is not required for accessories.

3.1.3 Exterior containers. Exterior containers (see 3.3.1, 3.3.2, and 3.3.3) shall be of minimum tare and cube consistent with the protection required and shall contain equal quantities of identical stock numbered or otherwise designated items to the greatest extent practicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:19Z
Check the source to verify that this is the current version before use.

3.2 Preservation. Preservation shall be in accordance with level A, B, or C, as specified (see 3.1 and 6.2).

3.2.1 Levels A and B (see 6.4).

3.2.1.1 Cleaning. Switches shall be cleaned in accordance with MIL-P-116, process C-1.

3.2.1.2 Drying. Switches shall be dried in accordance with MIL-P-116.

3.2.1.3 Preservatives. Contact preservatives shall not be used.

3.2.1.4 Unit packs.

3.2.1.4.1 Switches. The unit packs for switches shall be as specified in table I. The quantity per unit pack (QUP) shall be one.

3.2.1.4.2 Accessories (when separately acquired).

* 3.2.1.4.2.1 Indicator lights and switch housings. Unless otherwise specified in the contract (see 6.2), indicator lights and switch housings shall be unit packed one each in accordance with submethod IC-1 or IC-3 of MIL-P-116 (for level A) and method III of MIL-P-116 (for level B).

3.2.1.4.2.2 Boots. Unless otherwise specified in the contract (see 6.2), boots shall be unit packed five each in accordance with method III.

3.2.1.4.2.3 Other accessories. Other accessories such as caps, filters, lenses, and panel seals shall be unit packed in accordance with method III. Unit pack quantities for other than one each shall be as specified (see 6.2).

* 3.2.1.4.3 Supplementary containers. Each switch, unit packed in a bag or envelope as specified in 3.2.1.4.1, with a unit pack volume exceeding 15 cubic inches (245.85 cubic centimeters) shall be placed in a supplementary container conforming to variety 2 of either PPP-B-566 or PPP-B-676. For level B any variety of these containers may be used.

* 3.2.1.5 Intermediate packs. When the unit pack is a bag of any type or the unit pack is less than 64 cubic inches (1,049 cubic centimeters), uniform quantities of switches or accessories of the same NSN shall be placed in intermediate containers conforming to variety 2 of either PPP-B-556 or PPP-B-676; or PPP-B-636, class weather resistant. Alternatively, nonweather or nonwater resistant versions of these containers may be used provided they are overwrapped with waterproof barrier materials. For level B any variety or class of the containers specified may be used. Intermediate containers shall contain multiples of five unit packs not to exceed 100 unit packs. No intermediate packs are required when the total quantity shipped to a single destination will result in only one intermediate pack per shipping container.

* 3.2.2 Level C. The level C preservation of switches and accessories shall conform to the MIL-STD-2073 requirements for this level. Unless otherwise specified in the contract (see 6.2), the quantity per unit pack shall be at the option of the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:19Z
Check the source to verify that this is the current version before use.

* TABLE I. Levels A and B preservation requirements for switches.

Type	Net weight or cube	Method or submethod of MIL-P-116		Additional requirements
		Level A	Level B	
Switch capsules and other hermetically sealed switches with wire leads or solderable terminal lugs.	0-10 pounds (4.536 kilograms)	III	III	See 3.2.1.4.3 and 3.2.1.5
	Over 10 pounds (4.536 kilograms)	III	III	Unit container shall be in accordance with the requirements of 3.3.2
Air and liquid flow switches with external vanes.	---	IA-15	IC-2	Container shall conform to PPP-B-566 or PPP-B-676 (see 3.1.2.1).
Pressure (without "O" rings) and stepping switches.	0-10 pounds (4.536 kilograms)	IIe	IA-15	Container shall conform to PPP-B-566, PPP-B-676, or PPP-B-636.
	Over 10 pounds (4.536 kilograms)	IIb	IA-14	Exterior container shall be in accordance with the requirements of 3.3.2.
Box, fiber optic inertia, leaf spring, pressure (with "O" rings), push button, rotary, thermostatic, toggle, and all other switches not otherwise designated in this table.	0-15 cubic inches (245.85 cubic centimeters)	IA-8	IC-1 or IC-3	See 3.2.1.4.3 and 3.2.1.5
	Over 15 cubic inches (245.85 cubic centimeters) 10 pounds (4.536 kilograms)	IA-15	IC-2	Container shall conform to PPP-B-566, PPP-B-676, or PPP-B-636.
	Over 10 pounds (4.536 kilograms)	IA-14	IC-2 with supplementary container	Exterior container shall be in accordance with the requirements of 3.3.2.

Source: https://assist.dla.mil -- Downloaded: 202610-20T15:19Z
Check the source to verify that this is the current version before use.

3.3 Packing. Packing shall be level A, B, or C, as specified (see 3.1 and 6.2).

3.3.1 Level A. Switches and accessories, preserved as specified in 3.2, shall be packed in wood containers conforming to PPP-B-601, overseas type or PPP-B-621, class 2. Closure and strapping shall be in accordance with the applicable container specification except that metal strapping shall conform to QQ-S-781, type I, finish A. The requirements for level B packing shall be used when the total quantity of a stock numbered switch or accessory for a single destination does not exceed a packed volume of one cubic foot (0.02832 cubic meter).

3.3.2 Level B. Switches and accessories, preserved as specified in 3.2, shall be packed in fiberboard containers conforming to PPP-B-636, class weather resistant, style optional, special requirements. The requirements for box closure, waterproofing, and reinforcing shall be in accordance with method V of the PPP-B-636 appendix.

3.3.3 Level C. Switches and accessories, preserved as specified in 3.2, shall be packed in fiberboard containers conforming to PPP-B-636, class domestic, style optional, special requirements. Closures shall be in accordance with the PPP-B-636 appendix.

3.3.4 Unitized loads. Unitized loads, commensurate with the level of packing specified in the contract or purchase order, shall be used whenever total quantities for shipment to one destination equal 40 cubic feet (1.1328 cubic meters) or more. Quantities less than 40 cubic feet need not be unitized. Unitized loads shall be uniform in size and quantities to the greatest extent practicable.

3.3.4.1 Level A. Switches and accessories, packed as specified in 3.3.1, shall be unitized on pallets in conformance with MIL-STD-147, load type I, with a wood cap (storage aid 5) positioned over each load.

3.3.4.2 Level B. Switches and accessories packed as specified in 3.3.2, shall be unitized on pallets in conformance with MIL-STD-147, load type I, with a weather resistant fiberboard cap (storage aid 4) positioned over each load.

3.3.4.3 Level C. Switches and accessories, packed as specified in 3.3.3, shall be unitized as specified in 3.3.4.2 except that the fiberboard caps shall be class domestic.

* 3.4 Marking. The following marking is mandatory for shipments both to U.S. Government and non-Government activities.

* 3.4.1 Standard marking. In addition to any special or other identification marking required by the contract (see 6.2), each unit, supplementary, intermediate, and exterior container and unitized load shall be marked in accordance with MIL-STD-129. The complete military or contractor's type or part number, as applicable, including the Commercial and Government Entity (CAGE) code, shall be marked on all unit and intermediate packs in accordance with the identification marking provisions of MIL-STD-129. When specified in the contract (see 6.2), the marking of domestic shipments for civil agencies shall be in accordance with FED-STD-123.

3.5 First article and quality conformance inspections. First article and quality conformance inspections and tests shall be required as specified in 4.4 and 4.5, respectively. Samples for these tests shall be furnished in accordance with the procedures outlined in 4.4 and 4.5. The performance of the visual and dimensional inspections, rough handling tests, and leakage tests shall conform to the inspections and tests outlined in 4.6.1, 4.6.2.1, and 4.6.2.2, respectively.

Source: https://assist.dla.mil -- Downloaded: 202610-20T15:19Z
Check the source to verify that this is the current version before use.

3.5.1 Functional requirements.

3.5.1.1 Rough handling test (when specified, see 6.2). When packs have been tested in accordance with 4.6.2.1, all materials and components comprising each pack shall be free from damage or evidence of misplacement which might affect the utility of the preservation method or pack. The switches and accessories within the tested packs shall show no visible signs of damage. When specified (see 6.2), functional tests in accordance with the group A inspection requirements of the applicable commodity specification shall be conducted on these switches subjected to the rough handling test to determine freedom from operational malfunction.

3.5.1.2 Leakage test (when applicable). When a barrier enclosed unit pack has been tested in accordance with 4.6.2.2, there shall be no evidence of moisture within the unit pack.

3.6 Workmanship. The quality of workmanship shall assure acceptance of the completed preservation, packing, and marking requirements in accordance with the inspections specified in section 4.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract (see 6.2), the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of section 3. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Test equipment and inspection facilities. Test and measuring equipment and inspection facilities of sufficient accuracy, quality, and quantity to permit performance of the required inspection shall be established and maintained by the contractor. The establishment and maintenance of a calibration system to control the accuracy of the measuring and test equipment shall be in accordance with MIL-STD-45662.

4.1.3 Inspection conditions. All inspections shall be performed in accordance with the test conditions specified in the general requirements of MIL-STD-202.

4.2 Classification of inspection. The inspections specified herein are classified as follows:

a. Materials inspection (see 4.3).

b. First article inspection (see 4.4).

c. Quality conformance inspection (see 4.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:19Z
Check the source to verify that this is the current version before use.

4.3 Materials inspection. Materials inspection shall consist of certification supported by verifying data that the materials used are in accordance with the applicable requirements specified herein.

4.4 First article inspection. When specified (see 6.2), first article inspection shall be performed by the contractor, after award of contract and prior to production, at a time and location acceptable to the Government. First article inspection shall not be required:

a. When there have been no changes in materials, processes, or packaging design that will adversely affect item protection since the last recorded inspection.

b. When detailed packaging instructions are furnished by the acquisition activity.

c. When level C protection is specified.

d. When a prior successful inspection was conducted on a like item and pack (subject to the approval of the administrative contracting officer).

4.4.1 Sample size. One sample unit consisting of a level A or level B pack, as applicable, shall be submitted for first article inspection. The sample for the rough handling test shall consist of the pack selected for first article inspection. The sample for the leakage test shall be five unit packs selected at random from the first article exterior pack (shipping container).

4.4.2 Inspection routine. The sample shall be subjected to the inspections specified in tables II and III. The leakage test, when applicable, shall follow the rough handling test.

4.4.3 Failures. One or more failures shall be cause for refusal to grant first article approval.

4.4.4 Resubmission of first article sample. If the sample fails to pass first article inspection, the contractor shall change the preservation and packing processes to correct the cause of the deficiency. First article inspection shall be performed on a corrected sample to prove that the corrective action is acceptable.

* TABLE II. Visual and dimensional inspections.

Major defects	Requirement paragraph	Test paragraph
Preservation and packing materials not conforming to referenced specification requirements	3.1, 3.2, and 3.3	4.6.1
Uncleaned or improperly cleaned items	3.2.1.1 and 3.2.1.2	
Incorrect preservation method	3.2.1.4.1 and 3.2.1.4.2	
Punctured or improperly fabricated barrier bag	3.2.1.4.1 and 3.2.1.4.2.1	
Wrong quantity per unit pack	3.2.1.4.1, 3.2.1.4.2, and 3.2.2	
Nonuse or incorrect applications of intermediate containers	3.2.1.5	
Improper box closures	3.3.1, 3.3.2, and 3.3.3	
Omitted, incorrect, or illegible marking	3.4	

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:19Z
Check the source to verify that this is the current version before use.

* TABLE III. Functional inspections.

Test	Requirement paragraph	Test paragraph
Rough handling (when specified)	3.5.1.1	4.6.2.1
Leakage (when applicable)	3.5.1.2	4.6.2.2

4.5 Quality conformance inspection. This inspection shall consist of the inspections and tests specified in tables II and III, respectively.

4.5.1 Inspection lot. An inspection lot, as far as practicable, shall consist of unit or exterior (shipping) packs produced under essentially the same conditions and offered for inspection at one time. For the purpose of selecting samples to be inspected and tested for compliance with the requirements of this specification, either items in process or completed packs except as stated herein, may be combined into lots without regard to individual items, contracts, or the quantities therein. Unit packs of the same size and made from the same packaging materials may be grouped together except when item complexity, item value, or the complexity of the preservation method warrants that the inspection of such items be performed on a separate basis. A separate application of the sampling or inspection procedure shall be made on these items. The combination of items to be subjected to inspection shall be determined by either the Government or the contractor, subject to the approval of the Government.

4.5.2 Visual and dimensional inspection. Visual and dimensional inspection shall consist of those inspections specified in table II.

4.5.2.1 Sampling plan. Statistical sampling and inspection shall be in accordance with MIL-STD-105 for special inspection level S-4. The acceptable quality level (AQL) shall be 4.0 percent defective for all inspections of table II combined.

4.5.2.2 Rejected lots. If an inspection lot is rejected, the contractor may rework it to correct the defects, or screen out the defective units, and resubmit for reinspection. Resubmitted lots shall be inspected using tightened inspection. Such lots shall be separate from new lots, and shall be clearly identified as reinspected lots.

4.5.2.3 Disposition of sample units. Sample units which have passed all the inspections specified in table II may be delivered on the contract, provided the lot is accepted.

4.5.3 Functional inspection. Functional inspection shall consist of the tests specified in table III.

4.5.3.1 Sampling plan. Sampling plans shall be as follows:

a. One sample unit for the rough handling test shall be selected whenever the design of the item or packaging is changed.

b. For unit packs requiring waterproof or water-vaporproof barriers, five sample units for the leakage test shall be selected daily at random from the first lot processed each day. Five additional samples shall be selected at random from the day's total production.

c. The leakage test shall also be performed following the rough handling test on unit packs requiring waterproof or water-vaporproof barriers. Five sample units or the number of units contained within the shipping container (if less than five) shall be selected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:19Z
Check the source to verify that this is the current version before use.

4.5.3.2 Failures. One or more failures shall be cause for rejection of the lot.

4.5.3.3 Disposition of sample units. Sample units which have passed the inspections specified in table III may be delivered on the contract if the lot is accepted and opened packs have been reprocessed.

4.5.3.4 Noncompliance. If a sample fails to pass the inspections specified in table III, the contractor shall take corrective action on the materials or processes or both, as warranted, on all unit, intermediate, and exterior (shipping) packs which can be corrected and which were processed under essentially the same conditions, with essentially the same materials, and which are considered subject to the same failure. Acceptance of the unit, intermediate, and exterior packs shall be discontinued until corrective action has been taken and the applicable inspections specified in table III have been repeated on additional sample units. (All inspections or the inspection which the original sample failed shall be at the option of the Government.) Inspections specified in table III may be reinstituted; however, final acceptance shall be withheld until the reinspection in accordance with table III has shown that the corrective action was successful. In the event of failure after reinspection, information concerning the failure and corrective action taken shall be furnished to the administrative contracting officer.

4.6 Methods of inspections and tests.

4.6.1 Visual and dimensional inspections. Unit, intermediate, and exterior packs shall be examined to verify that the materials, designs, methods, physical limitations, marking, and workmanship are in accordance with the applicable requirements (see 3.1 through 3.6).

4.6.2 Functional tests.

4.6.2.1 Rough handling. Packs shall be subjected to the applicable rough handling tests and the interpretation of results or cause for rejection as specified in 3.5.1.1 and MIL-P-116.

4.6.2.2 Leakage. When a waterproof or water-vaporproof barrier is required, the unit pack shall be subjected to the applicable leakage test and interpretation of results specified in 3.5.1.2 and MIL-P-116.

5. PACKAGING

* This section is not applicable to this specification.

6. NOTES

* (This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

* 6.1 Intended use. The preservation, packing, and marking specified herein are intended for direct shipments to the Government. Unless otherwise designated, the general requirements (3.1) and marking requirements (3.4) are applicable for the preparation of military specification switches and accessories for shipment from the parts manufacturer to non-Government activities.

* 6.2 Acquisition requirements. Acquisition documents must specify the following:

* a. Title, number, and date of the specification.

b. Levels of preservation and packing (see 3.2 and 3.3).

* c. Quantity per unit pack, if other than specified (see 3.2.1.4.1, 3.2.1.4.2, 3.2.1.4.3, and 3.2.2).

Source: https://assist.dla.mil -- Downloaded: 20260-20T15:19Z
Check the source to verify that this is the current version before use.

the switches and accessories within [illegible] delivery of the preservation method or pack.

* d. If any other standard or special marking is required (see 3.4.1).

* e. If FED-STD-123 is required for civil agency marking (see 3.4.1).

f. If a rough handling test is required (see 3.5.1.1).

g. If switch functional tests are required (see 3.5.1.1).

h. If the contractor is not responsible for the performance of all inspection requirements (see 4.1).

i. If first article inspection is required (see 4.4).

* 6.3 First article. The sample pack submitted for first article inspection (when satisfactorily performed as specified in 4.4) will serve as the production standard for subsequent packaging operations. The contractor should inform the acquisition activity or the activity administering the contract of the time and location of this specification so that the Government representative will have an opportunity to witness the tests.

6.4 Conditions for use of level B preservation. When level B preservation is specified (see 3.2), this level of protection should be reserved for the acquisition of switches and accessories for resupply worldwide under known favorable handling, transportation, and storage conditions.

* 6.5 Subject term (key word) listing.

Electrical switches
Fiber optic switches
Packing
Physical protection
Preservation
Switch accessories

6.6 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 99
DLA - ES

Review activities:
Navy - AS, SH
Air Force - 84

User activities:
Army - MI
Navy - MC

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project PACK-0896)

★U.S. GOVERNMENT PRINTING OFFICE: 1990--704-034/30401

Source: https://assist.dla.mil -- Downloaded: 2026-02-20 15:19Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-S-28786B	

3. DOCUMENT TITLE
Switches, Electrical and Fiber Optic, Packaging of

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON
Defense Electronics Supply Center		

c. ADDRESS (Include Zip Code)	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:
1507 Wilmington Pike Dayton, OH 45444-5276	Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD Form 1426, OCT 89 — Previous editions are obsolete. — 98.29C

Source: https://assist.dla.mil -- Downloaded: 20260-20T15:19Z
Check the source to verify that this is the current version before use.