INCH-POUND

MIL-M-28787/10B
AMENDMENT 1
31 March 1993

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

GATE, NAND, DIGITAL, KEY CODE GDB

This amendment forms a part of Military Specification MIL-M-28787/10B(EC), dated 8 June 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Test conditions H1-H8, Test type column: Delete "X" and substitute "S".

PAGE 6

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through U shall be performed in any order with the following exceptions. Test conditions A, B, C, H, and Q are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, H, or Q are part of a sequence of tests, the order of testing shall be as follows: Q, A, B, C, and H where applicable, followed by the remaining tests in the sequence."

4.5.1, line 5: Delete "C through N," and substitute "D through G, J through N,".

4.5.3, line 3: Delete "C through U" and substitute "D through G, J through P, and R through U".

4.5.3, line 6: Delete "C through U" and substitute "D through G, J through P, and R through U."

Custodians:
Army - ER
Navy - SH
Air Force - 85

Preparing activity:
Navy - NW

(Project 5963-0087)

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:25Z
Check the source to verify that this is the current version before use.