INCH-POUND

MIL-M-28787/6C
AMENDMENT 2
31 December 1992
SUPERSEDING
AMENDMENT 1
6 September 1983

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

COUNTER, BINARY, SYNCHRONOUS, DIGITAL, KEY CODE FDA

This amendment forms a part of Military Specification MIL-M-28787/6C(EC), dated 8 December 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 5

*TABLE I, Test conditions P1 and P2, Test type column: Delete "S" and substitute "X".

PAGE 8

*4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through JJ shall be performed in any order with the following exceptions. Test conditions A, B, C, D, and N are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, D, or N are part of a sequence of tests, the order of testing shall be as follows: D, A, B, C, and N where applicable, followed by the remaining tests in the sequence. If test conditions A and B are successively repeated, the time interval between performance of these test conditions shall be a minimum of 10 seconds to preclude detrimental effects due to module heating."

*4.5.1, line 6: Delete "C, E through P, and S through JJ" and substitute "E through M, P and S through JJ".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:23Z
Check the source to verify that this is the current version before use.

*4.5.4: Delete and substitute the following:

"4.5.4 Life test. The life test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 2. Following the life test and while still at the maximum class temperature, electrical tests E through M, P, and S through JJ shall be performed in the order specified in 4.4.2 using the operating temperature end-of-life requirements in table I. Following the return of the module to 25 ± 5°C, electrical tests E through M, P, and S through JJ shall be performed in the order specified in 4.4.2 using the 25 ± 5°C ambient end-of-life requirements in table I."

PAGE 9

6.3: Delete and substitute the following:

"6.3 Cross reference of classification. Military Specification MIL-M-28787/6 supersedes Department of the Navy, Naval Ordnance Systems Command Drawing No. 2658826. Part number M28787/6-1 supersedes part numbers 2658826 and M28787/6."

PAGE 17

*FIGURE 5, NOTE 2: Delete "moduel" and substitute "module".

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - SH
Air Force - 85

Preparing activity:
Navy - NW

(Project 5963-0084)

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:23Z
Check the source to verify that this is the current version before use.