INCH-POUND

MIL-M-28787/8B
AMENDMENT 1
31 March 1993

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

GATE, NAND, DIGITAL, KEY CODE GDC

This amendment forms a part of Military Specification MIL-M-28787/8B(EC), dated 4 August 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Test conditions H1-H8, Test type column: Delete "X" and substitute "S".

PAGE 6

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through U shall be performed in any order with the following exceptions. Test conditions A, B, C, H, and Q are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, H, or Q are part of a sequence of tests, the order of testing shall be as follows: Q, A, B, C, and H where applicable, followed by the remaining tests in the sequence."

4.5.1, line 5: Delete "C through P," and substitute "D through G, J through P,".

4.5.3, line 3: Delete "C through P," and substitute "D through G, J through P,".

4.5.3, line 6: Delete "C through U" and substitute "D through G, J through P, and R through U".

PAGE 54

FIGURE 20, Item C01 box: Delete "C01" and substitute "C06".

FIGURE 20, NOTE, first line: Delete "(C01)" and substitute "(C06)".

FIGURE 20, NOTE, second line: Delete "Frequency = 120 Hz." and substitute "Frequency = 1 KHz."

Custodians:
Army - ER
Navy - SH
Air Force - 85

Preparing activity:
Navy - NW

(Project 5963-0085)

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:24Z
Check the source to verify that this is the current version before use.