MILITARY SPECIFICATION

TRANSMITTING SET, RADIO, AN/FRT-84B(V)

This amendment forms a part of Military Specification MIL-T-28783B(EC), dated 18 August 1982, and is approved for use by the Naval Electronic Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1, "MIL-E-15090": Delete "(Formula No. 11)" and substitute "(Formula No. 111)".

PAGE 5

3.3.1.2.8, line 8: Delete "breaker" and substitute "breakers".

PAGE 6

3.3.1.14: Add the following new sentence:

"In addition to the unacceptable materials listed in MIL-E-16400, polychlorinated biphenyls, asbestos and asbestos compounds, fragile and brittle materials, beryllium and beryllium compounds (unless so identified), lithium and lithium compounds (unless specifically approved by the procuring activity) shall not be used in the transmitter."

PAGE 8

3.3.1.19.6, lines 1 and 2: Delete "18 kilograms (kg) (39.6 pounds (lb))" and substitute "16 kilograms (kg) (35 pounds (lb))".

PAGE 11

3.3.2.4, lines 7, 8, and 19: Insert hyphen between "phase" and "locked".

3.3.2.4, line 14: Delete "phase lock loop" and substitute "phase-locked loop".

3.3.2.4, line 17: Delete hyphen between "two" and "phase".

3.3.2.4.2, line 2: Insert hyphen between "phase" and "locked".

PAGE 13

3.3.2.19: Delete the text and substitute:

"In addition to the VFG hold time adjustment control specified in 3.3.2.10.2 and the STD OVEN indicator specified in 3.3.2.9.1.3, the exciter shall be equipped with controls, control-indicators, indicators, and meters specified in 3.3.2.19.1 through 3.3.2.19.17.3."

PAGE 17

3.3.2.19.16j: Delete and substitute:

"j. FREQ STD LOCK (see 3.3.2.19.16.1)".

3.3.2.19.17, line 3: Delete "3.3.2.19.17.1 through 3.3.2.19.17.3," and substitute "3.3.2.19.1 through 3.3.2.19.15,".

PAGE 18

3.3.3.6: Delete the text and substitute:

"The electronic keyer shall be equipped with controls specified in 3.3.3.6.1 through 3.3.3.6.2.3."

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:16Z
Check the source to verify that this is the current version before use.

PAGE 19

3.3.3.6.2, first sentence: Delete.

PAGE 26

TABLE II, "Switch positions 4 and 5", under "Function column": Delete "A" and substitute "amplifier".

PAGE 27

3.3.8.4, line 1: Delete "FSK".

PAGE 35

3.7.2.2, first sentence: Delete and substitute:

"The Procurement of equipments and subsystems having met other EMI requirements paragraph of MIL-STD-461 is applicable to this specification."

PAGE 39

3.7.5.4, first sentence: Delete and substitute:

"The Procurement of equipments and subsystems having met other EMI requirements paragraph of MIL-STD-461 is applicable to this specification."

PAGE 41

3.1.2.2, line 2: Delete "$0.04g^2/Hz$" and substitute "$0.02g^2/Hz$".

PAGE 46

TABLE VIII: Move last entry "Driver amplifier avg noise power output rating" to immediately precede "PP-6067A/FRT:".

PAGE 49

4.5.4.1, line 2: Delete "end item" and substitute "assembly".

4.5.4.1.1: Delete and substitute:

"4.5.4.1.1 Vibration set up conditions. The vibration shall be random or, subject to procuring activity approval, pseudorandom or complex waveform vibration, for an accumulated time of 10 minutes in the axis deemed most susceptible to vibration excitation. All items shall be hard-mounted (without shock isolators) and subjected to the vibration conditions of FIGURE 2. Input vibration levels shall be measured at the mounting points of the item under vibration. If variations are found at these points, the level used for control purposes shall be the avg of the levels at the mounting points. Control equipment having a bandwidth no greater than 10 Hz for vibration frequencies above 500 Hz shall be used for the control analysis of the acceleration spectral density (ASD). The instantaneous acceleration peaks shall be limited to three times the rms acceleration level."

4.5.4.2, last three sentences: Delete and substitute:

"The dwell time shall be maintained until the largest electrical or electronic part in the transmitter reaches 80 percent of the chamber temperature. When failures occur, the transmitter shall be reworked and the cycling continued for a cumulative total of 10 cycles."

Source: https://assist.dla.mil -- Downloaded: 20261O-20T15:16Z
Check the source to verify that this is the current version before use.

FIGURE 2: On the "ASD axis (vertical axis)": Delete "0.04" and substitute "0.02".

4.5.5: Add after paragraph title:

"Leakage current shall be measured at each of the nominal three phase power line voltages and frequency limits specified in 3.3.1.2.4.1 and at each of the nominal single phase power line voltages and frequency limits specified in 3.3.1.2.7."

Preparing activity:
Navy - EC
(Project 5840-N209(EC))

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:16Z
Check the source to verify that this is the current version before use.