NOT MEASUREMENT SENSITIVE
MIL-L-11484/160A
7 September 1989
SUPERSEDING
MIL-L-11484/160
17 March 1988

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, ACHIEVEMENT MEDAL FOR CIVILIAN SERVICE, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense. The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.



MATERIAL: Gilding Metal

DIMENSIONS INCHES (METRIC):

DIAMETER: 5/8 Inch (1.59 cm) (REF)
THICKNESS (Edge): .065 inch (0.165 cm) ± .010 inch (0.025 cm) (REF)

FINISH: ENAMELED, OXIDIZED, RELIEVED, POLISHED HIGHLIGHTS.

NOTES:
1. The attaching device shall be a prong with pick and clutch.
2. The prong shall be 5/16 inch (0.79 cm) ± 1/64 inch (0.04 cm) long and shall be centered on reverse face. The prong may be fused or hard soldered to lapel button at the option of the manufacturer.
3. Enameled areas shall be as indicated and shall match TIOH blue color chip #18.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA-CT

(Project No. 8455-A426)

User activities:
Army - IH

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:05Z
Check the source to verify that this is the current version before use.