NOT MEASUREMENT SENSITIVE

MIL-L-11484/160B
14 January 1994
SUPERSEDING
MIL-L-11484/160A
7 September 1989

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, ACHIEVEMENT MEDAL FOR CIVILIAN SERVICE, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.



MATERIAL: Gilding Medal

DIMENSIONS:
DIAMETER: 5/8 inch (1.59 cm) (REF)
THICKNESS (At Edge): 0.065 inch ± 0.005 inch (0.165 cm ± 0.012 cm)

FINISH: Hard Enameled, Oxidized, Relieved, Polished Highlights

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:05Z
Check the source to verify that this is the current version before use.

2. Enameled area shall be blue as indicated. The color shall conform to the TIOH color chip number 18 or the standard sample.

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer.

4. Attaching device shall be prong with pick and wing type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

Custodians:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0745)

Source: https://assist.dla.mil - Downloaded: 2026-10-17T17:05Z
Check the source to verify that this is the current version before use.