INCH - POUND

MIL-DTL-11484/165D
9 April 2018
SUPERSEDING
MIL-DTL-11484/165C
3 November 2015

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, EXCEPTIONAL ENGINEERING ACHIEVEMENT MEDAL, NASA

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: 24K Gold Plated, Matte Finish Polished Highlights and shall match The Institute of Heraldry Metal Finish Chip Number 8.

DIMENSION:
DIAMETER: 9/16 inch (REF)
THICKNESS (At thickest point): 0.080 inch $\pm$ 0.005 inch

ATTACHING DEVICE:
1. The attaching device shall be prong with pick and flat ball type clutch.

2. The prong shall be centered on the reverse side and fused or soldered to the label button.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:06Z
Check the source to verify that this is the current version before use.

NOTES:
1. The term (REF) refers to the measurements taken from the obverse Government furnished hub or die.

2. Lapel button shall be lacquered.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2018-163)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:06Z
Check the source to verify that this is the current version before use.