MILITARY SPECIFICATION SHEET
CHAFF ROVING BUNDLE (TYPE RR-179/AL)

This specification is approved for use within the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the chaff roving bundle described herein shall consist of this specification and the latest issue of MIL-C-85691.

APPLICABLE DOCUMENTS:

Military:

MIL-R-60346	Roving, Glass, Fibrous

REQUIREMENTS:

Item definition: A chaff roving bundle assembly comprised of aluminum coated glass filaments of the quantity and type specified herein.

Item description: Shall be "Chaff Roving Bundle, RR-179/AL."

Detail requirements:

Roving assembly: Chaff roving bundle shall be comprised of a continuous strand of 3000 metalized glass fibers in accordance with MIL-C-85691 and DL 1050AS160.

Chaff filaments:

Filament material: Glass monofilament coated continuously with aluminum.

Glass monofilament: Type E glass made from a composition similar to that specified in MIL-R-60346.

Glass monofilament diameter: 0.95 mil maximum.

Aluminum coating: 99 percent or purer aluminum shall cover the length continuous and cover 30 percent minimum of the circumference at no less than 0.06 mil thickness. The weight

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:24Z
Check the source to verify that this is the current version before use.

of the coated monofilament shall be 12 grams +/-1.8 grams per ten feet of roving.

Binder: Applied to filament material in accordance with MIL-C-85691.

Assembly:

Chaff roving bundle: Shall be fabricated in accordance with MIL-C-85691. Rovings shall be wound in such a way as to allow removal from the inside to the outside without entangling or knotting.

Chaff roving bundle weight: Gross weight of the roving bundle shall be not less than 40 pounds +4, -2 pounds.

Chaff roving bundle dimensions: Height 12.25 inch +/-0.25, Diameter 10.44 inch +0, -0.25, Rim Thickness 3.75 inch +/-0.25 (See 1050AS160).

Packaging, marking, preservation and palletizing: Shall be in accordance with MIL-C-85691, DL1050AS161 and DL1050AS163.

Quality assurance provisions:

Radar requirements: Use M-33 radar or approved equivalent radar.

Frequency: 9.050 +/- 0.453 GHz

PRF: 1000 +/- 100 pps

Pulsewidth: 0.25 us

Radar cross-section (RCS) test procedures:

Aircraft operation: In accordance with Figure 2 of MIL-C-85691 and flight profile data of Table I.

TABLE I. Flight profile test data

Flight requirement	Value
Aspect Angle	5 -20
Aircraft Speed	250 kts. TAS
Altitude	1500 feet
Dispense Command	5,000 yards

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:24Z
Check the source to verify that this is the current version before use.

TABLE 1. Flight profile test data - continued

Standby Command	6,000 yards
Cutter Roller	0.58 inch
Dispense Rate	300 inches per seconds

Data gathering:

Standby command: See TABLE I.

Dispense command: See TABLE I.

Data processing:

A sufficient number of runs will be conducted to allow 100 units of 1024 pules to be processed and averaged. Gates seven through ten will be used for averaging.

Correction factors:

Antenna gain: Antenna pattern as specified in MIL-STD-2071 or order polynomial.

Fourth order polynomial for radar for M-33 or approved equivalent radar:

$14{,}824X^4 - 18.7422X^3 + 8.86719X^2 - 1.36035X + 1.0220$ (where X = angle off boresite degrees).

Loading requirements:

One chaff roving bundle shall be loaded for dispensing. The roving shall be threaded through the chaff cutter and power applied for not less than of two seconds to insure system operation.

Radar cross-section (RCS):

One hundred units of 1024 pules each, will average not less than 2 3.5m when corrected for boresight and aspect.

Preparing Activity
Navy - AS
(Project 5865-N061)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:24Z
Check the source to verify that this is the current version before use.