MILITARY SPECIFICATION

NETWORKS, CAPACITOR-RESISTOR

This specification is approved for use by the U.S. Army Armament Research and Developmemt Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification provides quality assurance provisions for the fabrication and packing of Fixed Film Resistors and Ceramic Capacitors Networks for use in various Scatterable Mines.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-R-39032	-	Resistors, Preparation For Delivery of
MIL-R-83401	-	Resistor Networks, Fixed Film, General Specification for
MIL-N-87144	-	Networks, Fixed Film Resistors And Ceramic Capacitors, General Specification For

FSC 1345

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:47Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures And Tables For Inspection By Attributes
MIL-STD-202	-	Test Methods for Electronics and Electrical Component Parts
MIL-STD-883	-	Test Methods and Procedures for Microelectronics
MIL-STD-1188	-	Commercial Packaging of Supplies and Equipment
MIL-STD-1285	-	Marking of Electrical and Electronic Parts
MIL-STD-45662	-	Calibration Systems Requirements

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9292137	- Network, Capacitor-Resistor
9292138	- Network, Capacitor-Resistor

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

3. REQUIREMENTS

3.1 General. The manufacturer of capacitor-resistor networks in compliance with this specification shall have production and test facilities and a quality and reliability assurance program adequate to assure successful compliance with the provisions of this specification. Only networks which are inspected for and meet all of the requirements specified herein shall be marked and delivered.

3.2 Detail specification. The complete requirements for the networks shall be in accordance with Drawing 9292137/9292138 (detailed drawings), as specified in this detail specification and MIL-N-87144.

3.3 Design and construction. The networks shall consist of a dual coated ceramic substrate with conductors, insulating and resistance and capacitance patterns applied by thick film-hybrid techniques in the order necessary to meet the requirements of this specification. The element values between terminals shall be in accordance with the tables and network schematics in detailed drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:47Z
Check the source to verify that this is the current version before use.

3.3.1 Solderability. Terminal leads shall be free of foreign material, flash marks, and other irregularities and conform to the requirements of DUG 9292137/9292138. Leads shall also be conditioned for machine insertion,

3.3.2 Enclosure. The network shall be coated and encapsulated to withstand the environmental tests as specified in detailed drawings and this specification.

3.3.3 Physical Dimensions. The physical dimensions of the resistor network package shall comply with all requirements in detailed drawing. Inspection of the physical dimensions shall be in accordance with MIL-STD-883, Method 2016.

3.4 Electrical characteristics.

3.4.1 Capacitor-Resistor network characteristics. When capacitor-resistor networks are subjected to the test or condition specified in Table I the percent change in resistance or in capacitance in each element shall not exceed the value specified in Table I. The condition or test requirement method shall be in accordance with MIL-N-87144 for characteristic *M* resistor networks unless otherwise specified herein. The condition or test requirement method for capacitors shall be in accordance with those specified in this specification or when applicable in accordance with MIL-N-87144.

3.4.1.1 Resistance. Resistance and tolerance values are specified on DWG 9292137/9292138.

3.4.1.2 Capacitance. Capacitance and tolerance values are specified on DWG 9292137/9292138.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:47Z
Check the source to verify that this is the current version before use.

TABLE I. Resistor-Capacitor Network Characteristics.

Test or Condition	1/ Requirement Paragraph		Value		Units
	Herein	MIL-N-87144	For Resistor Elements*	For Capacitor Elements	
Thermal Shock		3.7	± 0.5	± 10	Percent Change
Power And Voltage Conditioning		3.8	± 0.5	± 10	Percent Change
DC Resistance	3.3,3.4.1	3.9	See dwg.	-	
Capacitance	3.3,3.4.1	3.10		± 10	Percent Change
Dissipation Factor		3.11		± 3	Percent Change
Physical Dimensions	3.3.3		See dwg.		
Visual & Mechanical Examination	3.2				
Solderability	3.3.1				
Resistance To Solvents	3.5.2				
Resistor-Temperature Characteristic		3.14.1	+ 250		PPM/°C
Dielectric Withstanding Voltage (Network)		3.18.1			
Capacitor-Temperature Characteristic		3.14.2	-	See 3.14.2	Percent Change
Low Temperature Operation		3.15	± 0.5	± 10	Percent Change
Short Time Overload		3.16	± 0.5	-	Percent Change
Terminal Strength		3.17	± 0.25	See 3.17	Percent Change
Dielectric Withstanding Voltage (Capacitor)		3.18.2	-		
Insulation Resistance		3.19	$10x10^3$	See 3.19.2	Megohms
Resistance To Soldering Heat		3.20	± 0.25	± 5	Percent Change
Moisture Resistance		3.21	± 0.5	See 3.21	Percent Change
Shock (Mechanical) Specified Pulse		3.22	± 0.25	-	Percent Change
Vibration-High Frequency		3.23	± 0.25	See 3.23	Percent Change
Life		3.24	± 2.0	See 3.24	Percent Change
Power Rating	3.4.4		± 0.5	-	Percent Change
Low Temperature Storage		3.26	± 0.5	See 3.26	Percent Change

1/ The headings for test or conditions above are the prime references to MIL-N-87144, paragraph numbers are given to possibly facilitate locating references.

* + 0.01 ohm to be added percent change for resistor elements

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:47Z
Check the source to verify that this is the current version before use.

3.4.2 Maximum voltage. The maximum continuous working voltage applied to the resistor elements shall be 25 volts d.c. or 25 volts rms (root-mean-square, sine-wave).

3.5 Device marking.

3.5.1 Marking. Each network shall be marked in accordance with Method 1 of MIL-STD-1285 as follows:

a. Part number revision code: part number plus revision letter.

b. Supplier's code symbol.

c. Inspection lot date code: first two digits shall be the last two digits of the number of the year. The third and fourth digits shall indicate the calendar week of the year.

d. Pin No. 1 identifier, see DWG 9292137/9292138.

3.5.2 Resistance to solvents. Markings on the networks shall be legible after being subjected to the resistance to solvents test of MIL-STD-202. Method 215.

3.6 Data requirements. Data shall be recorded on a go/no-go basis and retained for all tests called out by this specification (see 6.4).

3.7 First article inspection. This specification contains provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship. Each network shall be fabricated and finished in a thorough, workmanlike manner consistent with the best practices of the industry. It shall be free of dirt, corrosion products and other foreign matter. The cleaning method used shall not be injurious to the network. Also, the parts shall be free of harmful cleaning and soldering agents that may be injurious to the thick film (TF). All markings and stampings, shall be displayed and visibly defined. The TF shall be-manufactured and processed in such a manner as to be uniform in quality and free from defects that will affect life, configuration and serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-N-87144 shall apply and are hereby made a part of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:47Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First article inspection.

b. Quality conformance inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of sixty (60) C-R networks.

4.3.2 Inspections to be performed. See Table II specified herein. It is the intent of this document to have the capacitor and resistor element tests run simultaneously or successively, as applicable, to improve efficiency in running the tests.

4.3.3 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of the item in the sample to comply with any of the stated requirements.

4.3.4 Requalification. The device shall be subjected to another First Article as stipulated in the contract if:

a. The contractor's manufacturing techniques or process controls which affect the form, fit, function or internal geometry of the device are revised by either the contractor or one of his sub-contractors supplying parts or assemblies.

b. The contractor relocated his assembly facilities.

c. The contractor uses a new sub-contractor for material, parts, or assembly.

d. A change occurs in devices' material, performance or assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:47Z
Check the source to verify that this is the current version before use.

TABLE II. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-N-63400(AR)

PARAGRAPH	TITLE: Network, Capacitor-Resistor		SHEET 1 OF 2		DRAWING NUMBER: 9292137 or 9292138
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Group I Non-destructive	60		3.4.1	MIL-N-87144 1/
	Physical dimensions			3.3.3	MIL-STD-883, Method 2016
	Visual and Mechanical Examinations			3.2,3.3, 3.3.2, 3.5,3.8	* 4.5.1
	Thermal shock				4.6.3
	Power and voltage conditioning			3.4.1, 3.4.2	4.6.4
	DC resistance				4.6.5
	Dielectric withstanding voltage of the capacitor				4.6.14.2
	Capacitance				4.6.6
	Dissipation Factor				4.6.7
	Insulation resistance of the capacitor				4.6.15.2
	Group II	10			
	Solderability			3.3.1	MIL-STD-202, Method 208
	Resistance to solvents			3.5.2	MIL-STD-202, Method 215
	Group III	10		3.4.1	MIL-N-87144
	Resistance-temperature characteristic				4.6.10.1, 2/ Sheet 2 herein
	Capacitance-temperature characteristic				4.6.10.2, 3/ Sheet 2 herein
	Low temperature operation				4.6.11
	Short time overload			3.4.1, 3.4.2	4.6.12
	Terminal Strength				4.6.13

NOTES: All sixty (60) sample units shall be subjected to Group I test and IA examinations and provided there are zero rejects then divided as shown for groups II thru VII inclusive and subjected to the tests for their particular group. All groups tests and examinations are to be conducted in the order shown. *Method paragraph herein.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:47Z
Check the source to verify that this is the current version before use.

TABLE II. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-N-63400(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	Network, Capacitor-Resistor				9292137 or 9292138
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Group IV	10		3.4.1	MIL-N-87144
	Dielectric withstanding voltage				4.6.14
	Insulation resistance				4.6.15
	Resistance to soldering heat				4.6.16
	Moisture resistance				4.6.17
	Group V	10			
	Shock (specified pulse)			3.4.1	4.6.18
	Vibration, high frequency			3.4.1	4.6.19
	Group VI	10			
	Life			3.4.1	4.6.20
	Group VII	10			
	Low temperature storage			3.4.1	4.6.22

NOTES: 1/ Test headings given for first article are the prime references to MIL-N-87144, paragraph numbers are given to possibly facilitate locating references. 2/ Follow the sequence called out by MIL-N-87144, Table IX, titled "Resistance-temperature characteristics". 3/ Follow the sequence called out by MIL-N-87144, Table X, titled "Capacitance-temperature characteristics"

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:47Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provision of MIL-N-87144.

4.4.2 Examination. Inspection of product for delivery shall consist of groups A and B. See 4.4.2.1 thru 4.4.2.6 herein.

4.4.2.1 Group A inspection. Group A inspection shall consist of the examinations and test specified in 4.4.2.4, and shall be made on the same set of sample units, in the order shown.

a. Sampling plan. Sampling and inspection for subgroups 1 and 2 shall be in accordance with MIL-STD-105 for general inspection level II.

4.4.2.2 Group B inspection. Group B inspection shall consist of the tests specified in 4.4.2.5, in the order shown. They shall be performed on sample units that have been subjeted to and have passed the Group A inspection.

a. Sampling plan. Sampling and inspection shall be in accordance with MIL-STD-105 for special inspection level S-4 with an AQL of 2.5 percent. Samples units which have passed all the Group B inspections may be delivered on the contract provided they are within tolerance and meet requirements for visual and mechanical inspection.

4.4.2.3 Group C inspection. Group C inspection shall consist of the tests specified in 4.4.2.6, in the order shown. They shall be performed periodically, as specified in 4.4.2.6, on sample units selected from lots that have passed groups A and B inspection.

a. Sampling plan. The sample size for each subgroup in 4.4.2.6 shall be 10 units. Sample units which have been subjected to group C inspection shall not be delivered on the contract. If rejects exceeds those allowed in 4.4.2.6, supplier shall perform failure analysis and furnish copy to technical agency listed in 6.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:47Z
Check the source to verify that this is the current version before use.

Quality conformance inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-N-63400(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Network, Capacitor-Resistor		9292137 or 9292138
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Group A, Subgroup I (non-destructive tests)				
	Thermal shock		0.40%	3.4.1	MIL-N-87144, 4.6.3, 3/
	Power and voltage conditioning		0.40%	3.4.1, 3.4.2	MIL-N-87144, 4.6.4
	DC resistance 4/		0.40%	3.4.1	MIL-N-87144, 4.6.5
	Dielectric withstanding voltage of the capacitor 4/		0.40%	3.4.1	MIL-N-87144, 4.6.14.2
	Capacitance 4/		0.40%	3.4.1	MIL-N-87144, 4.6.6
	Dissipation Factor 4/		0.40%	3.4.1	MIL-N-87144, 4.6.7
	Insulation resistance of the capacitor 4/		0.40%	3.4.1	MIL-N-87144, 4.6.15.2
	Group A, Subgroup 2 (non-destructive)	1/	1.0%		
	Physical dimensions			3.3.3	MIL-STD-883, Method 2016
	Visual and mechanical examinations	2/		3.2,3.3, 3.3.2, 3.5,3.8	4.5.1 herein
	Group A, Subgroup 3				
	Solderability (all terminals)	10	0-1	3.3.1	MIL-STD-202, Method 208

NOTES: 1/ See 4.4.2.2.a. 2/ Body: cracks or holes which would cause probable failure; Leads: leads broken, crushed or nicked which would cause probable failure in use, lead spacing incorrect; Markings: incorrect, illegible. 3/ Headings listed for tests are prime references to MIL-N-87144, paragraph numbers are given to possibly facilitate locating references. 4/ Performed as part of the thermal shock and power and voltage conditioning.

Source: https://assist.dla.mil -- Downloaded: 2026-03-23T02:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-N-63400(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Network, Capacitor-Resistor		9292137 or 9292138
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Group B (non-destructive) See 4.4.2.2.a		2.5%	3.4.1	MIL-N-87144, 2/
	Resistance-temperature characteristic				4.6.10.1
	Capacitance-temperature characteristic				4.6.10.2
	Dielectric withstanding voltage (network)				4.6.14.1
	Insulation resistance (network)				4.6.15.1
	Short-time overload			3.4.1, 3.4.2	4.6.12
	Dielectric withstanding voltage of the capacitor			3.4.1	4.6.14.2
	Capacitance			3.4.1	4.6.6
	Dissipation factor			3.4.1	4.6.7
	Insulation resistance of the capacitor			3.4.1	4.6.15.2
	Packaging		1/	5.2	MIL-R-39032
	Packing		1/	5.3	MIL-R-39032
	Marking		1/	5.4	MIL-R-39032, MIL-STD-1188

NOTES: 1/ Sample and accept and reject as per MIL-R-39032 for visual and dimensioning. 2/ Test headings listed above are prime references to MIL-N-87144, paragraph numbers are given to possibly facilitate locating references.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-N-63400(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Network, Capacitor-Resistor	1 OF 1	9292137 or 9292138
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST 1/, 2/	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Group C, Monthly	10	1-2	3.4.1	MIL-N-87144, 3/
	Low-temperature operation				4.6.11
	Short-time overload			3.4.1, 3.4.2	4.6.12
	Terminal strength				4.6.13
	Group C, Subgroup 1, Quarterly	10	1-2	3.4.1	
	Dielectric withstanding voltage (network)				4.6.14
	Insulation resistance (network)				4.6.15
	Resistance to soldering heat				4.6.16
	Moisture resistance				4.6.17
	Subgroup 2	10	1-2	3.4.1	4.6.20
	Life				
	Group C, Subgroup 1, Semiannually	10	1-2	3.4.1	
	Shock (specified pulse)				4.6.18
	Vibration, high frequency				4.6.19
	Subgroup 2	10	0-1		
	Solderability			3.3.1	MIL-STD-202, Method 208
	Resistance to solvents			3.5.2	MIL-STD-202, Method 215
	Subgroup 3	10	1-2		
	Low temperature storage			3.4.1	4.6.22

NOTES: 1/ The ten (10) samples per subgroup: samples shall be subjected to the tests in each subgroup in order shown. 2/ DESTRUCTIVE TESTS: Sample units shall not be delivered on the contract. * Method paragraph herein. 3/ Test headins listed above are prime references to MIL-N-87144, paragraph numbers are given to possibly facilitate locating references.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026/10-23T02:47Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection forms.

4..4.4 Inspection equipment. The inspection equipment required to perform the examinations and test prescribed herein is described in the "Paragraph Reference/Inspection Method Column" of the First Article and Quality Conformance forms. Test and measuring equipment and inspection facilities of sufficient accuracy, quality and quantity to permit performance of the required inspection shall be established and maintained by contractor. The establishment and maintenance of a calibration system to control the accuracy of the measuring and test equipment shall be in accordance with MIL-STD-45662. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract (see 6.3).

4.5 Methods of examination and test. The methods of examination and test shall be in accordance with MIL-N-87144 for resistor and capacitor elements inspection.

4.5.1 Visual and mechanical examination. Capacitor-Resistor networks shall be examined to verify that the materials, design, contsruction, physical dimensions, markings per MIL-STD-1285, and workmanship are in accordance with the applicable requirements (See 3.2, 3.3, 3.3.2, 3.3.3, 3.5 and 3.8).

5. PACKAGING

5.1 Preservation - Packaging. The C-R networks shall be packaged in accordance with the requirements specified for resistor networks (those covered by MIL-R-83401) level B of MIL-R-39032.

5.2 Packing. The C-R networks shall be packed in accordance with level B of MIL-R-39032.

5.3 Marking. The packed components shall be marked in accordance with the commercial requirements of MIL-STD-1188.

5.4 Shipping. When C-R networks from more than one lot are shipped together, each lot shall be kept separate, and the divisions between lots clearly indicated to prevent mixing of lots in transit.

6. NOTES

6.1 Intended use. The networks covered by this specification are intended for single-use, non-repairable military devices.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:47Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Provisions of submission of first article samples.

c. Quantity required and delivery schedules.

d. Certificates of conformance for each lot or shipment of product.

6.3 Submission of inspection equipment designs for approval. (See 4.4.4). Submit equipment designs, DI-R-1714 Tailored, as required to Commander: U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAA-I, Dover, New Jersey 07801.

6.4 Distribution of inspection failure and analysis data reports. Distribution of inspection failures and analysis data reports shall include the following: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAA-M, Dover, New Jersey 07801.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADOM.

Custodian:
Army -AR

Preparing Activity:
Army-AR

(Project 1345-A119)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:47Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-N-63400 NETWORKS, CAPACITY-RESISTOR

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO

DATE

DD FORM 1 OCT 78 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:47Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament R&D Command
Attn: DRDAR-QAA
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:47Z
Check the source to verify that this is the current version before use.