MIL-P-50571A (AR)
3 November 1978
SUPERSEDING
MIL-P-50571 (MU)
14 July 1971

MILITARY SPECIFICATION

PROJECTILE, 155MM, HE, ROCKET ASSISTED
M549 & M549A1, DELAY ASSEMBLY
PARTS FOR

This specification is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense

1. SCOPE

1.1 This specification contains requirements not covered by the drawings and provides quality assurance provisions for the fabrication of delay assembly parts for the 155MM Rocket Assisted Projectile, M549.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-45662 - Calibration System Requirements
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-1169 - Packaging, Packing and Marking for Interplant Shipment of Inert Ammunition Components, General Specification For

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC: 1320

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

9235980 - Housing, Delay
9235981 - Plug, Igniter
9235982 - Washer, Delay

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts.-The parts shall comply with all requirements specified on drawings listed in paragraph 2.1 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 First article inspection.-This specification makes technical provisions for first article inspection. Requirements for the submission of first article sample by the contractor shall be as specified in the contract.

3.4 Workmanship.-All parts shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, unblended radii, tears, holes, porosity, dirt, and grease. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions.-Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections.-The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

4.3 First article inspection

4.3.1 Submission.-The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
Housing, Delay	9235980	10
Plug Igniter	9235981	20 Consecutively produced from each cavity of each mold
Washer, Delay	9235982	10

4.3.2 Inspections to be performed.-See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection.-See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-50571A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Delay Assembly Parts				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Housing, Delay (Dwg. 9235980)				
	Examination for Defects	10	-	3.2	4.4.2.1
	Plug, Igniter (Dwg. 9235981)				
	Examination for Defects	20/ Cavity	-	3.2	4.4.2.3
	Washer, Delay (Dwg. 9235982)				
	Examination for Defects	10	-	3.2	4.4.2.2

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation.-Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination.-See MIL-A-48078.

a. Sampling plans.-Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 3		DRAWING NUMBER
4.4.2.1	Housing, Delay				9235980
					NEXT HIGHER ASSEMBLY
					9236005
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Two delay column holes do not break through counterbore at tube		100%	3.2	Visual
102	Minor thread diameter		0.40%	3.2	Gage
103	True position of thread to thread counterbore		0.40%	3.2	Gage
104	Diameter of thread counterbore		0.40%	3.2	Gage
105	Surface finish of thread counterbore		0.40%	3.2	Visual
106	Minimum effective thread		0.40%	3.2	Gage
107	Diameter of two column holes		0.40%	3.2	Gage
108	Knurl missing		0.40%	3.2	Visual
109	Location of 1.539 basic diameter		0.40%	3.2	Gage
110	Location of .947 basic diameter		0.40%	3.2	Gage
111	Circular runout of 1.539 basic diameter		0.40%	3.2	Gage
112	Circular runout of .947 basic diameter		0.40%	3.2	Gage
113	Depth of O-ring groove		0.40%	3.2	Gage
114	Diameter of counterbore hole intersecting two column holes		0.40%	3.2	Gage
115	Outside diameter of tube		0.40%	3.2	Gage
116	Protective finish on outside surface		0.40%	3.2	Visual
117	Depth of two column holes		0.40%	3.2	Gage
118	Distance from end surface to two column holes		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-50571A (AR)

PARAGRAPH	TITLE		SHEET 2 OF 3		DRAWING NUMBER
4.4.2.1	CONTINUATION SHEET				9235980
					NEXT HIGHER ASSEMBLY
					9236005
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	True position of counterbore with tube		0.65%	3.2	Gage
202	Circular runout of thread shoulder to thread counterbore		0.65%	3.2	Gage
203	Chamfer at thread counterbore missing		0.65%	3.2	Visual
204	True position of 2 column holes to tube		0.65%	3.2	Gage
205	Outside diameter adjacent to 1.539 basic diameter		0.65%	3.2	Gage
206	Diameter of surface before knurling		0.65%	3.2	Gage
207	Distance large end surface to chamfer at large outside diameter		0.65%	3.2	Gage
208	Width of O-ring groove		0.65%	3.2	Gage
209	Location of O-ring groove		0.65%	3.2	Gage
210	Corner radii of O-ring groove missing		0.65%	3.2	Visual
211	Surface finish of O-ring groove		0.65%	3.2	Visual
212	Overall length		0.65%	3.2	Gage
213	Distance large end surface to shoulder at tube		0.65%	3.2	Gage
214	Distance end of tube to web between two column holes		0.65%	3.2	Gage
215	Distance end of tube to chamfer at bottom of tube		0.65%	3.2	Gage
216	True position of counterbore intersecting 2 column holes		0.65%	3.2	Gage
217	Wall thickness of tube		0.65%	3.2	Gage
218	Wall thickness of tube at groove		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-50571A (AR)

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER
4.4.2.1	CONTINUATION SHEET				9235980
					NEXT HIGHER ASSEMBLY
					9236005
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
219	Angle of groove in tube		0.65%	3.2	Gage
220	Location of groove in tube		0.65%	3.2	Gage
221	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-50571A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Washer, Delay				9235982
					NEXT HIGHER ASSEMBLY 9235983
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
Minor					
201	Inside diameter		0.65%	3.2	Gage
202	Protective finish missing		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.0%	3.4	Visual
204	Thickness		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Plug, Igniter				9235981
					NEXT HIGHER ASSEMBLY
					9235983
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter	Note a	0.40%	3.2	Gage
Minor					
201	Inside diameter	Note a	0.65%	3.2	Gage
202	Inside wall thickness	Note a	0.65%	3.2	Gage
203	Overall length	Note a	0.65%	3.2	Gage
204	Evidence of poor workmanship	Note a	1.0%	3.4	Visual

NOTES:
a. See paragraph 4.4.3.1.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.-Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.3.1 Molded components.-After production of 10,000 pieces per cavity per mold, 20 pieces from each cavity of each mold shall be consecutively produced and inspected for all drawing and specification requirements and verified by the Government inspector. If any part fails to meet all drawing or specification requirements, production shall be stopped and the mold corrected. During production, the molding procedures shall be monitored for uniformity of molding practices. Suspected deviation in mold product shall be examined to determine if corrective action or mold repair is required. If during production correction or repair is required, 20 consecutively produced units from each affected mold cavity shall be inspected and shall comply with all drawing and specification requirements.

4.4.4 Inspection equipment.-The inspection equipment required to perform the examinations and tests prescribed herein is described in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6 herein.

4.5 Methods of inspection

4.5.1 Materials, components and processes.-Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and mechanical inspections.-The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Sections 3 and 5 of this specification in accordance with 4.4.2 herein and Table I.

5. PACKAGING

5.1 Packaging, packing and marking.-Packaging, packing and marking shall be in accordance with MIL-STD-1169.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use.-The components covered by this specification are intended for use on the 155MM Rocket Assisted Projectile, M549.

6.2 Ordering data.-See MIL-A-48078.

6.3 Submission of inspection equipment for design approvals - See MIL-A-48078.-Submit designs as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, NJ 07801.

6.4 Data requirements.-Data cards shall be prepared for each lot in accordance with the information specified in MIL-STD-1167.

6.5 Drawings.-Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

6.6 Changes from previous issue.-Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army - AR

Preparing activity:
Army - AR

Project No. 1320-A435

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-P-50571A PROJECTILE 155MM HE ROCKET ASSISTED M549 & M549A1 DELAY ASSY PARTS FOR

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
US ARMY ARMAMENT RESEARCH & DEVELOPMENT COMMAND
ATTN: DRDAR-QAR
DOVER, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

NOTICE
OF VALIDATION

MIL-P-50571A(AR)
NOTICE 1
21 May 1987

MILITARY SPECIFICATION

PROJECTILE, 155MM, HE, ROCKET ASSISTED
M549 AND M549A1, DELAY ASSEMBLY
PARTS FOR

MIL-P-50571A(AR), dated 3 November 1978, has been reviewed and determined to be valid for use in acquisition.

Preparing activity:
Army - AR

AMSC N/A

FSC 1320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-22T20:23Z
Check the source to verify that this is the current version before use.

INCH-POUND

MIL-P-50571A (AR)
AMENDMENT 1
03 FEBRUARY 1989

MILITARY SPECIFICATION

PROJECTILE, 155MM, HE, ROCKET ASSISTED
M549 & M549A1, DELAY ASSEMBLY
PARTS FOR

This Amendment forms a part of Military Specification MIL-P-50571A (AR), dated 3 November, 1978 and is approved for use within the US Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of Defense.

PAGE 6

4.4.2.1 Add the following Major Defects:

"119. Position of two washer seats - 0.40% 3.2 Gage
120. Diameter of two washer seats - 0.40% 3.2 Gage
121. No sharp corners on column holes (2 places) - 0.40% 3.2 Visual"

PAGE 8

4.4.2.1 Add the following Minor Defect:

"222. Depth of washer seat - 0.65% 3.2 Gage".

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1320-A881)

AMSC N/A

FSC 1320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.