MILITARY SPECIFICATION

PROJECTILE, 20MM, HEIT-SD, M246; METAL PARTS

1. SCOPE

1.1 This specification covers the body assembly (painted) for Projectile, 20mm, HEIT-SD, M246.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-C-490 - Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings

MILITARY

MIL-S-46070 - Steel Bar for Projectile Stock

STANDARDS

FEDERAL

Federal Test Method Standard No. 151 - Metals; Test Methods

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-651 - Visual Inspection Standards for 20mm Ammunition and Components

Source: https://assist.dla.mil -- Downloaded: 20261O-23T00:55Z
Check the source to verify that this is the current version before use.

STANDARDS (Contd)
MILITARY

MIL-STD-1168	- Lot Numbering of Ammunition
MIL-STD-1169	- Packaging, Packing, and Marking for Shipment of Inert Ammunition Components
MIL-STD-1235	- Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

MUNITIONS COMMAND

D10542425	- Projectile, 20mm, HEIT-SD, M246, Metal Parts
D10542426	- Projectile, 20mm, Body and Rotating Band Assembly
B7258816	- Blank, Rotating Band, for Projectiles, 20mm
F7258861	- Carton for Interplant Shipment of Projectiles, 20mm, Assemblies and Metal Parts Assemblies (200)
D7259136	- Shipping Container for Inert Projectile, 20mm Assemblies and Metal Parts Assemblies (10,000)
D10542434	- Cartridge, 20mm, for Projectile, HEIT-SD, M246, Metal Parts Security Test
IEL 10542425	- Inspection Equipment Lists for: Projectile, 20mm, HEIT-SD, Metal Parts

PUBLICATIONS

U.S. ARMY MATERIEL COMMAND

AMCR 715-505	- Ammunition Ballistic Acceptance Test Methods, Volume 8, Test Procedures for 20mm Cartridges

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions shall be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials.-Materials shall be in accordance with applicable drawings and specifications. Prior to producing projectile bodies from a heat of steel, the contractor shall conduct tests in his own laboratory or other facilities and services acceptable to the Government, to verify that the bar stock meets the requirements of MIL-S-46070(MU).

3.2 Parts and assembly.-The parts and assemblies shall comply with all the requirements of Drawing (Dwg.) D10542425 and with all requirements of the drawings and specifications shown thereon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:55Z
Check the source to verify that this is the current version before use.

3.3 Manufacturing process.-All parts and assemblies shall be manufactured by a process approved by the contracting officer and no deviation from that process shall be made without his prior approval. (see 6.3)

3.4 Banding.-The rotating band blank and the rotating band seat shall be clean at the time of banding. Shot or sandblasting shall not be used to clean the rotating band seat after knurling. The rotating band blank shall fill the band seat except that the average radial void between the seated band and the band seat knurling shall not exceed 0.004 inch.

3.5 Soundness.-Metal discontinuity in the projectile body, as determined by eddy current inspection, shall be less than that represented by Production Check Standard (PCS) No. 1.

3.6 Protective coating.

3.6.1 Phosphate coating.-The pretreatment process used shall comply with applicable requirements of Dwg. D10542425. The phosphate coating shall comply with the requirements of TT-C-490, appearance and minimum weight, as applicable to the type of phosphate coating.

3.6.2 Paint coating.-The interior and exterior coatings shall comply with applicable requirements of Dwg. D10542425. The paint adhesion shall comply with the applicable requirements of TT-C-490.

3.6.3 Corrosion resistance.-The exterior painted surface of the assembly shall show no evidence of corrosion (red rust) after exposure to a 5% solution of atomized salt spray for 24 hours.

3.7 Metal parts security.-The body and rotating band assemblies, loaded and assembled into test cartridges in accordance with the requirements of Dwg. D10542434, shall not separate or breakup in the test for metal parts security.

3.8 Workmanship.-The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.8.1 Processing defects.-The body, rotating band and assemblies shall be free of dents, scratches, cuts, sharp edges, burrs, and other forms of sub-standard workmanship.

3.8.2 Cleanliness.-The body, rotating band and assemblies shall be free of all foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specificed in the contract or order, the supplier may use his own or other facilities suitable for the performance of the inspection requirements

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:55Z
Check the source to verify that this is the current version before use.

specificed herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.-Reference shall be made to MIL-STD-109 for definition of quality assurance terms.

4.1.2 Bar stock verification.-Independent of tests and inspections performed by the steel bar supplier, an examination shall be made on each lot of bars. The inspections and tests used to verify the bar stock quality shall be as specified by MIL-S-46070(MU), Table IV, using the requirements, acceptance criteria and test methods referenced therein, with the following modifications:

Chemical composition: Sulfur only is required.
Mechanical properties: Unmodified
Grain size: Unmodified
Soundness:
Macro-etch
Billet: See Note 1
Bar: See Note 1
Magnetic: See Note 1
Surface decarburization: Not required
Dimensions: Diameter only.
Workmanship: See Note 1.

NOTE 1. The suppliers' macro-etch, magnetic and visual inspection shall be monitored to the extent necessary to assure compliance with MIL-S-46070(MU).

4.2 Manufacturing process.-Submission of the contractor's proposed manufacturing process and subsequent changes for approval, shall be as directed by the contracting officer.

4.3 First article sample.

4.3.1 Initial production sample.-At the beginning of regular production, a sample applicable to the process shall be submitted in accordance with contract requirements and shall consist of:

a. Inspection and nonfiring tests:

(1) 100 Rotating band blanks
(2) 100 Bodies (unbanded)
(3) 100 Body and rotating band assemblies (prior to pretreatment for painting)
(4) 100 Body and rotating band assemblies (painted)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:55Z
Check the source to verify that this is the current version before use.

b. Firing test:

4,000 Body and rotating band assemblies (painted)

The sample shall be manufactured using the same materials, equipment, processes and procedures as will be used in regular production.

4.3.1.1 Examination and test.-After inspection and provisional acceptance at source, as directed by the contracting officer, the sample shall be inspected for all requirements of the drawings and specifications at a government laboratory or such other facility specified in the contract. (see 6.2)

4.3.1.2 Initial production sample failure.-Failure of the sample to comply with requirements of the drawings and specifications shall result in sample disapproval. The contracting officer will advise what subsequent action is required to qualify for approval of a sample.

4.4 Inspection provisions.

4.4.1 Submission of product.-The product shall be submitted in accordance with MIL-STD-105 or MIL-STD-1235, as applicable.

4.4.1.1 Lot formation.-A lot shall consist of body and rotating band assemblies (painted) produced by one manufacturer in one unchanged process, in accordance with the same drawings and drawing revisions, and the same specification and specification revision. (see 3.3)

4.4.1.2 Lot identification.-Each metal parts assembly and each packed metal parts assembly lot shall be identified in accordance with applicable drawings and MIL-STD-1168, supplemented as directed by the procuring agency.

4.4.2 Examination.-One hundred percent examination shall be performed by the contractor for all critical defects. Examination for major and minor defects shall be performed as specified herein. Each part and each assembly found to be defective, shall be rejected.

4.4.2.1 Sampling plans.-The sampling plans of either MIL-STD-105 or MIL-STD-1235 shall apply, at the option of the contractor. To determine product acceptability, major and minor defects as listed herein, may be considered on a class basis, or they may be considered individually. However, where a group of major defects is considered on a class basis, the acceptance number for a particular defect of the group shall be limited by the assigned AQL supplement, to an acceptance number which is less than that for the class. In addition, where three or less defects appear in a classification, or where MIL-STD-1235 is used, sampling plans applicable to a class shall not be used for major defects. (see 6.4)

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:55Z
Check the source to verify that this is the current version before use.

4.4.2.2 AQL's.-The following AQL's are assigned to major and minor defects:

a. Individual:

Major	0.25%
Minor	0.40%

b. Class basis:

Major	1.50%
Minor	2.50%

c. Individual defects associated with the class basis:

Major	0.40%

4.4.3 Classification of defects 1/.-The classification of defects shall be as specified herein. (see 6.5)

4.4.3.1 Rotating band blank (see Dwg. B7258816).

Categories and Defects	Method of Inspection	
Critical: None defined		
Major:		
101. Foreign matter	Visual	(see 3.4)
102. Defective metal, including lamination	Visual	
103. Incomplete or deformed	Visual	2/
Minor: None defined		

4.4.3.2 Body, prior to banding (see a detail of D10542426).

Critical: None defined		
Major:		
101. Knurling missing or incomplete	Visual	
102. Foreign matter in rotating band seat	Visual	(see 3.4)
103. Depth of knurling, min.	Visual	3/
104. Length, mouth to rear of rotating band seat	Gage	
Minor:		
201. Diameter, rotating band seat, knurled	Gage	
202. Width, rotating band seat	Gage	
203. Width, knurling, min.	Visual	3/

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:55Z
Check the source to verify that this is the current version before use.

4.4.3.3 Body and rotating band assembly, unpainted (see Dwg. D10542426)

Categories and Defects	Method of Inspection	
Critical:		
1. Ferrous metal discontinuity	Soundness Test	
Major:		
101. Length, mouth to rear of rotating band	Gage	
102. Diameter, bourrelet, min.	Gage	
103. Diameter, body rear of rotating band, min.	Gage	
104. Diameter, rotating band	Gage	
105. Concentricity, igniter cavity, with bourrelet	Gage	
106. Concentricity, body, rear of rotating band, with bourrelet	Gage	
107. Concentricity, rotating band, with bourrelet	Gage	
108. Width, rotating band	Gage	
109. Location, crimping groove	Gage	
110. Profile, crimping groove	Gage	
111. Radius, rear edge of crimping groove	Gage	
112. Thickness of web between body and tracer cavity	Gage	
113. Height of boss (tracer cavity)	Gage	
114. Depth, metering disc seat to bottom of tracer cavity	Gage	
115. Unfilled band seat (gap)	Visual	
116. Diameter, body cavity	Gage	
117. Diameter, igniter cavity	Gage	
118. Length to datum diameter of boss in tracer cavity	Gage	
119. Thickness of igniter cavity base	Gage	
120. Diameter, tracer cavity	Gage	
121. Concentricity, tracer cavity with bourrelet	Gage	
122. Diameter, metering disc cavity	Gage	
123. Depth, metering disc cavity	Gage	
124. Radius, metering disc cavity, base	Visual	4/
125. Thickness, crimping lip	Gage	
126. Concentricity, metering disc cavity with bourrelet	Gage	
127. Angle of crimping lip	Gage	
128. Perforation or fracture in tracer cavity	Visual	
129. Wall thickness variation	Gage	
Minor:		
201. Foreign matter in metering disc seat	Visual	
202. Finish improper	Visual	
203. Outside diameter, mouth end	Gage	
204. Depth and width of undercut, front and rear of rotating band	Gage	
205. Diameter, thread counterbore	Visual	5/
206. Overall length	Gage	
207. Depth, thread counterbore, max.	Visual	5/
208. Break, mouth, at ogive, max.	Visual	6/
209. Chamfer at mouth of igniter cavity	Visual	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:55Z
Check the source to verify that this is the current version before use.

4.4.3.4 Body and rotating band assembly (coated, prior to painting)(see Dwg. D10542426).

Categories and Defects	Method of Inspection
Critical: None defined.	
Major:	
101. Pitch diameter, thread	Gage
102. Concentricity, thread with bourrelet	Gage
Minor:	
201. Minor diameter, thread	Gage
202. Length, complete thread, min.	Gage

4.4.3.5 Body and rotating band assembly (painted)(see Dwg. D10542425).

Categories and Defects	Method of Inspection
Critical: None defined.	
Major:	
101. Diameter, bourrelet	Gage
102. Diameter, body, rear of rotating band	Gage
103. Diameter, metering disc cavity	Gage
104. Diameter, tracer cavity	Gage
105. Foreign matter in cavities or threads	Visual
106. Depth, metering disc seat to bottom of tracer cavity	Gage
107. Mutilated	Visual
108. Weight	Balance
Minor:	
201. Paint not dry	Tactile
202. Marking incorrect, incomplete, illegible, or missing	Visual
203. Paint on rotating band	Visual
204. Paint on threads	Visual
205. Rotating band damaged	Visual
206. Interior or exterior paint inadequate	Visual
207. Foreign matter on exterior	Visual

1/ MIL-STD-651 shall apply in defining and evaluating visual defects.

2/ A rotating band blank which is deformed or is judged to lack sufficient metal in any part of its width or thickness to provide for complete band seat fill and minimum rotating band profile dimensions, shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:55Z
Check the source to verify that this is the current version before use.

3/ Measurement of knurling for compliance with the minimum depth and width requirements shall apply where visual inspection indicates that the depth or width dimension is borderline.

4/ Visual inspection may be used to judge the base radius of the metering disc seat, with measurement to apply when the maximum acceptable radius is suspect or borderline.

5/ Measurement of the diameter and depth, max., of the thread counterbore shall apply where visual inspection indicates that the diameter or depth, max., dimension is borderline.

6/ Measurement of the mouth-ogive break shall apply where visual inspection indicates that the maximum dimension is borderline.

4.4.4 Tests.-The tests listed in Table I shall be conducted in compliance with the test methods and procedures prescribed in 4.5. The individual test shall be acceptable if in the first sample, or in the accumulated first and second samples, the number of defectives (defects) is less than the specified rejection number applicable to the sample. The sampling plans for these tests shall be as specified in Table I.

Table I

Test	Sample Size		Item	Req. Para.
Band tightness	1/	315	Bodies, banded, unpainted	3.4
Automatic inspection effectiveness	2/		PCS No. 1 (see 4.5.3)	--
Soundness verification	3/	300	Projectiles, unpainted	3.5
Phosphate coating (appearance & weight)	4/	3	Standard panels (see TT-C-490)	3.6.1
Paint adhesion	5/	13	Assemblies, painted	3.6.2
Corrosion resistance	6/	32	Assemblies, painted	3.6.3
Metal parts security	7/	250	Assemblies, painted	3.7

1/ If two or more units of the sample fail to comply with the band tightness requirement, the lot shall be rejected. If one unit of the sample fails to comply with the requirement, a second sample consisting of the same number of units as specified for the first sample shall be tested. If in the accumulated samples, two or more units fail to comply with the band tightness requirement, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:55Z
Check the source to verify that this is the current version before use.

2/ Failure of the flaw detector to reject PCS No. 1 shall be cause for rejection of all assemblies inspected for "soundness" since the preceding test and shall require requalification of the equipment for automatic inspection (see 4.5.3).

3/ Rejection of one or more units of the sample by the flaw detector in the test for body metal soundness shall be cause for rejection of the lot.

4/ Failure of the phosphate coating on the standard panels to comply with the applicable requirements shall be cause for rejection of all projectiles phosphated since the preceding test.

5/ If two or more units of the sample fail to comply with the requirement for paint adhesion, the lot shall be rejected. If one unit of the sample fails to comply with the requirement, a second sample consisting of the same number of units as specified for the first sample shall be tested. If in the accumulated samples, two or more units fail to comply with the requirement for paint adhesion, the lot shall be rejected.

6/ If two or more units of the sample fail to comply with the corrosion resistance requirement, the lot shall be rejected. If one unit fails to comply with the requirement, a second sample consisting of the same number of units as specified for the first sample shall be tested. If in the accumulated samples, two or more units fail to comply with the corrosion resistance requirement, the lot shall be rejected.

7/ The occurrence of one or more of the following casualties, as witnessed by hole(s) in the fragmentation screen(s), or recovery of the part(s) or fragment(s), shall be cause for rejection of the lot, except as otherwise provided:

a. Body breakup.

b. Complete rotating band separation. This is defined as detachment of all or part of the band having band seat knurling imprint. The following acceptance criteria shall apply to detached band fragments having no visible evidence of band seat knurling imprint:

(1) The lot shall be accepted if two or less projectiles throw band fragments having length not greater than 0.500 inch.

(2) The lot shall be rejected if three or more assemblies throw band fragments having length not greater than 0.500 inch.

(3) The lot shall be rejected if any projectile throws a band fragment having length greater than 0.500 inch (indicative of deep seated band lamination).

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:55Z
Check the source to verify that this is the current version before use.

(4) The lot shall not be penalized for band particles thrown as a result of normal band fringing or slivering.

4.4.5 Packaging, packing and marking inspection.-Inspection for packaging, packing and marking shall comply with applicable requirements of MIL-STD-1169.

4.4.6 Inspection equipment.-Index of Inspection Equipment List No. IEL 10542425 identifies the applicable Inspection Equipment List required to perform examination and tests prescribed herein. Equipment design shall be in accordance with code designation on the applicable IEL (reference is made to Inspection Equipment List for definition of coding format).

4.5 Test methods and procedures.

4.5.1 Band tightness.-The method of test shall comply with all requirements of the operating instructions for the band tightness tester (see Dwg. B7259545, a detail of IEL 10542425). The inspection sample shall be cycled through the tester to determine compliance with the rotating band tightness requirement. The total measurement of radial void (band looseness), registered on the tester indicator at final ram pressure, shall be divided by four (number of indentors) to determine the average radial void.

4.5.2 Soundness.-The method of inspection shall comply with all requirements of Operating Instructions Manual, Eddy Current Flaw Detector, Dwg. D11075203 (a detail of IEL 10542425) for Detecting Metal Discontinuity in Projectile Bodies for 20mm Ammunition, except for those inspection requirements which are reserved for Government application, as specified herein.

4.5.2.1 Application of defect standards.-Master defect standards, referenced in the operating instruction manual, shall apply to resolve inspection discrepancies occurring between the results of defect standards supplied for contractor "soundness" inspection and those supplied for Government "soundness" verification. (see 6.6)

4.5.3 Automatic eddy current inspection effectiveness.-Equipment checkout shall be performed as stated in the operation instruction manual at the start of each shift and after any adjustment or shutdown. Upon completion of checkout, cycle the PCS #1, front slot and rear slot standards through the inspection system during automatic operation. All three standards must be rejected to assure correct adjustment for reject level and scan limits. During remainder of shift the PCS #1 shall be cycled through the equipment at intervals of 20 ± 5 minutes during automatic operation.

4.5.3.1 Equipment verification.-The government inspector will maintain, independent of the contractor, a set of standards and may cycle these standards through the equipment at any time. Failure of equipment to reject standards will be evidence that the equipment is not properly adjusted and the contractor will so be notified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:55Z
Check the source to verify that this is the current version before use.

4.5.4 Soundness verification.-After equipment checkout and verification as specified in 4.5.3 and 4.5.3.1 the entire lot sample will be inspected with the equipment operating automatically. Any rejected unit of the sample will be automatically cycled through the equipment with the CAL. button pressed (to lower the sensitivity one step below that used for production inspection). Any unit which is rejected at the lower sensitivity shall be classed as a defective.

4.5.5 Phosphate coating.-The method of test shall be as prescribed by TT-C-490 for the type of coating used (see Dwg. D10542425). The prescribed panels shall be processed, with the assemblies to be represented, at the start of daily production and at 4-hour intervals, maximum, thereafter. Appearance and weight of the coating shall be recorded.

4.5.6 Paint adhesion.-The method of test shall be as prescribed by TT-C-490. The test shall be made on the painted bourrelet of each unit of the sample. Visible exposure of underlying phosphate coating or ferrous metal of any unit of the sample as a result of the test, shall be classed as a defect.

4.5.7 Corrosion resistance.-The method of test shall be as prescribed in Method 811.1 of Federal Test Methods Standard No. 151, Metals; Test Methods. The rotating band and base end of the sample assemblies may be masked out by a wax coating or other suitable material. The salt spray solution and exposure time shall be as specified in 3.6.3.

4.5.8 Metal parts security.-The method of test will be as prescribed by AMCR 715-505, Volume 8, as applicable. The test sample will be loaded and assembled as specified on Dwg. D10542434, Cartridge, 20mm, for Projectile, HEIT-SD, M246, metal parts security test. The test cartridges, at ambient temperature, will be fired in an XM168 gun in bursts of 50 shots. The gun barrel will be at ambient temperature for the firing of each burst. The cyclic rate of fire will be recorded for informational purposes.

5. PREPARATION FOR DELIVERY

5.1 Packing, Level C.-Each lot of product shall be packed as specified by Dwg. F7258861 or Dwg. D7259136 as directed by the procuring agency.

5.2 Marking and labeling.-Marking or labeling of packed cartons shall comply with applicable requirements of MIL-STD-1169.

6. NOTES

6.1 Ordering data.-Invitations for bids and contracts or orders will specify the following:

6.1.1 Title, number, and date of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:55Z
Check the source to verify that this is the current version before use.

6.1.2 Place of inspection, if not place of manufacture.

6.1.3 Packing instructions. (see 5.1)

6.1.4 Provision for shipment (as applicable) and testing of production lot samples for metal parts security. (see 4.5.8)

6.1.5 Provision for the supply, maintenance and disposition of mandatory ballistic test equipment for acceptance inspection purposes.

6.2 Initial production sample.-Where an initial production sample is required by the contract, the contracting officer will notify the testing facility when to proceed with the metal parts security test.

6.3 Process deviation.-A process deviation is defined as a change in the basic method of manufacture, or an operational change which alters the metallurgical or physical properties of the item of contract.

6.4 AQL's.-The optional use of AQL values for either individual defects or classes of defects, with individual major defect limitation, is intended to minimize inspection agency administrative burden which might result from an exclusive assignment of individual defect AQL's. The option also permits flexibility where sampling inspection for acceptance is integrated into the manufacturing process.

6.5 Intermediate point inspection.-The classification of defects identifies the defect characteristics (among other things) for acceptance inspection. It may be necessary to modify the sequence of inspection stations to best suit the manufacturing process. Inspection for defect characteristics which will be hidden or altered by subsequent processing operations (including unrelated operations), should be scheduled to prevent premature acceptance which could be detrimental to the attainment of optimum product quality in the end item.

6.6 Defect standards.-The initial supply of defect standards and instructions for contractor and Government application to the eddy current method of inspection, will be furnished with the inspection equipment. Replacement standards shall be requisitioned through normal channels by the Government agency having contract administration responsibility.

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1305-A602

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:55Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

[ ] DIRECT GOVERNMENT CONTRACT [ ] SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

[ ] YES [ ] NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:55Z
Check the source to verify that this is the current version before use.