MIL-P-82008C
4 December 1987
SUPERSEDING
MIL-P-82008B
7 September 1982

MILITARY SPECIFICATION

PAVING BREAKER SETS, PORTABLE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers portable pneumatic paving breakers equipped with specific operating tools and contained in a tool chest to form a complete set.

1.2 Classification. The paving breaker set shall be one of the following sets as specified (see 6.2.1).

Set I - 25 pound (lb) pneumatic type paving breaker, equipped with operating tools.
Set II - 80 lb pneumatic type paving breaker, equipped with operating tools.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP-T-60 - Tape: Packaging, Waterproof.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3820

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116 - Preservation, Methods of.
MIL-B-121 - Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-B-385 - Breakers, Paving, Pneumatic-Powered, 25-Pound Class (7/8-Inch Hexagon by 2-3/4-Inch Chuck).
MIL-R-423 - Ripping Tools, Metal Drum, Paving Breaker.
MIL-B-467 - Breakers, Paving: Pneumatic.
MIL-B-22191 - Barrier Material, Transparent, Flexible, Heat Sealable.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables For Inspection By Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-147 - Palletized Unit Loads.
MIL-STD-794 - Parts and Equipment, Procedures for Packaging and Packing.

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. Each set shall consist of a pneumatic paving breaker, complete with operating tools, and contained in a tool chest. All paving breakers shall be complete and ready for operation when supplied with air.

3.2 First article. When specified in the contract or purchase order, a sample shall be subject to first article inspection (see 4.2.1 and 6.4).

3.3 Tool chest. Tool chest shall be designed to contain the paving breaker, repair parts, tools, accessories, and operating tools.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

3.4 Set I. Set I shall consist of a 25 lb pneumatic type paving breaker conforming to MIL-B-385 and the following items:

Quantity	Item	Conforming to
1	Chest	MIL-B-385
1	Spade	MIL-B-385
3	Moil point	MIL-B-385
4	Ripping tool	MIL-R-423, type 1
4	Ripping tool	MIL-R-423, type 2

3.5 Set II. Set II shall consist of an 80 lb pneumatic type paving breaker conforming to MIL-B-467 and the following items:

Quantity	Item	Conforming to
1	Chest	MIL-B-467
1	Tamping rod	MIL-B-467
1	Tamping pad	MIL-B-467
4	Moil point	MIL-B-467
4	Chisel	MIL-B-467
1	Sheeting driver	MIL-B-467
1	Spade	Manufacturer's standard not less than 5-1/2 inches wide.

3.6 General requirements. The identification marking, instruction plates treatment, painting, and workmanship shall be in accordance with the referenced specifications.

3.7 Standard commercial product. The breaker sets shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the breaker sets being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

3.8 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.2 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in the applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on one breaker set when a first article is required (see 3.2 and 6.2.1). This inspection shall include the examination of 4.4 and the tests of 4.5. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.4, the tests of 4.5, and the packaging inspection of 4.6. This inspection shall be performed on the samples selected in accordance with 4.3.

4.3 Sampling. Sampling shall be in accordance with MIL-STD-105. All breaker sets offered for delivery at one time shall be considered a lot for the purpose of inspection. The inspection level shall be level II and the Acceptable Quality Level (AQL) shall be 4.0 percent defective. If an inspection lot is rejected, the contractor may rework it to correct the defects, or screen out the defective units, and resubmit for a complete reinspection. Resubmitted lots shall be inspected using tightened inspection. Such lots shall be separate from new lots, and shall be clearly identified as reinspected lots.

4.4 Examination. Each breaker set shall be examined for compliance with the requirements of the applicable referenced specifications.

4.5 Tests. Tests shall be conducted in accordance with the referenced specifications. The fit and compatibility of the operating tools shall be determined by inserting the operating tool shank into the chuck of the paving breaker.

Source: https://assist.dla.mil -- Downloaded: 202610-23T06:37Z
Check the source to verify that this is the currentversion before use.

4.6 Packaging inspection. The preservation, packing, unitization, and marking of the item shall be inspected to verify conformance to the requirements of section 5.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or commercial as specified (see 6.2.1).

5.1.1 Level A.

5.1.1.1 Methods of preservation. Cleaning processes, drying procedures, preservatives, and methods of preservation are listed in MIL-P-116 and shall conform to the requirements of MIL-P-116 and any applicable specifications.

5.1.1.2 Cleaning and drying. Prior to the application of preservative compounds or paint, surfaces shall be cleaned by process C-1 and dried by any applicable procedure of MIL-P-116.

5.1.1.3 Unprotected surfaces. Unprotected exterior metal surfaces requiring the application of a contact preservative in accordance with MIL-P-116 and not specifically provided for herein shall be preserved as follows:

5.1.1.3.1 Unfinished (not machined) surfaces. Unfinished exterior metal surfaces shall be coated with type P-1 preservative.

5.1.1.3.2 Machined surfaces. Exposed machined surfaces shall be coated with type P-6 or P-11 preservative and wrapped or covered, as applicable, with barrier material conforming to MIL-B-121, type I, grade A, class 2 or MIL-B-22191, type II. The material shall be secured in place with waterproof tape.

5.1.1.4 Air motors. Interior surfaces of air motors shall be coated with type P-10, grade 2 preservative. The preservative shall be applied through the lubricating system, or by feeding the preservative into the air inlet while operating the motor, until the preservation appears at the exhaust ports. Air inlets and outlets shall be closed with caps or plugs, or with tape conforming to PPP-T-60, type IV.

5.1.1.5 Accessories. Unpainted surfaces of operating accessories, such as spades, axes, moil points, ripping tools, tamping pads and rods, chisels, and sheeting drivers, shall be coated with type P-1 preservative.

5.1.1.6 Hose. When a hose is furnished, the hose shall be coiled and the coil secured with a minimum of three equally spaced ties of tape or twine.

5.1.1.7 Repair parts and maintenance tools. The preservative application criteria and applicable methods of preservation of MIL-P-116 shall be used to preserve repair parts and maintenance tools.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

5.1.1.8 Consolidation. The tool chest shall be used for the consolidation of all components of the breaker set. Items shall be cushioned, blocked, and braced as required to prevent movement and damage. Each chest shall be packaged in a box conforming to PPP-B-636, class weather-resistant; PPP-B-640; class 2; PPP-B-601, overseas type; or PPP-B-621, class 2.

5.1.2 Commercial. The material shall be preserved in accordance with the contractor's standard practice in a manner to prevent deterioration and damage.

5.2 Packing. Packing shall be level A, B, or commercial as specified (see 6.2.1).

5.2.1 Levels A and B. Packing shall be in accordance with MIL-STD-794. Containers shall be selected from table I for the appropriate level.

5.2.2 Commercial. The material shall be prepared for shipment in a manner which will insure arrival at destination in a satisfactory condition. Preparation for delivery shall comply with applicable carrier rules and regulations.

5.3 Palletization. Material shall be palletized in accordance with MIL-STD-147 when the following criteria is met:

a. Load to consist of four or more unskidded containers; and,
b. Load shall utilize a minimum of 80 percent of the pallet base.

5.4 Marking. Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The paving breaker sets are intended for use in breaking consolidated soils or soft rock, cutting and breaking asphalt pavement, and breaking portland cement concrete pavement, tamping soil, splitting drums filled with asphalt cement, and performing general demolition work.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Paving breaker set required (see 1.2).
c. When manufacturer's or commercial publications are required (see 3.7).
d. When first article inspection and approval is required and time frame for submission (see 4.2.1 and 6.4).
e. Level of preservation and level of packaging required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 202610-23T06:37Z
Check the source to verify that this is the current version before use.

6.3 First article. When a first article inspection is required, the item will be tested and should be a first production item consisting of one complete paving breaker set or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.4 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

6.5 Subject term (key word) listing.

Pneumatic
Portable
Tool sets

Custodians:
Army - ME
Navy - YD
Air Force - 99

Review activity:
Air Force - 84

Preparing activity:
Navy - YD

(Project 3820-0183)

Source: https://assist.dla.mil -- Downloaded: 202610-23T06:37Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

Commanding Officer (Code 156)
Naval Construction Battalion Center
Port Hueneme, CA 93043-5000

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer
Code 156
Naval Construction Battalion Center
Port Hueneme, CA 93043-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-82008C	PAVING BREAKER SETS, PORTABLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.