MIL-T-50303A(MU)
1 February 1971
SUPERSEDING
MIL-T-50303(MU)
10 May 1969

MILITARY SPECIFICATION
THRUSTER, CARTRIDGE ACTUATED: M26
METAL PARTS ASSEMBLY

1. SCOPE

1.1 This specification covers Thruster, Cartridge Actuated: M26 Metal Parts Assembly. The assembly will ultimately be loaded and used in conjunction with other propellant actuated devices in aircrew emergency escape systems.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-A-2550	-Ammunition and Special Weapons, General Specification for

STANDARDS

Military

MIL-STD-105	-Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	-Quality Assurance Terms and Definitions
MIL-STD-413	-Visual Inspection Guide for Rubber O-Rings

DRAWINGS

Munitions Command

F10551372	-Thruster, Cartridge Actuated, M26 Metal Parts Assembly
C9243197	-Container, Ammunition Fiber, for Thruster, Cartridge Actuated, M26
C9243198	-Box, Packing, Ammunition for Thruster, Cartridge Actuated, M26
IEL 10551372	-Inspection Equipment List for Thruster, Cartridge Actuated, M26 Metal Parts Assembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

2.1 (Cont'd)

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.- The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bid or request for proposal shall apply.

ASA B46.1 - Surface Texture

(Application for copies should be addressed to the American Standards Association, 10 East 40th Street, New York, N. Y. 10016.)

3. REQUIREMENTS

3.1 General.- Materials, parts and assemblies shall comply with the requirements specified on the applicable drawings, and in the referenced specifications.

3.2 Material.- The contractor shall be responsible for selecting from the classification list contained in the raw material specification, the surface and physical condition of the raw material intended for use in manufacture.

3.3 Mechanical properties.- Mechanical properties required by the drawing shall be uniform throughout the part within specified tolerances. Mechanical properties for all alloy steel parts shall be achieved by quenching and tampering.

3.4 Metal parts assembly.- Parts shall be combined to produce an assembly which conforms to the requirements of the metal parts assembly drawing.

3.5 Protective finish.- Protective finish shall be in accordance with the applicable specifications and drawings and shall apply to all surfaces of the component regardless of contour configuration.

3.6 Residual magnetism.- The metal parts assembly shall not deflect the indicator of the compass more than 3 degrees in either direction when passed in front of the compass at a distance of 6 inches.

3.7 Workmanship.- The requirements for workmanship are as specified on the applicable drawings, references specifications and the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

3.7.1 Metal defects.- All components shall be free from cracks, splits cold shuts, inclusions, porosity or other metal defects.

3.7.2 Burr.- No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.7.3 Foreign matter.- No part or assembly shall contain chips, dirt, grease, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.- Reference is made to MIL-STD-109 to define quality assurance terms used.

4.1.2 Inspection.- Inspection shall be in accordance with MIL-A-2550 except as specified herein.

4.2 First article sample.

4.2.1 Initial production sample.- At the beginning of regular production, samples shall be submitted in accordance with contractual requirements and shall consist of 5 metal parts assemblies, 10 sets of parts, fifty shear pins and fifty inital lock shear pins from the same lot of shear pins tested by the contractor. The samples shall be subjected to the tests in 4.3.3. The test procedures shall be in accordance with 4.4. The sample shall be manufactured in the same manner, using the same materials, equipment, processes and procedures as used in regular production. All parts and materials, including packaging and packing must be the same as used in regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and Test.- After inspection and provisional acceptance at source, the samples shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.2.1.2 Initial production sample failure.- Failure of the sample to comply with requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions.

4.3.1 Lot.

4.3.1.1 Submission of product.- Unless otherwise specified by the contracting officer, formation of lots and presentation of lots shall be in accordance with the "Submission of Product", provisions of MIL-STD-105.

4.3.1.2 Size of lot.- The shipping lot of metal parts assemblies shall consist of 1200 thrusters, maximum, provided the homogeneity requirements of inspection lots have been retained. A smaller lot may be shipped upon approval of the contracting officer.

4.3.2 Examination.- One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plans and associated criteria in Table I and II. For an individual defect (single characteristic), the criteria in in Table I shall be used. For total defects within a major or minor group, the criteria in Table II shall be used. All nonconforming material shall be rejected. The roughness comparison specimens prescribed in ASA B46.1 shall be used as a basis of comparison for surface roughness determination. Inspection for rubber O-rings shall be in accordance with MIS-STD-413. Four power (4X)magnification may be used in performing visual examination for such defects as burr and foreign matter.

TABLE I

Lot Size		Major		Minor	
		Accept	Reject	Accept	Reject
1 - 300	100% Examination				
301 - 1300	110	1	2	2	3
1301 - 3200	150	2	3	3	4
3201 - 8000	225	3	4	4	5
8001 - 22000	300	4	5	5	6

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

TABLE II

No. of Defects in Class	Sample Sizes for Major Defects			
	110	150	225	300
	Total Allowable Defects per Sample Size			
2 - 3	1	2	3	4
4 - 7	2	3	4	5
8 -19	3	4	5	7
20 -43	4	5	8	10
over 43	6	8	11	14

No. of Defects in Class	Sample Sizes for Major Defects			
	110	150	225	300
	Total Allowable Defects per Sample Size			
2 - 3	2	3	4	5
4 - 7	3	4	5	7
8 - 16	4	5	8	10
17 - 48	6	8	11	14
Over 48	8	11	17	20

4.3.2.1 Sleeve, Dwg. D10551375, covering a detail of Dwg. F10551372.

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
101. Pitch diameter of thread, max.	Gage
102. Minor diameter of thread, max.	Gage
103. "True Position of small inside diameter with pitch diameter of threads	Gage
104. Min, wall	Gage
105. Concentricity of internal groove diameter to small inside diameter	Gage
106. True Position of "O" ring bore diameter with small inside diameter	Gage
107. Perpendicularity of sleeve face to small inside diameter	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.3.2.1 (Cont'd)

Defect	Method of Inspection
MAJOR	
108. Parallelism of internal undercut shoulder with sleeve face	Gage
109. Small inside diameter	Gage
110. Inside diameter of groove	Gage
111. Outside diameter	Gage
112. Depth from face to groove	Gage
113. Groove width	Gage
114. Depth from face to undercut	Gage
115. Diameter of "O" ring groove	Gage
116. Depth of "O" ring groove	Gage
117. Surface finish of bore improper	Visual (See 6.2)
118. Metal defective	Visual
119. Protective finish inadequate or defective	Visual
120. Sharp edge omitted from groove	Visual
121. Burr or sharp corner, except as otherwise classified	Visual
122. Foreign matter	Visual
MINOR	
201. Pitch diameter of thread, min.	Gage
202. Total length	Gage
203. Radii or chamfers incorrect	Gage
204. Width of undercut	Gage
205. Radii or chamfers missing	Visual
206. Surface finish improper except as otherwise classified	Visual

4.3.2.2 Tube, Inside Assembly, Dwg. D10551376, covering a detail of Dwg. F10551372.

CRITICAL	
None defined	
MAJOR	
101. Pitch diameter of thread, min	Gage
102. Major diameter of thread, min	Gage
103. True position of large outside diameter with thread pitch diameter	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.3.2.2 (Cont'd)

Defect	Method of Inspection
MAJOR	
104. True position of intermediate outside diameter with thread pitch diameter	Gage
105. Concentricity of groove diameter with large outside diameter	Gage
106. True position of small outside diameter with thread pitch diameter	Gage
107. True Position of threaded end bore diameter with thread pitch diameter	Gage
108. True Position of long bore diameter with thread pitch diameter	Gage
109. True position of small inside diameter with thread pitch diameter	Gage
110. Runout of undercut diameter with small outside diameter	Gage
111. True Position of wrench flats	Gage
112. Intermediate outside diameter	Gage
113. Small outside diameter	Gage
114. Small inside diameter	Gage
115. Inside diameter threaded end	Gage
116. Inside diameter of long bore	Gage
117. Groove width	Gage
118. Profile of groove	Gage
119. Surface finish improper	Visual (See 6.2)
120. Protective finish inadequate or defective	Visual
121. Metal defective	Visual
122. Burr or sharp edge	Visual
123. Foreign matter	Visual
124. Large outside diameter	Gage
125. Groove diameter	Gage
126. Width across wrench flats	Gage
127. Pellet protrusion, max.	Gage
128. Pellet loose, missing or improperly inserted	Manual/Visual
129. Undercut diameter	Gage
MINOR	
201. Location of groove	Gage
202. Location of small bore	Gage
203. Location of thread undercut	Gage
204. Undercut width	Gage
205. Pitch diameter of thread, max.	Gage
206. Total length	Gage
207. Length from threaded end to groove shoulder	Gage
208. Length of intermediate outside diameter	Gage
209. Length of inside bore	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.3.2.2 (Cont'd)

Defect	Method of Inspection
MINOR	
210. Radii or chamfers incorrect	Gage
211. Width of wrench flats	Gage
212. Location of wrench flats	Gage
213. Diameter of pellet hole	Gage
214. Depth of Pellet Hole	Gage
215. Location of pellets	Gage
216. Radii or chamfers missing	Visual
217. Surface finish improper, except as otherwise classified	Visual
218. Marking missing, incorrect or illegible	Visual

4.3.2.3 Tube, Outside Assembly, Dwg. D10551377, covering a detail of Dwg. F10551372.

CRITICAL	
None defined	
MAJOR	
101. True position of body diameter with thread pitch diameter	Gage
102. Runout of thread undercut diameter with body diameter	Gage
103. True position of large inside diameter with thread pitch diameter	Gage
104. True position of intermediate inside diameter with large inside diameter	Gage
105. True position of wrench flats with body	Gage
106. Perpendicularity of wrench flats with body	Gage
107. Pitch diameter of thread, min.	Gage
108. Major diameter of thread, min.	Gage
109. Thread undercut diameter	Gage
110. Outside body diameter	Gage
111. Large inside diameter	Gage
112. Depth to bottom of small inside diameter	Gage
113. Spherical radius	Gage
114. Perpendicularity of threaded face to thread pitch diameter	Gage
115. Runout of small outside diameter with body diameter	Gage
116. Location of wrench flats	Gage
117. Protrusion of pellets, max.	Gage
118. Pellet loose, missing or improperly inserted	Manual/Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.3.2.3 (Cont'd)

	Defect	Method of Inspection	
MAJOR			
119.	Metal defective	Visual	
120.	Protective finish inadequate or defective	Visual	
121.	Surface finish improper	Visual	(See 6.2)
122.	Burr or sharp edge	Visual	
123.	Foreign matter	Visual	
MINOR			
201.	Small inside diameter	Gage	
202.	Intermediate inside diameter	Gage	
203.	Pitch diameter of thread, max.	Gage	
204.	Small outside diameter	Gage	
205.	Angle of nose	Gage	
206.	Depth to intermediate inside diameter	Gage	
207.	Depth of small inside diameter	Gage	
208.	Total length	Gage	
209.	Length of nose tip	Gage	
210.	Location of thread undercut	Gage	
211.	Width of thread undercut	Gage	
212.	Angle of thread undercut	Gage	
213.	Location of pellets	Gage	
214.	Depth of pellet holes	Gage	
215.	Diameter of pellet holes	Gage	
216.	Radii or chamfers incorrect	Gage	
217.	Radii or chamfers missing	Visual	
218.	Marking missing, incorrect or illegible	Visual	
219.	Surface finish improper, except as otherwise classified	Visual	

4.3.2.4 Tube, Intermediate, Dwg. F10551378 covering a detail of Dwg. F10551372.

CRITICAL		
None defined		
MAJOR		
101.	True position of large outside diameter with body diameter	Gage
102.	True position of intermediate outside diameter with body diameter	Gage
103.	True position of body diameter with large inside diameter	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.3.2.4 (Cont'd)

Defect	Method of Inspection
MAJOR	
104. Concentricity of groove diameter with large outside diameter	Gage
105. True position of small inside diameter with large inside diameter	Gage
106. Large outside diameter	Gage
107. Intermediate outside diameter	Gage
108. Small outside diameter	Gage
109. Large inside diameter	Gage
110. Small inside diameter	Gage
111. Groove diameter	Gage
112. Groove width	Gage
113. Angles on large outside diameter	Gage
114. Angle on small inside diameter	Gage
115. Profile of groove	Gage
116. Surface finish inadequate	Visual (See 6.2)
117. Metal defective	Visual
118. Burr or sharp edge	Visual
119. Foreign matter	Visual
MINOR	
201. Total length	Gage
202. Length to large outside diameter	Gage
203. Length of intermediate outside diameter	Gage
204. Depth to small inside diameter	Gage
205. Length from face to groove	Gage
206. Radii or chamfers incorrect	Gage
207. Radii or chamfers missing	Visual
208. Surface finish improper, except as otherwise classified	Visual
209. Marking missing, incorrect or illegible	Visual

4.3.2.5 Pin, Firing, Dwg. C10551380 covering a detail of Dwg. F10551372

CRITICAL

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.3.2.5 (Cont'd)

Defect		Method of Inspection
MAJOR		
101.	Concentricity of groove to body	Gage
102.	Concentricity of striker to body	Gage
103.	True position of pin hole	Gage
104.	Diameter of body	Gage
105.	Diameter of groove	Gage
106.	Diameter of striker	Gage
107.	Diameter of pin hole	Gage
108.	Length of striker	Gage
109.	Tip contour not spherical with radius, or tangent to diameter	Gage
110.	Profile of groove	Gage
111.	Pin hole edges not sharp	Visual
112.	Surface finish of striker tip, body and groove, improper	Visual (See 6.2)
113.	Metal defective	Visual
114.	Protective finish inadequate or defective	Visual
115.	Burr or sharp corners, except as otherwise classified	Visual
116.	Foreign matter	Visual
MINOR		
201.	Total length	Gage
202.	Location of pin hole	Gage
203.	Depth of slot	Gage
204.	Location of groove	Gage
205.	Width of slot	Gage
206.	Width of groove	Gage
207.	Location of slot	Gage
208.	Radii or chamfers incorrect	Gage
209.	Radii or chamfers missing	Visual
210.	Markings missing, incorrect or illegible	Visual
211.	Surface finish improper, except as otherwise classified	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.3.2.6 Housing, Dwg. C10551381, covering a detail of Dwg F10551372

CRITICAL

None defined

Defect	Method of Inspection
MAJOR	
101. True position of small bore diameter with large bore diameter	Gage
102. Concentricity of groove diameter to large outside diameter	Gage
103. True position of intermediate outside diameter with outside body diameter	Gage
104. True position of bore diameter with outside body diameter	Gage
105. Perpendicularity of boss face to outside diameter	Gage
106. Perpendicularity of shoulder to outside diameter	Gage
107. True position of pin hole with bore diameter	Gage
108. Large outside diameter	Gage
109. Groove diameter	Gage
110. Large inside diameter	Gage
111. Small inside diameter	Gage
112. Pin hole diameter	Gage
113. Groove width	Gage
114. Groove profile	Gage
115. Location of pin hole	Gage
116. Width from boss face to bottom of cavity	Gage
117. Width of boss	Gage
118. Metal defective	Visual
119. Protective finish inadequate or defective	Visual
120. Surface finish improper	Visual (See 6.2)
121. Burr or sharp corner	Visual
122. Foreign matter	Visual
MINOR	
201. Small outside diameter	Gage
202. Outside diameter of boss	Gage
203. Total length	Gage
204. Length from boss face to shoulder	Gage
205. Length from boss face to groove shoulder	Gage
206. Radii or chamfers incorrect	Gage
207. Markings missing, incorrect or illegible	Visual
208. Radii or chamfers missing	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.3.2.7 Pin, Shear, Dwg. B10551383, covering a detail of Dwg. F10551372

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
101. Diameter	Gage
102. Total length	Gage
103. Metal defective	Visual
104. Protective finish inadequate or defective	Visual
105. Surface finish improper	Visual (See 6.2)
106. Burr or sharp corners	Visual
107. Foreign matter	Visual
MINOR	
None defined	

4.3.2.8 Pin, Shear, Initial Lock, Dwg. B10551384, covering a detail of Dwg. F10551372

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
101. Diameter	Gage
102. Total length	Gage
103. Incorrect chamfers	Gage
104. Protective finish inadequate or defective	Visual
105. Surface finish improper	Visual
106. Burr	Visual
107. Metal defective	Visual
108. Foreign matter	Visual
MINOR	

4.3.2.9 Cap Assembly, Dwg. C10551373 covering a detail of Dwg. F10551372

CRITICAL

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.3.2.9 (Cont'd)

Defect		Method of Inspection
MAJOR		
101.	Pitch diameter of external thread, min.	Gage
102.	Major diameter of external thread, min.	Gage
103.	Pitch diameter of internal thread, max.	Gage
104.	Minor diameter of internal thread, max.	Gage
105.	True position of outside body diameter with thread pitch diameter	Gage
106.	True position of intermediate bore diameter with thread pitch diameter	Gage
107.	Run out of outside midsection diameter with thread pitch diameter	Gage
108.	Perpendicularity of external shoulder with thread pitch diameter	Gage
109.	Perpendicularity of internal shoulder with thread pitch diameter	Gage
110.	True position of pin hole	Gage
111.	Diameter of body	Gage
112.	Diameter of intermediate cavity	Gage
113.	Location of pin hole	Gage
114.	Diameter of pin hole	Gage
115.	Depth from body face to bottom of intermediate cavity	Gage
116.	Diameter of external thread undercut	Gage
117.	Diameter of internal thread undercut	Gage
118.	Diameter of bore	Gage
119.	Max. protrusion of pellets	Gage
120.	Surface finish improper	Visual (See 6.2)
121.	Pellet loose, missing or improperly inserted	Manual and Visual
122.	Thread damaged or not full	Visual
123.	Metal defective	Visual
124.	Protective finish inadequate or defective	Visual
125.	Burr or sharp edge	Visual
126.	Foreign matter	Visual
MINOR		
201.	Pitch diameter of external thread, max.	Gage
202.	Pitch diameter of internal thread, min.	Gage
203.	Width of flats (2 places)	Gage
204.	Location of flats (2 places)	Gage
205.	Total length	Gage
206.	Angle of flange	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.3.2.9 (Cont'd)

Defect	Method of Inspection
MINOR	
207. Length from flange to threaded face	Gage
208. Depth to bottom of internal undercut	Gage
209. Width of internal undercut	Gage
210. Length from body face to flange	Gage
211. Length from external threaded face to shoulder	Gage
212. Length from external threaded face to undercut shoulder	Gage
213. Location of pellet holes	Gage
214. Diameter of pellet holes	Gage
215. Depth of pellet holes	Gage
216. Width of external undercut	Gage
217. Outside diameter of midsection	Gage
218. Outside diameter of flange	Gage
219. Radii or chamfers incorrect	Gage
220. Radii or chamfer missing	Visual
221. Marking missing, incorrect or illegible	Visual

4.3.2.10 Metal Parts Assembly DWG F10551372 less all components, except C10551380, C10551381 and MS 29513-10

CRITICAL	
1. Protrusion of firing pin	Gage
MAJOR	
101. Metal defective	Visual
102. Protective finish inadequate or defective	Visual
103. Burr	Visual
104. Foreign matter	Visual
MINOR	
None defined	

4.3.2.11 Metal Parts Assembly Dwg. F10551372

CRITICAL	
None defined	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.3.2.11 (Cont'd)

Defect	Method of Inspection
MAJOR	
101. Pellet missing in cap assembly threads	Visual
102. Improper assembly	Visual
103. Any part missing not other wise classified	Visual
104. Material defective	Visual
105. Thread damaged	Visual
MINOR	
201. Protective finish defective	Visual
202. Shipping cap missing	Visual
203. Foreign matter	Visual

4.3.2.12 Fiber Container, Dwg. C9243197

CRITICAL	
None defined	
MAJOR	
None defined	
MINOR	
201. Contents loose	Manual
202. Metal ends loose	Manual
203. Gap between body and cover, max.	Visual
204. Cut or damaged through all impregnated layers	Visual

4.3.2.13 Packing Box, Dwg. C9243198

CRITICAL	
None defined	
MAJOR	
None defined	
MINOR	
201. Contents loose	Manual
202. Hardware missing, loose, broken or improperly engaged	Manual & Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.3.2.13 (Cont'd)

Defect	Method of Inspection
MINOR	
203. Strapping missing, loose, broken or improperly assembled	Manual & Visual
204. Contents of box exposed	Visual
205. Box damaged	Visual
206. Marking missing, incorrect or illegible	Visual
207. Number of units incorrect	Visual

4.3.3 Inspection testing - The following tests shall be performed in accordance with the provisions of 4.4.

4.3.3.1 Hardness - Fifty units from each heat treated lot of components shall be tested for compliance with the values noted on the applicable drawing. Failure of any unit to comply with drawing requirements shall be cause for rejection of the lot.

4.3.3.2 Shear strength

4.3.3.2.1 Shear pin strength - Fifty pins from each lot shall be tested for shear strength. Failure of any shear pin to comply with the requirements of the drawing shall be cause for rejection of the lot.

4.3.3.2.2 Shear pin, initial lock - Fifty pins from each lot shall be tested for shear strength. Failure of any shear pin to comply with the requirements of the drawing shall be cause for rejection of the lot.

4.3.3.3 Protective finish - The number of units for protective finish tests shall be in accordance with the applicable MIL-Standard. Failure of any sample to comply shall be cause for rejection of the lot.

4.3.3.4 Residual magnetism - Each assembly shall be subjected to the test for excessive residual magnetism. Failure of any unit to comply with the requirements of 3.6 shall be cause for rejection of the assembly.

4.3.5 Inspection equipment- The examination and tests shall be made using equipment listed on IEL-10551372.

4.4 Test methods and procedures.

4.4.1 Hardness - Prior to the application of protective finish, a hardness testing machine shall be used to determine the hardness values specified on the detail drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.4.2 Shear pin strength - After application of protective finish, the pins shall be subjected to the shear strength test. The load shall be applied at a steady rate of 0.125 inches per minute.

4.4.3 Protective finish - Test procedures for protective finish shall be in accordance with the MIL-Standard referenced on the component drawing.

4.4.4 Residual magnetism - The thruster shall be tested for excessive residual magnetism in an area free of local magnetic effects by placing the thruster 6 inches from and at the same height as an approved compass, in a north-south horizontal position (head end at south) with the compass set in an east-west heading. The thruster shall be moved slowly past the compass in a longitudinal direction for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly back past the compass. This procedure shall be repeated for each 90 degree rotation of the thruster.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking - Level A. - Packing and marking shall be in accordance with Drawings C9243197 and C9243198.

6. NOTES

6.1 Ordering data - Procurement documents should specify the title, number and date of this specification.

6.2 When compliance with the applicable requirements is in doubt as a result of visual examination the characteristic shall be measured or gaged to determine acceptability.

Custodian

Army - MU

Preparing activity:

Army - MU - (FA)

Project No. 1377-A432

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
Department of the Army

OFFICIAL BUSINESS

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-T1000
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)*

CITY AND STATE

CONTRACT NO.

QUANTITY OF ITEMS PROCURED

DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*

DATE

DD, FORM 1426 APR 63

REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE

C-8279

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.