MILITARY SPECIFICATION

TANK, LIQUID, CARBON DIOXIDE, 40,000 LBS CAPACITY, SEMI-TRAILER MOUNTED

COMMERCIAL

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a commercial 20-ton CO_2 transporter having a 325 psig working pressure, tandem axle, tank, and semi-trailer made to DOT MC331 specifications.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

BB-N-411	- Nitrogen, Technical.
UU-T-81	- Tags, Shipping and Stock.

FSC 3655

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and DevelopmentCommand, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED. STD. No. 595	- Colors.

MILITARY

MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-281	- Automobiles, Trucks, Truck-Tractors, Trailers and Trailer Dollies; Preservation and Packaging of.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code Section VIII Division I. - Rules for Construction of Unfired Pressure Vessels.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

DEPARTMENT OF TRANSPORTATION (DOT)

49 CFR - Transportation.
49 CFR 567 and 568 - Certification.
49 CFR 571 - Federal Motor Vehicle Safety Standards (FMVSS).
49 CFR 390 and 393 - Federal Motor Carrier Safety Regulations (FMCSR).

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.

STATE OF CALIFORNIA DEPARTMENT OF MOTOR VEHICLES

California Vehicle Code.

(Application for copies should be addressed to the Department of Motor Vehicles, 2570 24th Street, Sacramento, CA 95804.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.)

TRUCK-TRAILER MANUFACTURERS ASSOCIATION, INC. (TTMA)

TTMA Recommended Practices.
TTMA Technical Bulletins.

(Application for copies should be addressed to the Truck-Trailer Manufacturers Association, Inc., 2430 Pennsylvania Avenue, NW, Washington, DC 20037.)

REGULAR COMMON CARRIER CONFERENCE (RCCC)

RCCC Recommended Practices Manual.

(Application for copies should be addressed to the Regular Common Carrier Conference, 1616 P Street, NW, Washington, DC 20036.)

TIRE AND RIM ASSOCIATION, INC. (TRA)

Tire and Rim Association Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313.)

INDUSTRIAL FASTENERS INSTITUTE (IFI)

IFI Standards.

(Application for copies should be addressed to the Industrial Fasteners Institute, 1517 Terminal Tower, Cleveland, OH 44113.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General. The transporter shall be of the latest model of the standard product of the offeror and shall have been marketed for 1 year prior to the dates of the opening of the technical proposal. The transporter shall be complete with all components that are customarily offered with a transporter of this type, furnished as standard equipment whether stipulated herein or not, together with such other equipment as may be necessary to enable the transporter to function reliably and efficiently in sustained operation, or to meet requirements set forth in this specification.

3.1.1 First article. Unless otherwise specified, a first article shall be submitted or made ready for approval by the contracting officer or his authorized representative.

3.1.2 Container. The container shall conform to DOT Specification MC-331 of 49 CFR and ASME Code Section VIII, Division I, from SA 517-E, 115,000 psi tensile strength quenched-and-tempered steel, stress-relieved, magnafluxed and X-rayed to ASME specifications. Working pressure shall be no less than 325 psig. Shell thickness shall not be less than 352 inches, head thickness shall not be less than .250 inches. Shape shall be cylindrical with a 61.2 inch diameter having one compartment with three SA 517 E steel internal baffles spaced for control of the liquid CO_2. One manway 15 inches in diameter located in the fronthead, shall be provided.

3.2 Insulation. Between the container and the outer shell there shall be a 6-inch blanket of foamed-in-place polyurethane insuring that all gaps are filled. To prevent heat transfer at metal-to-metal points, Micarta sheets shall be used as thermal barriers and Micarta coating shall be used on the bolts that hold components in place on the container.

3.3 Outer shell. The outer shell shall be made of .063 inch thick aluminum with lapped joints.

3.4 Hose tubes. Four hose storage tubes 6 inches in diameter and 25 feet 6 inches in length, having covers at each end shall be provided. Two tubes shall be located on each side of the tank.

3.5 Cabinets. One rear-mounted cabinet shall be provided. The cabinet shall contain any controls for transfer equipment, liquid level gage, pressure gage, pressure safety reliefs, liquid withdrawal and vapor flanges, and all flow control valves.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.

3.6 Pressure gage. One pressure gage shall be provided with a shut-off valve in the line so it can be removed for servicing without draining the container. It shall have a face of at least 4 inches in diameter, be of the bourdon tube or helical bourdon coil. It shall be of the dial-indicating type, calibrated from 0 to 600 psig in 5 psi increments.

3.7 Liquid level gage. One liquid level gage, of the magnetel float type calibrated in gallons shall be provided.

3.8 Liquid withdrawal. A liquid withdrawal pump, 50 gpm, driven by a 220 volt, 3 phase, 60 Hz, electric motor shall be provided. The electric components shall be of the enclosed type for use in explosive atmospheres. A 100 foot power cord shall be provided. Piping and valving shall be 1-1/2 inches standard National Pipe Threads (NPT). A by-pass for the pump shall be provided. The valves shall be capable of functioning without leaking or freezing during withdrawal or filling of CO_2 at sub-zero temperatures.

3.9 Vapor line. A 1-inch vapor line with standard national pipe threads (NPT) shall be provided. The line shall have a shut-off valve capable of functioning without leaking or freezing during withdrawal or filling of CO_2 at sub zero temperatures.

3.10 Semitrailer requirements.

3.10.1 Weights and dimensions. The tanker weights and dimensions shall be as follows with the tanker prepared for highway travel and tires inflated in accordance with the TRA Yearbook:

(a)	Tanker Curb Weight	Max 21,500 lb.
(b)	Payload Weight, Liquid CO_2	Min 40,000 lb.
(c)	Tanker, GVWR, per DOT 49 CFR 567 and TTMA RP No. 39	Min 57,000 lb.
(d)	Front Coupler Weight limit	Max 46% of GVWR
(e)	Rear Tandem Weight limit	Max 68% of GVWR
(f)	Overall Length	Max 474 inches
(g)	Overall Height	Max 144 inches
(h)	Overall Width	Nominal Max 98 inches
(i)	SAE J701 Interchange Coupling Dimensions:	
	(1) Support Clearance Radius (LCW)	Min 90 inches.
	(2) Swing Radius (SR)	Max 58 inches

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.

(3)	Kingpin Setting (KP)	Range 24 inches to 36 inches
(4)	Coupler Plate Height (FWH)	Nominal 53 inches

3.10.2 Specifications. The transporter semitrailer specifications shall be in accordance with Table I.

Table I. Semitrailer Specifications

Feature	Requirements
(a) Legal Requirements	(1) DOT Certification 49 CFR 567 & 568 (2) DOT FMVSS 49 CFR 571 (3) DOT FMCSR 49 CFR 390 & 393 (4) California Vehicle Code
(b) Industry Standardization	(1) SAE Handbook (2) TTMA RP's & TB's (3) RCCC RP Manual (4) TRA Yearbook (5) IFI Standards
(c) Upper Coupler Assembly	Per DOT FMCSR 393.70, TTMA RP No. 6 and No. 19, TOFC rated; Kingpin per SAE J700, 2-inch diameter, heat treated alloy steel type;
(d) Intervehicular Connections	Front air brake and electrical connections per RCCC RP-107.
(e) Front Supports	Per TTMA RP No. 4 including TOFC operation; Leg travel min 14 inches; providing height compatibility of up to 58 inches tractor 5th wheel heights; Equalizing mud shoes; Gearboxes with silicone base grease per RCCC Advisory AV 7-5.
(f) Suspension	Heavy duty, Min, 36,000 lb tandem rating; Equalizing, two-point-mount type with flexible springs, providing two stage, empty and loaded, ride qualities; Provide longitudinal axle locating rods to counteract brake-torque reactions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.

Table I. Semitrailer Specifications (Cont'd)

Feature	Requirements
(g) Axles	Furnish 2 - each, Tandem configuration; Per DOT FMVSS and TTMA RP #39 GVWR Min 20,000 lb. hub axle rating having Min 21,000 lb axle beams and Min 20,000 lb brakes; Min size 16-1/2 x 7 foundation brakes with type 30 heavy duty spring-brake-chambers, automatic slack adjustors, and outboard mounted brake drums; Lube oil seals per TTMA RP No 43 with visual cap windows; axle hubs per SAE J694, 10 stud, 11-1/4 inch BC; Hubodometer furnished on rearmost curbside axle hub.
(h) Tires and Wheels	All components per TRA Yearbook; Furnish 9 ea, dual tandem, plus spare, inflated tire and disc wheel assemblies. Conventional dual, size Min 11.00-22 or 11.00-24, LR-G (14 PR) with tubes and flaps; Metal valve caps. Cold inflation pressure matched to loading and info painted on rear fender - i.e. "TPXX".
(i) Misc Components	
(1) Fenders, Front & Rear	Per SAE J682 and J683; Fenders of light-weight type of aluminum or FRP material; Bracing to support a min 400 lb load on fenders.
(2) Splash Guards	Per TTMA RP No. 41 and SAE J683; Anti-Sail guard of elastomer material, cold-weather type.
(3) Rear Bumper	Per DOT FMCSR and TTMA RP No 10.
(j) Brake system	Per DOT FMVSS, DOT FMCSR and California Vehicle Code; Straight air service and emergency-parking system;
(1) Gladhands	Per SAE J318 with ID tags, and spring loaded dust covers; Color code yellow for control (SER) and red for supply (EMER); Location 2-ea front per RCCC RP 703.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.

Table I. Semitrailer Specifications (Cont'd)

Feature	Requirements
(2) Reservoir	Per SAE J10; Automatic drain valve on each reservoir.
(3) Anti-lock	121 system, waterproof components, shielded from RFI and EMI; TTMA RP No. 42 indicator on roadside; indicators furnished with bulbs and red lenses.
(4) Plumbing	All hose type per RCCC RP 305 having stainless reinforcement and reusable swivel fittings which permit hose replacement from bulk hose supply.
(k) Vehicle Electrical System	Per DOT, California Vehicle Code, SAE Handbook, RCCC RP Manual and TTMA RP's No 9 and No 14; Heavy duty tanker type vapor proof system providing protection from physical damage, shock, vibration, and environment; System 12-volt potential with negative ground per SAE J538.
(1) Front Receptacle	Per RCCC RP 703 and TTMA RP No 6; Receptacle per TTMA RP 107 with elastomer truck tractor plug support bracket; Connection box with nut and stud terminals, circuit breakers per SAE J553.
(2) Wiring	Per SAE J163 and J555 and RCCC RP Manual; Wire ID code per SAE J560 or, optionally SAE J821; RCCC RP 110 wire having RCCC RP 112 terminals; Wiring encased in instrument grade elastomer tubing water tight system.
(3) Marker Lamps	Per RCCC RP 108/1 vaporproof type flush mount or RCCC RP 108/3 vapor proof type in-line mount; In-line marker lamp of #4 mounting hole type in lieu of #2 mounting hole in 108/3; Reflectors secured to vehicle with metal fastener(s).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.

Table I. Semitrailer Specifications (Cont'd)

Feature	Requirements
(4) Rear Combination Lamps	Per TTMA RP No 14 and SAE J759, SAE IST, vaporproof flush mount, with either shallow or deep lenses, for TTMA hole; Double filament configuration; Total 4 ea., 2 ea outboard Turn & Clearance and 2 ea inboard stop and tail functions.
(5) Bulbs & Lenses	Heavy duty fleet service bulbs; Lenses of polycarbonate plastic.
(6) Wiring Diagram	Plastic or metal plate, showing wiring furnished, Per TTMA TB No 65, installed on each semitrailer.

3.11 Maintenance characteristics. The transporter design, together with accessories, shall permit access to all items requiring periodic maintenance service in the field. Periodic maintenance will be accomplished with the use of conventional general purpose tools normally associated with equipment of this nature. The replacement and adjustment of components and accessories shall be accomplished with minimum drainage requirements and minimum disturbance to other elements of the transporter.

3.12 Lifting and tiedown. Lifting and tiedown attachments, if offered as standard or optional equipment by the offeror shall be provided. If these attachments are not offered as standard or optional equipment, suitable procedures for lifting and tying down shall be provided by the offeror. Instructions for the use of the attachments or procedures shall be included on plates permanently affixed to the transporter.

3.13 Safety. When available as standard or optional equipment, all moving parts and stationary parts subject to high or low operational temperatures that are of such a nature or are so located as to be or could become a hazard to the operating or attending personnel, shall be substantially guarded or insulated to the extent necessary to eliminate the hazard.

3.14 Treatment and painting. The parts of the transporter normally painted shall be cleaned, treated, and painted in accordance with the offeror's standard commercial practice provided it is equal to MIL-T-704, Type D, for pretreatment and primer. The exterior finish of the tank shall be Color No. 24087 conforming to FED. STD. No. 595.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined and tested in accordance with referenced specifications, standards, and drawings, as applicable.

4.2 First article evaluation and demonstration. Prior to delivery, the manufacturer shall make one or more transporters available, selected at random from transporters being produced from production tooling, *for first article transporter evaluation and demonstration.* The transporter and its components shall be compared with this document, DOT MC331 specification, published literature, calculations, and test data, to verify compliance with this specification. The transporter shall then be subjected to a demonstration as specified herein. Permanent deformation, malfunction, failure to meet performance requirements, or failure to complete any demonstration, shall be basis for rejection of the first article transporter. If such deficiencies do arise, they shall be corrected and the first article evaluation and demonstration shall be repeated.

4.3 Demonstrations.

4.3.1 Demonstration conditions. Unless otherwise specified herein, demonstrations shall be conducted at the ambient temperature and climatic conditions existing at the place of demonstration. Only that maintenance established by the contractor and submitted as a maintenance schedule prior to commencement of the demonstrations shall be performed during the demonstrations.

4.3.2 Mobility. With the transporter prepared for travel, complete with all equipment installed and secured, couple the transporter to the applicable truck-tractor and perform the mobility demonstrations as shown in Table II and as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.

Table II. Road Demonstrations

Course	Mileage and speed
Highway	300 mi. at up to 55 mph, min.
Secondary roads	180 mi. at up to 30 mph, min.
Off-road	20 mi. at up to 20 mph, min.

During the road demonstrations perform the following and record actual results:

(a) Tow the transporter over minimum 7-inch-high obstacles such that all combinations of transporter wheels have passed over the obstacles. Observe tire-to-surface contact, evidence of binding or interference, and, after returning the suspension to normal, measure the diagonals and parallels. Questionable tire-to-surface contact shall be retested with single sheets of newspaper under the tires. Ability to remove the newspaper from under any tire shall be evidence of insufficient tire-to-surface contact.

(b) Tow the transporter through mud at least 12 inches deep for not less than 100 feet. Any prime mover may be used for this phase.

(c) Tow the transporter over V-ditches, negotiating the ditches both perpendicular and at 45 degrees to direction of travel for at least 20 times, total. V-ditches shall be the standard highway type of at least 36 inches wide and 18 inches deep.

(d) Measure and record the deviation or off-tracking of the transporter with respect to the truck-tractor, when towed straight ahead on a level-paved-surface, and compare with DOT FMCSR.

(e) Jackknife the transporter at angles of at least 90 degrees from straight ahead both to the left and to the right.

(f) Turn the combination in the sharpest rolling turn to the right for two complete circles and repeat in the opposite direction to the left.

(g) Demonstrate the brake performance of the transporter for conformance to DOT FMVSS, DOT FMCSR, and the California Vehicle Code.

(h) Test the transporter air brake system as specified in TTMA RP No. 12 and RP No. 44.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.

(i) Demonstrate compatability of the transporter to couple and uncouple from truck-tractors. Demonstrate the ability of the front supports to raise and lower the transporter and to withstand free falls, during uncoupling, by rapidly pulling the truck-tractor out from under the transporter.

4.3.3 Performance. The transporter shall be loaded with not less than 40,000 pounds of CO_2 and run thru not less than 50 percent of the road demonstrations in Table II.

4.3.3.1 Pump. After completion of 4.3.3, the remaining CO_2 shall be pumped out of the transporter.

4.4 Inspection of packaging.

4.4.1 Quality conformance inspection of pack.

4.4.1.1 Examination. Each transporter shall be examined for the following defects. One or more defects shall be cause for rejection.

101. Nitrogen not in accordance with referenced document for Level A.
102. Tank not completely purged with nitrogen for Level A.
103. Tank not pressurized to required pressure for Level A.
104. Nitrogen cylinder not supplied and not as specified for Level A.
105. Tag not as specified and not printed with waterproof ink for Level A.
106. Marking illegible, incorrect, or incomplete.

4.5 First article demonstration report. The contractor shall prepare and submit the first article demonstration report to the contracting officer for approval within the time frame specified (see 6.2). The report shall include a detailed description of the examination and demonstration performed, deficiencies encountered and actions taken to correct the deficiencies.

5. PACKAGING

5.1 Preservation. Preservation shall be Level A or Commercial as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.

5.1.1 Level A.

5.1.1.1 Tank. The tank and lines shall be purged with dry nitrogen conforming to BB-N-411, Type I, Class 1, Grade A or B. After purging, the tank shall be pressurized with nitrogen to a pressure of 5 psig minimum. A 200 cu. ft. nitrogen cylinder charged to 2200 psi shall be provided to maintain pressure in the tank. The cylinder shall be secured in an accessible location and a tag attached to the valve indicating: "This tank is pressurized with dry nitrogen." The tag shall conform to UU-T-81, Type A. Printing thereon shall be with waterproof ink.

5.1.1.2 Trailer. The trailer shall be preserved in accordance with the Level A requirements of MIL-STD-281.

5.1.2 Commercial. The tank trailer shall be preserved to afford protection against deterioration and damage during shipment from the contractor to the initial destination.

5.2 Packing. The tank trailer shall be prepared for mobile shipment and requires no packing (see 6.3).

5.3 Marking (see 6.3).

5.3.1 Military. Marking for military packaging shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Marking for commercial packaging shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The transporter is intended for use in transporting and limited storage of liquid CO_2.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) When a first article is not required.
(c) Time frame for submitting the first article demonstration report (see 4.5).
(d) Degree of preservation and packing required (see 5.1 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.

6.3 The tank trailer is prepared for mobile shipment and therefore packing levels are not specified in this document. For the purpose of marking, the levels of packing shall be designated Level A or Commercial with the designation being the same as that specified for preservation, i.e. A/A or Commercial/Commercial.

6.4 Publications. The contracting officer shall determine that the contractor's operators parts, maintenance, and overhaul manuals are approved by the Government prior to shipment of the first transporter.

6.5 The contracting officer should include requirements for such data as technical publications, instructional materials, illustrated parts lists, and contractor's operator and maintenance manuals to be furnished with each transporter.

6.6 Provisioning. The contracting officer should include provisioning requirements for repair parts and maintenance tools as necessary (including any manuals, special tools), and shipping instructions.

6.7 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification (see 3.4).

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 3655-A083

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Mobility Equipment Research and
Development Command
ATTN: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-T-52949(ME) Tank, Liquid, Carbon Dioxide, 40,000 Lbs Capacity, Semi-Trailer Mounted Commercial

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.