MILITARY SPECIFICATION

TURRET SUBSYSTEM, UNIVERSAL (UTS) FOR ARMAMENT SUBSYSTEM, HELICOPTER, 20MM: M97E1 AND M97E2, UNIVERSAL BORESIGHT KIT FOR

The specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains quality assurance provisions and preparation for delivery for Universal Boresight Kits (UBK) for the Armament Subsystem/ Helicopter, 20mm: M97E1 and M97E2.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-W-63150	-	Weapons and Support Materiel, Standard Quality Assurance Provisions for.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-0-23103:03Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

MIL-STD-595 - Color

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-810 - Environmental Test Methods.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and pulications form a part of this specification to the extent specified herein.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

11830730 Boresight Kit, Universal

PACKAGING DATA SHEETS

P11830730 Boresight Kit, Universal

AhiERiCAN SOCIETY FOR TESTING AND MATERIALS (ASTM]

ASTM E 18 - Method and Tests for Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials.
ASTM B 117 - Method of Salt Spray (Fog) Testing.

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, P3 19103.)

(Copies of specifications, standards, handbooks, drawings and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings, specifications and standards.

3.2 Parts. All parts shall comply with applicable drawings, specifications and standards.

3.3 Universal Boresight Kit. The universal Boresight Kit (UBK) shall comply with all requirements specified on Drawing (Dwg) 11830730, all associated drawings, and with all requirements specified in applicable specifications and standards.

3.4 Performance requirement. The UBK shall provide a means of projecting the centerline of the firing barrel of the gun (7.62MM, 20MM, or 30MM) onto a distant boresight target with a maximum angular error of 1.50 mils. The fiber optic eyepiece shall be of sufficient length and clarity that the crewman can view the boresight target through the telescope without having to stand in the gun barrel path in the event the barrels are slewed during boresighting.

3.4.1 Weight. The UBK shall not exceed 20 lbs.

3.4.2 Color. The carrying case of the UBK shall have a slate gray color, complying with FED-STD-595 Color No. 26270.

3.5 Environmental conditions (first article testing only). The universal Boresight Kit (UBK) shall operate and meet the performance requirements of 3.4 under any of the environmental conditions, or reasonable combination of these conditions, as specified below:

3.5.1 Natural environment. UBK components shall operate satisfactorily and withstand storage in the worldwide conditions as listed below:

3.5.1.1 High temperature. The UBK shall perform all functions satisfactorily after being subjected to +160°F when tested as specified in 4.5.4.1.

3.5.1.2 Humidity. The UBK shall operate satisfactorily in relative humidity up to 100 percent including conditions where condensation is in the form of water and frost when tested as specified in 4.5.4.1.

3.5.1.3 Salt atmosphere. The UBK shall operate satisfactorily after being subjected to MIL-STD-810, Method 509.1 for 12 hours when tested as specified in 4..5.4.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

3.5.1.4 Sand and dust. The UBK shall operate satisfactorily after being subjectea to MIL-STD-810, Method 510.1.

3.5.1.5 Explosive atmosphere. The UBK shall operate satisfactorily in explosive vapor within or surrounding the equipment.

3.5.1.6 Rain. The UBK components shall operate satisfactorily without degradation in specified performance and shall sustain no physical damage during periods of heavy precipitation.

3.6 Interchangeability. All parts having the same part number shall be completely Interchangeable with each other and with like parts of other manufacture with respect to installation and performance.

3.7 Proof test (first article inspection only). UBK's shall operate satisfactorily in accordance to the intent of the design When boresighting an accepted Universal Turret Subsystem.

3.8 First article inspection. This specification contains technical previsions for first article inspection. Requirements for the submission of first article by the contractor shall be as specified in the contract.

3.5 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner: and all manufacturing, processing, and assembly operations shall be correctly performed. The parts shall be clean and free of burrs, sharp edges, cracks, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous, however, a few light scratches not exposing base material may be permitted. All required markings and stamping shall be neat and sharply defined. Required packing shall be dry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-W-63150 shall apply and are hereby made a part of this detail specification.

4.1.1 Certification of provisions. The certification provisions of MIL-W-63150 shall apply (see 6.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The following types of inspection shall be conducted on this item:

a. First Article Inspection (see 4.3).

b. Quality Conformance Inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing	Quantity
Adapter, Muzzle, 20MM	B11830732	2
Adapter, Muzzle, 30MM	B11830734	2
Adapter, Muzzle, 7.62MM	B11830736	2
Case, Carrying	D11830737	2
Fiberscope	C125C3894	2
Telescope, Boresight	C125C3921	2
Boresighting Kit, Universal	C11830730	2

4.3.2 Inspections to be performed. See Table I specified herein.

4.3.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon amy failure of any assembly component or test specimen in the sample to comply with any of the stated requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-T-63531(AR)

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
	Boresight Kit, Universal		1 OF 2		See Below
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Adapter, Muzzle, 20MM (Dwg. 11830732)				
	Examination for defects	2		3.2	4.4.2.1
	Adapter, Muzzle, 30MM (Dwg. 11830734)				
	Examination for defects	2		3.2	4.4.2.2
	Adapter, Muzzle, 7.62MM (Dwg. 118307365)				
	Examination for defects	2		3.2	4.4.2.3
	Hardness	2		3.2	4.5.3
	Salt Test	2		3.2	4.5.2
	Case, Carrying (Dwg. 11830737)				
	Examination for defects	2		3.2	4.4.2.4
	Fiberscope (Dwg. 125C3894)				
	Examination for defects	2		3.2	4.4.2.5
	Telescope, Boresight (Dwg. 125C3921)				
	Examination for defects	2		3.2	4.4.2.6

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:03Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63531(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
Cont'd	Boresight Kit, Universal				See Below
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Boresight Kit, Universal (Dwg. 11830730)				
	Examination for defects	2		3.2	4.4.2.7
	Environmental tests	2		3.5	4.5.4
	Interchangeability	2		3.6	4.6
	Proof test	2		3.7	4.5.5

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-04-29T03:03Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Lot formation. The term “inspection lot” is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which drawn and presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions and complies with the provisions for submission of product as specified in MIL-STD-105. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with the requirements. In addition, each lot shall contain:

a. Carrying Cases of one lot interfix number from one manufacturer.

b. Fiberscopes of one lot interfix number from one manufacturer.

c. Boresight telescopes of one lot interfix number from one manufacturer.

d. Carrying Cases of one lot interfix number from one manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-T-63531(AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Adapter, Muzzle, 20MM				B11830732
					NEXT HIGHER ASSEMBLY
					B11830731
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter under flange and end diameter (.7885)		0.65%	3.2	SMTE
102	True position of diameter under flange and end diameter		0.65%	3.2	SMTE
Minor					
201	Position of holes		1.50%	3.2	SMTE
202	Total length		1.50%	3.2	SMTE
203	Marking misleading, illegible or missing		1.50%	3.2	Visual
204	Poor workmanship		2.50%	3.9	visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63531(AA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Adapter; Muzzle, 30MM		B11830734
			NEXT HIGHER ASSEMBLY B11830733

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter under flange and end diameter (1.1855)		0.65%	3.2	SMTE
102	True position of diameter under flange and end diameter		0.65%	3.2	SMTE
Minor					
201	Position of holes		1.50%	3.2	SMTE
202	Length to flange		1.50%	3.2	SMTE
203	Marking misleading, illegible or missing		1.50%	3.2	Visual
204	Poor workmanship		2.50%	3.9	Visual

NOTES:

10

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63531(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Adapter, Muzzle, 7.62MM				B11830736
					NEXT HIGHER ASSEMBLY
					B11830735
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter on A surface (0.2950)		0.65%	3.2	SMTE
102	Diameter immediately under flange (.304)		.065%	3.2	SMTE
103	Parallelism of internal taper		0.65%	3.2	SMTE
Minor					
201	Length to flange (chamfer end)		1.50%	3.2	SMTE
202	Length to smaller diameter (4.516)		1.50%	3.2	SMTE
203	Knurl missing or unsatisfactorily		1.50%	3.2	Visual
204	Sharp edges or corners or projection dangerous to handling personnel		1.50%	3.2	Visual/Manual
205	Marking misleading, illegible or missing		1.50%	3.2	Visual
206	Poor workmanship		2.50%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER D11830737
4.4.2.4	Case, Carrying				NEXT HIGHER ASSEMBLY C11830730
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Filler cushion material improper or missing		0.65%	3.2	Visual
102	Color incorrect		0.65%	3.2	Visual
103	Hardware broken, loose		0.65%	3.2	Visual
104	Closure unsatisfactorily		0.65%	3.2	Visual/Manual
105	Case damaged (punture, dented or deformed)		0.65%	3.2	Visual
Minor					
201	Length		1.50%	3.2	SMTE
202	Width		1.50%	3.2	SMTE
203	Height		1.50%	3.2	SMTE
204	Marking misleading, illegible or missing		1.50%	3.2	Visual
205	Poor workmanship		2.50%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OR DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER C125C3894
4.4.2.5	Fiberscope				NEXT HIGHER ASSEMBLY C11830730
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Coherency unsatisfactorily *(Note 3)		0.65%	3.2	SMTE
102	Minor diameter of thread		0.65%	3.2	SMTE
103	Pitch diameter of thread		0.65%	3.2	SMTE
104	Part missing (eyepiece, eyecup, cuff of jacket)		0.65%	3.2	Visual
105	Part damaged, dented punctured or deformed		0.65%	3.2	Visual
Minor					
201	Poor workmanship		2.50%	3.9	Visual

NOTES:

* Notes refer to drawing.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63531(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER C125C3921
4.4.2.6	Telescope, Boresight				NEXT HIGHER ASSEMBLY C11830730
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Optical line of sight deviation, max		0.65%	3.2	SMTE
102	Major diameter of thread		0.65%	3.2	SMTE
103	Pitch diameter of thread		0.65%	3.2	SMTE
104	Thread length, min.		0.65%	3.2	SMTE
105	Part missing		0.65%	3.2	Visual
106	Part damaged, punctured, dented or deformed		0.65%	3.2	Visual
Minor					
201	Marking misleading, illegible or missing		1.50%	3.2	Visual
202	Poor workmanship		2.50%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIOFICATION OF DEFECTS & TESTS

MIL-T-63531(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER C11830730
4.4.2.7	Boresight Kit, Universal				NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Performance		0.65%	3.4	4.5.1
102	Weight, maximum		0.65%	3.4.1	Balance
103	Part or assembly missing		0.65%	3.2	Visual
104	Part damaged (cracked, dented, etc)		0.65%	3.2	Visual
105	Assembly in case improper		0.65%	3.2	Visual
106	Marking misleading, unidentifiable or missing		0.65%	3.2	Visual
Minor					
201	Identification plate missing		1.50%	3.2	Visual
202	Carrying case damaged, dented or deformed		1.50%	3.2	Visual
203	Hardware, screw or rivet loose or missing		1.50%	3.2	Visual
204	Poor workmanship		2.50%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

4.4.2 Examination. The examinations listed in this specification for Classification of Defects shall be performed on inspection lots as defined in 4.4.1 of this specification.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Tests Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the “Paragraph Reference/Inspection Method column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.5). All inspection and test equipment shall be calibrated in accordance with MIL-W-63150. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See 6.3 herein.

4.5 Methods of inspection.

4.5.1 Performance test. The Universal Boresight Kit (UBK) shall be tested for compliance with the specified performance requirements. Any UBK which fails to comply with the specified performance requirement or evidences degradation of its operational performance shall be classed defective. Test equipment and procedures shall be satisfactory to the contracting officer (see 4.4.4).

4.5.2 Salt spray test. Samples shall be selected from each protective finished lot and subjected to the salt spray test in accordance with the procedures specified in ASTM B 117. Unless otherwise specified on the applicable drawing the minimum exposure time shall be one and one half (1 1/2] hours using a 5% sodium chloride solution. Rejection shall be in accordance with the applicable protective finish specification.

4.5.3 Samples shall be selected from each heat treatment batch (see Note) and subjected to this test. If any part fails to comply with the requirement specified on the applicable drawing, the part shall be classed defective. The hardness test shall be performed in accordance with the procedure specified in ASTM E 18. Each heat treat batch shall remain segregated until completion of

Source: https://assist.dla.mil - Downloaded: 2026-10-25T03:03Z
Check the source to verify that this is the current version before use.

4.5.4 Environmental characteristics (first article inspection only).

4.5.4.1 Temperature-humidity. The Universal Boresight Kit (UBK) shall be subjected to temperature-humidity testing as follows:

a. With the temperature nonoperating, adjust chamber temperature at +160°F with uncontrolled humidity and stabilize UBK. Maintain this condition for not less than 4 hours.

b. Return chamber to room ambient (temperature and humidity). Upon stabilization of UBK, operate UBK as specified in 4.5.1.

4.5.4.2 Salt fog. The UBK shall be subjected to the test of Method 509.1 of MIL-STD-810. Operation of the UBK shall not be requires and failure criteria shall be limited to corrosion of finishes and metals only. Such corrosion shall be defined as visible degradation of the UBK surfaces that can be attributed to flakey, pitted, blistered, or otherwise loosened finish or metal surface.

4.5.4.3 Sand and dust. The UBK shall be subjected to the test of Method 510.1 of MIL-STD-810, Procedure 1, except temperature to be +73°F and relative humidity of less than 22 percent. Air velocity to be 1750 ± 250 feet per minute and dust concentration at 0.3 ± 0.2 mx/ft3 and maintain these conditions for 6 hours. After 6 hours, turn off air velocity and dust feed and stabilize. Perform operation test (4.5.1] before any cleaning is performed.

4.5.4.4 Explosive atmosphere. The UBK shall be subjected to the test of Method 511.1 of MIL-STD-810, Procedure I, except test to be limited to altitude of ground level.

4.5.4.5 Rain. Method 506.1, Procedure I, of MIL-STD-810 shall apply. During each 30 minute rain period, the wind shall be maintained for net less than 15 minutes commencing 5 minutes after the start of the period as specified in the procedures. The UBK shall be operated as specified in 4.5.1 during the last 10 minutes of the 30-minute period.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

4.5.5 Proof test (first article inspection only). When specified in the contract (see 6.2) two (2) UBK'S shall be

4.6 interchangeability testing (first article inspection only).

4.6.1 Universal Boresight Kit (UBK). A sample of 2 UBK's, randomly selected, shall be tested for interchangeability using the test method specified in 4.6.3. UBK's taken for interchangeability testing shall have been found satisfactory in all other examinations and tests. The 2 UBK's shall comply with the applicable specification functioning test of 4.5.1, before and after the interchange of parts. It shall be the responsibility of the agency responsible for the test to inform the contracting officer by letter or other methods satisfactory to the contracting officer, when selective assembly has become necessary. Statement shall contain as a minimum, the contractor's name and FSCM, contract number, parts involved in the selective fit, conditions of parts and rationale for action taken. No hand refinement of parts shall be permissible without approval by the contracting officer. No malfunctions shall be allowed in the functioning tests. Failure of drive assembly in the interchangeability test shall cause retest or rejection of the represented lot. At the discretion of the Government representative, an interchangeability retest may be allowed without reconditioning the lot. Failure during the retest shall cause rejection of the represented lot subject to reconditioning and further test as a reconditioned lot. A sample of 4 UBK'S from each retest or reconditioned lot shall be tested using the same procedure described below.

4.6.2 Repair parts. At least 2 parts from each inspection lot of concurrent repair parts shall be subjected to the interchangeability test specified in 4.6.3. Failure of any part to meet the interchangeability requirements shall be cause for rejection of the represented lot, subject to reconditioning and further test as a reconditioned lot. A sample consisting of double the number of parts used in the original test shall be tested from each reconditioned lot using the test methods specified above.

4.6.3 Test method for interchangeability. UBK's shall be tested by disassembling and then reassembling the parts specified below. Parts shall be disassembled from the UBK'S and identical parts placed together and mixed. Any commercial part (screws, pins, etc) rendered unserviceable by-disassembly shall be replaced without penalty to the interchangeability test.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

LIST OF INTERCHANGEABLE PARTS

Part Description	Drawing
Adapter, Muzzle, 20MM	B11830732
Adapter, Muzzle, 30MM	Bl1830734
Adapter, Muzzle, 7.62MM	B11830736
Case, Carrying	D11830737
Fiberscope	C125C3894
Telescope, Boresight	C125C3921

4.6.4 Repair parts. Concurrent repair parts shall be tested by disassembling a UBK previously tested 4.6.3 and then reassembling them using the concurrent repair parts. No hand refinement of parts will be allowed and the assembled UBK shall operate and function as intended. This test may be performed independently of the UBK interchangeability testing specified in 4.6.1 and at more frequent intervals using accepted UBK'S taken from current production

5. PACKAGING

5.1 Preservation, packaging, packing and marking. Universal boresight kits shall be preserved, packaged, packed and marked in accordance with the requirements of the preservation and Packaging Data Sheet P11830730.

5.1.1 Spare parts or replacement parts. Spare parts or replacement parts shall be cleaned, preserved, packaged and packed as specified in the contract or order.

6. NOTES

6.1 Intended use. The UBK covered by this specification is intended for use with Gun, automatic, 20MM: M197 on Armament Subsystem, Helicopter, 20MM: M97E1 and M97E2.

6.2 Ordering data. Procurement documents shall specify the following:

6.2,1 Procurement requirements.

a. Title, number and date of this specification.

b. Quantity required and delivery schedules

Source:https://assist.dla.mil - Downloaded: 2026-02-23T08:03Z
Check the source to verify that this is the current version before use.

e. First Article sample requirements, if other than specified in section 4 of this specification.

f. Packaging requirements, if other than specified in Section 5 of this specification.

g. Certificates of conformance for each lot or shipment of product.

6.2.2 Contract data requirements. Contract data requirements for inspection equipment design shall conform to Data Item Description DI-R-1714, Tailored.

6.3 Submission for inspection equipment design for approval. See MIL-W-63520. Equipment designs shall be submitted as required to: Commander, ARRADCOM, ATTN: DRDAR-QAF, Dover, NJ 07801. Request letter of submittal shall state contractor, contract number, specification number, item nomenclature, and classification of defects and test paragraphs.

6.4 Submission of results of contractor-conducted examinations and tests. Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to: Commander, ARRADCOM, ATTN: DRDAR-QAF-S, Dover, NJ 07801.

Custodian:
Army-AR

Preparing activity:
ArmY-AR

(project 1OO5-A613)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-T-63531 (AR) TURRET SUBSYSTEM

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.