INCH-POUND

MIL-DTL-3628/208A
21 June 2000
SUPERSEDING
MIL-DTL-3628/208
14 April 2000

DETAIL SPECIFICATION SHEET

BADGE, IDENTIFICATION, SECRETARY, DEPARTMENT OF HEALTH AND HUMAN SERVICES

Inactive for new design after 14 April 2000.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

ASSEMBLED



BASE



EAGLE DEVICE

OAK LEAVES DEVICE

Dash No.
-1: Regular Size
-2: Miniature Size

MATERIAL:

BASE: Gilding Metal
OAK LEAVES DEVICE: Red Brass
EAGLE DEVICE: Gilding Metal

FINISH:

BASE: Hard Enameled, Nickel Plated, Silver Plated, Oxidized, Relieved, Matte Finish and shall match The Institute of Heraldry (TIOH) Metal Finish Chip number 14.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:09Z
Check the source to verify that this is the current version before use.

OAK LEAVES DEVICE: Gold Plated, Matte Finish, Polished Highlights and shall match
TIOH Metal Finish Chip number 8.
EAGLE DEVICE: Enameled, Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip number 8.

DIMENSIONS:

HEIGHT (assembled):
-1: 2-1/8 inches (REF)
-2: 1-3/8 inches (REF)

EAGLE DEVICE HEIGHT (highest to lowest point)
-1: 1-3/8 inches (REF)
-2: 7/8 inch (REF)

BASE DIAMETER:
-1: 2 inches (REF)
-2: 1-5/16 inches (REF)

OAK LEAVES DEVICE WIDTH:
-1: 1-7/8 inches (REF)
-2: 1-1/4 inches (REF)

THICKNESS (assembled, at thickest point):
-1: 0.162 ± 0.010
-2: 0.158 ± 0.010

OTHER THICKNESSES:
BASE (at enameled ring):
-1: 0.075 ± 0.005
-2: 0.075 ± 0.005
EAGLE DEVICE (at center of shield):
-1: 0.083 ± 0.005
-2: 0.081 ± 0.005
OAK LEAVES DEVICE (at corner of bottom left leaf)
-1: 0.085 ± 0.005
-2: 0.075 ± 0.005

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Refer to TIOH drawing number B-5-150 for the location of the 12 piercings:

11 internal piercings:
a. between wings of caduceus and snake heads (2)
b. between neck of eagle and left wing (1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:09Z
Check the source to verify that this is the current version before use.

c. between head of eagle and top of left wing (1)
d. above corner of right shield and lower portion of right wing (1)
e. between lower edge of right wing and top portion of anchor (1)
f. inside lug on top of anchor (1)
g. in and around ropes (4).

1 external piercing: between lower left of shield and right bottom edge of anchor.

3. Attaching device shall be prong and flat ball clutch type:

a. -1: three prongs shall be located on a 1-3/4 inch ± 1/64 inch diameter circle.
b. -2: three prongs shall be located on a 1 inch ± 1/64 inch diameter circle.
c. -1 and -2: prongs shall be spaced 120 degrees apart with the top prong located on the vertical centerline at the top of the badge.

4. The eagle device shall be attached to the base by means of a screw post and Type A back plate shown on TIOH Drawing 4-4-89. The screw post shall be made from any type brass. The back plate shall be made from any type of 1/4 inch hard brass. The screw post shall be 0.140 inch ± 0.005 inch long and shall be hard soldered or fused to the device in a location to correctly position the device on the base. The base shall have a 0.130 inch ± 0.003 inch square hole cut through and centered on the base. The oak leaves device may be soldered or attached to the base as determined by the manufacturer.

5. Enameled areas shall be as indicated below, and colors shall conform to the following TIOH Hard Enamel Color Chip numbers:

AREA	COLOR	CHIP NUMBER
Device:		
background behind stars	ultramarine blue	18
stripes inside shield	red	1
Base: outside circle	ultramarine blue	18

6. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer. When epoxy resin is used in lieu of hard enamel, the material requirement shall be gilding metal or red brass.

7. The base shall be lacquered prior to assembly. The devices may be lacquered at the option of the manufacturer.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0015)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:09Z
Check the source to verify that this is the current version before use.