INCH-POUND

MIL-DTL-3628/212
24 April 2001

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, AVIATION, AIR BATTLE MANAGER, SENIOR, AIR FORCE

Inactive for new design after 24 April 2001.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass or Nickel Silver

FINISH: Nickel Plated (Red Brass only), Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.

DIMENSIONS:

HEIGHT (overall):
-1: 1-3/16 inches (REF)
-2: 25/32 inch (REF)
WIDTH (overall):
-1: 3 inches (REF)
-2: 2 inches (REF)
THICKNESS (at thickest point of wings):
-1: 0.130 inch ± 0.005 inch
-2: 0.095 inch ± 0.005 inch

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:10Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to measurements taken from the Government furnished hub or die.

2. Attaching device shall be prong and wing-type clutch. The prongs shall be located on the horizontal center line, equidistant from each end and the following distance apart.

Dash -1: 2 inches ± 1/32 inch
Dash -2: 1-1/2 inches ± 1/32 inch

3. A mock forcer may be used to bring up the design of the shield and ridge line of the wings only.

4. Piercing shall be as indicated.

Custodian:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activities:
Air Force - 99
DLA - CT

(Project No. 8455-0045/002)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:10Z
Check the source to verify that this is the current version before use.