NOT MEASUREMENT SENSITIVE


MIL-DTL-3628/216B
5 October 2020
SUPERSEDING
MIL-DTL-3628/216A
4 December 2015

DETAIL SPECIFICATION SHEET


# BADGE, QUALIFICATION, EXPLOSIVE ORDNANCE DISPOSAL, U.S. ARMY

This specification is approved for use by all
Departments and Agencies of the Department of Defense


The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628.




**BASIC**




**SENIOR**




**MASTER**

DASH NO:
- -1: Basic, Regular Size
- -2: Senior, Regular Size
- -3: Master, Regular Size
- -4: Basic, Regular Size, Subdued
- -5: Senior, Regular Size, Subdued
- -6: Master, Regular Size, Subdued
- -7: Basic, Dress Miniature Size
- -8: Senior, Dress Miniature Size
- -9: Master, Dress Miniature Size

MATERIAL:
-1 thru –3, and -7 thru -9: Red Brass 85/15 (UNS Alloy No. C-230) or Nickel Silver 65/35 (UNS Alloy No. C-752)

-4 thru -6: Red Brass 85/15 (UNS Alloy C-230)

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:11Z
Check the source to verify that this is the current version before use.

FINISH:
-1 thru –3, -7 thru -9: Nickel plated, Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 16. Reverse shall be bright and clean.

-4 thru -6: Dull, Flat Black Enamel Finish and shall match TIOH Metal Finish Chip Number 21.

DIMENSIONS:
HEIGHT (Overall):
-1, -2, -4, -5: 1 inch (REF)
-3, -6: 1-7/16 inches (REF)
-7, -8: 1/2 inch (REF)
-9: 3/4 inch (REF)
WIDTH (Overall):
-1 thru -6: 1-3/4 inches (REF)
-7 thru -9: 7/8 inch (REF)
THICKNESS (At thickest point):
-1, -4, -8, -9: 0.095 ± 0.010 inch
-2, -3, -5, -6: 0.140 ± 0.010 inch
-7: 0.060 ± 0.010 inch

ATTACHING DEVICE:
1. Attaching device shall be prong and clutch type.

2. Two prongs shall be located at each intersection of the horizontal center line of the badge and the center of each side of the wreath.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Piercing shall be as indicated except that piercing around wreath and star applies to regular size badges only.

4. -1 through -3 and -7 through -9 Silver Plated Oxidized Buffed Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14, May be used for commercial sale.

5. Other specification sheets which, in addition to MIL-DTL-3628/216, supersede the canceled MIL-DTL-3628/25M are as follows:
MIL-DTL-3628/217 BADGE, QUALIFICATION, EXPLOSIVE ORDNANCE DISPOSAL, AIR FORCE
MIL-DTL-3628/218 BADGE, QUALIFICATION, EXPLOSIVE ORDNANCE DISPOSAL, NAVY AND MARINE CORPS

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:11Z
Check the source to verify that this is the current version before use.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2020-572)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:11Z
Check the source to verify that this is the current version before use.