INCH-POUND

MIL-DTL-3628/222A
28 May 2003
SUPERSEDING
MIL-DTL-3628/222
18 October 2002

DETAIL SPECIFICATION SHEET

BADGE, IDENTIFICATION, U.S. NORTHERN COMMAND

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-3628.



REGULAR SIZE



MINIATURE SIZE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Gilding Metal or Red Brass

FINISH:

-1 and -2: Hard Enameled or Epoxied, Gold Plated, Mirror-like Polished, and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 6.
-1 Letters: Nickel Plated, Mirror-like Polished, and shall match TIOH Metal Finish Chip Number 16.

DIMENSIONS:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:13Z
Check the source to verify that this is the current version before use.

DIAMETER:
-1: 2-1/4 inches (REF)
-2: 1-1/2 inches (REF)

THICKNESS (at thickest point):
-1: 0.085 ± 0.010 inch
-2: 0.075 ± 0.010 inch

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. When hard enamel is used, the material requirement shall be gilding metal. When epoxy is used, the material requirement shall be gilding metal or red brass.

3. Epoxy/enamel colors shall match TIOH Hard Enamel Chip Colors and shall be located as follows:

COLOR	DASH NO.	LOCATION
Scarlet # 1	-1 -1 & -2	Outside and inside circular borders surrounding motto. Three alternating stripes of shield. (Total of seven stripes are white, red, white, red, white, red, white.)
Transparent Green # 11	-1 & -2	Olive branches.
Green # 13	-1 & -2	Land masses.
Cobalt Blue #20	-1 -1 & -2 -2	Background of motto. Chief of shield surrounding stars. Outside circular border.
Transparent Brown # 25	-1 & -2	Eagle's wings, legs, and top portion of tail feathers.
White # 28	-1 & -2 -1 & -2	Eagle's head and bottom portion of tail feathers. Alternating four stripes of shield (starting and ending with white).
Bluebird #33	-1 & -2	Background areas of badge which signify water.

4. Attaching device shall be prong and flat ball type clutch. Three prongs shall be located on the reverse on an approximate 2 inch diameter circle for -1 and a 1 inch diameter circle for -2. Each prong shall be spaced 120° apart with the bottom prong located on the vertical center line at the bottom of the badge.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0120/001)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:13Z
Check the source to verify that this is the current version before use.