INCH-POUND

MIL-F-63090A(AR)
AMENDMENT 4
12 February 1993
SUPERSEDING
AMENDMENT 3
3 May 1984

MILITARY SPECIFICATION

FIRING DEVICE, MULTI-PURPOSE, M142
PARTS, ASSEMBLY AND PACKING

This amendment forms a part of MIL-F-63090A(AR), dated 21 April 1981, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1: DRAWINGS - Add the following to the list of drawings:

"9349653 - Test Cap, Blasting, Non-Electric, for M142 Firing Devices."

3.3.2, Lines 3 and 4: Change to read:

"the tension release attachment is released upon cutting the trip wire or flipping it off a pin when tested as specified in 4.5.1.2."

PAGE 3

3.3.4: Delete this paragraph and substitute a new paragraph to read:

"3.3.4 Pressure release. The firing device shall function at two (2) pounds or less when a load of four (4) pounds is applied to the sear platform and then gradually reduced when tested as specified in 4.5.1.4."

PAGE 11

* 4.4.2.5: Under "DRAWING NUMBER", change to read:

"9296867-1 or 929687-2"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:10Z
Check the source to verify that this is the current version before use.

PAGE 13

4.4.2.7: Change "missing, not opened or improperly assembled" to "not in place".

PAGE 22

4.4.2.16, Major 101: Delete and sustitute a new Major 101 to read:

"101 Any warning statement, phrase or word not printed in proper color"

PAGE 29A

* 4.4.2.24: Add new paragraph 4.4.2.24 as included.

PAGE 37

4.5.1.1: Second sentence: Delete "Screw ... switch." and substitute a new sentence to read:

"Screw coupling base with attached M7 Non-Electric Blasting cap or alternative test cap (Dwg. 9349653) into the switch."

4.5.1.2: Delete this paragraph and substitute a new paragraph to read:

"4.5.1.2 Tension release. Secure switch to a fixed object with nails, screws or wire. Screw coupling base with attached M7 Non-Electric Blasting cap or alternative test cap (Dwg. 9349653) into the switch. Fit tension release attachment and loop end of trip wire over the curved neck. Apply the specified tension to the trip wire and observe for compliance with 3.3.2.1. Remove the pin with the round loop. Then carefully remove the safety pin (cotter pin) from a safe distance by means of a length of wire or cord. The trip wire shall then be released by cutting or flipping off a pin while maintaining the specified tension. Observation shall be made for compliance with the applicable requirement."

4.5.1.3: (See change to 4.5.1.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:10Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12589971
4.4.2.24	Clip, Retaining (if used)				NEXT HIGHER ASSEMBLY 9296867
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Incorrect material		-	3.1	Certification
102	Incorrect heat treatment		-	3.1	Certification
103	Hydrogen embrittlement not properly removed		(1)	3.2	4.5.6
104	Finish		-	3.1	Certification
105	Radius (S)		.40%	3.2	Gage
106	Total length		.40%	3.2	Gage
107	Total length of inner clip		.40%	3.2	Gage
108	Turnup height		.40%	3.2	Gage
109	Length from centerline to closing ends		.40%	3.2	Gage
Minor					
201	Poor workmanship		.65%	3.7	Visual

NOTES:
1 - The sampling plan for this test shall be in accordance with MIL-STD-105 using Code Letter G and on AQL of .40 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:10Z
Check the source to verify that this is the current version before use.

4.5.1.4: Delete this paragraph and substitute a new paragraph to read:

"4.5.1.4 Pressure release. Secure switch to a fixed object with nails, screws or wire. Screw coupling base with attached M7 Non-Electric Blasting cap or alternative test cap (Dwg. 9349653) into the switch. A preload of four (4) pounds shall be applied to the sear plate platform. Remove the pin with the round loop. Then carefully remove the safety pin (cotter pin) from a safe distance by means of a length of wire or cord. Gradually reduce the load on the sear plate platform while observing the gage to determine compliance with the applicable requirement."

4.5.2: (See change to 4.5.1.1).

PAGE 38

4.5.3, First sentence: Delete "Condition ... hours." and substitute a new sentence to read:

"Condition firing devices, with coupling base with attached M7 Non-Electric Blasting cap or alternative test cap (Dwg. 9349653) screwed in, at minus 50° for not less than sixteen (16) hours."

* 4.5.6: Add new paragraph 4.5.6 as follows:

"4.5.6 Spring embrittlement. The springs shall be pulled to the minimum point of permanent distortion by any approved method. Clips so tested shall be scrapped."

5.4: After "Unitization" add "(Palletization)."

5.4.1, Line 2: Delete "19-48-4116/8S-20PA1002" and substitute "19-48-4116-20PA1002 Appendix 128F."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project: 1375-A496)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:10Z
Check the source to verify that this is the current version before use.