INCH-POUND

MIL-A-70788A (AR)
AMENDMENT 2
14 February 1995
SUPERSEDING
AMENDMENT 1
26 August 1994

MILITARY SPECIFICATION

ADAPTER, METAL AND WOOD PALLET

This amendment forms a part of Military Specification MIL-A-70788A (AR), dated 5 February 1993, and is approved for use by the U.S. Army Armaments, Research, Development and Engineering Center and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2 Classification. Add the following:

"Type VI - Adapter, Pallet, PA150 Container
Type VII - Adapter, Pallet, PA151 Container"

PAGE 2

2.1.1 Specifications, standards and handbooks. Under "MILITARY SPECIFICATIONS", add:

"MIL-C-53072 - Chemical Agent Resistant Coating (CARC) System Applications Procedures and Quality Control Inspection"

PAGE 3

2.1.2 Other Government documents, drawings and publications.

Delete: "AC200000812 - 44 x 40 Adapter Lug Positioning Test Fixture"

Add: "ACV00155 - Combination of Adopted Items, Pallet and Pallet Adapter, Unitization of PA151 Container
ACV00156 - Combination of Adopted Items, Pallet and Pallet Adapter, Unitization of PA150 Container"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

2.2 Non-Government publications.

Under "AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)", add "ASTM - D4138 - Measurement of Dry Film Thickness of Protective Coating System by Destructive Means"

PAGE 4

3.2 Adapters. After "ACV00134", add "ACV00155 and ACV00156"

3.3 Welding. After "MIL-STD-1261", add "Class 1, to include submission of the welding procedure and workmanship specimens with the First Article Samples."

3.4 Lifting ring (bar) pull test.

Change "Each lifting ring (bar) of the adapter ..." to "Lifting rings (bars) of the adapter ..." Add to end of sentence "(see 4.4.2.2)"

PAGE 7

Table I. First article inspection.

Under "Top assembly, unpainted", add "ACV00157 and ACV00159" to list of drawings.
Under "Top assembly, painted", add "ACV00157 and ACV00159" to list of drawings.
Under "Bottom assembly, unpainted", add "ACV00158 and ACV00160" to list of drawings.
Under "Bottom assembly, painted", add "ACV00158 and ACV00160" to list of drawings.
Under "Adapter Assembly", add "ACV00155 and ACV00156" to list of drawings and change "AC@00000501" to "AC200000501"

PAGE 11

4.4.2.1 Lifting ring (bar). Under Note 2, add "ACV00155 and ACV00156" to list of drawings.

PAGE 12

4.4.2.2 Top Assembly, Unpainted

Major 102. Change "100%" to "Level II"
Major 103. Delete reference to "(Note 4)"
Under Note 1, add "ACV00157 and ADV00159" to list of drawings.
Under Note 2, add "ACV00155 and ADV00156" to list of drawings

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

Delete Note 3 in its entirety and substitute as follows:
"3. A Certified Material Test Report (CMTR) shall be submitted for all chemical and physical requirements for compliance with the applicable drawing."
Note 4. Delete in its entirety.

PAGE 13

4.4.2.3 Top Assembly, Painted

Add new major defect as follows:
"104 Primer coat thickness (see AC00000423 and Note 3).
Level IV 3.2 Gage"

Under Note 1, add "ACV00157 and ACV00159" to list of drawings
Under "Note 2, add "ACV00155 and ACV00156" to list of drawings.
Note 3. Delete second sentence and substitute: "The primer thickness may be determined from a test panel, when representative of the part for CARC topcoat. When destructive testing is done on samples (e.g. ASTM-D4138), these surfaces may be touched up in accordance with 3.6.1 of MIL-C-53072."

PAGE 14

4.4.2.4 Bottom Assembly, Unpainted.
Major 102, Delete "Note 4"
Note 1, add "ACV00158 and ACV00160" to list of drawings
Note 2, add "ACV00155 and ADV00156" to list of drawings
Note 3. Delete in its entirety and substitute:

"3. A Certified Material Test Report (CMTR) shall be submitted for all chemical and physical requirements for compliance with the applicable drawing."

PAGE 15

4.4.2.5 Bottom Assembly, painted

Add Major 104 as follows:
"104. Primer coat thickness (see AC200000423 and Note 3)
Level IV 3.2 Gage"
Note 1. Add "ACV00158 and ACV00160" to list of drawings
Note 2. Add "ACV00155 and ACV00156" to list of drawings
Note 3. Delete second sentence and substitute: "The primer thickness may be determined from a test panel, when representative of the part for CARC topcoat. When destructive testing is done on samples (e.g. ASTM-D4138), these surface may be touched up in accordance with 3.6.1 of MIL-C-53072."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

PAGE 16

4.4.1.6 Intermediate Assembly - Pallet Adapter, PA125 Container, Unpainted

Delete Note 1 in its entirety and substitute:

"1. A Certified Material Test Report (CMTR) shall be submitted for all chemical and physical requirements for compliance with the applicable drawing."

PAGE 17

4.4.2.7 Intermediate Assembly, Pallet Assembly, PA125 Container, painted

Add new major defect as follows:
"104. Primer coated thickness (see AC200000423 and note 3) Level IV 3.2 Gage"

Note 1. Delete second sentence and substitute:
"The primer thickness may be determined from a test panel, when representative of the part for CARC topcoat. When destructive testing is done on samples (e.g. ASTM-D4138) these surfaces may be touched up in accordance with 3.6.1 of MIL-C-53072."

PAGE 18

4.5.1 Unit load test.

First sentence. Change "Prototype unit loads" to "Unit loads"
Second sentence. Delete in its entirety and substitute:

"The gross weight of the ammunition load shall be 2,500 pounds minimum."

4.5.2 Lifting ring pull test.

Title of paragraph. After "ring", add "(bar)"
First sentence. Delete in its entirety and substitute:
"Lifting rings (bars) of the adapter top assembly shall be placed in a test machine designed for pull testing."
Forth (last) sentence. After "length of the ring", add "(bar)" and after "separation of the ring", add "bar".

PAGE 20

Add the following APPENDIX as pages 21 and 22, included herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

"APPENDIX

QUALITY ASSURANCE PROVISIONS FOR REFURBISHMENT

10. SCOPE:

10.1 Scope. This appendix provides the Quality Assurance provisions for the refurbishment of metal pallet adapters.

20. APPLICABLE DOCUMENTS:

STANDARDS

* FEDERAL

FED-STD-595 - Colors

MILITARY

MIL-STD-171 - Finishing of Metal and Wood Surfaces

30. REFURBISHMENT:

30.1 Cleaning. Loose paint, dirt, grease and rust shall be removed.

30.2 Refinish. The parts shall be finished in accordance with the applicable drawings with the following exception:

* a. For refinishing of adapter AC200000807 (training rounds only), No. 5.1.1 or 5.2 shall be applied to all bare metal, followed by No. 20.1 to all surfaces in accordance with MIL-STD-171, color forest green No. 34079 per FED-STD-595 may be used as an alternate.

* b. An "R" shall be placed directly following the part number of refurbished adapters, using the same size stencil and color specified on the drawing.

40. REQUIREMENTS:

40.1 Welds. Welds shall be in accordance with good commercial practices.

40.2 Stackability. The pallet shall not be deformed to the extent that it effects safely stacking of pallets in storage.

40.3 Lifting rings. The lifting rings shall not be damaged or deformed to the extent of preventing safe handling by a sling during top lifting operations.

40.4 Adapters. The top lift shall not be deformed to the extent that it does not engage the containers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

40.5 Workmanship. See paragraph 3.6 unless otherwise specified below:

a. Deformation or damage that does not effect stacking, slinging or assembly of the pallet is allowed.

b. Damage or deformation to the pallet legs that does not allow four way entry or prevents the pallet from resting evenly on a level surface is not allowed.

c. Bottom adapter is deformed to the extent that it does not mate with the pallet is not allowed.

50. INSPECTION:

50.1 Examination. Unless otherwise specified examinations for major and minor characteristics shall be performed in accordance with TABLE II. Attributes sampling inspection.

50.1.1 Metal pallet adapter (see drawings listed in 2.1.2, as applicable).

CLASS	CHARACTERISTICS	CONFORMANCE CRITERIA	INSPECTION METHOD
Critical	None defined		
Major			
101	Welds missing or broken	Level III	40.1/Visual
102	Stacking surface deformed	Level III	40.2/Visual
103	Lifting rings damaged or deformed	Level III	40.3/Visual
104	Adapter damaged or deformed	Level III	40.4 Visual
Minor			
201	Marking, missing, incorrect or illegible	Level III	3.2/Visual
202	Protective finish damaged	Level III	3.2/Visual
203	Poor workmanship	Level III	40.5/Visual"

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assures no liability, whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 8140-0043)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.