MILITARY SPECIFICATION

PLUG, BASE, TRAINING, ATOMIC PROJECTILE

1. SCOPE

1.1 This specification covers requirements, quality assurance provisons, and the preparation for delivery criteria for one type of training base plug used on M423 projectile loading assembly.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1167 - Ammunition Data Cards
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169 - Packaging, Packing and Marking for Shipments of Inert Ammunition Components

DRAWINGS

ORDNANCE CORPS

8808362 - Packing and Marking for Storage and Shipments
8787202 - Base Plug, Training, Atomic Projectile
8883534 - Bag, Packing for Repair Parts
EL-8787202 - Equipment List

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:39Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The base plug shall comply with all requirements specified on the drawing (dwg) 8787202, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein

3.3 Workmanship.

3.3.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.3.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.3.3 Burrs. Parts shall be free from burrs.

3.3.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.3.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. Not applicable.

4.3 Product acceptance inspection.

4.3.1 Lot formation. Lot formation shall be in accordance with MIL-STD-1168. Changes in lot numbers shall be recorded on Ammunition Data Cards in accordance with MIL-STD-1167 and MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T20:39Z
Check the source to verify that this is the current version before use.

4.3.1.1 Inspection lot. An inspection lot shall be the quantity of parts, subassemblies or assemblies from the same lot, which are submitted to inspection for Government acceptance.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Base plug, training, atomic projectile (see dwg 8787202).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:39Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Width of flange, min	Gage
102.	Diameter of flange	Gage
103.	Diameter of 2 holes, min	Gage
104.	Depth of 2 holes, min	Gage
105.	Radius or chamfer present	Visual
106.	Pitch diameter of thread	Gage
107.	Major diameter of thread	Gage
108.	Feather edge of thread removed	Visual
109.	Diameter of thread clearance, max	Gage
110.	Total length, max	Gage
111.	Location of 2 holes	Gage
112.	Material (see 3.1)	Visual
113.	Objective evidence (see 6.2) for protective finish in accordance with dwg 8787202	Visual
Minor:		
201.	Surface finish	Visual
202.	Marking or stamping	Visual
203.	Workmanship (see 3.4)	Visual/Manual

4.3.2.1.2 Preparation for delivery (see 5.1).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Preservation, packaging, packing and marking in accordance with MIL-STD-1169	Visual/Manual
Minor:		
201.	Workmanship (see 3.4)	Visual/Manual

4.3.2.1.3 Bag, packing for repair parts (see dwg 8383534) covering part number 8883534-7 and 5.2.

Categories	Characteristics	Method of Inspection
Critical:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:39Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
Major:		
101.	Material (see 3.1)	Visual
102.	Length before packing, min	Measure*
103.	Width before packing, min	Measure*
104.	Proper heat seal	Visual/Manual
105.	Objective evidence (see 6.2) for heat seal test in accordance with MIL-P-116	Visual
106.	Properly packed	Visual
107.	No tear, split or crack in bag	Visual

*Measure with suitable scale.

Minor:		
201.	Marking	Visual
202.	Workmanship (see 3.4)	Visual/Manual

4.3.2.1.4 Packing and Marking for Storage and Shipments (see dwg 8808362 and section 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Gross load weight, max	Measure*
102.	Contents tight in package	Manual
103.	Correctly packed	Visual/Manual
104.	Package material (see 3.1)	Visual

*Determine weight with a suitable scale.

Minor:		
201.	Marking	Visual
202.	Workmanship (see 3.3)	Visual/Manual

4.3.3 Testing. Not applicable.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (See EL-8787202). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval as specified in 6.3 prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired.
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL. (see 6.1.2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:39Z
Check the source to verify that this is the current version before use.

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. Not applicable.

5. PREPARATION FOR DELIVERY

5.1 Production items.

5.1.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1.1 Level A. The base plug shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169.

5.1.1.2 Level C. The base plug shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169.

5.1.2 Packing.

5.1.2.1 Levels A and C. The base plug shall be packed in accordance with the applicable instructions contained in MIL-STD-1169.

5.1.3 Marking. Marking shall be in accordance with MIL-STD-1169.

5.2 Repair parts.

5.2.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.2.1.1 Level A. The base plug shall be packaged in accordance with dwgs 8883534 and 8808362 using the specified moisture barrier.

5.2.1.2 Level C. The base plug shall be packaged in accordance with dwg 8808362 except that the moisture barrier may be omitted.

5.2.2 Packing.

5.2.2.1 Level A and C. The base plug shall be packed in accordance with dwgs 8883534 and 8808362

5.2.3 Marking. Marking shall be as specified in accordance with dwgs 8883534 and 8808362.

5.3 Data cards. Data cards shall be prepared in accordance with MIL-STD-1167.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:39Z
Check the source to verify that this is the current version before use.

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Production or Repair Part.
c. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1 and 5.3). Data specified in 4.3.4.1 and 5.3 will be delivered as identified on a numbered DD Form 1667 when specified on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T-T.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. 110-A048

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:39Z
Check the source to verify that this is the current version before use.