MIL-V-50065A

30 SEPTEMBER 1964

SUPERSEDING
MIL-V-50065(CmlC)
30 JUNE 1959

MILITARY SPECIFICATION

VALVE, NOSECUP

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of protective mask nosecup valve.

2. APPLICABLE DOCUMENTS

2.1 **Government documents.** The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105 – Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129 – Marking for Shipment and Storage.

DRAWINGS

EDGEWOOD ARSENAL

B5-2-464 – Valve, Nosecup.

A5-2-1005 – Disc, Valve.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 **Other publications.** The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification Ratings, Rules and Regulations.

(Application for copies of these freight classification rules should be addressed to the Uniform Classification Committee, 202 Union Station, Chicago 6, Ill.)

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:15Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 **Materials and components.** All materials and components shall conform to the specifications and drawings forming a part of this specification. Material listed as part No. B5-2-464C, listed on Drawing B5-2-464, shall be used.

3.2 **Manufacture and assembly.** The nose-cup valve shall be manufactured and assembled as specified on Drawing B5-2-464.

3.3 **Valve leakage.** Leakage through the valve assembly shall not exceed 150 milliliters per minute when tested as specified in 4.7.1.

3.4 **Preproduction sample.** Prior to the start of regular production, a preproduction sample of five valves shall be produced using the same methods, materials, tools, and equipment as will be used during regular production. Any change in methods, materials, tools, and equipment or in operating conditions shall require a new preproduction sample.

3.5 **Workmanship.** The valve shall be free from foreign matter and damage, such as distortion, surface irregularities, or dents on the seating surface which would impair its use.

4. QUALITY ASSURANCE PROVISIONS

4.1 **Responsibility for inspection.** Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to insure that supplies and services conform to specified requirements.

4.2 **Special provisions.**

4.2.1 *Alternative inspection.* The supplier may utilize any alternative inspection procedure which will provide equal or better assurance of quality by submitting a written proposal with justification and obtaining written approval from the Government prior to its institution. In case of dispute, the procedures of the specification will govern.

4.2.2 *Objective evidence.* The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2.3 *Inspection substation.* If the supplier elects to establish inspection substations for the purpose of conducting inspection for certain listed defects, the Acceptable Quality Levels (AQL's) for each inspection substation shall be equal to the AQL which is the next numerically lower value than the AQL specified for the total listed defects. The requirements of MIL-STD-105 are applicable to each substation and to the end item.

4.3 **Preproduction sample inspection.**

4.3.1 *Examination.* The sample valves shall be inspected for all requirements of the drawings and this specification.

4.3.2 *Tests.* The sample valves shall be tested in accordance with 4.7.

4.3.3 *Acceptance/rejection criteria.* The valves shall meet the examinations and tests specified by 4.3.1 and 4.3.2 to be acceptable. The supplier shall obtain written approval from the contracting officer before proceeding with regular production.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:15Z
Check the source to verify that this is the current version before use.

4.4 Lotting. A regular production lot shall consist of the valves produced by one manufacturer, at one plant, from the same materials, the same tools, and under the same manufacturing conditions.

4.5 Sampling. Sampling shall be conducted in accordance with MIL-STD-105.

4.6 Inspection provisions.

4.6.1 ***For examination and nondestructive tests.*** **Sample valves shall be examined and tested in accordance with the classification of defects and with MIL-STD-105.**

4.6.2 ***Classification of defects.***

4.6.2.1 *Valve, nosecup (DwgB5-2-464).*

Categories	*Defects*	*Acceptance standards*
Critical:	None defined.	
Major:	AQL 1.0 percent defective.	
101	Rivet missing, incorrect, or incorrectly assembled.	
102	Workmanship (see 3.5).	
*103	Outside diameter of flanges incorrect.	
104	Inside diameter of cup incorrect.	
Major A:	AQL 0.25 percent defective.	
150	Valve leakage.	4.7.1
Minor:	AQL 2.5 percent defective.	
201	Protective finish missing or incorrect.	
202	Burrs or sharp edges.	

*This characteristic is tool controlled.

4.7 Tests.

4.7.1 *Valve leakage.* The nosecup valve, assembled with a disc (Dwg A5-2-1005), shall be tested for leakage at a pressure differential of 25 millimeters of water using Edgewood Arsenal M4A1 Outlet Valve Leakage Indicator.

5. PREPARATION FOR DELIVERY (For repair parts packaging, see 6.4).

5.1 Packaging, Level C. Nosecup valves shall be packaged to afford adequate protection from the supply source to the first receiving activity for immediate use.

5.2 Packing, level C. Nosecup valves, packaged as specified in 5.1, shall be packed to insure carrier acceptance and safe delivery to the first domestic destination. Containers shall comply with Uniform Freight Classification rules or regulations of other carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. This specification covers the nosecup valve intended to be used with the ABC-M17 protective mask.

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:15Z
Check the source to verify that this is the currenversion before use.

6.2 Ordering data. Procurement documents should specify the title, number, and date of this specification.

6.3 Valve disc. The valve discs required for use in performing the valve leakage tests will be furnished by the Government and should be obtained as directed by the contracting officer.

6.4 Repair parts packaging. When repair parts packaging is required for items authorized for stocking as repair parts, the repair parts packaging data sheet covering the nosecup valve should be used.

(Copies of repair parts packaging data sheets may be obtained from the Director of Engineering and Industrial Services, ATTN: Chief, Design Branch, U.S. Army Edgewood Arsenal, Md. 21010.)

6.5 International interest. Certain provisions of this specification are the subject of ABC international standardization agreement. When amendment, revision, or cancellation of this specification is proposed, the departmental custodians will inform their respective Departmental Standardization Offices so that appropriate action may be taken respecting the international agreement concerned.

Custodians:

Army—MU

Navy—SH

Air Force—84

International interest (see 6.5)

Review activities:

Army—MD

Navy—SH

User activities:

Navy—MC

Air Force—84

Preparing activity:

Army—MU (EA)

Project No. 4240-0075

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:15Z
Check the source to verify that this is the current version before use.