RR-A-1255C
May 16, 1977
SUPERSEDING
Fed. Spec. RR-A-1255B
November 11, 1971

FEDERAL SPECIFICATION

ASH RECEIVER, TOBACCO

(WALL MOUNTED, PARABOLOIDAL SHAPE, 2 QUART CAPACITY)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers wall mounted ash receivers for cigar, cigarette, and pipe refuse.

1.2 Classification. Wall mounted ash receivers shall be furnished in the following type, and classes, as specified.

Type I - Wide bracket.
II - Narrow bracket

Class 1 - Two semi-bowl shaped blades.
2 - Single disc shaped blade.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

Federal Specification:

PPP-B-636 - Box, Shipping, Fiberboard.

Federal Standards:

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).
Fed. Test Method Std. No. 151 - Metals; Test Methods.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Services Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 9920

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:11Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

American Society for Testing and Materials (ASTM) Standard:

A-480 - General Requirement for Flat-Rolled Stainless and Heat-Resisting Steel Plate, Sheet and Strip.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

American Society for Metals:

Metal Handbook, Vol. 2 - Heating Treating, Cleaning and Finishing.

(Application for copies should be addressed to the American Society for Metals, Metals Park, Ohio, 44073.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Material. Unless otherwise specified (see 6.1) or herein, component parts shall be corrosion-resisting steel, aluminum, or aluminum alloys at the manufacturer's option.

3.1.1 Corrosion-resisting steel. Sheet and plate shall be AISI 302 or 304, (see 4.4.1.1 and 4.4.1.2).

3.1.2 Aluminum and aluminum alloys.

3.1.2.1 Plate and sheet. Plate and sheet shall be aluminum 1100 or aluminum alloy 3003. Temper of both shall be at the manufacturer's option (see 4.4.1.1 and 4.4.1.2).

3.1.2.2 Extruded shapes. Extruded shapes shall be alloy 6063. Temper of the alloy shall be at the manufacturer's option (see 4.4.1.1 and 4.4.1.2).

3.1.2.3 Die casting. Die castings shall be alloy 380 (see 4.4.1.1 and 4.4.1.2).

3.1.3 Plastics. Plastic parts shall be rigid acrylonitrile-butadiene-styrene (ABS), or polyamide (PA, nylon). Type of PA plastic shall be at the manufacturer's option.

3.2 Construction. Receivers shall consist of an outer shell, bracket, removable inner bucket, removeable (lift off) top ring and blade assembly, and screws for fastening to a wall. The outer shell shall be securely fastened to the bracket. The receivers shall be completely assembled.

3.2.1 Brackets.

3.2.1.1 Type I. Wide bracket - shall be corrosion-resisting steel, aluminum alloy die-casting, or extruded aluminum alloy. Width of bracket shall be 9-1/2 $\pm$ 1/8 inches and 3-3/8 $\pm$ 1/8 inches in height.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

3.2.1.2 Type II. Narrow bracket - shall be formed corrosion-resisting steel, extruded aluminum alloy or aluminum die-casting. Width of bracket shall be 3-1/2 ± 1/8 inches, and 8-3/4 ± 5/8 inches in height.

3.2.2 Outer shell, types I and II. The outer shell shall be one piece of seamless parabolic shape.

3.2.2.1 Corrosion-resisting steel. Outer shell shall be a minimum of 0.026 inch thick.

3.2.2.2 Aluminum alloy. Outer shell shall be a minimum of 0.051 inch thick.

3.2.3 Inner bucket, types I and II. The inner bucket shall be removable for cleaning and dumping tobacco refust. The busket shall be one piece or seamless formed aluminum or aluminum alloy with lift tabs or handle to facilitate removal. Capacity of the bucket shall be 2 quarts, with a minus tolerance of 5 percent (see 4.4.2).

3.2.4 Top ring and blade assembly types I and II. The top ring and blade assembly, removeable (lift-off hinged), shall consist of a top ring; (a) class 1 - two semi-bowl shaped blades and a tilting lever or (b) class 2 - single disc shiped blade, and a tilting lever. The top ring and blade assembly shall be hinged to prevent pilferage or the ring and blade.

3.2.4.1 Top ring, thickness. Thickness of top ring shall be 0.030 inch or greater for corrosion-resisting steel, and 0.051 inch or greater for aluminum alloy.

3.2.4.2 Blades.

3.2.4.2.1 Class 1 - Two semi-bowl shaped blades. The blades shall be securely hinged to the top ring. Bearings shall be PA (see 3.1.3), plastic or formed from the blade or ring material. A downward force of 5 pounds shall be applied to the tilting lever shall rotate ro seperate the blades, and produce a minimum opening of 2-3/8 inches measured at the centerline of the blades. Removal of the applied force shall close the blades instantly by gravity force to form a close line contact bowl shaped recepticle for the retention of refuse (see 4.4.3).

3.2.4.2.2 Class 2 - Single disc shaped blades. Blades shall be hinged in the center and rotate to open position by the tilting lever. Removal of the applied force shall result in closing the blades by spring action (see 4.4.3). The disc diameter shall be a minimum of 3 inches.

3.2.4.2.3 Thickness. Thickness of corrosion-resisting steel blades shall be 0.025 inch or greater, and thickness of aluminum alloy blades shall be 0.051 inch or greater.

3.2.4.3 Tilting lever. The tilting lever shall be formed aluminum alloy, aluminum alloy die die-casting, or ABS plastic. Plastic lever shall be chromium plated.

3.2.5 Dimensional requirements, types I and II. Dimensional requirements for ash receivers shall be in accordance with table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions for ash receivers

Type	Class	Overall height	Depth from wall	Bracket Width	Bracket Height	Lever minimum thickness	Outer shell minimum thickness CRS	Outer shell minimum thickness AL	Inner bucket minimum thickness	Top Ring minimum thickness CRS	Top Ring minimum thickness AL	Blade minimum thichness CRS	Blade minimum thichness AL
		Inches	Inches	Inches	Inches	Inch	Inch	Inch	Inch	Inch	Inch	Inch	Inch
I	1	8-3/8 ± 3/8	9-5/8 ± 1/4	9-1/2 ± 1/8	3-3/8 ± 1/8	1/4	0.026	0.056	0.030	0.030	0.051	0.025	0.051
I	2	8-3/8 ± 3/8	9-5/8 ± 1/4	9-1/2 ± 1/8	3-3/8 ± 1/4	1/4	0.026	0.056	0.030	0.030	0.051	0.025	0.051
II	1	9-3/4 ± 3/4	8-5/8 ± 5/8	3-1/2 ± 1/8	8-3/4 ± 5/8	1/4	0.026	0.051	0.030	0.030	0.051	0.025	0.051
II	2	9-3/4 ± 3/4	8-5/8 ± 5/8	3-1/2 ± 1/8	8-3/4 ± 5/8	1/4	0.026	0.051	0.030	0.030	0.051	0.025	0.051

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:11Z
Check the source to verify that this is the current version before use.

3.3 Finish.

3.3.1 Corrosion-resisting steel. Corrosion-resisting steel shall have a No. 4 general-purpose polished finish, as specified in ASM Handbook Vol. 2.

3.3.2 Aluminum and aluminum alloys. Aluminum and aluminum alloys shall have a M32 medium satin finish. Coared aluminum and aluminum alloys shall have a R10 resinous finish, as specified in ASM Handbook Vol. 2.

3.3.3 Chromium plated parts. Chromium plated parts shall have a satin finish.

3.4 Marking for identification. The receivers shall be plainly and permanently marked with the manufacturer's name, trade name, or trademark of such known character that the source may be determined.

3.5 Workmanship. The finished receivers shall be free from sharp edges, slivers, burrs, and other defects which may affect appearance or serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Sampling for examination and tests. Sampling for visual examination shall be in accordance with inspection level S4 in MIL-STD-105. Sampling for dimensional examination shall be in accordance with inspection level S-2. Sampling for test shall be in accordance with inspection level S-2.

4.3 Examination and tests of end item.

4.3.1 Visual examination. Samples selected in accordance with 4.2.1 shall be examined for the defects in Table II. The acceptable quality level shall be (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of percent defective.

TABLE II. Classification of defects

Examine	Defect	Major	Minor
Finish	Stain or discolored		X
Construction and Workmanship	Any sharp edge, sliver, or burr.	X	
	Any part missing, or not specified type.	X	
	Any component fractured, split, buckled, bent, punctured, malformed, or otherwise impaired.	X	
	Operation omitted or not properly performed.		
	Functioning component inoperative or does not function as intended.	X	
Marking	Missing, not legible, incorrect.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

4.3.2 Dimensional examination. Samples selected in accordance with 4.2.1 shall be examined for dimensional defects. Any dimension not within specified requirements shall be classified as a defect. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of percent defective.

4.3.3 End product tests. Samples selected in accordance with 4.2.1 shall be tested as specified in 4.4. The AQL for tests shall be 4.0 percent defective.

4.3.4 Examination of preparation for delivery. An examination shall be made to determine that packaging and packing as required by section 5 are complied with. Defects shall be scored as specified in Table III. The sample unit shall be one shipping container fully prepared for delivery. The inspection level shall be S-2 with an AQL or 4.0, expressed in terms of defects per hundred units.

TABLE III. Examination for preparation for delivery

Examination	Defect
Marking (exterior and interior container)	Omitted; incorrect; illegible; of improper side, location, sequence, or method of application.
Materials	Component missing, damaged, or otherwise defective.
Workmanship	Inadequate application of components such as incomplete closure of container flaps; loose strapping or tape banding; inadequate stapling; bulging or distortion of containers.
Contents	Content per container is more or less than required.

4.4 Test methods.

4.4.1 Chemical composition, metals.

4.4.1.1 Frequency of test. Unless otherwise specified (see 6.1), this test shall be performed on the initial lot and thereafter only when changes are made in the material.

4.4.1.2 Procedure. Determine chemical composition by the wet chemical method in accordance with method 111, or by the spectrochemical method in accordance with method 112 in Fed. Test Method Std. No. 151. In case of dispute, analysis by method 111 shall be the basis for acceptance or rejection (see 3.1.1, 3.1.2.1, 3.1.2.2, and 3.1.2.3).

4.4.2 Inner bucket capacity. Completely fill the inner bucket with water. Measure the volume of water (see 3.2.3).

4.4.3 Top ring with class 1 or class 2 blade assembly. Apply and release a finger force ten times to the tilting lever (see 3.2.4.2.1 and 3.2.4.2.2).

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, or commercial as specified (see 6.1).

5.1.1 Level A. Each ash receiver shall be packaged in a box conforming to PPP-B-636, class domestic.

5.1.2 Commercial. Ash receivers shall be packaged in accordance with the suppliers commercial practice.

5.2 Packing. Packing shall be level A, or commercial as specified (see 6.1).

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:11Z
Check the source to verify that this is the current version before use.

5.2.1 Level A. Unit packages in quantities as specified shall be packed in a box conforming to PPP-B-636, class weather-resistant. The box shall be closed and water-proofed in accordance with appendix to the box specification.

5.2.2 Commercial. Ash receivers shall be packed in a manner which will insure arrival at destination in satisfactory condition and be acceptable to the carrier at lowest rates. Containers and packing shall comply with Uniform Freight Classification or National Motor Freight Classification.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Federal Standard No. 123 or MIL-STD-129, as applicable (see 6.1).

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Material (see 3.1).
(c) Type and class (see 1.2).
(d) Frequency of tests for metals (see 4.4.1.1).
(e) Level of packaging, and level of packing required (see 5.1).
(f) Whether marking shall be as required for civil or military agencies. (see 5.3).

6.2 Finish on metals. For information on finishes for corrosion-resisting steels refer to page 598, and for aluminum finishes refer to page 634 in Metal Handbook, Vol. 2, Heat Treating and Finishes, available from the American Society for Metals, Metals Park, OH 44073. Finishes for corrosion-resisting steel are also in ASTM A480, available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

Preparing Activity:

GSA - FSS

Civil Agency Coordinating Activity

GSA - FSS, PBO

1

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 30 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.