RR-B-800E
September 22, 1972
SUPERSEDING
Int. Fed. Spec. RR-B-00800D(GSA-FSS)
August 5, 1966
Fed. Spec. RR-B-800C
August 18, 1959

FEDERAL SPECIFICATION

BUCKETS, MOP, METAL

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. The mop buckets covered by this specification are made of metal and are generally used during wet mopping operations. Small galvanized pails are covered by Federal Specification RR-P-35. Mop wringer and bucket combinations are covered by Federal Specification RR-M-1075.

1.2 Classification.

1.2.1 Types and classes. The buckets covered by this specification shall be of the following types and classes, when applicable as specified (see 6.1):

Type I. - Single bucket.
Class 1. - With spider chassis and casters.
Class 2. - Without spider chassis and casters.
Class 3. - With silencers.

Type II. - Two buckets mounted on truck.

Class 3. - With silencers on buckets and truck.

1.2.2 Size and capacities. The buckets shall have the following respective capacities in quarts and ounces for the various size numbers, as specified (see 3.4, 4.6.9 and 6.1).

Size 1	16 quart Plus 1 quart	Minus 18 ounces
Size 2	20 quart Plus	or Minus 16 ounces
Size 3	26 quart Plus 2 quarts 8 ounces	Minus 24 ounces
Size 4	35 quart Plus 1 quart 8 ounces	Minus 1 quart

1.2.3 Shapes. The buckets covered by this specification shall be of the following shapes (see 6.1):

Shape A. - Oval with tapering sides.
Shape D. - Round with tapering sides. This shape is limited to size 1 and 2 buckets for use only in conjuction with roller wringer mopping outfits for type I of RR-M-1075.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

QQ-N- 281 - Nickel-Copper-Alloy (Monel and R-Monel) Bars, Plates, Rods, Sheets, Strips, Wire, Forgings, and Structural and Special Shaped Sections.
QQ-P- 416 - Plating, Cadmium, (Electrodeposited).
QQ-S- 698 - Steel, Sheet and Strip, Low-Carbon.
QQ-S- 766 - Steel, Corrosion-Resisting; Plates, Sheets, Strips, & Structural Shapes.
QQ-W- 461 - Wire, Steel, Carbon (Round, Bare and Coated).
RR-W- 670 - Wringer, Mop.
RR-M-1075 - Mopping Outfits, Floor.
PPP-B- 591 - Boxes, Fiberboard, Wood-Cleated.
PPP-B- 601 - Boxes, Wood, Cleated-Plywood.
PPP-B- 621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B- 636 - Boxes, Shipping, Fiberboard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified the issue in effect on date of invitation for bids or request for proposal shall apply.

American Iron and Steel Institute (AISI) Steel Products Manual:

(Application for copies should be addressed to the American Iron and Steel Institute, 150 East 42nd Street, New York, NY 10017.)

3. REQUIREMENTS

3.1 Preproduction sample. When specified (see 6.1), before production is commenced, a sample covered by this specification shall be submitted or made available to the contracting officer or his authorized representative for approval in accordance with 4.2. The approval of this preproduction sample authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured in the same facilities to be used for the manufacture of the production items.

3.2 Materials. Materials shall conform to the referenced specifications and requirements specified herein. Where materials are not definitely specified, they shall be of the quality and chemical composition normally used for the purpose in commercial practice.

3.2.1 Rubber. Whenever the term "rubber" is used, it shall include natural rubber, synthetic rubber, or compounds thereof.

3.3 Capacities. The capacity in quarts and ounces for each size shall be within the tolerances established by 1.2.2, when tested as specified in 4.6.9.

3.4 Capacity graduations. Shape A buckets shall be die-embossed with capacity graduations as follows:

Size 1 - Size 1 buckets shall have a minimum of two numeric capacity graduations. These shall be located at the one and two gallon levels.
Size 3 - Size 3 buckets shall have a minimum of four numeric capacity graduations. These shall be located at one gallon increments up to the four gallon level.
Size 4 - Size 4 buckets shall have a minimum of six numeric capacity graduations. These shall be located at one gallon increments up to the six gallon level.

In lieu of numeric designations, odd number capacity levels of size 3 and 4 buckets may be indicated by significantly located reinforcing beads.

A horizontal line may be embossed on each side of each numeric graduation to clearly indicate the capacity level.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

3.5 Bucket rim radii. To facilitate the use of appropriate size squeeze type downward pressure gear and rack wringers conforming to type II, class 2, of RR-W-670, the oval ends of shape A buckets shall have radii not less than the minimum specified below when measured at the inside perimeter of the rim.

Size	Minimum radii
1	5-5/16 inches
3	5-11/16 inches
4	6-1/4 inches

3.6 Marking for identification. Buckets shall be distinctly marked either on the body or bottom with the name of the manufacturer or trademark of such known character as to make the source of manufacturer easily determined.

3.7 Construction. Construction of all components and assemblies of the buckets covered herein shall conform to this specification. Bucket bodies shall be fabricated of uncoated steel conforming to QQ-S-698 which shall be zinc coated after fabrication by the molten bath process specified in 3.8. Cutting, punching, drilling or any other operation which will result in an uncoated metal edge or surface shall be performed prior to the molten bath process. Solder shall not be used to supplement sealing of the water compartment of zinc coated buckets. All metal components of type I zinc coated buckets such as the bail, bail ears, rivets and rim reinforcing wire shall be heavily cadmium or zinc coated. Class 1 units shall be furnished with a metal or nylon spider chassis. Metal spider chassis which are not of corrosion resistant metal shall be heavily cadmium coated in conformance with QQ-P-416, or zinc coated. Class 1 caster assemblies for zinc coated buckets shall be heavily cadmium or zinc coated. Type II trucks shall be heavily cadmium or zinc coated and at the option of the contractor may have a supplementary clear chromate treatment. In lieu of the chromate treatment, zinc coated trucks may be flash coated with cadmium. Cadmium coatings shall be in conformance with QQ-P-416.

3.7.1 Body. Body of the pails shall be fabricated of metal specified herein and shall conform to either the one-piece or two-piece method as specified in 3.7.1.1 and 3.7.1.2 respectively.

3.7.1.1 One-piece body method. One-piece body method shall consist of forming one piece of steel with vertical ends joined together by either welding or a lock seam.

3.7.1.2 Two-piece body method. Two-piece body method shall consist of forming two pieces of steel with vertical ends joined together by either welding or two locked seams located diametrically opposite each other.

3.7.2 Bottoms. Bottoms for all buckets shall be fabricated of metal specified herein and shall be either welded or lock seamed to the side of the body.

3.7.3 Driving of rivets. Rivets shall be thoroughly driven with heads flush against surface and the ends shall be securely set.

3.7.4 Welding. Welding shall be complete, sound, smooth, and free from burn through area, porosity, crack, fracture and excess flux deposit.

3.8 Finish. Prior to the attachment of bails, buckets shall be cleaned, and loose scale and rust removed. Every portion of the buckets, inside and outside, shall be completely coated with zinc by the molten bath process. Weight of the coating shall not be less than 2.2 ounces per square foot, total on both sides, when tested as specified in 4.5.1. The zinc coating shall be smooth, adherent, continuous and thorough and shall be free from such imperfections as lumps, blisters, gritty areas, uncoated spots, acid and black spots, dross and flux within the limits consistent with the best commercial practice. There shall be no cracking or flaking of the zinc coating when tested as specified in 4.6.2.

3.9 Type I, class buckets with casters. All sizes of type I, class 1 buckets shall consist essentially of a body with bottom, spider chassis, 4 ball bearing casters, a bail and 2 fasteners for the bail.

3.9.1 Body with bottom. The body and its bottom shall be fabricated of metal specified in 3.7. The thickness of the bare metal in the body and bottom shall be not less than 0.022 inch for all sizes. The bucket shall be provided with at least three lateral corrugations (or beads) around the body. Seams or joints of all buckets shall be leakproof when tested as specified in 4.6.8. Seams or joints of corrosion resistant metal buckets shall be equally corrosion resistant as the metal of which the bucket is fabricated. Rivets for securing the bail fasteners are permitted to extend into the water compartment of the bucket, but devices used to secure the spider chassis to the bucket are not permitted to extend into the water compartment. The top rim of all buckets shall be reinforced and the method shall be in accordance with the contractor's standard commercial practice. When this method is by rolling the body metal over wire to form a bead, there shall not be more than 3/32 inch opening between the bead edge and wall. The top rim and bucket sidewalls shall show no readily apparent visual permanent deformation when tested as specified in 4.6.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

3.9.2 Chassis and casters. Each bucket shall be mounted on a spider chassis with four high grade rubber wheel swivel casters having threaded stems. Not more than 1/8 inch of the threaded stem shall project above the torqued securing nut. Casters shall be ball bearing at the swivel and metal sleeve bearing at the axle. Rubber wheels shall be slightly crowned and be non-marking. Caster wheels shall be not less than 2 inches in diameter. The casters shall be so mounted that the center of the swivel extends outside the periphery of the bottom of the bucket a minimum of 1-5/16 inches to insure adequate stability while maneuvering and during the wringing operation. When the bucket assembly is placed on a flat surface, the distance or clearance between the surface and the bottom of the spider shall measure not less than 2-1/8 inches. The bucket, chassis and casters shall show no readily apparent visual signs of permanent deformation, tire marks, lack of free swiveling ability or other defects and shall be suitable in all respects for the purpose intended after performance of the test in 4.6.5.

3.9.3 Bail. The bail shall be coated steel wire conforming to QQ-W-461 or corrosion resistant metal as applicable (see 3.7). Bucket bails shall be designed to rest on the top of the bucket rim. Bail fastening loops shall be closed fully when attached to bail fasteners. The bail shall move freely in the fastener from one side of the bucket to the other without binding or catching and be so attached that it cannot be accidently detached from the fasteners. The bail shall show no readily apparent visual signs of permanent deformation when tested as specified in 4.6.3.

3.9.4 Bail fasteners. Two fasteners such as lugs, ears or similar fastenings shall be attached to the bucket in a manner to permit the bail to hinge from one side of the bucket to the other. The fasteners shall be made of either coated steel or malleable iron or corrosion resistant metal as applicable (see 3.7). If the fasteners are attached to the bucket with rivets in lieu of welding, the rivet heads shall be neatly set and the rivet holes, after setting of the rivet, shall be leakproof. Fasteners shall show no readily apparent visual signs of permanent deformation when tested as specified in 4.6.3.

3.10 Type I, class 2 buckets without chassis and casters. Type I, class 2 buckets shall be in accordance with type I, class 1 buckets (see 3.9) except without chassis and casters. In addition, size 1 buckets which are to be furnished with mopping outfits having roller type wringers as specified for type I, class 1 of RR-M-1075 shall be fabricated of metal not less than 0.017 inch thick. Buckets furnished with type I outfits of RR-M-1075 are permitted to have bail and bail fastener construction in accordance with the contractor's commercial practice and the rim of these buckets shall show no sign of permanent deformation when tested as specified in 4.6.7. The bottom of type I, class 2 buckets shall not have any sharp edges that might mar a smoothly finished floor. Glides or similar means may be provided for ease in sliding the bucket on the floor.

3.11 Type I, class 3 buckets with silencers. Type I, class 3 buckets shall be in accordance with type I, class 1 buckets except without spider chassis and casters. The bucket shall have rubber or other suitable material on portions of the bottom and bail in a manner to make them practically noiseless in operation. The joint of the bail and bail fastener shall be made silent operating by a friction joint or other suitable means.

3.12 Type II, combination of two buckets without casters, mounted on a truck. Type II buckets shall consist of a combination of two oval buckets mounted on a metal truck. The truck shall have two compartments. Each compartment shall accommodate an oval bucket of the size specified and fit the manufacturers' finished buckets. A one piece protective bumper of rubber or other suitable nonmarking material having a minimum thickness of 1/2 inch shall be fastened around the entire periphery of the truck. Each bumper shall be secured in at least seven places. This bumper shall be installed in such a manner that upon impact the truck frame metal will not come into contact with walls, corners, or interior trim molding when being maneuvered. The truck shall be provided with four high grade rubber casters consisting of two swiveling casters at the front of the truck where the handle is attached, and two non-swiveling casters at the rear. The truck caster wheels shall be at least 3 inches in diameter. The two swiveling casters shall be ball bearing at the swivel and all casters shall be metal sleeve or ball bearing at the axle. Handles shall be furnished on all trucks and be designed to stay erect in a pulling or pushing position by means of adjustable tension friction hinges which permit the handle to be folded flat against the truck for convenient storage. When tested as specified in 4.6.4 the rubber tires shall show no signs of permanent damage, the swivel joints shall swivel freely and in correct alignment and none of the balls shall be missing from the swivel ball race. Neither the truck or casters shall show any sign of permanent deformation or other defects.

3.12.1 Class 3. Type II, class 3 combinations shall consist of two type I, class 3 buckets mounted on a truck for practically silent operation. The bottom of the buckets and the bail fasteners shall be equipped with silencing material. If the truck handle contacts the bucket, the contact shall be made silent by the addition of silencing material approximately 1/8 inch thick by 6 inches long. The bail shall be made silent operating by the addition of silencing material to that portion of the bail that contact the bucket.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

3.13 Workmanship. Workmanship shall be first class in every respect. Buckets shall be free from defects which may affect their durability, serviceability or appearance. Rivets, if used, shall be neatly set. Bolts, screws, and nuts, if used, shall be of the standard American National Form and shall be installed with an adequate means for preventing loss of proper tightness. All fasteners, when subject to removal, shall not be swaged, peened, staked, or otherwise permanently deformed. Zinc coating shall be in accordance with 3.7. The buckets shall not present any sharp edges which might cause personal injury or snag or cut the mop.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Preproduction sample inspection. When a preproduction sample is required, inspection shall be made of the completed end item for conformance with all provisions of this specification.

4.3 Inspection lot. All buckets of the same type, class and size, offered to the Government at one time shall be considered a lot for purposes of acceptance, inspection and tests.

4.4 Inspection for acceptance. Inspection shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.4.1 Inspection of components. In accordance with 4.1 above, the supplier is responsible for insuring that components and materials are manufactured, tested and inspected to insure conformance with the requirements of this specification.

4.4.2 In-process examination. When applicable, examination shall be made during the manufacturing process for the requirements specified in table I to establish that no deviation is made from the indicated requirements. Whenever a non-conformance is noted, correction shall be made to the affected items and the process.

TABLE I. In-process examination

Requirement	Requirement reference
Cleaning and removing of loose scale and rust prior to zinc coating.	3.8

4.4.3 Examination of the end item. The end item shall be examined for defect in design, material, construction and workmanship as listed in table II. For sampling, buckets shall be taken at random from each inspection lot in accordance with MIL-STD-105 at inspection level II and the acceptable quality level (AQL) shall be 1.5 percent defective. The sample unit for this examination shall be one completely fabricated and finished bucket and truck, when applicable. Any item in the sample containing one or more defects shall be rejected, and if the number of defective items in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

TABLE II. Visual examination

Examine	Defect
Finish Coating	Not corrosion-resistant coated as applicable. Coating not smooth, adherent, continuous and thorough. Lump, blister, gritty area, uncoated spot, acid or black spot, dross or flux not consistent with the best commercial practice.
General	Bucket not clean, evidence of oil, grease or dirt. Rough or sharp edge, burr or sliver which may cause injury. Component missing. Any bucket failing to meet specified type, class, size or shape. Clearance between floor and bottom of spider chassis on class 1 bucket is less than 2-1/8 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

TABLE II. Visual examination (con.)

Examine	Defect
Construction and Workmanship	Poor construction or workmanship affecting serviceability, durability or appearance Rivet or weld missing. Rivet head not flush against surface. End of rivet not securely set.
Soldering	Not complete, sound or smooth (when applicable).
Welding	Not complete, sound or smooth. Evidence of burn through area, porosity, crack, fracture or excess flux deposit.
Body	Not fabricated as specified, i.e. not conforming to either the one-piece or two-piece method such as more than two seams. Top edge not reinforced. Less than three reinforcing beads around circumference of sidewall. Chassis fastening devices which extend into water compartment. Vertical ends of body not welded or joined together by a locked seam. Two seams not located diametrically opposite each other.
Bottom	Not one piece construction. Not welded or lock seamed to the sides of body.
Bail Fasteners	Not at points, diametrically opposite. Malformed, i.e. causing interference of the free movement or bail with catching or binding.
Bail	Not engaging bail fastener. Malformed, i.e. causing interference of the free movement in ear with binding or catching. Fastening loops not fully closed when secured to bail fasteners.
Casters	Not metal sleeve bearing at axle. Not ball bearing at swivel. One or more balls missing from ball race. Rubber tires not slightly crowned. Wheels under minimum size specified. Stems not threaded. More than 1/8 inch of threaded stem projecting above the torqued securing nut.
Silencing Material	Not as specified.
Rubber Bumper (type II truck)	Bumpers are less than 1/2 inch thick. Bumpers do not extend around entire periphery of the frame. Bumpers not fastened in at least seven places.
Truck Handles	Truck handle not designed to stay erect in a pulling or pushing position or which does not fold flat for convenience of storage. Truck handle not provided with adjustable tension friction hinges.
Marking	Missing, illegible, or incomplete. Embossed capacity graduation not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

4.4.4 Inspection of preparation for delivery requirements. An inspection shall be made to determine that the packaging, packing and marking comply with the requirements in section 5 of this specification. Defects shall be scored in accordance with table III. For examination of interior packaging the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an acceptable quality level (AQL) of 4.0 defects per hundred units.

TABLE III. Classification of preparation for delivery defects

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Distortion of container.

4.5 Testing of the end item. A random sample of buckets and trucks, when applicable, shall be taken from each inspection lot in accordance with table IV and shall be subjected to the tests specified in section 4. Any sample item which does not meet the requirements for any of the tests specified shall be rejected. If the number of nonconforming items in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected. The sample unit for testing shall be one completely fabricated and finished bucket and truck, when applicable.

TABLE IV. Sampling for lot acceptance tests

Number of buckets in inspection lot	Number of buckets in sample	Acceptance number (defective)	Rejection number (defective)
15 and under	3	0	1
16 to 40	5	0	1
41 to 110	7	0	1
111 to 300	10	0	1
301 to 800	15	1	2
801 to 1300	20	1	2
1301 and over	30	2	3

4.5.1 Zinc coating testing. Testing shall be performed in accordance with table V for the characteristics shown therein. At the same time that buckets are cleaned, loose scale and rust removed, and coated with zinc, three (3) test panels having an area of at least 2-1/4 square inches shall be prepared concurrent with production. These test panel specimens shall be prepared on each lot or batch of zinc or when any change occurs in the molten bath process.

TABLE V. Zinc coating testing

Characteristic	Requirement paragraph	Test method paragraph	Sample unit	Results reported as
Weight of zinc coating	3.8	4.6.1	3 test specimens	To nearest .01 ounce

4.6 Test procedures.

4.6.1 Weight of zinc coating. The weight of zinc coating shall be determined in accordance with triple spot test of Method 512 of Fed. Test. Std. No. 151, except that the three test specimens shall be as specified in 4.5.1. Results shall then be examined to determine compliance with 3.8.

4.6.2 Adhesion of zinc coating. From a height of 2 feet, drop a one-half pound weight on each bucket selected for test. Examine test area of bucket for compliance with 3.8.

4.6.3 Bail and bail fastener test. The bail and bail fastener of each sample bucket shall be tested by placing a pole through the bail opening and then suspending the bucket by resting the pole on two supports of equal height. The bucket shall then be filled with water to the top of the rim. Allow the bucket to remain suspended for at least one and not more than two minutes and then dump the water from the bucket. Examine the bail and bail fasteners for compliance with 3.9.3 and 3.9.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

4.6.4 Truck test. Type II trucks shall be tested by loading both buckets on the truck with suitable material to the applicable weight specified in table VI for each bucket. Fasten a board, with sharp corners, to the floor. The board shall be 3/8 inch thick, at least 2 inches wide of sufficient length so that all four casters will ride over the board. At a walking pace, move the loaded truck back and forth over the board 10 times. While the truck is still loaded, measure the frame for sagging by using a straight edge and rule. The truck frame shall not sag more than 1/8 inch. Unload the bucket and examine the truck frame and casters for compliance with 3.12.

4.6.5 Caster and chassis test. Type I, class 1 sample buckets shall be placed upright on a metal surfaced platform scale. Place all four casters in a spread-eagle position, i.e., wheels pointed directly outward from the center axis of the spider chassis. On the top rim of the bucket place a flat 5/8 inch thick steel plate which will support the test load. The plate shall be of sufficient size to distribute the test load equally around the circumference of the rim. The bucket assembly shall then be subjected to the applicable test load specified in table VI. The test load may be applied by any device suitable for the purpose, i.e., pressure exerted by a hydraulic jack positioned under a stationary girder or other suitable object. Pressure need not be applied any longer than the time required to read the scale. Examine casters, chassis and bucket for compliance with 3.9.2. Examination for free swiveling and non-marking characteristics shall be determined after the test bucket has been filled with a test weight equal to 1-1/2 times the amount of water to fill the bucket. The bucket shall then be rolled over a clean, smooth surface on which abrupt 90 degree turns of directions are made.

4.6.6 Bucket rim and sidewall test. When class 1 buckets are tested the spider chassis shall be removed. If the spider chassis is not removable, remove the casters only. Place the bucket upright on a platform scale. Mount a wringer to the bucket rim in the conventional manner. The wringer shall be designed for use with the specific size bucket being tested and shall conform to type II, class 2 of RR-W-670 except the wringer mechanism may be modified to endure the test load specified in table VI. Place a block in the wringer hopper of sufficient thickness so that the pressure bars bottom on the block at a point where the wringer handle arrives at a horizontal position. While in the horizontal position securely mount a hydraulic jack on top of the handle where the hand would normally grip. Place the test bucket directly under a stationary girder or other suitable object and apply the test load specified in table VI. Pressure need not be applied any longer than the time required to read the scale. Examine bucket rim and sidewall for compliance with 3.9.1.

4.6.7 Top rim test. This test is applicable only to type I, class 2, size 1 and 2 sample buckets which are to be furnished with mopping outfits having roller type wringers specified for type I of RR-M-1075.

Size 1 and 2 buckets shall be tested at 67 and 83 pounds respectively. Place the empty bucket with one bail fastener resting on a platform scale, then apply the applicable test weight near the opposite bail fastener, as near to the top rim as possible. The weight may be manually applied and need not be held any longer than the time required to read the scale. Examine bucket rim for compliance with 3.10.

4.6.8 Leakage test. Subsequent to all other applicable tests, each sample bucket shall be filled to within one half inch of top of bucket and allowed to stand for 24 hours. Examination shall be made to determine compliance with 3.9.1.

4.6.9 Capacity test. Stand the bucket to be tested on a flat surface and fill the bucket with water to the top so that it overflows. Measure the contents of the bucket to the nearest ounce, for compliance with 3.3.

TABLE VI. Test weight

Bucket size	Caster and chassis test ± 10 pounds	Bucket rim and sidewall test ± 5 pounds	Truck test ± 1 pound
1	1000 pounds	425 pounds	50 pounds
3	1200	425	75
4	1300	425	100

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.1).

5.1.1 Level A.

5.1.1.1 Type I, single bucket.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

5.1.1.1.1 Class 1. Each type I, class 1 bucket shall be packaged in a close-fitting box conforming to PPP-B-636, class weather-resistant. Fiberboard inner packing forms, with the fiberboard meeting the requirements of PPP-F-320, type CF, class domestic, variety SW shall be utilized for cushioning and blocking. The box shall be closed in accordance with the appendix to the box specification.

5.1.1.1.2 Class 2 or 3.

5.1.1.1.2.1 Shape A or D. Two nested type I, class 2 or 3, shape A or D buckets of like description shall be packaged in a close-fitting box conforming to PPP-B-636, class weather-resistant. The box shall be closed in accordance with the appendix to the box specification.

5.1.1.2 Type II, class 3, two buckets mounted on truck.

5.1.1.2.1 Disassembly. Simple disassembly, which requires no special tools for reassembly, shall be affected prior to packaging.

5.1.1.2.2 Packaging. Each type II, class 3 bucket outfit, disassembled as specified in 5.1.1.2.1 shall be packaged in the most compact manner in a close-fitting box conforming to PPP-B-636, class weather-resistant. The contents shall be immobilized and cushioned in a manner to prevent movement or damage while in transit. Each box shall be closed in accordance with the appendix to the box specification.

5.1.2 Level B. The buckets or bucket and truck shall be packaged in accordance with 5.1.1, except the PPP-B-636 box shall be class domestic.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.1).

5.2.1 Level A. The type I or II buckets or trucks shall be packed in a close-fitting box conforming to PPP-B-585, class 3, PPP-B-591, class II, PPP-B-601, overseas type or PPP-B-640, class 2, grade A. The boxes shall be closed and strapped in accordance with the applicable specification or appendix thereto. The gross weight shall not exceed 200 pounds.

5.2.2 Level B. No packing required.

5.2.3 Level C. The buckets or trucks shall be packed to insure carrier acceptance and safe delivery at destination at the lowest rates, in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military activities. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Shape, type and class required (see 1.2.1 and 1.2.3).
(c) Size required (see 1.2.2).
(d) When preproduction sample is required (see 3.1).
(e) Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

6.2 Bucket and wringer compatibility. To obtain maximum performance and serviceability, it is recommended that the size combinations of buckets and wringers shown below be used.

Bucket Sizes	Wringer Sizes (RR-W-670)
1 (16 quart)	Type I ; Class 1; Size 1
	Type II; Size 1
2 (20 quart)	Type I ; Class 1; Size 1
	Type II; Size 1
3 (26 quart)	Type I ; Class 1; Size 2
	Type I ; Class 2; Size 2
	Type II; Size 2
4 (35 quart)	Type I ; Class 1; Size 3
	Type I ; Class 2; Size 4
	Type II; Size 3

Orders for this publication are to be placed with the General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 15 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.