RR-C-1039A
November 12, 1973
SUPERSEDING
Fed. Spec. RR-C-1039
May 17, 1966

FEDERAL SPECIFICATION

COFFEE-MAKER, VACUUM

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers a two-bowl, vacuum type coffee-maker of 12-cup brewing capacity and coffee-maker components to be heated by means of gas or electric hotplate-type stoves or ranges which are purchased separately.

1.2 Classification. The coffee-maker and components covered by this specification shall be the following type, items, grades, and styles as specified (see 6.2).

Type I	-	Complete coffee-maker.
Item 1	-	Upper bowl, stainless steel, with bushing (gasket).
Item 2	-	Lower bowl, stainless steel.
Item 3	-	Filter.
Grade A	-	Stainless steel.
Grade C	-	Cloth.
Item 5	-	Handle assembly.
Style 1	-	With cover.
Style 2	-	Without cover.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specification:

PPP-B-636 - Boxes, Shipping, Fiberboard.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-M-14 - Molding Plastics and Molded Plastic Parts, Thermosetting.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

American Society for Testing and Materials (ASTM) Standards:

A 167 - Stainless and Heat-Resisting Chromium Nickel Steel Plate, Sheet, and Strip.
A 176 - Stainless and Heat-Resisting Chromium Steel Plate, Sheet, and Strip.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

National Sanitation Foundation (NSF) Standard:

No. C-2 - Basic Criteria for the Evaluation of Special Equipment and/or Devices.
Listing of Food Service Equipment.

(Application for copies should be addressed to the National Sanitation Foundation, NSF Building, Ann Arbor, Michigan 48105.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N. W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:11Z
Check the source to verify that this is the currentversion before use.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the supplier shall furnish a sample of the item to be procured under this specification for first article inspection and approval (see 4.2, 6.3).

3.2 Standard product. The coffee-maker or component part furnished under this specification shall be the manufacturer's standard commercial product, except as modified herein. All coffee-makers furnished under this specification for any one contract including components thereof, shall be new and interchangeable.

3.3 Codes and standards. The coffee-maker shall comply with the applicable requirements of NSF Standard C-2.

3.3.1 Compliance. Prior to approval of the first article, if one is submitted, or prior to commencing production, the supplier shall submit to the contracting officer or his authorized representative, satisfactory evidence that the coffee-makers he proposes to furnish under this specification meet the applicable requirements of NSF Standard C-2 as follows:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" or display of the NSF seal on the finished coffee-makers

(2) A certification for the coffee-makers issued by NSF under their special one-time contract evaluation/ certification service, or

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the coffee-makers are being procured, indicating that the coffee-makers have been tested and conform to NSF Standard C-2.

3.4 Materials. Materials shall conform to applicable referenced documents to the extent specified herein. Materials used, but not specified, shall be of the best quality used for the purpose in commercial practice.

3.4.1 Stainless steel. The stainless steel shall conform to type 302 or 304 of ASTM A 167; or type 430 of ASTM A 176.

3.4.2 Plastic. Plastic parts shall be molded from type MFG or MFI-20 plastic conforming to MIL-M-14.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

3.5 Design and construction. The coffee-maker shall consist of one each of the following components:

Upper bowl (metal)
Lower bowl (metal)
Bushing (gasket)
Filter
Handle assembly with cover

Bowls shall have a usable brewing capacity of 60 ounces (12 cups). When specified (see 6.2), the components may be ordered separately and upper bowls shall be furnished with a bushing (gasket).

3.5.1 Bowls. The bowls shall be made of stainless steel conforming to 3.4.1. The metal thickness of the finished product shall be not less than 0.025 inch.

3.5.1.1 Upper bowl. The upper bowl shall be provided with a tubular stem for insertion into the lower bowl. It shall be fitted with a bushing (gasket) that provides a leak prcof seal with the lower bowl in 3.5.1.2, when assembled for brewing. When assembled, the bottom of the stem shall be not more than 1 inch nor less than 1/2 inch above the inside bottom of the lower bowl.

3.5.1.2 Lower bowl. Unless otherwise specified (see 6.2), the lower bowl shall conform to the following dimensions:

Neck inside diameter:	2.850 to 2.920 inches
Top opening:	3-1/8 to 3-1/4 inches
Bowl height (overall):	5-5/8 to 6 inches
Bowl outside diameter: (at widest part)	6-1/4 to 6-5/16 inches
Bowl base diameter:	4-3/16 to 4-5/16 inches

3.5.2 Handle assembly. A handle made from plastic material conforming to 3.4.2 shall be provided on the lower bowl. The handle shall be shaped to prevent the operator's hand from coming into contact with the bowl during normal use. The handle shall be attached to the neck of the bowl by a stainless steel band in a manner to prevent swivelling and shall require no more than the use of a screwdriver for replacement. Unless otherwise specified

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:11Z
Check the source to verify that this is the current version before use.

(see 6.2), the handle shall be fitted with a hinged stainless steel cover to protect the contents of the lower bowl. In the raised (uncovered) position, the cover shall not interfere with the assembly of the bowls for brewing. Fastening devices for the cover and handle assembly shall be made of stainless steel, chromium-plated brass, nickel plated or nickel chromium plated carbon steel.

3.5.3 Filter. A commercial-type cloth or stainless steel filter shall be provided and shall be designed to provide the performance in 3.7. The filter shall be held securely and firmly in place to prevent its being loosened while stirring coffee during the brewing process.

3.6 Finish. Finish shall be in accordance with manufacturer's standard practice.

3.7 Performance. The coffee-maker shall be capable of brewing coffee in not more than 5 minutes and without the presence of coffee grounds in the brew when tested in accordance with 4.4. Compliance with the capacity specified in 3.5 shall also be determined.

3.8 Workmanship. The finished item shall be clean, well-made, and free from defects which may affect appearance or serviceability. There shall be no burrs, sharp edges, or projections.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and service conform to prescribed requirements.

4.2 First article inspection. When a first article is required it shall be examined for the defects listed in table I, for dimensions specified and the complete coffee-maker (type I) shall be tested as specified in 4.4. Failure to pass the test shall be cause for rejection of the first article. The presence of any defects listed in table I or any dimension not within specified requirements shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

4.3 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105.

4.3.1 Component and material inspection. In accordance with 4.1, component and materials shall be inspected and tested in accordance with all the requirements of referenced specifications and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.3.2 End item inspection. The sample unit shall be one complete coffee-maker or the individual component, as applicable. The lot size shall be expressed as the number of coffee-makers or individual components in the inspection lot.

4.3.2.1 Visual examination. Each sample unit shall be examined for the defects in table I. The inspection level shall be level II and the acceptable quality level (AQL) shall be 2.5 for major defects and 6.5 for total defects, expressed in defects per hundred units.

TABLE I. Classification of defects for visual examination

Examine	Defects	Classification Major	Minor
Materials:	Any material not as specified	X	
Design and construction:	Any component missing	X	
	Components do not assemble in the specified manner	X	
	Handle not shaped to prevent operator's hand from contacting lower bowl	X	
	Handle not attached to lower bowl as specified	X	
	Handle not replaceable as specified	X	
	Cover does not protect contents of lower bowl	X	
	Cover interferes with assembly of upper and lower bowl	X	
Workmanship:	Component or part fractured, split, malformed, or otherwise impaired	X	

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:11Z
Check the source to verify that this is the currentversion before use.

TABLE I. Classification of defects for visual examination (con.)

Examine	Defects	Classification Major	Minor
Workmanship: (con.)	Pits, slag, or other welding imperfections on coffee contact surface	X	
	Soil or stain on coffee contact surface which cannot be removed	X	
	Plated parts not smooth, uniform appearance throughout		X
	Any burr, sharp edge, or projection	X	
	Welding imperfection, soil, or stain on noncoffee contact surface		X

4.3.2.2 Dimensional examination. Each sample unit shall be examined for compliance with all specified dimensions. Any deviation from specified dimensions shall constitute a defect. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

4.3.2.3 End item testing. When a first article is not required, the first produced coffee-maker shall be tested as specified in 4.4. The inspection level shall be S-2 and the AQL shall be 4.0 percent defective. Failure of test shall be cause for rejection of the first produced item or the inspection lot, as applicable.

4.3.3 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing, and marking as required by section 5 are complied with. Defects shall be as indicated in table II. The sample unit shall be one shipping container fully prepared for delivery. The lot size shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 with an AQL of 2.5 defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:11Z
Check the source to verify that this is the currentversion before use.

TABLE II. Examination of preparation for delivery

Examine	Defects
Markings (interior and exterior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Components missing, damaged, or otherwise defective
Contents	Number per container is more or less than required

4.3.3.1 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in closure, waterproofing, and strapping shall be in accordance with PPP-B-636.

4.3.4 Standards compliance. Proof of compliance with NSF requirements of 3.3 shall be available to the Government representative.

4.4 Performance test. The sample unit selected in accordance with 4.3.2.3 shall be tested as follows for conformance with 3.7. Sixty ounces (12 cups) of water shall be heated to boiling in the lower bowl. The upper bowl, with filter in place and containing 2.5 to 3.0 ounces of ground coffee, shall then be placed into the lower bowl of boiling water. The pressure generated in the lower bowl shall then force the water up the tubular stem of the upper bowl, through the filter, and into the upper bowl containing the ground coffee. The coffee maker shall then be removed from the heat source, and the vacuum created in the lower bowl shall draw the brewed coffee through the filter into the lower bowl. The brewing time shall not exceed 5 minutes and shall be measured from the time the upper bowl is inserted into the lower bowl of boiling water until the brewed coffee is returned to the lower bowl. The contents of the upper bowl shall be stirred during the brewing process.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C, as specified (see 6.2 and 6.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. Each coffee-maker shall be packaged in a snug-fitting fiberboard box conforming to style RSC, type CF, class domestic, grade 200 of PPP-B-636. Inner packaging, such as cushioning, wrapping, or buffer pads shall be provided to prevent movement or damage during transit and provide clearance for projecting parts of the coffee-maker. Closure shall be in accordance with PPP-B-636.

5.1.2 Level C. Each coffee-maker shall be packaged to afford adequate protection against damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Twelve coffee-makers, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, grade V3s of PPP-B-636. Each shipping container shall be closed, waterproofed by means of tape, and reinforced with flat strapping or tape banding in accordance with PPP-B-636.

5.2.2 Level B. Twelve coffee-makers, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety SW, or type SF, class domestic of PPP-B-636. Each shipping container shall be closed in accordance with method II of the appendix of PPP-B-636.

5.2.2.1 When specified (see 6.2) the shipping container shall be V3c, V3s, or V4s, fabricated and closed in accordance with PPP-B-636.

5.2.3 Level C. Coffee-makers, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, all marking shall be in accordance with 5.3.1 or 5.3.2 as specified (see 6.2).

5.3.1 Civil agencies. Marking shall be in accordance with Fed. Std. No. 123.

5.3.2 Military requirements. Marking shall be in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The coffee-maker covered by this specification is intended for use in preparing relatively small quantities of coffee with an external heat source such as an electric hotplate.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type of coffee-maker or specific component(s) required (see 1.2 and 3.5). When ordering upper bowls or bushings separately, specify the inside neck diameter of lower bowl which bushing must fit (see 3.5.1.2).
(c) When cover is not required (see 3.4.2).
(d) When a first article is required (see 3.1, 4.2 and 6.3).
(e) Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).
(f) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
(g) Whether civil or military marking is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of ASPR 7-104.55. The first article should be a preproduction sample, initial production item or other specific item described under the definition of a First Article in the ASPR. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the first article.

6.4 Supersession data. Changes in classification of the coffee-maker and components between this revision of the specification and the previous edition are as follows:

RR-C-1039		RR-C-1039A	
Type I	- Metal upper and lower bowl	Type I	- Complete coffee-maker
Type II	- Metal upper and glass lower bowl		- Deleted
Item 1	- Upper bowl	Item 1	- Upper bowl, stainless steel, with bushing (gasket)
Grade A	- Corrosion-resisting steel		- Combined with item 1 identity

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

Item 2 - Lower bowl	Item 2 - Lower bowl, stainless steel
Grade A - Corrosion-resisting steel	- Combined with item 2 identity
Grade B - Glass	- Deleted
Item 3 - Filter	Item 3 - Filter
Grade A - Corrosion-resisting steel	Grade A - Stainless steel
Grade B - Glass	- Deleted
Grade C - Cloth	Grade C - Cloth
Item 4 - Bushing (gasket)	- Combined with item 1 identity
Item 5 - Handle assembly	Item 5 - Handle assembly
Style 1 - With cover	Style 1 - With cover
Style 2 - Without cover	Style 2 - Without cover

6.5 For civil agency procurements. Where level B packaging is required for civil agency procurements, the requirements in 5.1.1 for level A packaging shall apply.

Custodians:

Army - GL
Navy - SA
Air Force - 84

Review activity:

Army - MD
Navy - MC

User activity:

Navy - CG

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

GSA-FSS
HEW-NIH
VA-DMS

Project No. 7330-0462

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 15 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

Coffee-Maker, Vacuum RR-C-1039A

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. Army Natick Laboratories
Natick, Massachusetts 01760

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding General
U. S. Army Natick Laboratories
ATTN: STSNLT-EQS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.