RR-C-625C
July 20, 1971
SUPERSEDING
Int. Fed. Spec. RR-C-00625B(GSA-FSS)
October 1, 1970

FEDERAL SPECIFICATION

# COVER, RECEPTACLE, SWINGING DOOR (FOR 55 GALLON METAL DRUMS)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

## 1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers swinging door waste receptacle covers.

1.2 Classification. Waste receptacle covers shall be furnished in the following types and styles, as specified (see 6.2):

Type I - Single swinging door.
Style a - vertical door - raised top.
Style b - horizontal door - inclined top.

Type II - Double swinging door.

## 2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-B-585 - Boxes, Wood, Wirebound.
PPP-B-591 - Boxes, Fiberboard, Wood-Cleated.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Box, Fiberboard.
PPP-B-640 - Boxes, Folding, Fiberboard, Corrugated, Triple Wall.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).
Fed. Std. No. 595 - Colors.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Senter at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-P-116 - Preservation, Methods of.

Military Standards:

MIL-STD-105 - Sampling and Tables for Inspection by attributes.
MIL-STD-129 - Marking for Shipment and Storage.

FSC 7240

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM) Standards:

A90 - Methods of Test for Weight of Coating on Zinc-Coated (Galvanized) Iron or Steel Articles.
A123 - Specification for Zinc (Hot-Galvanized) Coatings on Products Fabricated From Rolled, Pressed, and Forged Steel Shapes, Plated, Bars, and Strip.
A219 - Method of Test for Local Thickness of Electrodeposited Coatings.
A464 - Recommended Practice for use of Magnetic Type Instruments for Measurement of Thickness of Hot Dip Galvanized Coating on Iron or Steel.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA. 19103.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street, N. W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 202 Union Station, 516 W. Jackson Blvd., Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Material.

3.1.1 Steel. Steel sheets, strips or shapes used in the fabrication of items covered by this specification shall be cold rolled, commercial quality plain carbon steel.

3.1.2 Spring wire. Wire shall be commercial spring wire zinc coated or painted.

3.1.3 Copper alloys. Copper alloy type or number shall be at the manufacturer's option.

3.1.4 Rubber and rubber-like plastics. Rubber shall be natural (NR) or synthetic (SBR). Rubber and rubber-like plastics shall be nonmarking and resilient.

3.2 Design and construction.

3.2.1 Type I, style a. The cover shall be designed to fit a 55 gallon metal drum, providing an enclosure, with a single vertical swinging door for waste material.

3.2.1.1 Top. Top shall be formed into a hemispherical dome or hood shape at the manufacturer's option. Height of the dome or hood measured from the top surface of the cover shall be 10 ± 1/2 inches. Thickness of hood shaped sheet steel shall be 0.0269 inch or greater, and for domed shaped sheet steel shall be 0.0329 inch or greater before coating (see 4.4.1.2 and 4.4.2.1).

3.2.1.2 Door opening. Dimensions of the door opening for a vertical swinging door shall be not less than 7-1/8 inches or more than 9-1/8 inches in height, and shall be not less then 11 inches or more than 13-1/8 inches in width. The door frame shall be 1/8 inch minimum in width, and shall be formed integral with the top or formed separately and welded to the dome or hood at the manufacturer's option.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

3.2.1.3 Door. The door shall be hinged at the top with a single continuous hinge or with 2 or more hinges. Hinges shall be spot welded to the door and top or attached by rivets, self-locking screws, or fasteners with self-locking nuts. The door shall be designed to open inward and shall be constructed to return to the completely closed position by spring or gravity action, at the manufacturer's option. The word PUSH shall be embossed in the door in letters 1 inch or greater in height. Rubber or rubber-like door bumpers shall be provided at the manufacturer's option.

3.2.1.4 Cover. The cover shall be formed sheet steel 0.0269 inch or greater in thickness before coating, and shall not exceed 24-5/16 inches in diameter with a rim 1-1/2 inches or less in depth (see 4.4.1.2). The rim shall have a bead type reinforcement with a deburred or formed edge, or reinforced with a 0.0710 x 7/8 inches minimum formed steel strip welded inside of the rim. The top and door assembly shall be welded to the cover. The opening in the cover for hood shape shall be not less than 14-1/4 inches square, and for dome shape shall be not less than 17 inches in diameter

3.2.2 Type I, style b. The cover shall be desinged to fit a 55 gallon drum, providing an enclosure, with a single horizontal swinging door for waste material.

3.2.2.1 Top. The top shall be formed into an oblique frustum shape with an inclined angle of 7 to 8 degrees. Thickness of the steel sheet before coating shall be 0.0269 inch or greater (see 4.4.1.2). The inside diameter of the top shall not exceed 23-3/4 inches, and rim shall be 1-1/2 inches or less in depth. The bottom edge or rim of the top shall be formed for rigidity.

3.2.2.2 Door opening. Dimensions of the horizontal swinging door shall be not less than 15 inches or more than 16-3/8 inches in length, and shall be not less than 14 inches or more than 15-1/4 inches in width. The door opening shall have formed edges.

3.2.2.3 Door. The door shall be formed steel sheet 0.0269 inch or greater in thickness before coating, and shall be hinged at the top with a heavy duty zinc coated hinge (see 4.4.1.2). The hinge shall be riveted to the door. The door shall be designed to open downward only and shall return to the closed position by spring action when downward pressure is released. The word PUSH shall be embossed in the door in letters 2 inches or greater in height.

3.2.3 Type II. The cover shall be designed to fit a 55 gallon metal drum, providing an enclosure with double vertical swinging doors, for waste material.

3.2.3.1 Top. The top shall be semispherical or shaped with sloped sides. Steel sheet shall be 0.026 inch or greater before coating (see 4.4.1.2). The center height of the hood shall be not less than 7-5/8 inches or more than 10-3/8 inches. The base of the top where it joins the cover shall be square, each side shall be not less than 14-1/8 inches or more than 16-9/16 inches.

3.2.3.2 Door openings. Two openings shall be provided in the top to accomodate 2 nearly vertical swinging doors. The opening shall be spot or continuous welded at the corners, or the door frame shall be formed as an integral part.

3.2.3.3 Doors. The doors shall be formed sheet steel 0.029 inch or greater in thickness before coating (see 4.4.1.2). Doors shall be not less than 6-1/8 inches or more than 8-5/8 inches in height and shall be not less than 11-1/2 inches or more than 13-1/8 inches in width. Door shall be hinged at the top with zinc-coated hinges, or a hinge consisting of a 7/32 inch minimum diameter wire with ends welded to top and with top flange of door curled over the pin. Doors shall swing inward independent of each other or to swing inward simultaneously. The doors shall be constructed to return to the closed position by spring action or gravity when inward pressure is released. The word PUSH shall be embossed in each door, and in letters 1 inch or greater in height.

3.2.3.4 Cover. The cover shall be formed steel sheet 0.0269 inch or greater in thickness before coating (see 4.4.1.2). The cover shall not exceed 24-5/16 inches inside diameter. When the cover is held by its own weight, the depth of the rim shall be 1-1/4 inches or greater. The rim shall have a bead type reinforcement with a deburred or formed edge, or reinforced with a 0.0710 x 7/8 inches minimum formed steel strip welded inside of the rim. The top and door assembly shall be welded to the cover. The cover may be equipped with or without three or more position lock thumb screws to hold the cover in place, at the manufacturer's option.

3.3 Finish.

3.3.1 Type I, single swinging door.

3.3.1.1 Style A. Covers shall be zinc coated, or shall have a baked enamel finish olive green color, at the manufacturer's option.

3.3.1.2 Style B. Covers shall have a baked enamel finish gray color.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

3.3.2 Type II. Covers shall have a baked enamel finish white or green, as specified (see 6.2).

3.3.3 Enamel.

3.3.3.1 Color. Unless otherwise specified (see 6.2), colors shall be the following color numbers in Fed. Std. No. 595:

| Color | Color number |
|---|---|
| Green | 24108 |
| Olive green | 14087 |
| Gray | 26314 |
| White | 27875 |

3.3.3.2 Thickness. Baked enamel thickness shall be 1 mil (0.001 inch) or greater (see 4.4.1.1).

3.3.3.3 Adherence. When tested in accordance with 4.4.1.3 the enamel shall not chip or flake. Base metal exposure shall be limited to the sharp line left by the knife blade.

3.3.4 Zinc coat.

3.3.4.1 Weight. Weight of zinc shall be 2.0 ounces per square foot or greater (see 4.4.2.2).

3.3.4.2 Adherence of zinc. The zinc coating shall neither crack nor flake when tested in accordance with 4.4.2.3.

3.4 Workmanship. The covers shall not present any sharp edges which might cut or snag. Fasteners shall be tightly set. Enameled surfaces shall be free from runs and unevenly coated areas. Zinc coated covers shall be completely coated with a uniform coat of zinc. All doors shall swing and return to closed position freely.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may use his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. Unless otherwise specified (see 6.2), lot shall consist of all waste receptacle covers of the same type and style, submitted for inspection at the same time.

4.2.2 Visual and dimensional examination of end item, and samples for test. Sampling for examination shall be in accordance with level S-3 in MIL-STD-105, and for tests shall be level S-2.

4.3 Inspection.

4.3.1. End item. Waste receptacle covers shall be examined for defects listed in table I. The Acceptable Quality Levels (AQL's) for defects listed in table I shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects, end item

| Defects | Major | Minor |
|---|---|---|
| Type and style not as specified. | X | |
| Flaking, peeling, blistering and zinc coating. | X | |
| Sags, runs, laps, blisters, orange peel in enamel finish. | X | |
| Sharp or burred edges which might cause injury | X | |
| Doors do not operate freely and smoothly. | X | |
| One rivet, weld or fastener missing. | | X |
| More than one rivet, weld or fastener missing. | X | |
| Component bent, dented, malformed or otherwise damaged or mispositioned. | | X |
| Damage or defects affecting function or serviceability. | X | |
| Damage or defects not affecting function or serviceability. | | X |

4.3.2 Inspection of preparation for delivery requirements. An inspection shall be made to determine that the packing and marking requirements comply with section 5 of this specification. Defects shall be scored in accordance with table II. For examination of contents the sample unit shall be one shipping container fully prepared for delivery selected just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closured listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and AQL shall be 4.0 defects per hundred units.

TABLE II. Classification of preparation for delivery defects

| Examine | Defects |
|---|---|
| Markings (exterior and interior) | Omitted; incorrect; illegible; improper size, location, sequence or method of application. |
| Materials | Any component missing or damaged. |
| Workmanship | Inadequate application of components, such as incomplete closure of container flaps, loose strapping, inadequate stapling. Bulging or distortion of container. |

4.4 Test methods.

4.4.1 Baked enamel covers.

4.4.1.1 Thickness of paint. Determine thickness by one of the following methods (see 3.3.3.2):

(a) Determine thickness using a micrometer. The difference between the measurement before the face paint is removed and the measurement after the paint is removed is the thickness of the face paint. Remove paint using methylene chloride or other organic solvent such as benzene, dry and measure thickness.

(b) Measure thickness of paint using a magnetic or scratch gauge.

4.4.1.2 Thickness of base metal. Dip a specimen, with the paint removed, into sulfuric acid, sp. gr. 184 (add 40 ml of c.p. $H_2SO_4$, to 950 ml of distilled water). Keep immersed until rapid evolution of hydrogen has ceased. Remove specimen and scrub or wipe off the black deposit, then wash with water and dry. Measure thickness of base metal with a micrometer (see 3.2.1.1, 3.2.1.4, 3.2.2.1, 3.2.2.3, 3.2.3.1, 3.2.3.3 and 3.2.3.4).

4.4.1.3 Enamel adhesion. Draw the point of a sharp knife across the enamel finish penetrating to the base metal over any portion of the inside or outside surfaces (see 3.3.3.3).

4.4.2 Zinc coated covers.

4.4.2.1 Thickness of base metal. Measure total thickness using a micrometer and subtract thickness of zinc determined in accordance with ASTM A464 (see 3.2.1.1).



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

4.4.2.2 Weight of zinc. Determine weight of zinc in accordance with ASTM A90, A219, or A464 (see 3.3.4.1 and 6.3).

4.4.2.3 Adherence of zinc. Adherence of zinc coating shall be tested in accordance with the pivoted hammer test in ASTM A123 (see 3.3.4.2).

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B or C as specified.

5.1.1 Level A. Each cover shall be packaged method III in accordance with MIL-P-116.

5.1.2 Level B. Each cover shall be packaged as specified in 5.1.1.

5.1.3 Level C. The covers shall be packaged in accordance with the suppliers commercial practice.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A. Covers of like description shall be packed in a close fitting box conforming to PPP-B-585, class 3; PPP-B-591, class II; PPP-B-601, overseas type; PPP-B-621, class 2; PPP-B-636, class weather-resistant; or PPP-B-640, class 2. The fiberboard boxes shall be closed, waterproofed, and strapped in accordance with the appendix to the applicable box specification. The gross weight of the triple wall box and the wood boxes shall not exceed approximately 200 pounds. The gross weight of the PPP-B-636 box shall not exceed the weight limitations of the box specification. Strapping shall be in accordance with the appendix to the applicable box specification.

5.2.2 Level B.

5.2.2.1 Type I. Two type I covers of like descriptions shall be packed in a box conforming to PPP-B-636, class domestic. The covers shall be blocked and braced to prevent movement and damage in shipment. The box shall be closed in accordance with the appendix to PPP-B-636.

5.2.2.2 Type II. Each cover shall be packed in a box conforming to PPP-B-636, class domestic. The cover shall be blocked and braced to prevent movement and damage in shipment. The box shall be closed in accordance with the appendix to PPP-B-636.

5.2.3 Level C. The covers, packaged as specified in 5.1, shall be packed to insure carrier acceptance and safe delivery to destination in containers complying with National Motor Freight Classification or Uniform Freight Classification.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military activities. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The receptacle covers, with swinging door, are intended for use as a self-closing top on 55 gallon metal drums providing an enclosure for the disposal of waste materials. Covers with horizontal doors are ordinarily intended for interior use.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type and style required (see 1.2).
(c) Type II, color of painted covers, and color numbers for all painted covers (see 3.3.2 and 3.3.3.1).
(d) Size of lot, if different from 4.2.1.
(e) Selection of applicable level of packaging and packing required (see 5.1 and 5.2).



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:11Z
Check the source to verify that this is the current version before use.

6.3 Zinc coated covers. Thickness of zinc coat can be determined using 1 ounce of zinc per square foot equivalent to a coating thickness of 1.7 mils (0.0017 inch). An average coating thickness of 1 mil (0.001 inch) corresponds to a coating weight of 0.59 ounces per square foot of surface.

MILITARY INTEREST:
Army - GL
Navy - MC
Air Force - 84

User activities:
Army - GL
Navy - MC
Air Force - 84

Preparing activity:

GSA-FSS

Orders for this publication are to be placed with the General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.