RR-D-00799A(GSA-FSS)
September 25, 1970
SUPERSEDING
Int. Fed. Spec. RR-D-00799(GSA-FSS)
May 26, 1964

# INTERIM FEDERAL SPECIFICATION

## DUSTPAN (LONG HANDLE, SWINGING PAN)

This Interim Federal Specification was developed by the General Services Administration, Federal Supply Service, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE

1.1 This specification covers one type of steel dustpan with a long metal handle and swinging pan.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

QQ-P-416 - Plating, Cadmium (Electrodeposited)
QQ-Z-325 - Zinc Coating, Electrodeposited, Requirements for
PPP-B-585 - Boxes, Wood, Wirebound
PPP-B-591 - Boxes, Fiberboard, Wood-Cleated
PPP-B-601 - Boxes, Wood, Cleated-Plywood
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner
PPP-B-636 - Box, Fiberboard
PPP-B-640 - Boxes, Folding, Fiberboard, Corrugated, Triple Wall

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies)

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:


MIL-P-116 - Preservation, Methods of

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage



Source: https://assist.dla.mil -- Downloaded: 202640-26T12:11Z
Check the source to verify that this is the currentversion before use.





2.2 Other publica
extent specified herei
for bids or request fo

Uniform Class
Uniform Fre

(Application for c
Chicago, Illinois 60

National Cla
National Mds

(Application for d.
Attn: Tariff Order Se

(Technical society
available for referen
Federal agencies.)

st of a pan and a handle, similar to figure 1, and
and table I.

from the floor by the handle, the pan shall swing
that sweepings will move into the hooded part. The
not interfere with the entrance of sweepings into
he handle on a 1/8 inch diameter rod shall be

tom with sides and hood. The hood shall extend from
bottom. The front edge shall be reinforced by
contact when the dustpan is supported by a level
th ends no more than 2 inches from the edges. The

zinc coated in accordance with QQ-Z-325 Type I,
Q-P-416 Class 3, Type I.

3. REQUIREMENTS

3.1 Material. Th

3.2 Illustration
exclude dustpans othe

ments form a part of this specification to the
ated, the issue in effect on date of invitation

3.3 Construction
shall conform to the

3.3.1 Handle.
downward by gravity
handle shall be attac
the pan. A means for
provided.

o the Uniform Classification, 202 Union Station,

3.3.2 Pan. The
the back to cover a
1/4 inch minimum wid
floor. When steel le
shall extend around
dimensions of the pa

o the American Trucking Associations, Inc.,
Washington, D.C. 20036.)

3.4 Finish.

3.4.1 Handle.
Class 3 or cadmium c

specifications and standards are generally
re also distributed among technical groups and using

all be the quality used to make commercial dustpans.

ence of identification. It is not intended to
this specification.



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:11Z
Check the source to verify that this is the currentversion before use.

3.4.2 Pan. The pan shall be coated with lacquer or enamel.

TABLE I. Dimensions in inches

| | Inches |
|---|---|
| Width of front edge (minimum) | 10-1/2 |
| Width of back (minimum) | 9-3/4 |
| Depth from front to back (minimum) | 7-1/2 |
| Height of sides 1/2 inch from front of pan (minimum) | 1/2 |
| Sheet metal thickness (minimum) | 0.0164 |
| Hood to pan bottom (clearance) (minimum) | 2-1/2 |
| Handle to pan (clearance) (minimum) | 2-1/2 |
| Handle wire diameter (minimum) | 0.135 |
| Handle length | 26 to 33 |

3.5 Performance.

3.5.1 Handle. The handle shall not become disengaged from the pan when dustpans are tested in accordance with 4.4.2 and 4.4.3.

3.5.2 Pan. When tested in accordance with 4.4.2 and 4.4.3, the front edge shall not bend or dent and the white paper shall not show evidence of dust leakage.

3.6 Marking. The dustpans shall be marked in a plain and permanent manner with the manufacturer's name or trade mark of such known character that the source of manufacture may be readily identified.

3.7 Workmanship. Dustpans shall be free from chipped paint, sharp edges, dents or corrosion.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any other commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. Unless otherwise specified (see 6.2), a lot shall consist of all dustpans offered for delivery at the same time.

4.2.2 Dimensional and visual examination of end item. Sampling for these characteristics shall be in accordance with level S-3 in MIL-STD-105.

4.2.3 Samples for test. Samples shall be selected as follows:

| Sample size | Level or number |
|---|---|
| up to 25 | 0 |
| 26 - 50 | S-1 |
| 51 and above | S-2 |

4.3 Inspection.

4.3.1 End item. Dustpans shall be examined and measured for defects listed in table II. The Acceptable Quality Levels (AQL's) for defects shall be 2.5 per cent for major defects and 4.0 per cent for minor defects, expressed in terms of defects per hundred units.



Source: https://assist.dla.mil -- Downloaded: 202640-26T12:11Z
Check the source to verify that this is the currentversion before use.

TABLE II. Classification of defects, end item

| Defects | Major | Minor |
|---|---|---|
| Paint blistered, peeled, chipped, area of thin or no coating | | X |
| Foreign matter imbedded in finish or evidence of rust | | X |
| Corrugations not as specified | | X |
| Front edge of blade not in continuous contact with level surface | X | |
| No provision for hanging provided | | X |
| Handle not securely attached | X | |
| Sharp edges or projections that may cause injury | X | |
| Front edge not hemmed as specified | X | |
| Dimensions below minimum of table I | X | |
| Damage or defects not affecting function or serviceability | | X |

4.3.2 Inspection of preparation for delivery requirements. An inspection shall be made to determine that packaging, packing and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with Table III. For examination of contents the sample unit shall be one shipping container fully prepared for delivery selected just prior to the closing operations. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be II and the AQL shall be 4.0 per hundred units.

TABLE III. Classification of preparation for delivery defects

| Examine | |
|---|---|
| Markings (exterior and interior) | Omitted; incorrect; illegible; or improper size, location, sequence, or method of application. |
| Materials | Any component missing, or damaged. |
| Workmanship | Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Bulging or distortion of container. |

4.4 Tests.

4.4.1 Acceptance. The AQL's for tests shall be 10 per cent defects per hundred units.

4.4.2 Drop test. The sample shall be held by the handle and dropped three times from a height of 18 inches onto a concrete slab or floor. It shall then be pushed slowly three times from a horizontal surface to fall freely 30 inches onto the concrete (see 3.5.1).

4.4.3 Shake test. Following the drop test (see 4.3.1), place 8 ounces of vacuum cleaner dust-free of matted lint or other large matter --into the dustpan and seal the opening with wrapping paper and masking tape. Hold the dustpan by its handle and shake back and forth vigorously twenty times, 6 inches above a white paper approximately 2 feet by 2 feet in size. (see 3.5.2)

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Each dustpan shall be packaged in accordance with MIL-P-116, method III.



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:11Z
Check the source to verify that this is the currentversion before use.

Delete and substitute:

5.1.2 Level B. The pan portion of each dustpan shall be completely wrapped in one thickness of minimum 30 pound kraft paper conforming to UU-P-268, grade B.

5.1.3 Level C. The dustpan shall be packaged in accordance with the suppliers commercial practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. The dustpans, packaged as specified in 5.1 and in quantities as specified (see 6.2), shall be packed in a box conforming to PPP-B-585, class 3; PPP-B-591, class II; PPP-B-601, overseas type; PPP-B-621, class 2; PPP-B-636, class weather-resistant; or PPP-B-640, class 2. The dustpans shall be block and braced to prevent movement and damage in shipment. The boxes shall be closed, waterproofed, and strapped in accordance with the applicable specification or appexdix thereto. The gross weight of the triple wall fiberboard box and the wood boxes shall not exceed approximately 200 pounds. The gross weight of the PPP-B-636 box shall not exceed the weight limitations of the box specification.

5.2.2 Level B. Twelve dustpans, packaged as specified in 5.1.1, shall be packed in a close fitting box conforming to PPP-B-636, class domestic. The dustpans shall be blocked and braced to prevent movement or damage in shipment. The box shall be close in accordance with the appendix to PPP-B-636.

5.2.3 Level C. The dustpans, packaged as specified in 5.1, shall be packed in containers to assure carrier acceptance and safe arrival at destination in compliance with Uniform Freight Classification or National Motor Freight Classification.

5.3. Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military activities. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The dustpans are intended to accept sweepings of dust and small trash for transfer to a trash receptacle.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number and date of this specification.
(b) Size of lot, if different than 4.2.1.
(c) Level of packaging and packing required (see 5.1 and 5.2).
(d) Quantity per level A shipping container (see 5.2.1).



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

GENERAL SERVICES ADMINISTRATION - FEDERAL SUPPLY SERVICE

# SPECIFICATION COMMENT SHEET

BUDGET BUREAU NO. 29-R0175

INSTRUCTIONS

This form provides a way for users of this specification to inform the originator of problems encountered in its use. It is not to be used to request changes to accommodate proprietary features. All comments will be considered and appreciated, but please do not expect a reply. To comment, detach, complete, and mail to General Services. Adm., FSS (FMSH), Washington D.C. 20406

NOTE: Comments on this form do not constitute or imply authorization to waive any part of the document or serve to amend contractual requirements.

1. SPECIFICATION

RR-D-00799A(GSA-FSS) Dustpan (Long Handle, Swinging Pan)

| 2. CONTRACT NO. *(If any)* | 3. QUANTITY ON CONTRACT *(Optional)* | 4. DOLLAR VALUE *(Optional)* |
|---|---|---|
| | | |

5. GENERAL NATURE OF PROBLEM *(e.g., inspection difficulties, manufacturers unable to meet tolerances, containers collapse under normal warehousing conditions, etc.)*

6. SPECIFIC REQUIREMENTS AFFECTED *(Include paragraph number and lines of wording)*

7. SPECIFIC PROBLEMS *(e.g. tests in 4.2.2 will not assure that the battery will last required time; temperature ranges in table 2 do not conform to commercially available items.)*

8. RECOMMENDATIONS

| 9. NAME OF MANUFACTURER, ASSOCIATION, GOVT., AGENCY, ETC. | 10. ADDRESS *(Number, Street, City, State and Zip Code)* |
|---|---|
| | |

| 11. NAME AND TITLE OF SUBMITTER | 12. DATE |
|---|---|
| | |

FORM GSA FEB 69 2200

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.