RR-D-1131B
September 14, 1971
SUPERSEDING
Fed. Spec. RR-D-1131A
October 21, 1966

FEDERAL SPECIFICATION

DISPENSER, DRINKING WATER, NONMECHANICALLY COOLED

(TO BE USED ONLY WHEN PRESSURE TYPE DISPENSERS ARE IMPRACTICABLE)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers two types of ice cooled, inverted bottle drinking water dispensers furnished with two 5-gallon capacity water bottles.

1.2 Classification.

1.2.1 Types. Water dispensers shall be of the following types as specified (see 6.2):

Type I - Stand mounted.
Type II - Cabinet mounted.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-P-291 - Paperboard, Wrapping, Cushioning.

Federal Standard:

FED-STD-123 - Marking for Domestic Shipment (Civil Agencies.)

FSC 4110

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:11Z
Check the source to verify that this is the current version before use.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of the Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-L-10547 - Liners, Case and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible.

Military Standards:

MIL-STD-105 - Sampling procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of U.S. Military Property.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, D.C. 20036.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 202, Union Station, 516 W. Jackson Blvd., Chicago, Ill. 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS.

3.1 Design. The drinking water dispenser shall consist of an insulated ice container, drinking water chamber, provisions for accommodating a 5-gallon water bottle, and a floor mounted cabinet or stand. The type I drinking water dispenser shall be stand mounted. The type II drinking water dispenser shall be cabinet mounted. The 5-gallon water bottle shall be inverted to dispense water to the water chamber. The water chamber shall be within the ice container, but separate from it, and connected to the faucet. The water chamber shall be so constructed as to preclude leakage of melted ice into the drinking water. A waste bucket shall be located on a rack beneath the drain. The shell of the insulated ice container shall be sealed to prevent penetration by water or water vapor into the insulation. The drinking water dispensers shall not leak when tested as specified in 4.3.1.

3.1.1 Cooling capacity. The dispensers shall be capable of lowering the temperature of the dispensed drinking water from a minimum 80° to 47°F. or lower, within 30 minutes after filling the ice container with a full charge of crushed ice. The dispenser shall be capable of maintaining the temperature of the dispensed drinking water at 47°F. or colder while the entire water capacity is being withdrawn at a rate of 1/2 pint of water per minute (see 4.3.2).

3.2 Materials. Materials not definitely specified shall be of the quality normally used by the manufacturer for water dispensers provided the completed item complies with all provisions of this specification.

3.3 Standard product. The dispensers delivered under this specification shall be the manufacturer's current commercial product, except for any changes necessary to comply with specification requirements.

3.4 Construction.

3.4.1 Welding. All welds of seams or joints shall be treated to resist corrosion. The welds shall be flush, and shall not contain pits and slag.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

3.4.2 Ice container. The ice container shall be made from steel galvanized on both sides, corrosion-resisting steel, or aluminum. The ice container shall be of insulated, double wall construction. Unless otherwise specified (see 6.2), the ice container shall have a minimum capacity of 25 pounds of crushed ice (see 4.3.2). Unless otherwise specified (see 6.2), a drainage outlet and a removable standpipe shall be provided to drain the ice container. When the stand-pipe is installed, it shall be designed to maintain a 3-inch water level and when the stand-pipe is removed, water in the ice container shall be completely drained into the waste bucket. The stand-pipe shall be fabricated of corrosion-resistant metal.

3.4.2.1 Ice container lid. A metal lid of the same material as the ice container shall be provided to cover the ice container opening. The lid shall be designed so that ice may be added without removing the water bottle. The lid shall be form fitted to prevent foreign substances from falling or leaking into the ice container.

3.4.3 Water chamber. The water chamber shall be porcelain or corrosion-resisting steel. A service faucet shall be positive action, self-closing, push type. Piping and piping connections between water chamber and service faucet shall be composed of substances generally recognized as safe for such use and sealed.

3.4.4 Metal stand or cabinet. The metal stand for type I, and the metal cabinet for type II, shall be fabricated of steel, corrosion-resisting steel, or aluminum. The legs shall be braced for rigid support. The ends of the legs shall be rounded and capped with rubber or plastic feet. When legs are provided, clearance between the floor and bottom of cabinet shall be not less than 6 inches. If a base is provided, the clearance between the floor level and the lower extension of the base shall not exceed 3/8 inch at any point. The stand or cabinet shall not rock when placed on a flat level surface in the position of normal use. The stand and cabinet shall have a rack or similar means of supporting a waste bucket.

3.4.5 Drip tray. A detachable drip tray, fabricated from the same material as the cabinet and stand, positioned under the service faucet and arranged to drain into the waste bucket without splashing on the floor shall be furnished. The drip tray shall be securely held in place but shall be removable for cleaning.

3.4.6 Waste bucket. A 12-quart capacity, watertight, waste bucket fabricated from galvanized steel, corrosion-resisting steel, or aluminum shall be furnished (see 4.3.2). The waste bucket shall have a bail for ease of handling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

3.4.7 Support ring. A rubber or plastic support ring with necessary air vents shall be provided to align and support the water bottle and to securely seal the opening against leakage of foreign matter and infiltration of dust. The material used for the support ring shall be of a substance generally recognized as safe for such use.

3.4.8 Water bottles. Unless otherwise specified (see 6.2), two 5-gallon capacity water bottles shall be furnished with each dispenser. The bottles shall be made of clear glass, cylindrical in shape with a flat bottom.

3.5 Finish. Unless otherwise specified herein, the finish shall be the manufacturer's standard finish.

3.6 Marking for identification.

3.6.1 Military marking. All parts shall be marked for identification in accordance with MIL-STD-130.

3.6.2 Civil marking. The dispensers furnished shall have the manufacturer's standard identification marking.

3.6.3 Service warning. In addition to the identification marking required in 3.6, a service warning plate of plastic shall be permanently attached above the faucet on the front outside of the dispenser cabinet or rack. It shall be printed in upper case letters 1/4-inch high and shall read as follows:

> PERSONS SERVICING THIS DISPENSER SHALL BE EXTREMELY CAREFUL. WHEN FILLING THE BOTTLE USE ONLY POTABLE WATER FROM A SAFE SOURCE, AND WHEN FILLING AND INSERTING THE BOTTLE, DO NOT CONTAMINATE THE WATER BY TOUCHING THE BOTTLE NECK NOR PERMITTING ANY FOREIGN MATTER TO ENTER THE BOTTLE OR THE WATER CHAMBER OF THE DISPENSER. THE WATER CONTAINERS MUST BE STERILIZED BY AN APPROVED METHOD WITH CHLORINE OR CAUSTIC PRIOR TO EACH REFILLING. WHEN FILLING THE BOTTLE, AN UNUSED, CLEAN, NEW PAPER CUP CONFORMING TO UU-C-806, STYLE E, SHALL BE PLACED OVER THE END OF THE BOTTLE NECK IMMEDIATELY AFTER THE BOTTLE IS RESTED ON ITS SHOULDER ON THE EDGE OF THE DISPENSER PRIOR TO COMPLETION OF THE INSERTION.

3.7 Workmanship. Sharp edged corners, burrs, and slivers shall be removed.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance

Source: https://assist.dla.mil -- Downloaded: 2026-04-26T12:11Z
Check the source to verify that this is the current version before use.

of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Inspection. Sampling for inspection and acceptance shall be in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.2.2 End item inspection. The sample unit shall be one completely fabricated dispenser. The inspection lot shall consist of all dispensers of one type offered for inspection at one time.

4.2.2.1 Visual examination. Examination of the dispenser shall be in accordance with defects listed in table I. The inspection level shall be II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Construction, design, and workmanship (applicable to all components and assemblies)	Part missing	X	
	Any component fractured, loose, or malformed	X	
	Operation omitted or not properly performed	X	
Faucet	Faucet that is inoperative, or will not function as intended	X	
Stand-pipe drain	Drain does not hold ice water at design level	X	
	Not removable	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Bolts, nuts, screws, and other types of threaded components	Missing, broken, stripped, or fractured		X
Welding	Not flush or contains pits or slag	X	
Finish	Not manufacturer's standard finish		X
Marking for identification	Not manufacturer's standard marking		X
Warning service plate	Missing	X	

4.2.2.2 End product testing. The drinking water dispenser shall be tested as specified in 4.3. The inspection level shall be S-2 with an AQL of 2.5, expressed in terms of defects per hundred units. The test specified in 4.3.2 shall be made on the initial unit of production.

4.2.3 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing, and marking as required by section 5 are complied with. Defects shall be as indicated in table II. The sample unit shall be one shipping container fully prepared for delivery. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-1 with an AQL of 6.5, expressed in terms of defects per hundred units.

TABLE II. Examination of preparation for delivery

Examine	Defects
Marking	Missing; incorrect; not legible; of improper size, location, sequence, or method of application.
Materials	Component missing, damaged, or otherwise defective.
Contents	Number per container is more or less than required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

4.2.3.1 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-601 or PPP-B-636, examination for defects in closure and strapping shall be in accordance with the applicable container specification.

4.3 Tests.

4.3.1 Leak test. The dispenser shall be assembled for use with the water bottle and ice container filled to capacity with water. The dispenser shall be examined to determine compliance with leakage requirement of 3.1. After 5 minutes, the water bottle and ice container shall be drained by using the service faucet and waste drain, respectively, to observe operation of components. Any leakage or failure of any component to operate shall constitute failure of this test.

4.3.2 Cooling capacity test. At an ambient temperature of 80° F. or higher, 5 gallons of water having a minimum temperature of 80°F. shall be placed in the water bottle and the dispenser shall be assembled for use. The ice container shall then be filled with a full charge of crushed ice and the time recorded. Observation shall be made of ice capacity for conformance with 3.4.2. After 30 minutes, the temperature of the drinking water in the water cooling container shall be measured. The entire capacity of the water bottle shall then be dispensed through the service faucet at a rate of not less than 1/2 pint per minute. The temperature of the dispensed water shall be recorded at 5-minute intervals. The recorded temperatures shall be evaluated to determine compliance with the water temperature requirements of 3.1.1. During the test, observation shall be made of the waste bucket capacity (see 3.4.6 and the ice container lid conforms to (3.4.2.1) Inability of the container to hold 25 pounds of ice or inability of the water to reach temperature requirements of 3.1.1 or components to operate or meet specified requirements shall constitute failure of this test.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly. The waste bucket shall be removed from the dispenser. When practical, the service faucet and drip tray shall be disassembled from the dispenser.

5.1.1.2 Packaging.

5.1.1.2.1 Drip tray and service faucet. Detached drip tray and service faucet shall be individually wrapped in paperboard conforming to type III,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

style 2 of PPP-P-291 and the wrap secured with minimum one-inch tape. The drip tray and service faucet shall then be placed in the waste bucket.

5.1.1.2.2 Water bottle. Each water bottle shall be packaged in a snug-fitting, corrugated, fiberboard box conforming to style RSC, type CF, class domestic of PPP-B-636. The bottle shall be cushioned within the box with die-cut scored sheets and corner pads of the same material as specified for the box; a minimum clearance of one-half inch shall be maintained between the inner surfaces of the box and the exterior of the water bottle. The box shall be closed in accordance with PPP-B-636.

5.1.1.2.2.1 Civil agencies. When civil agencies procure dispensers under this specification, the water bottle shall be omitted.

5.1.1.2.3 Waste bucket. Each waste bucket, with drip tray and service faucet, packaged as specified in 5.1.1.2.1, shall be packaged in a snug-fitting, fiberboard box conforming to style RSC, type CF, variety SW, or type SF, class domestic of PPP-B-636. The box shall be securely closed and secured to the shelf of the dispenser.

5.1.1.2.4 Dispenser. The water chamber shall be blocked and cushioned within the ice container with scored or die-cut fiberboard sheets fitted securely within the void space in a manner as to prevent movement or damage while in transit. The dispenser shall then be packaged in a snug-fitting, fiberboard box and the box securely closed.

5.1.2 Level C. The dispensers shall be packaged to afford adequate protection against damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Each dispenser, complete with water bottles, packaged as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to overseas type, grade B of PPP-B-601. The interior boxes shall be blocked and braced to prevent movement within the shipping container by the use of scored fiberboard sheets or wood blocking. The fiberboard sheets shall be of doublewalled construction and have a minimum bursting strength of 275 pounds per square inch (p.s.i.). Each shipping container shall be provided with a type I or II, grade C case liner conforming to MIL-L-10547. Closure and strapping shall be in accordance with PPP-B-601.

5.2.2 Level B. Each dispenser, complete with water bottles, packaged as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to style RSC, type CF, variety DW, or type SF, class domestic of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

PPP-B-636. The interior boxes shall be blocked and braced to prevent movement within the shipping container by the use of scored fiberboard sheets shall be of double-walled construction and have a minimum bursting strength of 275 p.s.i. Each shipping container shall be closed in accordance with method II of PPP-B-636.

5.2.2.1 When specified (see 6.2), the shipping container shall be V3c, V3s, or V4s fabricated and closed in accordance with PPP-B-636.

5.2.3. Level C. Dispensers, complete with water bottles, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with FED-STD-123.

5.3.2 Military requirements. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129. Special handling marking requirements applicable to fragile items shall apply.

6. NOTES

6.1 Intended use. The dispensers covered by this specification are used to cool and dispense drinking water.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type required (see 1.2.1).
(c) When ice container capacity is other than for 25 lbs. of crushed ice (see 3.4.2).
(d) Whether drain pipe is required (see 3.4.2).
(e) When other than 2 bottles are required (see 3.4.8).
(f) Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).
(g) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

6.3 Level B packaging. When level B packaging is specified for civil agency procurement, the requirements of paragraph 5.1.1, level A packaging shall apply (see 5.1.1).

6.4 Note. The improper handling and replacement of water bottles in inverted bottle type drinking water dispensers are considered by the U.S. Public Health Service of the Department of Health, Education, and Welfare to be unsanitary and conducive to contamination of potable water. However, where there are no substitute devices available, it is recommended that these dispensers be used only when it is impracticable to use a pressure type dispenser, and then only as directed on the plate attached to the front of the dispenser. Water for filling the bottle must come only from a safe source of potable water. None of the above is to be interpreted as a condemnation of the proper handling of safe bottled water by bottled water companies regularly inspected and approved by State Health Departments.

MILITARY CUSTODIANS:

Army - GL
Navy - YD
Air Force - 82

Review activities:

Army - MD
Navy - MS

User activities:

Army - CE
Navy - MC

Preparing activity:

Army - GL

CIVIL AGENCY INTEREST:

GSA
HEW

Project No. 4110-0220

☆ U. S. GOVERNMENT PRINTING OFFICE : 1971 O - 482-190 (3165)

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 15 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. Army Natick Laboratories
Natick, Massachusetts 01760

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

U.S.MAIL

OFFICIAL BUSINESS

Commanding General
U. S. Army Natick Laboratories
ATTN: [illegible]
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION
Dispenser, Drinking Water, Nonmechanically Cooled (To Be used When Pressure Type Dispensers Are Impracticable) RR-D-1131B

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.