RR-D-800A
January 31, 1973
SUPERSEDING
Fed. Spec. RR-D-800
March 28, 1963

FEDERAL SPECIFICATION

DUSTPAN, STEEL, SHORT HANDLE

This specification was approved by the Commissioner Federal Supply Service, General Services Administration for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers one type of steel dustpans with short handles.

1.2 CLASSIFICATION

1.2.1 Type, class, and size. Dustpans shall be of the following type, class, and size as specified (see 6.2 and 6.3).

Type II - Open pattern
Class 2 - One piece
Size - 12 inch

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

UU-P-268 - Paper, Kraft, Untreated, Wrapping.
UU-T-111 - Tape; Paper, Gummed (Sealing and Securing).
PPP-B-636 - Box, Fiberboard.
PPP-T-45 - Tape, Gummed, Paper, Reinforced and Plain, For Sealing and Securing.

Federal Standards:

Fed. Std. No. 102 - Preservation, Packaging and Packing Levels.
Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attribtues.
MIL-STD-129 - Marking for Shipment & Stroage.
MIL-STD-130 - Identification Marking of U.S. Military Property.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Preproduction sample. When specified (see 6.2), before production is commenced, a sample of the finished dustpan covered by this specification shall be submitted or made available to the contracting officer or his authorized representative for approval in accordance with 4.2. The approval of the preproduction sample authorizes the commencement of production, but does not relieve the contractor of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured by the contractor in the same facilities to be used for the manufacture of the production items.

3.2 Standard product. The dustpans shall be the manufacturer's standard commercial product, except for any changes necessary to conform to the requirements specified herein.

3.3 Materials. Sheet steel, reinforcing wire and finishing material shall be of the type and quality normally used in commercial practice to fabricate dustpans. The gage of steel and wire shall be as hereinafter specified.

3.4 Construction. The dustpans shall be contructed so that the front edge shall be in continuous contact with the floor when the pan is in use or when set unsupported on the floor. The blade shall be one piece. If the thickness is less than 0.020-inch nominal, there shall be at least three corrugations; convex on the upper side, extending radially from points not more than 2 inches from the front.

3.4.1 Type II, open pattern. The walls, inside at the back, shall be a minimum of 1-1/2 inches high, tapering gradually down the sides to the front end of the pan.

3.4.2 Class 2. The type II, class 2 dustpan including the back, blade, sides and handle shall be formed in one piece from 0.0359 inch (20 gage) minimum sheet steel.

3.5 Handles. All handles shall have a hole or loop for means of attachment to a wall hook.

3.5.1 Type II, class 2. The handle for type II, class 2 dustpans shall be a minimum of 4-1/2 inches in length, tapering from a minimum of 1 inch in diameter at the pan end to a nominal of 1-1/8 inch in diameter at the end.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

3.6 Dimensions. The dustpans shall conform to the following dimensions:

	Inches
Front edge (minimum)	12
Back edge:	
For 12 inch front edge (minimum)	9
Sides:	
Height at front (minimum)	3/8
Inside height at back (minimum)	1-1/2
Length of sides (minimum)	7
Back corners may be square or rounded to a radius of (minimum)	2

3.7 Finish. The dustpans shall be finished in accordance with manufacturer's standard practice, except that the color shall be black. There shall be no blistering, peeling, chipping or area of no film or thin film on the finish.

3.8 Workmanship. Dustpans shall be fabricated and finished in accordance with the best commercial practices and shall be free of sharp edges and projections, burrs, peeling, blisters and, other defects affecting the appearance or those which might affect the function or serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspection are deemed necessary to assure that supplies and services conform to the prescribed requirements.

4.2 Preproduction sample inspection. When preproduction samples are specified (see 6.2), they shall be inspected and tested to determine conformance with all the requirements of this specification.

4.3 Samplings.

4.3.1 Lot. Unless otherwise specified (see 6.2) a lot shall consist of one type, class, and size offered for inspection at one time.

4.3.2 Visual and dimensional examination of end item. Sampling for these characteristics shall be in accordance with level S-3 in MIL-STD-105.

4.3.3 Component and material inspection. In accordance with 4.1 above, the supplier is responsible for insuring that components and materials used are manufactured, tested and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified or, if none, in accordance with this specification.

4.3.4 Inspection.

4.3.4.1 End-item. Dustpans selected in accordance with 4.3.2 shall be examined for defects listed below. The sample unit for this examination shall be one (1) completely fabricated waste receptacle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects

Examine	Defects	Classification	
		Major	Minor
Finish	Not black color.		X
	Blistered, peeled, chipped, or area of thin film or no film.		X
	Foreign matter imbedded in finish or evidence of rust.		X
Construction and workmanship	Corrugations not as specified.		X
	Front edge of blade not in continuous contact with level surface.	X	
	No provisions for hanging provided.		X
	Not one-piece construction (when applicable).		X
	Handle not securely welded to the back, type II.	X	
	Handle not braced with hollow boss or support, type II.	X	
	Sharp edges or projections that may cause injury.	X	

4.3.4.2 Dimensional examination. Dustpans shall be examined for compliance with dimensions specified in 3.6. The sample size shall be determined in accordance with 4.3 and 4.3.4.3. Any deviation from specified requirements shall constitute a defect.

4.3.4.3 Inspection levels and AQL's. The AQL's expressed in defects per hundred units, and inspection levels shall be as follows:

For Examination in	Inspection levels	AQL's	
		Major	Total
4.3.4.1	II	2.5	6.5
4.3.4.2	L4		

4.3.5 Inspection of preparation for delivery. An inspection shall be made to determine that the packaging, packing and marking comply with the requirements in section 5 of this specification. Defects shall be scored in accordance with table II. For examination of interior packaging the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with and AQL of 4.0 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Markings	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Material	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling, or distortion of container.
Contents	Number per container is more or less than required. Net weight exceeds requirements of the box specification.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. Each dustpan shall be completely wrapped in one thickness of kraft Paper conforming to UU-P-268, grade B, minimum basis weight 30 pounds, or in a plastic bag constructed from material conforming to L-P-378, a minimum of 1 mil thick. Each package shall be secured with tape.

5.1.2 Level C. Dustpans shall be packaged in accordance with the manufacturers standard practice, providing that this will insure protection for the dustpans during shipment and provides for safe delivery to their destination.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A. Twenty-four dustpans of like description, packaged as specified in 5.1 shall be packed in the most compact manner in a close-fitting box conforming to PPP-B-636, class weather resistant. Each shipping container shall be closed, waterproof sealed and reinforced in accordance with the appendix to PPP-B-636.

5.2.2 Level B. Twenty-four dustpans of like description, packaged as specified in 5.1 shall be packed in the most compact manner in a close-fitting box conforming to PPP-B-636, grade 275 minimum. Closure of shipping containers shall be in accordance with method II of the appendix to PPP-B-636.

5.2.3 Level C. Dustpans packaged as specified in 5.1 shall be packed in a manner that will insure carrier acceptance and safe delivery to destination in compliance with the National Motor Freight Classification rules or the Uniform Freight Classification rules, as applicable.

5.3 Marking. In addition to any special markings required by the contract or order, all marking shall be in accordance with 5.3.1 or 5.3.2 as specified (see 6.2).

5.3.1 Civil agencies. All marking shall be in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. All marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The dustpans are intended to be used to pick up and transfer waste from the floor to a waste receptacle.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type, class, and size of dustpan required (see 1.2).
(c) When preproduction sample is required (see 3.1).
(d) Inspection record details (see 4.1).
(e) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

MILITARY CUSTODIANS:

Army - GL
Air Force - 84

User interests:

Army - GL

Preparing activity:

GSA-FSS

Orders for this publication are to be placed with the General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.