RR-H-1070B
December 28, 1973
SUPERSEDING
Fed. Spec. RR-H-1070A
August 6, 1968

FEDERAL SPECIFICATION

HOLDER, GARBAGE CAN

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers garbage can holders of the fixed post type.

1.2 Classification. Garbage can holders shall be of the following types as specified (see 6.2).

Type I - Single can holder
Type II - Double can holder

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

PPP-T-97 - Tape; Pressure Sensitive Adhesive, Filament-Reinforced.
PPP-B-636 - Box, Shipping, Fiberboard.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple Wall.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 7240

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM) Standard:

A153 - Zinc-Coating (Hot-Dip) on Iron and Steel Hardware.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA, 19103).

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agenct:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Techanical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups using Federal agencies.)

3. REQUIREMENTS

3.1 Design.

3.1.1 Type I. Type I. single can holders shall be designed to be adjustable to hold a garbage or trash can up to 55 gallon capacity off the ground a minimum of 9 inches. The holder shall be designed to keep the can in a level and upright-position at all times.

3.1.2 Type II. Type II, double can holder shall be of the same basic design as type I, except it shall be capable of holding two garbage or trash cans.

3.2 Construction.

3.2.1 Type I. Single can holders shall consist of a post, an adjustable bottom can support, a retaining hook which will accept the handle of the can to hold the can in an upright-position, and a top cap. Component parts for which a hot-dip galvanized coating is specified, shall be so coated after all fabrication is complete and left with its natural condition unpainted or without any additives to the coating.

3.2.1.1 Bottom Support. The bottom support shall be either cast aluminum or fabricated steel finished with a hot dip, galvanize coat at the option of the manufacturer. It shall provide continuous support at all points within an arc subtending 65 degrees minimum on the bottom circumference of the can. A raised lip of sufficient height to prevent the can from being dislodged from its normal position of rest shall be provided along the outer edge of the bottom support.

3.2.1.2 Retaining hook. The handle retaining hook shall be of 12 gage (0.1046 inch) hot dip galvanized steel and shall be an integral part of the cap. The coating shall be applied after welding.

3.2.1.3 Cap. The cap shall be of 12 gage (0.1046 inch) hot dip and shall be equipped with an eyelet for each can (1 for single can support, 2 for double can support) with a minimum inside diameter of 0.325 inch. The eyelet and handle and retaining hooks are to be an integral part of the cap and the cap shall be made to fit tight to the top end of the post to prevent its easy removal. The above components shall be hot-dip galvanized after fabrication.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:11Z
Check the source to verify that this is the current version before use.

3.2.1.4 Post. The post shall be of hot-dip galvanized steel.

3.2.2 Type II. Type II, double can holders shall be of a construction similar to type I except the bottom can support and hook arrangement shall be capable of holding two cans.

3.3 Performance. When installed in accordance with the manufacturers instructions, the type I holder shall be capable of withstanding the weight of a can loaded with 250 pounds without tipping or dipping more than 1/2 inch. Type II holder shall be capable of withstanding the weight of 2 cans, each loaded with 250 pounds of weight without tipping or dipping more than 1/2 inch for each can. (See 4.4.2).

3.4 Dimensions. The holder component parts shall be of a sufficient size and strength to conform to the performance requirements of 3.3. The post of both types of holders shall be 48 + 1 inch long and shall not be less than 1-1/2 inches in diameter and have a wall thickness of not less than 16 gage (0.0625).

3.5 Finishes-color. The component parts of the holder shall have their natural metallic finish for those materials which have some type of protective coating or where the material used is not corrosive; all other surfaces shall be painted any color at the option of the manufacturer.

3.6 Assembly and installation instructions. Assembly and installation instructions shall be furnished with the folder to insure proper use of the unit.

3.7 Workmanship. The holder shall be free of burrs, sharp edges, and cracks. Weld shall be sound and free of flux, splatter, holes, or cracks. The holders shall also be free of any other defects which may affect serviceability, durability, or appearance.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. Unless otherwise specified (see 6.2), a lot shall consist of all holders of the same type.

4.2.2 Dimensional and visual examination. Sampling for these characteristics shall be in accordance with level S-3 in MIL-STD-105.

4.2.3 Sampling for tests. Sampling for tests shall be in accordance with level S-3 in MIL-STD-105. The AQL for tests shall be 2.5 on the basis of percent defective.

4.3 Examination.

4.3.1 End item. Holders shall be examined and measured for defects listed in table I. The Acceptable Quality Levels (AQL's) for defects shall be 4.0 percent defective for major defects and 10 percent defective for minor defects.

TABLE I. Classification of defects

Defects	Major	Minor
Type not as specified.	X	
Material not as specified.	X	
Component parts missing.	X	
Dimensions not as specified.	X	
Finish of component not as specified.	X	
Burrs, sharp edges, cracks, flux, holes.		X
Defects affecting serviceability.	X	
Defects not affecting serviceability.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

4.3.2 Inspection of preparation for delivery. An inspection shall be made to determine that the packaging, packing and marking comply with the requirements in section 5 of this specification. Defects shall be scored in accordance with table II. For examination of interior packaging the sample unit shall be one shipping container fully prepared for delivery selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers in the end item inspection lot. The inspection level shall be S-2 with an acceptable quality level (AQL) of 4.0 defects per hundred units.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, or distortion of container.

4.4 Test.

4.4.1 Procedures. The post for type I and type II holders shall be placed in a jig or held by any method which would simulate or be equivalent to a concrete base 18 inches in depth and 24 inches in diameter, and the applicable number of cans placed on them.

4.4.2 Test. When post and cans are in place as prescribed in 4.4.1, a measurement shall be taken from the center of base of the can and ground level and noted, after which each can, as applicable, shall be filled with 250 pounds of weight and the same measurement made. The dipping and tipping shall not exceed that permitted by paragraph 3.3.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly. Disassembly shall be limited to parts that can be removed and reinstalled in accordance with the manufacturer's recommendations.

5.1.1.2 Unit-packaging.

5.1.1.2.1 Type I or II. Each type I or II holder components shall be secured together into a compact unit with tape conforming to PPP-T-97.

5.1.2 Level C. The holders shall be packaged in accordance with the suppliers commercial practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Holders of like description in quantities as specified (see 6.2) shall be placed in a close-fitting box conforming to PPP-B-636, grade V2S or PPP-B-640, class weather resistant. Blocking and bracing shall be provided. The box shall be closed and strapped in accordance with the appendix to the box specification.

5.2.2 Level B. Unless otherwise specified (see 6.2), holders of like descriptions, and in quantities not to exceed the weight limitation of the box specification, shall be packed, blocked, and braced, in a close-fitting box conforming to PPP-B-636, grade V3c. The box shall be closed in accordance with the appendix to the box specification. When the set screw in place, and the top hook, post, and base assembled into a compact unit and secured with tape conforming to PPP-T-97.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. The holders shall be packed in a manner which will insure arrival at destination in satisfactory condition and be acceptable to the carrier at lowest rates. Containers and packing shall comply with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, all interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to markings required by the contract or order, all interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended Use. Holders covered by this specification are intended to hold garbage cans suspended off the ground to prevent spillage and improve appearances in trash areas, prevent loss of can covers, and eliminate the breeding areas of roaches and other vermin.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents.

(a) Title, number, and date of this specification.
(b) Type (see 1.2).
(c) Quantities of bundles of holder in shipping containers (see 5.1 and 5.2.2).
(d) Level of packaging and level of packing required (see 5.1 and 5.2).

MILITARY CUSTODIANS:

Army - GL
Navy - YD
Air Force - 84

Review activities:

Army - MD

User activities:

Army - CE
Navy - CG, MC

Preparing activity:

GSA-FSS

Civil Agency Coordinating Activity:

JUSTICE-FPI

Military Coordinating Activity:

Navy - YD

Orders for this publication are to be placed with the General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.