INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

MOPPING OUTFITS, FLOOR

This interim amendment was developed by the General Services Administration, Federal Supply Service, Standardization Division, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification RR-M-1075A, dated November 16, 1972.

PAGES 3 AND 4

Paragraphs 3.2.3; 3.2.3.1; 3.2.3.2; 3.3; 3.3.1; 3.3.2; 3.3.3; 3.4; 3.4.1; 3.4.1.1; 3.4.2; and 3.4.2.1. Delete in their entirety and substitute the following:

"3.2.3 Type III Roller-type wringer mopping outfits.

3.2.3.1 Details of components. Buckets for type III mopping outfits shall conform to the requirements of RR-P-35 or RR-B-800 or as specified. Wringers shall conform to the requirements specified herein.

3.2.3.1.1 Type III, Class 1, Sets A and B. These mopping outfits shall have a roller type wringer without casters, conforming to the following: The roller design shall be either pull-through or crank-handle mop wringer. The wringer shall be securely fastened to the specified bucket with an attachment having a thickness of not less than 0.0598 inch thick. One wringer and one bucket shall be supplied for each set specified. Set A buckets shall have a capacity of 14 quarts, conforming to RR-P-35. Set B buckets shall have a capacity of 16 quarts conforming to shape D in RR-B-800.

3.2.3.1.2 Type III, Class 2, Set C. These mopping outfits shall have a slotted frame single bucket roller type wringer mounted on casters conforming to the following: The roller design shall be equipped with at least four casters and shall be of the crank-handle-operated steel-roller construction. The wringer frame and steel rollers shall be painted, enameled, or zinc coated iron or steel. The wringer shall be of sufficient width to accomodate freely and thoroughly wring mops from 12-32 ounce sizes (see T-M-561). The four casters shall be rubber tired. Two of the casters shall be of the swivel type. The two non-swivel casters shall be at least two inches in diameter and the swivel casters shall be at least 1-5/8 inches in diameter. Unless otherwise specified, one of the two rollers shall be either corrugated or perforated. The set C bucket shall conform to size 2, shape D of RR-B-800. These wringers shall have adjustable roller support arms guided and supported through slots provided in the framework. The wringer shall be provided with a bail for lifting and carrying the wringer. The wringer shall accommodate a single bucket of at least the minimum size as specified by the size number in the procurement documents. (See 6.1.)

3.3 Materials in type III roller-type wringer outfits.

3.3.1 Corrosion resisting metal. Material designated herein as corrosion resisting metal shall be steel or malleable iron electrogalvanized, electroplated, or finished with a baked-on or air-dried enamel coating.

3.3.2 Wood. Wood for rollers shall be maple, ash, cherry, birch, pecan, hackberry, or other suitable medium or high-density hardwood.

3.3.3 Rubber. Rubber for rollers shall be natural rubber, synthetic rubber, or a combination of natural and synthetic rubber.

3.4 Construction of Type III, roller-type wringers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

PAGES 3 AND 4 (con.)

3.4.1 Design. Wringers of all types described in this specification shall be designed with sufficient width and opening capacity to fully accommodate mops of the sizes for which they are intended. (see 1.2.1) They shall have the capacity to force sufficient water from a mop into a water container to produce a damp-dry mop meeting the requirements of this specification. The design of the wringer shall be such so that when placed over a water container of proper size, the stability of the water container shall not be affected by operation of the wringer.

3.4.2 Guard. Wringers shall be equipped with a mop guard to prevent loose ends of mop strands from catching in or entwining around roller shafts, axles, gears, or other components, as applicable.

3.4.3 Rollers. The rollers shall be made of wood, metal, or rubber, (natural, synthetic or a compound thereof), as specified in the invitation for bids (see 6.1.1). Unless otherwise specified, metal rollers may be painted, enameled, or plated to resist corrosion. If material is not specified, any of the above may be furnished. The rollers shall be not less than 1-5/8 inch in diameter and not less than 8 inches long. All roller surfaces shall be smooth and come together evenly over their entire length. The rollers shall be centered. Wood rollers shall be made of a suitable hardwood. (See 3.3.2.)

3.4.4 Framework. The framework shall be of ferrous metal not less than 0.125 inch thick before coating. It shall be zinc coated, painted or enameled. Wringer assembly shall be so constructed that it will not fall over when used without the pail.

3.4.5 Mechanism. When no pressure is applied to the foot pedal the operating mechanism shall open automatically wide enough for easy insertion of the mop.

3.4.6 Size and capacity. The size of the wringer shall be such as to accommodate a bucket without casters of at least the minimum size specified by size number. The wringer shall damp dry all sizes of mops in T-M-561 (12 to 32 ounces)."

PAGE 5

TABLE I Line 6 Change 3.2 to 3.3.

TABLE II Lines 16 and 17 Delete and substitute the following:

Rollers	Length	less than 8 inches
	Diameter	less than 1-5/8 inches

Lines 18 and 19 Delete and substitute the following:

Framework:	Thickness less than 0.125 inch thick.
Bracket (class 1):	Thickness less than 0.075 inch thick.

GSA DC 74 5615

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.