RR-S-00714C(GSA-FSS)
July 30, 1971
Interim Revision of
Fed. Spec. RR-S-714B
August 10, 1965

INTERIM FEDERAL SPECIFICATION

STENCIL SET, MARKING

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Federal Specification as a valid exception to Federal Specification RR-S-714B, dated August 10, 1965.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers marking stencil sets of interlocking letters and figures for composing reusable marking stencils.

1.2 Classification.

1.2.1 Types and sizes. The marking stencil set shall be of the following types and sizes as specified (see 6.2).

Type I - Letters and figures-One A font (see 3.2).
Type II - Letters and figures-Two A font (see 3.2).
Sizes - Height of letters and figures, 1/2, 3/4, 1, 1-1/4, 1-1/2, 1-3/4, 2, 2-1/2, 3, 4, 5, and 6 inches.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date on invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

QQ-B-613 - Brass, Leaded and Non-Leaded: Flat Products (Plate, Bar, Sheet, and Strip).
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Box, Fiberboard.
PPP-B-665 - Boxes; Paperboard, Metal Stayed, (Including Stay Material).
PPP-B-676 - Boxes, Setup.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Incorporated, Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the National Motor Freight Traffic Association, Inc., Agent, 1616 P Street, N.W., Washington, D. C. 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Tariff Publishing Officer, Room 202 Union Station, 516 W. Jackson Blvd., Chicago, Illinois 60606.)

Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.

3. REQUIREMENTS

3.1 Components. Unless otherwise specified (see 6.2), each marking stencil set shall consist of the following components:

Type I

Letter stencils, complete 26 letter alphabet.
Figure stencils, "0" to "9" inclusive.
One ampersand ("&"), one beginner, one period ender, one plain ender, two spacers, one period, one comma, and one apostrophe.

Type II

Letter stencils shall consist of the following letters:
Two of each: A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, R, S, T, U, and W.
One of each: Q, V, X, Y, and Z.
Figure stencils, two of each from "0" to "9" inclusive.
One ampersand ("&"), one beginner, one period ender, one plain ender, two spacers, two periods, one comma, and one apostrophe.

3.2 Materials. Materials shall conform to the applicable specification and requirements specified herein.

3.2.1 Brass sheet or strip. The brass shall be copper alloy number 260 or 268, sheet or strip, spring temper, conforming to QQ-B-613.

3.3 Design and construction. The marking stencils shall be cut or stamped from brass specified in 3.2.1. All characters shall be cut symmetrically about the vertical center line of the stencil. The character alignment margin requirements for top and bottom shall be equal. The thickness of the brass shall be as specified in table I. The edges of the stencil joining members of each individual size character shall be arranged to lock with, or join one another so as to form in a single strip any word name, or address, that can be readily assembled and disassmebled. Letters, figures, and punctionation marks, in the same size, shall be in alignment when assembled for horizontal straight line stenciling. The brass margin above and below the letters and figures shall be as specified in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

TABLE I. Minimum brass thickness and margin

Character size	Thickness	Brass margin above and below characters
Inches	Inch	Inches
1/2 to 1-1/2 incl.	0.006	3/4
1-3/4 to 4 incl.	.007	1
5	.008	1
6	.008	1-1/8

3.3.1 Strokes of letter and figures. The letters and figures shall have a stroke of not less than one seventh the height specified. The letters and figures, except the letter "I", figure "1", the period, comma, and apostrophe shall have a width of not less than one half the height specified.

3.4 Style of letters and figures. Unless otherwise specified (see 6.2), the style of letters and figures shall be Gothic style. The portions of letters and figures normally curved-shaped shall not be made straight-lined or squared.

3.5 Finish. The brass stencils shall be a natural finish.

3.6 *Workmanship*. The finished marking stencil sets (font) shall conform to the quality and grade of product established by this specification and shall be smooth, free from burrs, and sharp edges.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Inspection of components and materials. In accordance with 4.1 above, the supplier is responsible for insuring that components and materials used were manufactured, inspected, and tested in accordance with this specification or referenced subsidiary specifications and standards.

4.1.1.1 Component testing. Each lot of brass used in the fabrication of stencil sets shall be tested in accordance with the applicable test methods specified hereinafter, to determine compliance with the requirements of section 3. Each inspection lot shall consist of one shipment of brass of a single type or grade manufactued by the same source, under essentially the same conditions and used in the production of the quality of the end item submitted for inspection at one time.

4.2 Sampling, inspection and testing of brass. The brass shall be sampled, inspected and tested in accordance with the provisions of QQ-B-613.

4.3 Sampling for inspection and acceptance of the end item. Sampling for inspection and acceptance of the end item shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.3.1 Inspection of the end item. The lot shall be the number of marking stencil sets (font) of one type and size offered for inspection at one time. The sample unit for this inspection shall be one complete set.

4.3.1.1 Visual examination. Examination shall be made of the end items for defects in table II. The inspection level shall be II with an AQL of 4.0, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects

Examine	Defects
Construction and workmanship	Any components of set missing. Letters and figures not style specified. Brass stencil surface not smooth. Brass stencil surfaces spotted. Burrs or sharp edges.

4.3.1.2 Dimensional examination. Inspection shall be made of the marking stencil set (fonts) for compliance with dimensions specified. Any deviations from specified requirements shall constitute a defect. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

4.3.1.3 Assembly examination. An examination shall be made to determine that the letters and figures in the same set, can be readily assembled and disassembled and shall be in alignment for horizontal straight line stenciling. The inspection level shall be S-1 with an AQL of 2.5, expressed in terms of defects per hundred units.

4.3.2 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing, and marking as required by section 5 of this specification are complied with. Defects shall be scored as specified in table III. The sample unit shall be one shipping container fully prepared for delivery except it need not be sealed. The lot shall be the number of containers offered for delivery at one time. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units. Examination for closure and strapping (levels A and B packing, only) shall be in accordance with PPP-B-636.

TABLE III. Examination of preparation for delivery

Examine	Defects
Markings (exterior and interior container)	Missing; incorrect; illegible; of improper size, location, sequence or method of application.
Materials	Component missing, damaged or otherwise defective.
Weight	Weight of contents more than specified.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Unit package. Each stencil set shall be individually packaged in a close-fitting box conforming to PPP-B-566, PPP-B-665, or PPP-B-676. Each box shall be adequately closed to prevent accidental opening.

5.1.1.2 Intermediate package. Twelve stencil sets of one type and size only, unit packaged as specified in 5.1.1.1, shall be packaged in a close fitting box conforming to PPP-B-566, PPP-B-665, or PPP-B-636, class domestic. The weight limitation of each box shall not be exceeded. Each box shall be adequately closed to prevent accidental opening.

5.1.2 Level B. The stencil sets shall be packaged in accordance with 5.1.1.

5.1.3 Level C. The stencil sets shall be packaged in accordance with the manufacturer's standard practice, providing that this insures protection for the stencil sets during shipment and provides for safe delivery to their destination.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Stencil sets of one type and size only packaged as specified in 5.1 shall be packed in a close-fitting box conforming to PPP-B-636, class weather resistant, grade V2s. Closure, water-proof sealing and strapping of the boxes shall be in accordance with the appendix to PPP-B-636. The weight of the contents for a single box shall not exceed 65 pounds.

5.2.2 Level B. Unless otherwise specified, sets of one type and size only packaged as specified in 5.1 shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. Closure of the boxes shall be in accordance with the appendix to PPP-B-636. The weight of the contents for a single box shall not exceed 75 pounds. When specified (see 6.2), the boxes shall be in accordance with PPP-B-636, class weather resistant, grade V3c or V3s.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. Stencil sets packaged as specified in 5.1 shall be packed in containers that will assure carrier acceptance and safe arrival at destination in compliance with the National Motor Freight Classification rules and the Uniform Freight Classification rules.

5.3 Marking. Marking shall be in accordance with 5.3.1 or 5.3.2 as specified (see 6.2).

5.3.1 Civil agencies. In addition to any special marking required by the contract or order, all interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to any special marking required by the contract or order, all interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Stencil sets are intended for composing reusable stencils for marking shipments, signs, posters, and similar items.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type of set and size letters and figures required (see 1.2).
(c) When components of the set differ from type specified (see 3.1).
(d) Style of letters and figures required if other than Gothic (see 3.4).
(e) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
(f) Selection of marking required (see 5.3).
(g) When weather-resistant class fiberboard shipping containers are required for level B shipment (see 5.2.2).

6.3 Brushes, ink, and paint. Stencil brushes, ink, and paint are not included in the stencil marking set. Stencil ink for use on nonporous and porous surfaces may be procured under Federal Specifications TT-I-558 and TT-I-559, respectively. Flat stencil paint may be procured under Federal Specification TT-P-98 and stencil brushes under Federal Specification H-B-621.

GSA DC 72-1847

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

GENERAL SERVICES ADMINISTRATION - FEDERAL SUPPLY SERVICE

SPECIFICATION COMMENT SHEET

BUDGET BUREAU NO. 29-R0175

INSTRUCTIONS

This form provides a way for users of this specification to inform the originator of problems encountered in its use. It is not to be used to request changes to accommodate proprietary features. All comments will be considered and appreciated, but please do not expect a reply. To comment: detach, complete, **and mail to: Gen. Services Admin., FSS (FMSO), Washington, D.C. 20406**

NOTE: Comments on this form do not constitute or imply authorization to waive any part of the document or serve to amend contractual requirements.

1. SPECIFICATION

RR-S-00714C (GSA-FSS) - Stencil Set, Marking

2. CONTRACT NO. *(If any)*	3. QUANTITY ON CONTRACT *(Optional)*	4. DOLLAR VALUE *(Optional)*

5. GENERAL NATURE OF PROBLEM *(e.g., inspection difficulties, manufacturers unable to meet tolerances, containers collapse under normal warehousing conditions, etc.)*

6. SPECIFIC REQUIREMENTS AFFECTED *(Include paragraph number and lines of wording)*

7. SPECIFIC PROBLEMS *(e.g. tests in 4.2.2 will not assure that the battery will last required time; temperature ranges in table 2 do not conform to commercially available items.)*

8. RECOMMENDATIONS

9. NAME OF MANUFACTURER, ASSOCIATION, GOVT., AGENCY, ETC.	10. ADDRESS *(Number, Street, City, State and Zip Code)*

11. NAME AND TITLE OF SUBMITTER	12. DATE

FORM GSA FEB 69 2200

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.