RR-W-001588(GSA-FSS)
March 20, 1970

INTERIM FEDERAL SPECIFICATION

WASTE RECEPTACLE, WALL OR POST MOUNTED

This Interim Federal Specification was developed by the General Services Administration, Federal Supply Service, Washington, D.C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE. This specification covers one type and size metal receptacle wall or post mounted for waste and garbage.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-B-636 - Box, Fiberboard.
PPP-F-320 - Fiberboard Sheet Stock (Container Grade) and cut Shapes.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedure and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Classification Board:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Association, Inc., Attention: Tariff Order Section, 1616 P Street, N.W., Washington, D. C. 20036.)

FSC 7240

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:12Z
Check the source to verify that this is the current version before use.

Uniform Classification Committee:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, Chicago, Ill. 60606.)

3. REQUIREMENTS

3.1 Materials.

3.1.1 Steel. Carbon steel sheets, strips or shapes used in the fabrication of items covered by this specification shall be either hot or cold rolled, commerical quality.

3.1.2 Straps. Corrosion resistant straps and bolts shall be provided for pole mounting.

3.1.3 Hasps. Corrosion resistant hasps regularly used by the manufacturers shall be used.

3.1.4 Hinges. Corrosion resistant hinges piano or butter fly type, regularly used by the manufacturers shall be used.

3.2 Design and construction.

3.2.1 Body. Body shall be fabricated from not less than 0.0359 ± .003 inch (20 gage) carbon steel. The corner shall be rounded and all panels to form the body shall be joined by spot welding, fusion welding or seam welding. Body shall be not less than 30 inches or more than 34 inches in height and shall be not less than 15 inches or more than 19 inches in width, and not less than 10 inches or more than 14 inches in depth. Capacity shall be not less than 20 gallons of waste. Provisions for hanging a plastic or cotton cloth liner shall be provided.

3.2.2 Bracket. The body shall be designed to form a recessed section which shall extend the full height of the rear panel to serve as a provision for pole mounting, with adjustiable straps to allow mounting up to 14 inches in diameter. The width of the recessed section shall be 6 inches over all a tolerance of plus or minus 1 inch to the width shall apply.

3.2.3 Upper door. Upper door shall be fabricated from not less than 0.359 ± .003 inch (20 gage) carbon steel. The upper door shall be not less than 7 inches or more than 10 inches in height and shall be not less than 12 inches or more than 15 inches in width. The door shall be hinged at the top by a piano or butter-fly type hinge at the option of the manufacturer. Door shall be designed to swing inward and upward 90° and shall be constructed to return to the completely closed position by either spring or gravity action at the manufacturers option. The words "DEPOSIT LETTER" shall be embossed or silk screened in each door in black letters 1-1/2 inches minimum in height.

3.2.4 Lower door. Lower door shall be fabricated from not less than 0.359 ± .003 inch (20 gage) carbon steel. The lower door shall be not less than 9 inches or more than 12 inches in height, and shall be not less than 14 inches in width. The door shall be hinged at the top by a piano or butter-fly type hinge at the option of the manufacturer. Door shall be designed to swing outward and upward 180° and shall be constructed to return to the completely closed position by either spring or gravity action and shall be secured with corrosion resistant hasp, with provisions for pad locking.

3.2.5 Waste chute. The waste exit chute may be constructed by providing a lower front door and a rear hinged bottom with connecting linkage to form the chute. Waste chute in open position is angled forward with the horizonal at not less than 30 degrees. Or the waste exit chute may be constructed by providing a bottom floor angled forward with the horizonal at not less than 30 degrees, at the option of the manufacturer.

3.3 Finish.

3.3.1 Protective coating. Receptacle shall have a gloss enamel finish, inside and outside, colors shall be white or gray as specified (see 6.2).

3.3.2 Enamel. All enameled surfaces shall be free from runs and unevenly coated areas. When tested in accordance with 4.4.2 the enamel shall not chip or flake. Base metal exposure shall be limited to the sharp line left by the knife blade.

3.4 Workmanship. The receptacles shall not have any sharp edges which might cut or snag. Welded edges shall be smooth and tightly set. Bolts, screws and nuts, when used, shall be of the standard American National Form and shall be installed with an adequate means for preventing loss of proper tightness. Doors shall swing and return freely and smoothly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:12Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any other commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. Unless otherwise specified (see 6.2), a lot shall consist of all waste receptacles submitted for inspection at the same time.

4.2.2 Visual examination of end item. Sampling for this examination shall be according to level S-3 in MIL-STD-105. The Acceptable Quality Levels (AQL's) for defects listed in table I shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

4.2.3 Sampling for tests. Sampling for tests shall be in accordance with level S-2 in MIL-STD-105. The AQL for tests shall be 6.5 on the basis of percent defective.

4.3 Examination.

4.3.1 End item. Receptacles selected in accordance with 4.2.2 shall be examined for defects listed in table I.

TABLE I. Classification of defects, end item

Defects	Major	Minor
Dimensions of receptacle not as specified.	X	
Sags, runs, laps, blisters, orange peel in enamel finish.	X	
Sharp or burred edges which might cause injury.	X	
Doors do not operate freely and smoothly.	X	
One weld or fastener missing.		X
More than one weld or fastener missing.	X	
Component bent, dented, malformed or otherwise damaged or mispoisitioned.		X
Color not as specified.		X
Damaged or defects not affecting function or serviceability.		X

4.3.2 Inspection of preparation for delivery. An inspection shall be made to determine that the packing and marking requirements comply with section 5 of this specification. Defects shall be scored in accordance with table II. For examination of contents the sample unit shall be one shipping container fully prepared for delivery selected just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closures listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible, improper size, location, sequence or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, loose strapping, inadequate stapling. Bulging or distortion of container.

4.4 Tests.

4.4.1 General Receptacles selected in accordance with 4.2.3 shall be tested for compliance with the requirements of this specification.

4.4.2 Enamel adhesion. Draw the point of a sharp knife across the enamel finish penetrating to the base metal over any portion of the inside or outside surface to determine compliance with 3.3.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:12Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A, B or C, as specified (see 6.2).

5.1.1 Level A. Each waste receptacle shall be packed in a close-fitting box conforming to PPP-B-636, class weather-resistant. Fiberboard blocking and bracing shall be provided with the fiberboard meeting the requirements of PPP-F-320, class domestic, variety SW. The box shall be closed and strapped in accordance with the appendix to the box specification.

5.1.2 Level B. Each waste receptacle shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. Fiberboard blocking and bracing shall be provided with the fiberboard meeting the requirements of PPP-F-320, class domestic, variety SW. The box shall be closed in accordance with the appendix to the box specification.

5.1.3 Level C. The waste receptacle shall be packed to insure carrier acceptance and safe delivery at destination at the lowest rates, in containers complying with the rules and regulations applicable to the mode of transportation.

5.2 Marking.

5.2.1 Civil agencies. In addition to markings required by the contract or order, the shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.2.2 Military activities. In addition to markings required by the contract or order, the shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Waste receptacles covered by this specification are intended for collection of refuse, waste or garbage prior to bulk disposal.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Color (see 3.3.1).
(c) Size of lot, if different from 4.2.1.
(d) Selection of applicable level of packaging and packing (see 5.1 and 5.2).

GSA DC 70-12547

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:12Z
Check the source to verify that this is the current version before use.

GENERAL SERVICES ADMINISTRATION - FEDERAL SUPPLY SERVICE

SPECIFICATION COMMENT SHEET

BUDGET BUREAU NO. 29-R0175

INSTRUCTIONS

This form provides a way for users of this specification to inform the originator of problems encountered in its use. It is not to be used to request changes to accommodate proprietary features. All comments will be considered and appreciated, but please do not expect a reply. To comment: detach, complete, and mail to: General Services Administration, FSS (FMSH), Washington, D. C. 20406.

NOTE: Comments on this form do not constitute or imply authorization to waive any part of the document or serve to amend contractual requirements.

1. SPECIFICATION

RR-W-001588 (GSA-FSS) Waste Receptacle, Wall or Post Mounted

2. CONTRACT NO. *(If any)*	3. QUANTITY ON CONTRACT *(Optional)*	4. DOLLAR VALUE *(Optional)*

5. GENERAL NATURE OF PROBLEM *(e.g., inspection difficulties, manufacturers unable to meet tolerances, containers collapse under normal warehousing conditions, etc.)*

6. SPECIFIC REQUIREMENTS AFFECTED *(Include paragraph number and lines of wording)*

7. SPECIFIC PROBLEMS *(e.g. tests in 4.2.2 will not assure that the battery will last required time; temperature ranges in table 2 do not conform to commercially available items.)*

8. RECOMMENDATIONS

9. NAME OF MANUFACTURER, ASSOCIATION, GOVT., AGENCY, ETC.	10. ADDRESS *(Number, Street, City, State and Zip Code)*

11. NAME AND TITLE OF SUBMITTER	12. DATE

GSA DC 69-9761

FORM GSA FEB 69 2200

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:12Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:12Z
Check the source to verify that this is the current version before use.