MILITARY SPECIFICATION

Guided Missile Launching System Mark 13 Mod 0

This Specification has been approved by
Bureau of Naval Weapons, Department of the Navy

1. SCOPE

1.1 Scope - This specification governs the manufacture, test and preparation for delivery of the Guided Missile Launching System Mark 13 Mod 0.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, form a part of this specification. Of the documents listed, only those portions which are specifically referenced herein or on pertinent drawings, test data sheets, and the like, shall be considered applicable.

SPECIFICATIONS

Military Specifications

MIL-M-11473 Magnetic Particle Inspection

PUBLICATIONS

Ordnance Pamphlets

OP 2665 (4 Volumes) Guided Missile Launching System Mark 13 Mod 0; Description, Operation & Maintenance

DATA

Ordnance Data (NAVORD OD)

8852 - Commercial Material Specifications
8853 - Steel-Carbon and Alloy-Method of Specifying on Ordnance Drawings
13673- Factory Acceptance Tests
13674- Shipboard Installation Tests
15649- Installation and Alignment Procedure

DRAWINGS

List of Drawings 297980 and all Drawings and Specifications Listed Thereon.

FSC 1440

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:56Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

2.2 Other Publications - The following documents form a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

NATIONAL BUREAU OF STANDARDS PUBLICATION

Handbook H28--Screw Thread Standards for Federal Service

(Application for copies of the above publication should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, DC)

ASA B5.15 - Involute Splines

(Applications for copies of the above publication should be addressed to the American Society of Mechanical Engineers, New York, N. Y.)

2.3 Precedence - The order of precedence of applicable documents shall be as follows:

(a) The contract
(b) This specification
(c) NAVORD OD 13673
(d) LD 297980 and documents referenced thereon
(e) Other applicable documents referenced in 2.1 and 2.2

3. REQUIREMENTS

3.1 Material - All components and the assembled Guided Missile Launching System shall conform to the applicable drawings, specifications and standards with respect to dimension, tolerances, materials, processes, and finishes unless permission for departure therefrom has been obtained from the Bureau of Naval Weapons.

3.2 Performance - The equipment covered by this specification shall perform in accordance with the limits set forth in NAVORD OD 13673.

3.3 Components -

3.3.1 General - The component subassemblies which comprise a Guided Missile Launching System Mk 13 Mod 0 are defined by the Lists of Drawings referenced in Section 2. The launching system is subdivided into major

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:56Z
Check the source to verify that this is the current version before use.

component groups identified as the launcher, magazine, system control, strikedown system, anti-icing fluid heater, and identification and cabling assembly.

3.4 Weight - The weight of the Guided Missile Launching System Mark 13 Mod 0, exclusive of missiles, missile checkout equipment, hydraulic fluid, personnel, and associated Bureau of Ships gear, should not exceed 135,665 pounds. This weight condition will exist, if manufacture is performed in accordance with the applicable drawings, and tests by the system manufacturer to demonstrate compliance with this weight value will not be required.

3.5 Government-Furnished Material - The following items of equipment and material shall, unless otherwise specified by the Contracting Officer, be furnished by the Government at no expense to the contractor for use in producing the equipment covered by this specification:

3.5.1 Dummy missiles as required for test purposes.

3.5.2 Wings and fins as required for engineering and test purposes.

3.5.3 Dummy directors as required for test purposes.

3.6 Workmanship - Manufacture shall be accomplished in accordance with standards of workmanship necessary to produce components and assemblies which conform in all respects with the requirements prescribed by the specifications and drawings listed in paragraph 2.1 and those set forth herein.

4. QUALITY ASSURANCE PROVISIONS AND TEST REQUIREMENTS

4.1 Test - General - The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.4.1 All tests shall be performed with electrical power and control input at normal voltage and frequency as specified for the equipment.

4.1.2 Specified test routines shall be performed on suitable test stands so as to simulate to the maximum practicable degree static and dynamic characteristics of the components being tested. Drawings of suitable test stands will be made available to the manufacturer upon request to the Bureau of Naval Weapons.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:56Z
Check the source to verify that this is the current version before use.

istent with National laws and 5 Ratifying Nations agree that when con

4.1.3 Instrumentation shall be provided to accurately record test results to the extent required by the applicable specifications. Specialized test accessories shall be made available to the manufacturer to the extent set forth in paragraph 3.5 above.

4.1.4 Unless otherwise specified, the missile launching system components shall be subjected to acceptance tests under normal ambient conditions of temperature and humidity.

4.2 Acceptance Tests - All missile launching system components shall be subjected to the routine acceptance tests set forth in NAVORD OD 13673 and test results recorded in a copy thereof.

4.3 Inspection - The manufacturer shall provide himself with whatever gages are necessary and adequate to assure that component parts conform with dimensional and other requirements of the applicable drawings. The Bureau of Naval Weapons may make available to the manufacturer drawings for pertinent Navy Final Inspection Gages for guidance in the design and manufacture of inspection gages. However, such procedure shall not serve to relieve the manufacturer of his responsibility for satisfactory fulfillment of contract specification requirements.

4.3.1 Unless otherwise indicated on the applicable drawings, the standard of acceptance for magnetic particle inspection of steel weldments shall be as indicated in MIL-M-11473 STD 1A and MIL-M-11473 STD 1B.

4.3.2 Packaging and Packing - The inspector shall ascertain that the packaging and packing of the launching system equipment conform to Section 5 of this specification.

5. PREPARATION FOR DELIVERY

5.1 Division of Components for Shipment - For purposes of shipment, the launching system shall be divided into the following components or groups of components:

(1) Missile Launcher (assembled to maximum practicable extent consistent with existing rail shipment clearances)

(2) Magazine (partially disassembled)

(3) Control Panels

(4) Strikedown System

(5) Anti-icing Fluid Heater

5.2 Packing and Packaging - All equipment shall be packaged and packed in accordance with Section 14 of NAVORD OD 13673.

Source: https://assist.dla.mil -- Downloaded: 20260-19T17:56Z
Check the source to verify that this is the current version before use.

5.2.1 - Packaging - Launcher components and miscellaneous loose parts packaged in accordance with NAVORD OD 13673 shall be protected against damage caused by shock and vibration and protected against damage and deterioration caused by environmental conditions during direct shipment from the supply source to the first receiving activity and storage periods specified in the contract.

5.2.2 - Shipment - Packaged launcher components shall be suitably protected by dunnaging, blocking, bracing and tie-down methods applicable to the mode of transportation to assure acceptance by common carrier at lowest practicable commercial rates.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE C-8279

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:56Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

Commander
Naval Ordnance Systems Command
Engineering Support Division
Standardization Branch
Code 9343
Department of the Navy
Washington, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:56Z
Check the source to verify that this is the current version before use.