MIL-H-23799(WP)
Amendment 1
10 March 1966

MILITARY SPECIFICATION

HOSE ASSEMBLY, METAL, TRANSFER, LIQUID OXYGEN

This amendment forms a part of Military Specification MIL-H-23799(Weps) of 26 Jun 1963, and has been approved by the Bureau of Naval Weapons, Department of the Navy.

By this amendment, basic specification MIL-H-23799(Weps) is changed to read MIL-H-23799(WP), and throughout the specification (Weps) shall be changed to read (WP).

Paragraph 2.1, pages 1 and 2: Modify as follows:

Delete	Substitute
O-P-191 Perchloroethylene (Tetrachloroethylene), Technical Grade	O-T-236 Tetrachloroethylene (Perchloroethylene), Technical Grade
MIL-P-7936 Parts and Equipment, Aeronautical, Preparation for Delivery	MIL-STD-794 Parts and Equipment, Procedures for Packaging and Packing of
MIL-O-21749 Oxygen, Aviator's Breathing	MIL-O-27210 Oxygen, Aviator's Breathing, Liquid and Gas
AND 10375 Coors-Fluid Line Identification	MIL-STD-1247 Identification of Pipe Hose, and Tube Lines for Aircraft, Missiles, Space Vehicles, and Associated Support Equipment and Facilities.

Add

MIL-T-27730 Tape, Antiseize, Tetrafluoroethylene with Dispenser

Page 4, paragraph 3.4.1: Delete and substitute the following:

FSC 1660

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:56Z
Check the source to verify that this is the current version before use.

"3.4.1 Antiseize tape or compound - Antiseize tape or compound shall be used on all male pipe thread fittings. Antiseize tape shall conform to and shall be applied as specified in MIL-T-27730. Antiseize compound shall conform to MIL-T-5542 and shall be applied to the first three threads from the end of the fitting. When compound is applied, the end of the fitting shall be wiped off with a clean dry cloth. Tape or compound shall not be used on flare tube fitting straight threads, coupling sleeves, or on the outer side of tube flares. None of the tape or compound shall be allowed to enter the inside of a fitting."

Page 4, paragraph 3.5: Modify as follows:

a. Delete specification "O-P-191" and substitute "O-P-236."

a: Insert the following between 3.5(a) and 3.5(b): "Mechanically clean all welds or brazed joints as required."

c. Delete "250°F" and substitute "250 ± 25°F.

f. Delete "250°F" and substitute "250 ± 25°F."

Page 4, paragraph 3.5.1: Add the following:

"3.5.1 Cleaning procedure - The cleaning procedure shall be performed after visual examination (see 4.7.1.1 and 4.7.1.1.1) and prior to final assembly of dacron cover and insulation of the metal hose assembly."

Page 5, paragraph 3.8, line 3: Delete "Standard AND 10375" and substitute MIL-STD-1247 ."

Page 6, paragraph 4.3.1, line 10: After "MIL-H" add "23799(WP)."

Pages 7 and 8, Table I: Delete and substitute the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:56Z
Check the source to verify that this is the current version before use.

TABLE I

SAMPLE SIZE, ACCEPTANCE CRITERIA, TESTS, AND EXAMINATIONS OF THE HOSE ASSEMBLIES

INSPECTION	TYPE OF INSPECTION	METHOD	SAMPLE SIZE	ACCEPTANCE CRITERIA
Visual examination (See classification of defects)	Critical Minor	4.7.1.1	Every hose assembly for critical defects. Inspection Level II 1/ for minor defects.	Acceptance number zero, rejection number 1 for critical defects and an accepted quality level of 10.0 defects per hundred units for minor defects.
Dimensions	Major	4.7.1.1.1	Inspection Level S-2 1/	Acceptance number zero, rejection number 1.
Proof pressure	Critical	4.7.2	Every hose assembly	Reject all defective units.
Obstruction	Critical	4.7.3	Every hose assembly	Reject all defective units.
Endurance 2/ room temperature	Major	4.7.4.1	Inspection Level S-4 1/	Acceptance number zero, rejection number 1.
Impulse 2/ 3/	Major	4.7.6 (only 8000 cycles)	Inspection Level S-2 1/	Acceptance number zero, rejection number 1.
Preparation for delivery	Minor	4.7.1.2	Inspection Level S-2 1/	Total acceptable quality level of 4.0 percent defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:56Z
Check the source to verify that this is the current version before use.

Page 9, paragraph 4.5.2.2: Delete in its entirety.

Page 9, paragraph 4.6.1, line 2: Delete “Specification MIL-0-21749" and substitute "MIL-O-27210."

Page 10, paragraph 4.7: Delete and substitute the following:

“4.7 Inspection methods The inspections listed in paragraphs 4.7.2 thru 4.7.7 shall be performed on the metal hose assembly prior to the attachment of the dacron sleeving and the insulation."

Page 10, paragraph 4.7.1.1: Delete and substitute the following:

“4.7.1.1 Hose assembly - Every completed metal hose assembly shall be examined visually (for critical defects) to determine conformance to this specification and applicable drawings. The classification of defects Table II, shall be used to classify the defects found,

4.7.1.1.1 Dimensions - The completed metal hose assembly shall be checked dimensionally to determine conformance to the dimensions specified in ACEL drawings 33H1261 and 33C1262.

Page 11, Table III: Delete in its entirety.

Page 13, paragraph 5.1. line 2: Delete "Specification MIL-P-7936" and substitute "MIL-STD-794."

Page 13, paragraph 6.2(e), lines 8 and 9: Delete.

Page 13, paragraph 6.2: Add the following:

“6.2(f) Data required (see 6.5)."

Page 14, paragraph 6.4: Delete in its entirety.

Page 14, "Notice" paragraph: Delete in its entirety.

Page 14, paragraph 6.5: Add the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:56Z
Check the source to verify that this is the current version before use.