MILITARY SPECIFICATION

RECORDER ASSEMBLY

(For Torpedo Exercise Section Mark 64 Mod 2)

This specification has been approved by the Bureau of Naval Weapons, Department of the Navy

1. SCOPE

1.1 Scope. This specification describes the requirements for the manufacture, procurement, inspection and test of a recorder assembly, Bureau of Naval Weapons LD 613309.

2. APPLICABLE DOCUMENTS

2.1 The following document s of the issue in effect on the date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

NN-P-515	plywood, Container Grade
PPP-B-585	Boxes; Wood Wirebound
PPP-B-601	Boxes; Wood, Cleated Plywood
PPP-B-621	Boxes; Wood, Nailed and Look Corner
PPP-13-636	Box, Fiberboard

MILITARY

MIL-P-116	Preservation, Methods of
MIL-L-10547	Liners, Case, Waterproof
MIL-O-23560/4	Oscillograph
M1L-P-23810	Panel, Component, Recording

FSC 1355

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:59Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage

DRAWINGS

NAVY DEPARTMENT

BUWEPS LD 613309	Recorder Assembly (and all standards, specifications and drawings listed thereon)
BUWEPS Drawing 2436236	Recording Component Panel Schematic
BUWEPS Drawing 2436239	Recording Component Panel Wiring Diagram

PUBLICATIONS

BUREAU OF NAVAL WEAPONS

OS 6341	Miscellaneous General Ordnance Design Requirements

(Copies of specifications, standards, drawings, and publications request by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL BUREAU OF STANDARDS PUBLICATIONS

Handbook H28	Screw-Thread Standards for Federal Services

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:59Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D.C.)

CONSOLIDATED CLASSIFICATION COMMITTEE PUBLICATION

Consolidated Freight Classification Rules

(Application for **cpies** should be addressed to the Consolidated Classification Committee, 202 Chicago Union Station, Chicago 6, Illinois.)

AMERICAN TRUCKING ASSOCIATION, INC. , PUBLICATION

Motor Freight Classification Rules

(Application for copies should be addressed to the Issuing Officer, American Trucking Association, Inc., 1424 16th St., N.W., Washington 6, D.C.)

3. REQUIREMENTS

3.1 Description. - The recorder assembly is a device which receives and records information concerning various torpedo characteristics and functions as they exist during an exercise torpedo run. It consists of a recording oscillograph, MIL-O-23560/4 and a recording component panel, MIL-P-23810(Wep), connected together.

3.2 General requirements

3.201 Preproduction samples. Unless otherwise specified in the contract or order, preproduction samples of the recorder shall be manufactured using the methods and procedures proposed for the production lot. These samples will be tested as specified in section 4 herein, and are for the purpose of determining that the production item meets the requirements of this specification and design.

3.2.2 Materials. - Unless otherwise specified in the contract, requisition,or order all materials and purchased parts entering into the final assembly of the recorder shall conform strictly to the detailed requirements indicated on the drawings and specifications listed in BUWEPS LD 613309.

3.2.3 Finishes, coatings, construction, and dimensions, Finishes, coatings, construction, and dimensions for the recorder shall be in strict accordance with the applicable drawings, specifications, and publications listed in BUWEPS LD 613309.

3.2.4 Moisture, fungus, and corrosion. The recorder shall be rendered moisture, fungus, and corrosion resistant as required by NAVWEPS OS 6341,

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:59Z
Check the source to verify that this is the current version before use.

3.2.5 Marking. Marking of assemblies, subassemblies, and parts shall be in accordance with the applicable drawings listed in BUWEPS LD 613309.

3.2.6 Interchangeability. Individual parts of assemblies fabricated in agreement with their applicable drawings and specifications shall be interchangeable with mating parts of the unit and other like units. If deviations greater or smaller than the tolerances shown on the drawings or specifications are required for interchangeability, or if hand-fitting beyond that shown on the applicable drawings is required, then changes in dimensions are necessary and revision and correction of the applicable drawings or specification is required. See 3.2.9.

3.2.7 Gages. The contractor shall provide himself with whatever gages are necessary to insure that the material to which this specification applies will meet the dimensional requirements shown on the applicable drawings. If so stipulated in the contract, order, or requisition, the Government will furnish drawings of pertinent Navy Final Inspection Gages for guidance in the design of the contractor's inspection gages, However, such procedure shall not serve to relieve the contractor of his responsibility in the design and manufacture of such gages as may be required in the satisfactory fulfillment of the contract requirements, but is intended to facilitate acceptance of all components and assemblies by Navy Final Inspection Gages.

3.2.8 Threads. Unless otherwise specified, all threads shall be in accordance with the National Bureau of Standards Handbook H28. The class or fit for threads shall be as specified on the applicable drawings.

3.2.9 Conflicting requirements. Conflicting requirements arising between this specification or any specifications, publications, or drawings listed herein shall be referred in writing to the procuring agency or appointed agent for interpretation, clarification, and resolution (or correction).

3.3 Performance requirements and product. characteristics. The recorder shall meet the following performance requirements and product characteristics:

3.3.1 The recorder shall operate from the following power supplies:

3.3.1.1 AC, 115 volts plus or minus 3 percent, 400 cps plus or minus 2 percent, single phase.

3.3.1.2 DC, 24 volts plus or minus 10 percent.

3.3.2 The oscillograph shall conform to the requirements of MIL-O-23560/4

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:59Z
Check the source to verify that this is the current version before use.

3.3.3 The recording component panel shall conform to the requirements of MIL-P-

3.3.4 The recording component panel shall be wired as specified in BUWEPS Drawing 2436239.

3.35 When tested as specified in 4.4.4, all oscillograph channels shall perform as specified therein.

3.3.6 The operating life of the recorder shall be predicated on the life requirements specified in NIIL-O-23560/ and MIL-P-2381 O for their respective components.

3.4 Environmental requiremements

3.4.1 Vibration. The recorder, less pack and packaging and mounted as specified in 4.5.1, shall be capable of withstanding vertical vibrations for a period of 3 hours at a frequency of 60 cycles per second and a double amplitude (peak-to-peak) of 0.016 plus or minus 0.002 inch, and thereafter shall show no damage and shall meet the performance requirements and product characteristics of this specification.

3.4.2 Temperature and humidity. The recorder, less pack and packaging, shall be capable of withstanding a temperature of plus 160 degrees F plus or minus 5 degrees F, 90 to 95 percent relative humidity, for a period fof 24 hours, in accordance with the test procedures specified in 4.5.2, and thereafter shall show no corrosion or damage and shall meet the performance requirements and product characteristics of this specification.

3.4.3 Storage life. When level A preservation, packaging, and packing, as defined in 6.2.1 is specified, the recroder shall show no damage and shall meet all the performance and product requirements of this specification after being stored for a period of five years, in the packaging and packing specified, under temperature and humidity conditions as follows:

3.4.3.1 Temperature: Minus 65 degrees F to plus 16 0 degrees F
(Minus 54 degrees C to plus 71 degrees C)

3.4. 3.2 Humidity: 90 to 95 percent relative

3.5 Cleanup. Prior to and after final assembly, all parts, components, and the assembly shall be thoroughly cleaned of loose, spattered, or excess solder, metal chips, and other foreign matter, Burrs and sharp edges as well as rosin flash shall be removed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:59Z
Check the source to verify that this is the current version before use.

3.6 Workmanship. The equipment, including ail parts and accessories, shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention shall be paid to neatness and thoroughness of soldering, wiring, and marking of parts and assemblies, impregnation of coils, plating, painting, riveting, machine screw assemblage, welding, brazing, and freedom of all parts from all burrs and sharp edges.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Lot size. As applied to Government inspection of units of production, the term “lot” shall mean “inspection lot”, that is, a collection of units of production submitted by a supplier for Government inspection. Unless otherwise specified, the number of units of product in inspection lots will be determined by the Government inspector and may differ from the quantity designated in the contract or order in a lot for production, shipment, or other purpose.

4.1.2 Periodic production samples

Step 1. Upon the initiation of production the Government inspector shall randomly select one unit from each group of five units for submission to a Bureau of Naval Weapons activity.

Step 2. Upon satisfactory compliance of each unit from three consecutively produced groups, select a sample in accordance with MIL-STD-105, inspection level L-4 (acceptance number zero), based on the remainder of the contract.

Step 3. when a defective unit is found while the L level of inspection is in effect, shift to step 1 and proceed as indicated.

4.2 Classification of tests. The inspection and testing of the recorder shall be classified as follows:

4.2.1 Acceptance tests. Acceptance tests are to be accomplished on each recorder being submitted for Government approval prior to the commencement of production, These tests, detailed in 4.4, shall be performed by the manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:59Z
Check the source to verify that this is the current version before use.

4.2.2 Periodic production tests. Periodic production tests are those which are accomplished on samples selected as specified in 4.1.2 which are representative of the production of the recorder after the award of the contract to determine that the lot and production meet the requirements of this specification. These are detailed in 4.5. Acceptance shall be based on no defects in a sample.

4.3 Test equipment. The following items of test equipment are required to perform the acceptance tests set forth in this specification:

4.3.1 AC power supply, 115 volts plus or minus 3 percent, 400 cps plus or minus 2 percent, single phase, at 2 amperes.

4.3.2 DC power supply, 24 volts plus or minus 10 percent at 5 amperes.

4.3.3 Resistor, 1.2 megohms plus or minus 5 percent, 1/2 watt,

4.3.4 Potentiometer, 50, 000 ohms plus or minus 10 percent, 1 watt.

4.3.5 Resistor, 22,000 ohms plus or minus 5 percent, 1/2 watt.

4.3.6 Transformer, primary 115 volts, 400 cps, secondary (a) 6 volts (CT), (b) 10 volts.

4.3.7 Resistor, 150 phms plus or minus 5 percent, 1 watt.

4.3.8 AC - DC voltmeter, TS375.

4.3.9 Oscilloscope, OS-8/U

4.4 Acceptance tests

4.4.1 The contractor shall conduct acceptance tests as specified in 4.2.1 to assure that the recorder is in compliance with the requirements of 3.2 and 3.3.

4.4.2 Test conditions. Unless otherwise specified the recorder shall be subjected to acceptance tests under the following conditions:

4.4.2.1 Temperature: 65 degrees F to 95 degrees F
(18 degrees C. to 35 degrees C)

4.4.2.2 Altitude: Normal ground

4.4.2.3 Vibration: None

4.4.2.4 Humidity: Room ambient to 95 percent relative maximum

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:59Z
Check the source to verify that this is the current version before use.

4.4.3 Test and inspection equipment and facilities, The manufacturer shall furnish and maintain all necessary test equipment, facilities, and personnel for performing all acceptance tests. The test equipment shall be adequate in quantity, and, when definite requirements are not specified, they shall be of sufficient accuracy and quality to permit performance of the required acceptance tests.

4.4.4 Test procedure

4.4.4.1 All pin, terminal, plug, and connector numbers are given on BUWEPS Drawing 2436236.

4.4.4.2 Insure that the recording oscillograph is firmly plugged into recording component panel receptacle S71 and that oscillograph damping resistors are installed. Remove the oscillograph film magazine and mount the viewing screen in place to show channel traces.

4.4.4.3 Connect 24 volts dc (4.3.2) across terminals AA and BB, (positive to BB), and insure that the oscillograph lamp is lighted. This 24 volt connection shall be kept throughout the remainder of section 4.4.4.

4.4.4.4 Adjust and align, if necessary, all galvanometers traces so they appear at the location shown by the engraved lines on the viewing screen.

4.4.4.5 Connect the 24 volt dc supply (4.3.2) through the 1.2 megohm resistor (4. 3,3) to terminals A and B of P70 (A being positive). The channel 2 spot on the oscillograph viewing screen shall deflect 1.1 inches plus or minus 25 percent toward the channel 14 spot.

4.4.4.6 Disconnect the leads connected in 4.4.4.5 and apply a 400 cps, ac signal of 10 volts (4.3.6) across terminals C and D of P70. The oscillograph channel 3 spot shall describe a line across the viewing screen 0.16 inch long plus or minus 25 percent.

4.4.4.7 connect terminal E of P70 to terminal D. The line traced by the channel 3 spot shall deflect 0.16 inch plus or minus 25 percent toward the channel 14 spot.

4.4.4.8 Disconnect the ac lead to terminal D, leaving all other connections as in 4.4.4.7. Channel 3 shall revert to a spot, but shall remain displaced toward channel 14 as given in 4.4.4.7.

4.4.4.9 Disconnect the leads connected in 4.4.4.6 and 4.4.4.7.

4.4.4.10 Connect the 24 volt dc supply through 22,000 ohm resistor (4.3.5) to terminals F and BB of P70 (BB being positive). The channel 4 spot, shall deflect 0.5 inch plus or minus 25 percent toward the channel 1 spot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:59Z
Check the source to verify that this is the current version before use.

4.4.4.11 Disconnect the dc leads connected in 4.4.4.10, and connect the 50,000' ohm potentiometer (4.3.4) across the 3 volt, 400 cps, ac supply (4.3.6). Connect either potentiometer end and the potentiometer arm across terminals H and J of P70. Adjust the potentiometer arm to give an ac signal of 2.0 volts across terminals H and J of P70. The channel 5 spot shall describe a line across the viewing screen 0.5 inch long plus or minus 25 percent.

4.4.4.12 With connections made as given in 4.4.4.11 apply a 115 volt, 400 cps signal (4.3.1) across terminals CC and DD of P70, with terminal CC being in phase with terminal J. The line described by the channel 5 spot in 4.4.4.11 shall revert to a spot of the original, no signal size plus or minus 0.3 inch. With the application of the 115 volt ac signal, the channel 12 spot will describe a line across the viewing screen approximately 0.5 inch long. This is proper and the circuit will be checked in paragraphs 4.4.4.21 and 4.4.4.22.

4.4.4.13 With conditions as given in 4.4.4.12, reverse the polarity of the input across terminals H and J without changing terminals CC and DD. The channel 5 spot shall describe a line across the viewing screen 1.0 inch long plus or minus 25 percent.

4.4.4.14 Disconnect the ac inputs of 4.4.4.13 and 4.4.4.12 and connect the 24 volt dc supply through the 22,000 ohm resistor to terminals K and BB of P70 (BB to be positive). The channel 6 spot shall deflect 0.6 inch plus or minus 25 percent toward the channel 1 spot.

4.4.4.15 Disconnect the dc leads connected in 4.4.4.14 and connect the 24 volt dc supply directly across terminals L and BB of P70 (BB being positive). The channel 7 spot shall deflect 0.4 inch plus or minus 25 percent toward the channel 1 spot. Remove the lead from terminal L and move it to terminal HH of P70, The channel 7 spot shall deflect 0.22 inch plus or minus 25 percent from its unreflected position toward the channel 1 spot.

4.4.4.16 Disconnect the dc leads connected in 4.4.4.15 and connect the 10 volt, 400 cps, ac supply to terminals M and N of P70. The channel 8 spot shall describe a line across the viewing screen which shall be capable of adjustment between 0.2 and 0.5 inch long by means of the potentiometer R74.

4.4.4.17 Disconnect the ac leads connected in 4.4.4.16 and connect the 24 volt dc supply through the 1.2 megohm resistor to terminals P and R of P70 (R being positive. The channel 9 spot shall deflect 1.1 inch plus or minus 25 percent toward the channel 1 spot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:59Z
Check the source to verify that this is the current version before use.

4.4.4.18 Disconnect the dc leads connected in 4.4.4.17 and connect the 24 volt dc supply through the 22,000 ohm resistor to terminals S and BB of P70 (BB being positive). The channel 10 spot shall deflect 0.6 inch plus or minus 25 percent toward the channel 1 spot.

4.4.4.19 Transfer the negative dc input lead of 4.4.4.18 from terminal S to terminal T of P70. Oscillograph channel 11 shall deflect 0.6 inch plus or minus 25 percent toward channel 1.

4.4.4.20 Disconnect the dc leads connected in 4.4.4.19 and connect the 50,000 ohm potentiometer across the 3 volt, 400 cps, ac supply. Connect either potentiometer, end and the potentiometer arm across terminals U and V of P70. Adjust the potentiometer arm to give an ac signal of 2.0 volts across terminals U and V of P70. The channel 12 spot shall describe a line across the viewing screen 0.5 inch long plus or minus 25 percent.

4. 4.4.21 With connections as given in 4.4.4.20, apply 115 volts 400 cps, ac across terminals CC and DD of P70, with CC being in phase with terminal V. Oscillograph channel 12 shall revert to a spot of the original, no-signal size plus or minus 0.3 inch. With the application of the 115 volt ac signal, the channel 5 spot shall describe a line across the viewing screen approximately 0.5 inch long, This is proper and the circuit was checked in paragraphs 4.4.4.12 and 4.4. 4.13.

4.4.4.22 Without disturbing the 115 volt input of 4.4.4.21, reverse the polarity of the ac input to terminals U and V. Channel 12 shall describe a line across the viewing screen 1.0 inch long plus or minus 25 percent.

4.4.4.23 Disconnect the ac inputs of 4.4.4.22 and connect the 24 volt dc supply through the 22,000 ohm resistor to terminals W and X of P70 (terminal X being positive). The channel 13 spot shall deflect 0.7 inch plus or minus 25 percent toward the channel 1 spot.

4.4.4.24 Disconnect the dc input of 4.4.4.23 and connect a 150 ohm resistor (4.3.7) across terminals EE and FF of P70. Connect 115 volts 400 cps, ac across terminals CC and DD of P70 and measure the dc voltage developed across terminals EE and FF. It shall be 4.7 plus or minus 0.5 volts,

4.4.4.25 Measure the peak-to-peak ac ripple developed across terminals DD and FF in 4.4.4.24. It shall not exceed two percent of the measured dc voltage.

4.4.4.26 Connect the negative side of the 24 vdc power supply to pin JJ of P70. The channel 1 spot shall deflect 0.5 inch plus or minus 0.125 inch toward the channel 14 spot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:59Z
Check the source to verify that this is the current version before use.

4.4.4.27 Insert an open circuited phone plug or equivalent into phone jack J1. The oscillograph lamp shall be extinguished.

4.5 Preproduction and periodic production tests

4.5.1 Vibration. The recorder, less pack and packaging, shall be mounted rigidly, secured with the mounting base horizontal to a vibration device, utilizing the four mounting holes in the base. The recorder shall be vibrated vertically for a period of 3 hours at a frequency of 60 cycles per second and a double amplitude (peak-to-peak) of 0.016 plus or minus 0.002 inch. At the conclusion of this test the recorder shall meet the performance requirements and product characteristics of this specification.

4.5.2 Temperature and humidity. The recorder, less pack and packaging, shall be placed in a test chamber and subjected to a temperature of plus 160 degrees F, plus or minus 5 degrees F, 90 to 95 percent relative humidity, for a period of 24 hours. Condensation from the test chamber shall not be allowed to drip onto the recorder. At the conclusion of the test and after returning to room temperature the recorder shall meet the performance requirements and product characteristics of this specification. Prior to checkout, wiping or airhose drying may be performed, but no drying by heating or baking shall be done.

4.5.3 Light tightness. The film magazine of the oscillograph portion of the recorder shall be tested as specified in MIL-O-23560/4 and shall conform to the exposure requirements specified therein.

4.5.4 Oscillograph characteristics. The oscillograph portion of the recorder shall be tested for damping, film speed, frequency response, and balance as specified in section 4 of MIL-O-23560/4 and shall conform to the requirements listed therein.

4.5.5 Operating life. The recorder shall meet the performance requirements specified in MIL-O-23560/4 for the oscillograph and MIL-P-23810, for the recording component panel.

4.6 Failure of the recorder to meet any of the requirements and tests of this specification shall be cause for rejection.

4.7 Preservation, packing, and packaging. The inspector shall ascertain that the preservation, packing, andpackaging of the recorder conform to section 5 of this specification.

5. PREPARATION FOR. DELIVERY

5.1 Preservation and packaging (See 6.2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:59Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. Recorders shall be individually protected and unit packaged in accordance with method IIIb of Specification MIL-P-116, without the use of contact preservatives. All projections and sharp corners of the recorder shall be cushioned and the recorder shall be blocked within the primary container to prevent movement,

5.1.2 Level C. Recorders shall be afforded preservation and packaging in accordance with the manufacturer's replacement-parts practice.

5.2 Packing (See 6.2)

5.2.1 Level A. Four recorders packaged as specified shall be packed in nailed wood, wirebound wood (for class 3 use), or wood cleated plywood (overseas type) boxes conforming to Specifications PPP-B-621, PPP-B-585, and PPP-B- 601, respectively. Plywood shall be type I or II, class 2, conforming to Specification NN-P-515. Shipping containers shall have case liners conforming to Specification MIL-L-1 0547 and appendix thereto. Box closures shall be as specified in the appendix of the applicable box specification,

5.2.2 Level B. Four recorders packaged as specified shall be packed in nailed wood, corrugated or solid fiberboard, wirebound wood (for class 1 use), or wood cleated plywood (domestic type) boxes conforming to Specifications PPP-B-621, PPP-B-636, PPP-B-585, and PPP-B-601, specification or appendix thereto. Fiberboard boxes shall conform to the special requirements of the applicable box specification.

5.2.3 Level C. Recorders packaged as specified shall be packed to afford protection against damage during direct shipment from the supply source to the first receiving activity for immediate use. Containers shall comply with Consolidated Freight Classification Rules or other common carrier regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Normal marking. In addition to any special marking required by the contract or order, unit packages and exterior shipping containers shall be marked in accordance with Standard MIL-STD-129.

5.3.2 Serial numbers. Unit packages and shipping containers shall be marked with the serial numbers of the units contained within.

6. NOTES

6.1 Intended use. The recorder is intended for use in Torpedo Exercise Section Mk 64 Mod 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:59Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the specific title, number, and date of this specification and exceptions to this specification, applicable drawings and other documents, and selection of applicable levels of preservation and packaging, and packing.

6.2.1 Criteria for use of proper level of preservation, packaging, and packing shall be as follows:

For Level A This level shall be used for those items which are to be shipped to indeterminate destinations or stored under indeterminate conditions for redistribution anywhere.

For Level B This level shall be used only when it is definitely known that the item will be held in covered storage, either in domestic or overseas locations, for a period of six months or less.

For Level C This level shall be used only when it is definitely known that the packaged item is to be shipped to domestic installations for immediate use at the first receiving activity.

NOTICE

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government' may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:59Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:59Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:59Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:59Z
Check the source to verify that this is the current version before use.