INCH-POUND

MIL-C-70683A(AR)
22 August 1991
SUPERSEDING
MIL-C-70683 (AR)
25 January 1991

MILITARY SPECIFICATION

CHARGE, DEMOLITION: 40LB, CRATERING PARTS FOR AND LOADING, ASSEMBLING AND PACKING

This specification is approved for use by the U.S. Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers quality assurance provisions and preparation for delivery of the parts, loading, assembling and packing of Charge, Demolition: 40lb, Cratering.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-C-2440 - Container, Metal, For Propelling Charge.
MIL-C-14003 - Cap, Blasting, Special.
MIL-C-17124 - Cord, Detonating.
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document, should be addressed to: Commander U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 1375
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-129 - Marking for Shipment and Storage.

(Unless otherwise indicated, copies of federal and military specification, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Ave, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

US ARMY ARMEMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT AND PACKAGING DRAWINGS

9395714 - Charge, Demolition: 40lb, Cratering.
12624777 - Packing and Marking for Container, Metal, Ammo, M18A2, for Charge, Demolition: 40lb, Cratering.

PUBLICATIONS

HEADQUARTERS, DEPARTMENT OF THE ARMY

FM 5-25 - Explosives and Demolitions, Field Manual for
TM 9-1375-213-12 - Demolition Materials, Technical Manual for (Operator's and Organizational Maintenance Manual)

(Copies of drawings and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D 1556 - Density of Soil in Place by the Sand-Cone Method (DoD adopted)

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1137.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specified exemption has obtained.

3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Assemblies. The assemblies shall comply with all requirements specified on Drawing (dwg.) 9395714 and with all requirements specified in applicable specification.

3.3 Moisture content. The moisture content of the booster pellet shall not exceed 0.20 percent.

3.4 Waterproofness. The loaded assembly shall not leak when submerged 1/2 to 3 inches in water and subjected to a vacuum equivalent to 8 $\pm$ 1 inches of mercury for 15 seconds, minimum.

3.5 Functioning. The loaded assembly shall completely function when detonation initiated by blasting cap or detonating cord.

3.6 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.7 Workmanship. All parts and assemblies shall be fabricated and assembled in thorough, workmanlike manner. They shall be free of burrs, chips, weld spatter, sharp edges, chipped edges, gouges, cracks, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. All packing shall be dry.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIOS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of the manufacturing operations is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection.

b. Quality conformance inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated below and Table I:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

Part Description	Drawing	Quantity
Cover, Bottom	9395834	5
Body	9395835	5
Body Assembly	9395836	5
Pellet, Booster	9295839	5
Booster Assembly	9395842	5
Clip	9395848	5
Clip Assembly	9395849	5
Cover, Top	9395851	5
Cover, Top Assembly	9395852	10
Charge, Demolition: 40lb., Cratering, Loading Assembly	9395850	5
Charge, Demolition: 40lb., Cratering, (Prior to Installation of Cover, Top Assembly)	9395714	5
Charge, Demolition: 40lb., Cratering	9395714	20

4.3.2 Inspection to be performed. See MIL-A-48078 and Table I specified herein. If any items fail to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3.3 Rejection. See MIL-A-48078. If any items fail to comply with any of the applicable requirements, the first article sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 3	DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY: ---

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Cover, Bottom (Dwg. 9395834)			
	Examination for defects	5, 0-1	3.1	4.4.2.1
	Body (Dwg. 9395835)			
	Examination for defects	5, 0-1	3.1	4.4.2.2
	Body Assembly (Dwg. 9395836)			
	Examination for defects	5, 0-1	3.2	4.4.2.3
	Leak test	5, 0-1	3.2	4.5.4
	Pellet, Booster (Dwg. 9395839)			
	Examination for defects	5, 0-1	3.1	4.4.2.4
	Moisture content	5, 0-1	3.3	4.5.1

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 2 OF 3	DRAWING NUMBER: See below NEXT HIGHER ASSEMBLY: ---
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Booster Assembly (Dwg. 9395842) Examination for defects	5, 0-1	3.2	4.4.2.6
	Clip (Dwg. 9395848) Examination for defects	5,0-1	3.1	4.4.2.7
	Clip, Assembly (Dwg. 9395849) Examination for defects	5, 0-1	3.2	4.4.2.8
	Cover, Top (Dwg. 9395851) Examination for defects	5, 0-1	3.2	4.4.2.9
	Cover, Top Assembly (Dwg. 9395852) Examination for defects Strength of handle	10, 0-1 10, 0-1	3.2 3.2	4.4.2.10 4.5.3

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 3 OF 3	DRAWING NUMBER: See below NEXT HIGHER ASSEMBLY: ---

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Charge, Demolition: 40lb., Cratering Loading Assembly (Dwg. 9395850)			
	Examination for defects	5, 0-1	3.2	4.4.2.11
	X-Ray	5.,0-1	3.2	4.5.8
	Charge, Demolition: 40lb., Cratering (Prior to Installation of Cover, Top Assembly) (Dwg. 9395714)			
	Examination for defects	5, 0-1	3.2	4.4.2.12
	Charge, Demolition: 40lb., Cratering (Dwg. 9395714)			
	Examination for defects	20, 0-1	3.2	4.4.2.13
	Waterproofness	20, 0-1	3.4	4.5.2
	Functioning with blasting cap	10, 0-1	3.5	4.5.5
	Functioning with detonating cord	10, 0-1	3.5	4.5.6

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of cratering charges shall contain:

a. Metal parts from one lot interfix from one vendor.

b. Composition A-5 from not more than one lot or, if made in-house, from not more than one batch or homogeneous blend of batches.

c. Composition H-6 explosive charge mixture ingredients from not more than two lots from one manufacturer, of any ingredient.

4.4.2 Examination and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels stated in the Classification of Characteristics paragraphs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

TABLE II Attributes sampling inspection.

Lot Size	Inspection Level					
	I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	12	4
91 to 150	*	125	32	13	12	5
151 to 280	*	125	32	30	14	6
281 to 500	*	125	32	30	17	7
501 to 1200		125	74	35	20	9
1201 to 3200	1250	125	74	43	24	10
3201 to 10000	1250	125	87	50	30	10
10001 to 35000	1250	296	109	61	36	10
35001 to 150000	1250	296	124	74	40	10
150001 to 500000	1250	346	156	91	40	10
500001 and over	1250	431	187	102	40	10

Numbers under inspection levels indicate sample size; asterisks indicates one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

b. Alternative quality conformance provisions. Alternative quality conformance procedures, methods, or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.6). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality assurance provision(s) herein. In cases of dispute as to whether the contractor's proposed alternative(s) provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program or detailed inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70683A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Cover, Bottom		9395834
			NEXT HIGHER ASSEMBLY 9395836

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Body,	1 OF 1	9395835
			NEXT HIGHER ASSEMBLY 9395836

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Inside diameter	Level III	3.2	Gage
102	Evidence of full length weld	Level III	3.2	Visual
Minor				
201	Poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Body Assembly	1 OF 1	9395836
			NEXT HIGHER ASSEMBLY 9395714

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Leak test	Level III	3.2	4.5.4
102	Max. O.D., crimped end	Level III	3.2	Gage
103	Height	Level III	3.2	Gage
104	Evidence of 360° weld	Level III	3.2	Visual
Minor				
201	Poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Pellet, Booster		9395839
			NEXT HIGHER ASSEMBLY 9395842

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Diameter	Level III	3.2	Gage
102	Thickness	Level III	3.2	Gage
103	Weight	Level III	3.2	Scale
104	Density	Level III	3.2 1/	Calculations
105	Moisture Content	Level III	3.3	4.5.1
Minor				
201	Poor workmanship	Level V	3.7	Visual

NOTES:
1/ Required only if sample fails weight criteria.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70683A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 9395842
4.4.2.5	Booster Assembly, prior to swaging		NEXT HIGHER ASSEMBLY ---

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Components missing	Level III	3.2	Visual
Minor				
201	Poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Booster Assembly		9395842
			NEXT HIGHER ASSEMBLY 9395714

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Diameter, max.	Level III	3.2	Gage
102	Axial movement of booster pellet, and booster disc	Level III	3.2	Manual/Visual
Minor				
201	Poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.7	Clip		9395848
			NEXT HIGHER ASSEMBLY 9395849

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Radius of tunnel (2 places)	Level III	3.2	Gage
102	Total width	Level III	3.2	Gage
103	Position of tunnels (2 places)	Level III	3.2	Gage
Minor				
201	Poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.8	Clip, Assembly		9395849
			NEXT HIGHER ASSEMBLY 9395852

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Post securely fastened	Level III	3.2	Manual/Visual
Minor 201	Poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.9	Cover, Top		9395851
			NEXT HIGHER ASSEMBLY 9395852

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Presence sealing compound	Level III	3.2	Visual
Minor				
201	Poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70683A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Cover, Top Assembly		9395852
			NEXT HIGHER ASSEMBLY 9395714

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Strength of handle	25, 0-1	3.2	4.5.3
102	True position of clip assembly (2 places)	Level III	3.2	Gage
Minor				
201	Presence/proper orientation of handle, handle brackets and top cover	Level IV	3.2	Visual
202	Poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Charge, Demolition: 40lb., Cratering, Loading Assembly	1 OF 1	9395850
			NEXT HIGHER ASSEMBLY ---

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Weight of explosive	Level III	3.2	Scale
102	Depth of booster cavity	Level III	3.2	Gage
103	Diameter of booster cavity	Level III	3.2	Gage
104	True position of booster cavity	Level III	3.2	Gage
105	X-ray	25, 0-1	3.2	4.5.8
Minor				
201	Poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70683A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.12	Charge, Demolition: 40lb., Cratering (Prior to Installation of Cover, Top Assembly)		9395850
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Radial movement of components	Level III	3.2	Manual/Visual
102	Components missing	Level III	3.2	Visual
Minor				
201	Poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70683A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.13	Charge, Demolition: 40lb., Cratering		9395714
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Waterproofness	100%	3.4	4.5.2
102	Functioning with blasting cap	5, 0-1	3.5	4.5.5
103	Functioning with detonating cord	5, 0-1	3.5	4.5.6
104	Max. O.D.	Level III	3.2	Gage
105	Max. Height	Level III	3.2	Gage
Minor				
201	Correct marking	Level IV	3.2	Visual
203	Poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.14	Container, Metal, Ammo, M18A2, For Charge, Demo: 40lb., Cratering, ~~prior to sealing~~	1 OF 1	12624777
			NEXT HIGHER ASSEMBLY: ---

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor 201	Contents incorrect or missing	Level V	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70683A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.15	Container, Metal, Ammo, M18A2, For Charge, Demo: 40lb., Cratering	1 OF 1	12624777
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Presence of metallic seal	Level IV	3.2	Visual
102	Container damaged	Level IV	3.2	Visual
103	Contents of container exposed	Level IV	3.2	Visual
104	Pressure retention test	Level IV	3.2	4.5.7
Minor				
201	Contents loose	Level V	3.2	Manual/Visual
202	Container inadequately or improperly sealed	Level V	3.2	Visual
203	Marking missing, incorrect or illegible	Level V	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in Tables I and Classification of Defects and Tests herein.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column starting with 4.4.2.1. The contractor shall submit, for approval, inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Moisture content. A sample of booster pellets shall be selected from each (8) hours of production and analyzed, using an applicable standard analytical procedure. Should a sample contain excessive moisture, two (2) additional samples shall be selected from different locations of the production quantity. Failure of any of the two second sample in meeting the requirement shall reject the production represented by the sample.

4.5.2 Waterproofness. This test shall be performed 100 percent. The loaded assembly shall be submerged in water within the limits specified in 3.4, the required vacuum applied and observation for leakage made. Leakage is defined as the presence of a stream or streams of bubbles of any frequency. Any assembly exhibiting leakage shall be classed defective and removed from the lot.

4.5.3 Strength of handle. The cover top assembly shall be assembled to the applicable test equipment and a 100 lb. static load applied to the handle (See drawing 9395852, Note 3). Observation shall be made for failure of a weld or handle. either defect shall class a unit defective.

4.5.4 Leak test. Body assembly (Dwg. 9395836) shall be submerged in water, pressurized and observation for leakage made. Leakage is defined as the presence during test of a stream, or streams of bubbles of any frequency.

4.5.5 Functioning with blasting cap. A sample of five (5) charges from each lot shall be tested. All charges shall be ground emplaced and stemmed IAW FM 5-25, bore holes at a 5 ft. depth. All charges are to be primed and initiated IAW TM 9-1375-213-12, using blasting caps complying with Type II of MIL-C-14003. Testing shall be performed in virgin or compacted clay-type soil. For informational purposes, soil compaction shall be determined as specified in ASTM D 1556 or any other approved method. Observation shall be made for complete detonation of the charge. Any charge failing to so function shall be classed defective. Failure on one (1) or more units of sample to function as required shall reject the lot. For information purposes, the profile or the crater shall be determined and included with the test results.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

4.5.6 Functioning with detonating cord. Follow procedures detailed in 4.5.5 except, instead of a blasting cap, detonating cord complying with Type I, Class E of MIL-C-17124 shall be used for charge initiation. Pass the detonating cord through the shorter tunnel. A "uli" know (TM 9-1375-213-12) shall be made 24 inches from one end of the cord and drawn snugly against the tunnel, the knot positioned above the charge top. A blasting cap shall be attached to the other end of the cord and the cord shall be detonated.

4.5.7 Pressure retention test. The sealed M18A2 (Dwg. 12624777) shall be placed in an appropriate vessel, pressurized as required and observation for pressure retention made.

4.5.8 X-ray. Loaded assemblies (Dwg. 9395850) shall be x-rayed in each of two planes. Failure of one (1) or more units to comply with the drawing requirement shall reject the lot.

5. PACKAGING

5.1 Preservation and packing.

5.1.1 Level A. Each cratering charge shall be packed, sealed and tested in accordance with Dwg. 12624777 and MIL-C-2440.

5.1.2 Level B. Same as 5.1.1.

5.1.3 Level C. Same as 5.1.1.

5.1 Marking.

5.2.1 Level A. Each container shall be marked in accordance with Dwg. 12624777 and MIL-STD-129.

5.2.2 Level B. Same as 5.2.1.

5.2.3 Level C. Same as 5.2.1.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Acquisition requirements. Acquisition documents should specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

a. Title, number, and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1, 2.1.2 and 2.2).

6.2 Data cards. (See MIL-A-48078). Distribution of data cards shall include the following: Commander, US ARDEC, ATTN: AMSMC-QAT-M (D), Picatinny Arsenal, New Jersey 07806.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to: Commander, US Army ARDEC, ATTN: AMSMC-QAT-I (D), Picatinny Arsenal, New Jersey 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.4 Drawings. Drawings liested in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as US Army Armament Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.5 Subject term (key word) listing.

M18A2 Metal Ammo Container
Moisture Content
Waterproofness
Leak Test
Strength of Handle
Blasting Cap
Detonating Cord

6.6 Submission of alternative quality conformance provisions. Unless otherwise specified in the contract, proposed alternative quality conformance provisions will be submitted by the contractor for evaluation by the technical activity responsible for the preparation of this specification.

6.7 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A477)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-C-70683A (AR)	2. DOCUMENT DATE (YYMMDD) 22 August 1991

3. DOCUMENT TITLE

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (*Last, First, Middle Initial*)	b. ORGANIZATION	
c. ADDRESS (*Include Zip Code*)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (*If applicable*)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME Commander US Army ARDEC	b. TELEPHONE (*Include Area Code*) (1) Commercial: (201) 724-6675 (2) AUTOVON: 880-6675
c. ADDRESS (*Include Zip Code*) ATTN: SMCAR-BAC-S Picatinny Arsenal, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.