MILITARY SPECIFICATION

FUZE, MT, SQ, M582A1
LOADING, ASSEMBLING AND PACKING

This specification is approved for use within the US Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the loading, assembling and packing for the Fuze, Mechanical Time and Superquick, M582A1.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following documents of the issue in effect on the date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for
MIL-P-60412 - Packaging, Packing and Marking for Shipment of Artillery Type and Rocket Fuzes, General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament Research, Development and Engineering Center, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 1390
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:38Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

US Army Armament Research and Development Center (ARDC)

9352383 - Fuze, Mechanical Time and Superquick, M582A1

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

3.2 Parts and assemblies. The parts and assemblies shall comply with all requirements specified on the drawings and with all requirements specified in applicable specifications.

3.3 Workmanship. All parts shall be fabricated and finished in a thorough, workmanlike manner and all manufacturing, processing and assembly operations shall be correctly performed. The parts shall be clean and free of burrs, sharp edges, unblended radii, surface defects, cracks, chips, dirt, grease and oil (except where specifically required), rust and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat, legible and sharply defined.

3.4 Ballistic performance.

3.4.1 Premature bursts (see 6.4). There shall be no premature bursts in the gun bore, in flight or during handling.

3.4.2 Functioning (see 6.5).

3.4.2.1 Target impact functioning. The fuze, when set PD shall cause the projectile to function upon impact of the PD element when fired in the 155MM, M1 Tube, Charge 1 at a 6" plywood target located 820-5 feet from the muzzle of the weapon.

3.4.2.2 Airburst functioning. The fuze, when set for airburst functioning shall cause the projectile to function at or about its intended functioning zone along the projectile trajectory.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:38Z
Check the source to verify that this is the current version before use.

3.4.3 Target non-function. The fuze when set PD shall not cause the projectile to function upon impact of the PD element when fired in the 105MM, M103 Tube, Charge 7 at a 6" plywood target located 150-5 feet from the muzzle of the weapon.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detailed specification.

4.2 Classification of inspections. The following types of inspections shall be conducted on this item:

a. Quality conformance inspection

4.3 Quality conformance inspection. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot of complete fuze assemblies shall contain:

a. Metal parts of not more than one interfix from one manufacturer.

b. Booster pellets of not more than one interfix from one manufacturer.

4.3.2 Examination. See MIL-A-48078

a. Sampling Plans. Unless otherwise specified in the Classification of Defects and Tests tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:38Z
Check the source to verify that this is the currentversion before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70531 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8595509
4.3.2.1	Cup, Booster				NEXT HIGHER ASSEMBLY 9352383
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread		0.40%	3.2	Gage
102	Minor diameter of thread		0.40%	3.2	Gage
103	Cup cracked or otherwise damaged		0.40%	3.2	Visual
104	Inside depth, max.		0.40%	3.2	Gage
105	Thickness of cup at bottom		0.40%	3.2	Gage
106	Outside diameter, max.		0.65%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-0-23T03:38Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70531 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8595510
4.3.2.2	Pellet, Booster				NEXT HIGHER ASSEMBLY 9352383
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pellet cracked, chipped or broken		0.40%	3.2	Visual
102	Thickness		0.40%	3.2	Gage
103	Weight		0.40%	3.2	Gage
104	Outside diameter		0.40%	3.2	Gage
105	Radii		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 20240-23103:382
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70531 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.3.2.3	Fuze, Mechanical Time and Superquick, M582A1, Less Booster	1 OF 1	9352382
			NEXT HIGHER ASSEMBLY 9352383

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Fuze damaged		0.40%	3.2	Visual
102	Output lead functioned		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual
202	Marking Improper		0.65%	3.2	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70531 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.3.2.4	Fuze, Mechanical Time and Superquick, M582A1, prior to assembling Cup, Booster	1 OF 1	9352383
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Explosive material on booster cup threads		100%	3.2	Visual
Major					
101	Booster pellet missing		0.40%	3.2	Visual
102	Foreign matter in booster cup		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:38Z
Check the source to verify that this is the current version before use.

AMSMC Form 1570, 1 Feb 83 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70531 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.3.2.5	Fuze, Mechanical Time and Superquick, M582A1,	1 OF 1	9352383
			NEXT HIGHER ASSEMBLY: Final Assembly

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length below Ogive, Max.		0.40%	3.2	Gage
102	Booster cup cracked or otherwise defective		0.40%	3.2	Visual
103	Adhesive missing or excessive		0.40%	3.2	Visual
104	Fuze not set in ship position		0.40%	3.2	Visual
105	Booster cup fails disassembly torque		0.40%	3.2	Gage
106	Booster pellet loose (moves when shaken)		0.40%	3.2	Visual/Manual
107	Fuze threads damaged		0.65%	3.2	Visual
108	Fuze ogive damaged		0.65%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual
202	Marking missing, illegible or improper		1.0%	3.3	Visual

NOTES:

DRSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70531 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.3.2.6	Fuze, Mechanical Time and Superquick, M582A1, Destructive Tests	1 OF 1	9352383
			NEXT HIGHER ASSEMBLY: Final Assembly

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Target non-function test	10		3.4.3	4.4.1.3
2	Premature burst	30 (a)		3.4.1	4.4.1
Major					
101	Target function	10		3.4.2.1	4.4.1.1
102	Airburst function	10		3.4.2.2	4.4.1.2

NOTES:

(a) Samples for this test are the fuzes subjected to the target non-function, target function and airburst function tests.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:38Z
Check the source to verify that this is the current version before use.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

4.3.3 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed herin is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.3.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078 and section 6 herein.

4.4 Methods of inspection.

4.4.1 Ballistic performance test.

4.4.1.1 Premature burst. Any premature burst during the entire ballistic test shall cause the lot to be rejected.

4.4.1.2 Target functioning. The fuze shall be assembled to a 105MM, M107 projectile and fired at an adequately supported target as specified in 3.4.2.1. When fired, the fuze, projectile and charge shall be at a temperature of 70° ± 10°F. This may require temperature conditioning in accordance with 4.4.2. Observation of impact functioning is required and shall be noted on the ballistic records. If more than one fuze fails to function the lot shall be rejected.

4.4.1.3 Airburst functioning. The fuze shall be assembled to a 105MM, M1 projectile and set for 25.0 seconds. The fuze projectile shall be fired from a 105MM weapon with an M103 tube at Charge 7. When fired, the fuze, projectile and charge shall be at a temperature of 70° ± 10°F. This may require temperature conditioning in accordance with 4.4.2. All defects shall be recorded. A system of electric clocks or stopwatches shall be employed to measure the time to burst. These measurements shall be recorded to the nearest 0.01 seconds. If a round fails to function in flight observaiton shall be made to determine if the round functions on impact. If more than two (2) fuzes fail to function the lot shall be rejected.

4.4.1.4 Target non-function test. The fuze shall be assembled to a 105MM, M1 projectile and fired at an adequately supported target as specified in 3.4.3. When fired, the fuze, projectile and charge shall be at a temperature of 70° ± 10°F. This may require temperature conditioning in accordance with 4.4.2. Observation of impact non-functioning is required and shall be noted on the ballistic records. If any fuze functions on target impact the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:38Z
Check the source to verify that this is the current version before use.

4.4.2 Temperature conditioning. The projectile with the fuze assembled to it, and the charge shall be placed in a temperature conditioning chamber. With the components in the chamber, start the test at ambient temperature. The chamber shall then be maintained at the desired temperature until a steady-state condition exists. After a steady-state temperature condition is reached, the components shall be saturated for twenty-four (24) hours minimum at that temperature.

5. PACKAGING

5.1 Packaging, packing and marking. Packaging, packing and marking shall be in accordance with the requirements and inspection procedures specified in MIL-P-60412.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use in Artillery Systems.

6.2 Ordering data. See MIL-A-48078 (PA).

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs, as requred to Commander, ARDC AMSMC-QAR-I (D), Dover, NJ 07801-5001.

6.4 Premature burst. A premature burst is a malfunction in which a fuze functions before safe separation. In the point detonating mode (PD), safe separation is defined by the minimum arming distance per 3.4.3. In the airburst mode, safe separation is defined by the equation t-(4+.06t) where t is the set time.

6.5 Functioning. A function is evidenced by the detonation of the specified projectile. A projectile which does not function as intended is termed a dud.

6.5.1 Airburst dud. An airburst dud is a fuzed projectile set to function in the airburst mode but does not function in air. This is independent of whether or not the projectile functions upon subsequent impact.

6.5.2 Target dud. A target dud is a fuze which does not function on impact when it is intended.

6.6 Proving ground test summary.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:38Z
Check the source to verify that this is the currentversion before use.

TEST	WEAPON/ TUBE	CHARGE	DISTANCE/ SETTING	SAMPLE	ACCEPT	REJECT
Non-Function	105MM/M103	7	150-5 FT.	10	0	1
Function	155MM/M1	1	820-5 FT.	10	1	2
Airburst	105MM/M103	7	25.0 SEC.	10	2	3

6.7 Subject term (key word) listing.

Fuze, Mechanical Time
Fuze, Artillery
Fuze, Mechanical Time and Point Detonating
Fuze, Projectile
Fuze, Artillery Projectile
Fuze, Ammunition
Fuze, Artillery Ammunition

Custodian:
Army-AR

Preparing Activity
Army AR

(Project 1390-A446)

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:38Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT RSCH DEV & ENGR CENTER
ATTN: AMSMC-QA
DOVER, NJ 07801 5001

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:38Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-70531	FUZE, MT, SQ, M582A1 LOADING, ASSEMBLING AND PACKING

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:38Z
Check the source to verify that this is the current version before use.