MILITARY SPECIFICATION

PRIMER, STAB, M97
LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification contains requirements not normally required by the drawings and provides quality assurance provisions for the loading, assembling and packing for one type of initiating device designated as Primer, Stab, M97.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitations for bids, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 — Ammunition and Special Weapons; General Specification for

MIL-I-45208 — Inspection Requirements; General Specification for

MIL-I-45607 — Inspection Equipment; Supply and Maintenance of

STANDARDS

MILITARY

MIL-STD-105D — Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-109 — Quality Assurance Terms and Definitions

MIL-STD-1235 — Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

ORDNANCE CORPS

7549153 — Box, Packing, Ammunition for Primer, Stab M26, M55 or T92 Assembly, Details and Packing

7549154 — Box, Set-up, Packing, Ammunition, Inner and Outer for Primers, Stab, M26, M55 or T92 Assembly, Details, Packing and Marking

8857266 — Primer, Stab, M97

PUBLICATIONS

ORDNANCE CORPS

IEL 8857266 — Index of Inspection Equipment Lists

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

3.2 Primer. The primer shall comply with all requirements specified on Drawing (dwg.) 8857266 and with all requirements specified in applicable specifications.

3.3 Moisture content of lead azide. The moisture content of the lead azide used in loading the primer, at the time of loading shall not exceed 0.50 percent.

3.4 Moisture content of primer mixture. The moisture content of the primer mixture used in loading the primer, at the time of loading shall not exceed 0.50 percent.

3.5 Waterproofness. The primer shall be waterproof as evidenced by normal functioning, as specified in 3.6, after being immersed in water maintained at 70° Fahrenheit (F.) plus or minus 10° F., at a depth of 2 inches minimum for not less than 48 hours. The test shall be performed as specified in 4.3.3.

3.6 Sensitivity and output. The primer shall function on the first attempt when tested as specified in 4.3.3.1 and shall cause perforation of the coined lead disc to a diameter of not less than 0.250 inch, minimum.

3.7 Workmanship. All parts shall be free of cracks, chips, dirt, grease, rust and other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions. The supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL–STD–109 in order to define terms used herein. The provisions of Specification MIL–A–2550 shall apply.

4.1.1 *Contractor quality assurance system.* The contractor shall provide and maintain an effective quality assurance system in compliance with the requirements of Specification MIL–I–45208. The contractor's quality assurance system shall contain a procedure for the reporting of critical defectives found during the course of his inspection and during inspection by the Government. Any critical defect encountered, unless annotated by an asterisk (*) to the right of the characteristic code number (see 6.2), will be reported within 48 hours. A monthly summary report covering those critical defects annotated by an asterisk will be furnished. The agencies to whom the reports will be furnished are identified in paragraph 6.5. The reports shall contain, as a minimum, the following information:

(a) Contractor and contract number.

(b) Number and revision date of specification.

(c) Characteristic code number.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

(d) Lot or serial number.

(e) Number of defectives found.

(f) Assignable cause or analysis of occurence.

(g) Corrective action taken or recommended.

When the corrective action is beyond the control of the contractor or the scope of the contract, the report shall contain the contractor's recommendation to the Government.

4.1.2 *Submission of product.* At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

(a) A statement that the lot complies with all quality assurance provisions of the approved current written description of the system.

(b) Number of units of product inspected.

(c) Results obtained for all inspection performed.

(d) Drawing, specification number and date, together with an identification and date of changes.

(e) Certificates of analyses on all material procured directly by the contractor when such material is controlled by Government specification referenced in any of the contractual documents.

(f) Number of items in the lot.

(g) Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.3 *Government verification.* Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be in accordance with Specification MIL-I-45208 and will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified 'critical" be accepted solely on the basis of the contractor's records.

4.2 Inspection provisions.

4.2.1 *Lot formation.* A lot shall consist of primers produced by one manufacturer in one unchanged process in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety performance or fit, as determined by the Government, shall not necessitate changing the lot number. Each lot shall contain—

(a) Parts bearing the same lot interfix number from one manufacturer.

(b) Primer mixture from one batch or blending of batches which results in homogeneity of all primer mixture used in loading the entire primer lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

(c) Lead azide from one batch or blending of batches which results in homogeneity of all lead azide used in loading the entire primer lot.

4.2.2 *Examinations.* Sampling plans and procedures for the following classifications of defects shall be in accordance with Standard MIL–STD–105 except that inspection for critical defects, when listed, shall be 100 percent. Continuous sampling plans in accordance with Standard MIL–STD–1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to the individual characteristics listed, using an AQL of 0.25 percent for each Major defect and an AQL of 0.40 percent for each Minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Assembly (see dwg. 8857266).

Categories	*Defects*	*Method of inspection*	*Code No. (see 6.2)*
Critical:			
1.	Cup cracked or split	Visual	01001*
2.	Explosive exposed or explosive on exterior	Visual	01002*
Major:	AQL 0.65 percent		
101.	Length	Gage	01003
102.	Diameter, minimum (min)	Gage	01004
103.	Not crimped full 360°	Visual	01005
104.	Lacquer coating incomplete	Visual	01006
105.	Disc punctured or torn	Visual	01007
Minor:	AQL 1.50 percent		
201.	Diameter, maximum (max)	Gage	01008
202.	Primer distorted	Visual	01009
203.	Evidence of poor workmanship (see 3.7)	Visual	01010

4.2.2.2 Box, set-up, inner (see dwg. 7549154).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical:	None defined.		
Major:	AQL 0.25 percent		
101.	Box damaged	Visual	02001
102.	Number of assemblies incorrect	Visual	02002
Minor:	AQL 1.00 percent		
201.	Marking misleading or unidentifiable	Visual	02003
202.	Any packing material missing	Visual	02004

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

4.2.2.3 Box, set-up, outer (see dwg. 7549154).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical:	None defined.		
Major:	AQL 0.25 percent		
101.	Number of inner set-up boxes incorrect	Visual	03001
102.	Sealing strip torn, badly wrinkled, incomplete or otherwise fails to seal the box completely	Visual	03002
Minor:	AQL 1.50 percent		
201.	Box torn, cut or punctured	Visual	03003
202.	Marking misleading or unidentifiable	Visual	03004
203.	Contents move when box is shaken	Manual	03005

4.2.2.4 Sealed barrier bag (see dwg. 7549154).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical:	None defined.		
Major:	AQL 0.25 percent		
101.	Seal missing, incomplete or incorrectly located	Visual	04001
102.	Bag punctured, torn or cut	Visual	04002
Minor:	None defined.		

4.2.2.5 Box, Packing, Ammunition (see dwg. 7549153).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical:	None defined.		
Major:	AQL 0.25 percent		
101.	Board broken or split	Visual	05001
102.	Strapping missing, broken or loose	Visual	05002
Minor:	AQL 1.50 percent		
201.	Marking misleading or unidentifiable	Visual	05003
202.	Strapping improperly assembled	Visual	05004
203.	Contents move when box is tilted	Manual	05005

4.2.3 Testing.

4.2.3.1 *Moisture content of lead azide (see 3.4) Code No. 06001, Major defect.* The moisture content of the lead azide shall be determined for each lot at the time of loading. A sample of 2 grams shall be selected and tested as specified in 4.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

If the moisture content is in excess of the percentage specified and loading has not begun, the lot of lead azide shall be rejected until proper corrective action has been accomplished as verified by repeating the moisture content test specified in 4.3.1. If loading has begun, action on the unloaded lead azide shall be as specified above and all primers loaded with the questionable lead azide shall be rejected.

4.2.3.2 *Moisture content of primer mixture (see 3.3) Code No. 07001, Major defect.* The moisture content of the primer mixture shall be determined for each lot at the time of loading. A sample of 0.7 gram shall be selected and tested as specified in 4.3.2.1. If the moisture content is in excess of the percentage specified and loading has not begun, the lot of primer mixture shall be rejected until proper corrective action has been accomplished as verified by repeating the moisture content test specified in 4.3.2.1. If loading has begun, action on the unloaded primer mixture shall be as specified above and all primers loaded with the questionable primer mixture shall be rejected.

4.2.3.3 *Composition of primer mixture (see dwg. 8857266) Major defect, Code No. 07002.* The composition of the primer mixture shall be determined for each lot at the time of loading. A sample of 0.5 gram shall be selected and tested as specified in 4.3.2.2. If the composition of the primer mixture fails to conform to the requirements specified on the applicable drawing and loading has not begun, the lot of primer mixture shall be rejected. If the loading has begun, primers loaded with the questionable primer mixture shall be rejected.

4.2.3.4 *Waterproofness (see 3.5)—Major defect, Code No. 05011.* A sample of 25 complete primers shall be selected from each lot for this test. The test shall be performed as specified in 4.3.3, using test equipment specified in 4.2.4. If one or more assemblies fail to comply with the specified requirement the lot shall be rejected and acceptance testing for the Government discontinued.

4.2.3.5 *Sensitivity (see 3.6)—Major defect Code No. 05012 and output (see 3.6)—Major defect Code No. 05013.* A sample of 300 primers shall be tested for sensitivity and output as specified in 4.3.3.1, using test equipment specified in 4.2.4. If one or more assemblies fail to comply with the specified requirements the lot shall be rejected and acceptance testing for the Government discontinued.

4.2.4 *Inspection equipment.* Index of Inspection Equipment Number IEL–8857266 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.2.4.1 *Government rights to documentation.* Inspection equipment drawings and lists provided and revised in accordance with the requirements of the IEL may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement of parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and wherever inspection equipment drawings are needed.

4.2.4.2 Supply and maintenance. Supply and maintenance of the equipment listed on the IEL shall be in accordance with Specification MIL–I–45607.

4.2.4.3 *Government use of contractor's inspection and test equipment.* The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

4.3 Test methods and procedures.

4.3.1 *Moisture content of lead azide.* A tared dried aluminum dish 2 inches in diameter shall be covered with a sheet of polytetrafluoroethylene 2½ inches square and sufficiently flat to form a tight cover. An accurately weighed portion of approximately two grams of the sample shall be transferred to an oven and dried at 95° Centigrade (C.) plus or minus 2° C., for 2 hours. The cover shall be placed in the sulfuric acid desiccator during the drying period. After drying, the dish shall be quickly transferred to the desiccator and allowed to cool to room temperature. The polytetrafluoroethylene cover shall be placed on the dish and the assembly weighed. The loss in weight shall be calculated to the percentage of moisture in the lead azide to determine compliance with 3.3 as follows:

$$\text{Percentage of moisture} = \frac{100\ (A-B)}{A}$$

where:

A = weight of the sample before drying

B = weight of the sample after drying

4.3.2 Primer mixture.

4.3.2.1 *Moisture content.* Transfer a known weight, 0.4 to 0.7 grams of the sample primer mixture to a tared weighing dish approximately 55 millimeters in diameter and 30 millimeters in height. Place the dish and contents in an oven maintained at 55° to 65° C., or in a desiccator containing anhydros calcium chloride until constant weight is obtained. Calculate the loss in weight as the percentage of moisture.

4.3.2.2 Composition.

4.3.2.2.1 *Barium nitrate.* Transfer an accurately weighed portion of approximately 0.5 gram of primer mixture to a tared medium porosity, fritted glass crucible of 20 milliliters capacity. Add 3 milliliters of lead azide saturated distilled water at a temperature of 5° plus or minus 2° C. Agitate for one minute, if necessary, breaking up any lumps with a rubber policement attached to a glass rod, and apply suction. Repeat this procedure five times, making a total of six, 3 milliliter extractions. Rinse the sample in a filtering crucible three times with alcohol, dry in an oven maintained at 60° plus or minus 5° C. for 30 minutes. Cool in a desiccator and weigh. Calculate the loss in weight as the percentage of barium nitrate in the sample on a dry basis as follows:

$$\text{Barium nitrate percent} = \frac{.01MW(A-B)\times 100}{W(1-.01M)}$$

where:

W = weight of the sample

M = moisture content of the sample, percent

A = weight of crucible and sample

B = weight of the crucible and sample after extractions with lead azide saturated water

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

4.3.2.2.2 *Basic lead styphnate.* Extract the residue obtained in the determination of barium nitrate with six 5 milliliter portions of saturated ammonium acetate solution at about 25° C., (agitating each portion for about 30 seconds and allowing each portion to remain in contact with the residue for approximately 2 minutes). Wash the residue with water until the filtrate coming through the crucible appears colorless. Transfer quantitatively the filtrate and washings to a 250 milliliter calibrated volumetric flask, washing the beaker thoroughly with distilled water and dilute to the mark. Using a calibrated pipette, transfer a 2 milliliter aliquot of this solution to a 50 milliliter calibrated volumetric flask and dilute to the mark with distilled water. Transfer a portion of this solution to a corex glass spectrophotometric cell having a width of approximately 1 centimeter (CM) and determine its optical density at a wavelength of 410 millimicrons. Use as reference a similar cell containing ammonium acetate solution of the same concentration as the sample solution. Since the cell which holds the basic lead styphnate is not identical with the reference cell, correct the optical density obtained as described above for the difference in the amount of light which the two cells scatter and absorb. To do this, fill both cells with ammonium acetate solution and measure at a wavelength of 410 millimicrons, the optical density of the cell which originally contained the basic lead styphnate solution. Calculate the percentage of basic lead styphnate in the sample on a dry basis as follows:

$$\text{basic lead styphnate, percent} = \frac{28(A-B)}{W(1-0.1M)D}$$

where:

A = optical density of basic lead styphnate solution

B = optical density of ammonium acetate solution

D = width of corex cell, CM

M = moisture content of sample, percent

W = weight of sample

Note. Hot saturated ammonium acetate shall not be used as it dissolves antimony sulfide to some extent.

4.3.2.2.3 *Tetracene.* Wash the wet residue obtained in the determination of basic lead styphnate three times with alcohol, dry in an oven maintained at 60° plus or minus 5° C. for 30 minutes, cool in a desiccator and weigh. Transfer the dried residue in the crucible to a 125 milliliter beaker with a stream of water, add 25 milliliters of water, and boil the contents of the beaker on a hotplate for 5 minutes. Pour the contents of the beaker into the same crucible, wash the residue in the crucible three times with boiling water, and finally with alcohol. Dry the crucible and contents in an oven maintained at 60° plus or minus 5° C. for 30 minutes, cool in a desiccator and weigh. Calculate the loss in weight as the percentage of tetracene in the sample on a dry basis as follows:

$$\text{Tetracene, percent} = \frac{(C-D)100}{W(1-.01M)}$$

where:

C = weight of crucible and residue after extraction with saturated ammonium acetate solution

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

D = weight of crucible and residue after treating with hot water

W = weight of sample

M = moisture content of sample, percent

4.3.2.2.4 *Antimony sulfide.* Calculate the weight of the residue from the determination of tetracene to percentage of antimony sulfide in the sample on a dry basis as follows:

$$\text{Antimony sulfide, percent} = \frac{(D-E)100}{W(1-.01M)}$$

where:

D = weight of crucible and sample after treating with hot water

E = weight of crucible

W = weight of sample

M = moisture content of sample, percent

4.3.2.2.5 *Lead azide.* Determine the lead azide content in the sample by subtracting from 100 the combined percentages of barium nitrate, basic lead styphnate, tetracene and antimony sulfide.

4.3.3 *Waterproofness.* The primer shall be immersed in water at a depth of 2 inches with the water temperature maintained at 70° plus or minus 10° F. for not less than 48 hours. Within one hour after removal from the water the primers shall be subjected to the following test.

4.3.3.1 *Sensitivity and output.* The primer shall be assembled to the applicable test fixture specified in 4.2.4 and functioned by dropping a steel ball 0.75 inch in diameter and weighing one ounce, maximum from a height of 3.5 inch, maximum on the firing pin to function the primer. The height of drop shall be measured as the height from the top of the firing pin to the bottom of the ball. A primer which fails to fire or fails to create a hole of the required size in the lead disc shall be classed defective.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 *Level C.* Preservation and packaging shall be in accordance with dwg. 7549154.

5.2 Packing.

5.2.1 *Level C.* Packing shall be in accordance with dwg. 7549153.

5.3 Marking. Marking of all packaging and packing shall be in accordance with dwgs. 7549153 and 7549154.

5.4 Data cards. Data cards shall be prepared for each lot in accordance with the information specified in Specification MIL-A-2550.

6. NOTES

6.1 Ordering data. Procurement documents shall specify the following:

Title, number and date of this specification.

6.2 Inspection code numbers. The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment. The contractor shall design inspection equipment as required by the referenced Inspection Equipment Lists (IEL) in accordance with the instructions of 6.3.1 through 6.3.7.

6.3.1 *Inspection equipment lists.* Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (00 Form 1242-3) the numbers of drawings of existing equipment designs or codes as indicated in 6.3.2. Design action required of the contractor with respect to the different types of drawings that may be listed is described in 6.3.3 and 6.3.4. Action required by the contractor with respect to commercial inspection equipment is described in 6.3.5. The con-

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:04Z
Check the source to verify that this is the currentversion before use.

tractor will be required to prepare detailed drawings in accordance with 6.3.6 for all the equipment coded as "contractor design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.2 *Inspection equipment list codes.* The inspection equipment as defined in 6.3.3, 6.3.4, 6.3.5, and 6.3.6 will be designated in the inspection equipment list by the following codes:

CDOF — Contractor's design responsibility on Ordnance format; ORDM–608–12.

CDCF — Contractor's design responsibility on contractor format.

OD — Ordnance design.

ODMU — Ordnance design, mandatory for use.

CE — Commercial equipment.

SCD — Specification Control Drawing.

6.3.3 *Ordnance designs.* Ordnance designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Ordnance design is listed for an item of inspection equipment. Ordnance designs fall into two basic classifications; mandatory and nonmandatory. When an inspection equipment list references mandatory Ordnance designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with nonmandatory designs and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.4 *Specification control drawings.* Specification control drawings depict the minimum equipment requirements in outline, descriptive, diagrammatic, or pictorial form only and specify the required performance or other characteristics. Contractors must prepare detailed drawings (see 6.3.6) of their designs in support of specification control drawings. These contractor prepared designs must be approved by the Government prior to the fabrication or procuring of the equipment. Commercial equipment meeting the requirements of specification control drawings may be approved if described in sufficient detail to permit identification and evaluation by the Government. Designs shall be submitted for approval as specified in 6.3.7.

6.3.5 *Commercial equipment.* Commercial equipment is inspection equipment that has universal application for a specific function. It is comprised of items commonly used by industry and government. Contractors are not required to furnish drawings of commercial inspection equipment but a list of such equipment must be approved by the Government. Lists shall be submitted for approval to the inspection element of the agency administering the contract.

6.3.6 *Contractor designs.* Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Contractor designs identified as CDCF may be developed on the format the

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:04Z
Check the source to verify that this is the currentversion before use.

contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above. Contractor designs identified as CDOF shall comply with the format and requirements of ORDM 608–12, and, in addition, contain the detail and information specified above.

6.3.7 *Submission of contractor designs.* Designs shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND. Design review will normally be accomplished within one month after receipt by Picatinny Arsenal. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs.

6.4 Check test for possible deterioration. The following test is designed to prevent the loading of primers which have deteriorated into a major ammunition item. The test should be performed on primers from each lot which have been stored under normal conditions for more than 2 years, or under adverse conditions for any period of time. If the specification for the ammunition item into which the primers are loaded does not require that the check test be performed, the contracting officer should insert a provision for the performance of the check test in the contract. The contracting officer shall arrange to have the contractor reimbursed for any expense incurred in the performance of the check test for possible deterioration.

6.4.1 *Sensitivity and output.* A sample of 300 primers shall be selected from each lot for this test. The test shall be performed as specified in 4.3.3.1, using test equipment specified in 4.2.4. If 3 or more primers fail to comply with the specified requirement the lot shall be rejected.

6.5 Submission of critical defect reports. For U.S. Army Munitions Command procurements, one copy of each critical defect report will be furnished the cognizant Government inspection agency; the Army Ammunition Procurement and Supply Agency, ATTN: SMUPA-RO; Picatinny Arsenal, ATTN: SMUPA-ND.

6.5.1 *Reporting to other services.* For other than U.S. Army Munitions Command procurements, critical defect reporting shall be as prescribed by the contracting officer.

Custodian:

Army—MU

Preparing activity:

Army—MU

Project No. 1375–A689

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:04Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDING OFFICER
PICATINNY ARSENAL
ATTN: SMUPA-DC 7
DOVER, NEW JERSEY

FOLD

PLATE NO. 15419 (BAC)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity (as indicated on reverse hereof).

SPECIFICATION

ORGANIZATION (Of submitter) | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)

SUBMITTED BY (Printed or typed name and activity) | DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE PLATE NO. 1541

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.