MIL-R-45804D

9 September 1975
SUPERSEDING
MIL-R-45804C
17 February 1967
(See Section 6)

MILITARY SPECIFICATION

ROLLS, TOOLS AND ACCESSORIES:

GENERAL SPECIFICATION FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers cotton duck tool rolls of various sizes with pockets for holding tools and tie tapes or straps to secure the roll in a closed position.

* 1.2 Classification. The tool rolls shall be of the sizes specified on the specification sheets (see 6.2).

2. APPLICABLE DOCUMENTS

* 2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

V-T-285	-	Thread, Polyester
FF-R-556	-	Rivet, Solid, Small; Rivet, Split, Small; Rivet Tubular, Small; Burr; and Cap, Rivet; General Purpose
KK-L-271	-	Leather, Cattlehide, Strap, Vegetable-Tanned
CCC-C-419	-	Cloth, Duck, Cotton, Unbleached, Plied-Yarns, Army and Numbered
CCC-D-950	-	Dyeing and Aftertreating Processes for Cotton Cloths
DDD-L-20	-	Label; For Clothing, Equipage and Tentage (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard

FSC 5140

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:53Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-C-496 - Clips, End, Strap
MIL-W-530 - Webbing And Tape, Textile, Cotton, General Purpose, Natural Or In Colors
MIL-B-543 - Buckles, Tongueless And Web Strap
MIL-R-2583 - Rivets, Solid, Belt; And Washers, Flat (Burrs)
MIL-F-10884 - Fasteners, Snap
MIL-T-43566 - Tape, Textile, Cotton, General Purpose, Natural or In Colors

(See supplement 1 for list of associated specification sheets.)

STANDARDS

FEDERAL

FED-STD-123 - Marking for Domestic Shipment (Civil Agencies)
FED-STD-751 - Stitches, Seams and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures And Tables For Inspection By Attributes
MIL-STD-129 - Marking For Shipment And Storage
MIL-STD-130 - Identification Marking Of U. S. Military Property

DRAWINGS

ARMY NATICK DEVELOPMENT CENTER

5-7-20 - Rolls, Tools And Accessories; Size-19 - Illustration and Details
5-7-21 - Rolls, Tools and Accessories; Size-19 - Details
5-7-51 - Rolls, Tools and Accessories; Size-18 - Illustrations and Sections
5-7-52 - Rolls, Tools and Accessories; Size-18 - Body and Pocket Details
5-7-53 - Rolls, Tools and Accessories; Size-18 - Pocket Details, Scabbards and Sections
5-7-116 - Rolls, Tools and Accessories; Size-1
5-7-121 - Rolls, Tools and Accessories; Size-6
5-7-124 - Rolls, Tools and Accessories; Size-9
5-7-126 - Rolls, Tools and Accessories; Size-11
5-7-127 - Rolls, Tools and Accessories: Size-12
5-7-128 - Rolls, Tools and Accessories; Size-13
5-7-129 - Rolls, Tools and Accessories; Size-14 - Assembly and Sections
5-7-130 - Rolls, Tools and Accessories; Size-14 - Details
5-7-131 - Rolls, Tools and Accessories: Size-15
5-7-132 - Rolls, Tools and Accessories; Size-16
5-7-133 - Rolls, Tools and Accessories; Size-17
5-7-159 - Rolls, Tools and Accessories; Size-20

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:53Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 3. REQUIREMENTS

3.1 Specification sheets. The individual item requirements shall be as specified herein and in accordance with the applicable specification sheets.

3.2 First article. When specified, the supplier shall furnish a sample for first article inspection and approval (see 4.2, 6.2, and 6.3).

3.3 Material.

3.3.1 Cloth, duck, cotton. The cloth, before finishing, shall conform to type I of CCC-C-419 in the numbered duck and texture as follows:

For roll sizes 1, 6, 9 13, 15, 16, 17 and 20	No. 10, hard texture
For roll size 11	No. 6, hard texture
For roll size 12	No. 6, medium texture
For roll size 14	No. 4, medium texture
For roll sizes 18 and 19	No. 4, hard texture

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:53Z
Check the source to verify that this is the current version before use.

3.3.1.1 Color and treatment. The cloth shall be finished to conform to type I, class B of CCC-D-950 and shall be dyed to match olive drab shade No. 7.

3.3.2 Tape, textile, cotton. The tape shall conform to type I, class 4, 3/4 and 1 inch widths of MIL-T-43566 and shall be dyed to match olive drab shade No. 7.

3.3.3 Webbing, textile, cotton. The webbing shall conform to type IIb, class 4, 5/8 and 1 inch widths of MIL-W-530, and shall be dyed to match olive drab shade No. 7.

3.3.4 Thread, polyester. The thread for all stitching shall conform to type I or II, class 1, size FF of V-T-285. The thread shall be dyed shade S-1 (Cable No. 66022) and shall show fastness to chlorine bleaching equal to or better than the standard shade sample (see 6.4). If no standard shade sample is available, the thread shall show good fastness to chlorine bleaching.

3.3.5 Leather, cattlehide. The leather shall conform to type I, II, III or IV, class 1, 6/64-inch thick, russet in color of KK-L-271, except that the crocking requirement shall not apply.

3.3.6 Buckle, single bar, with lip. The buckles shall conform to type IV, class 1 or 3, and sizes 5/8 and 1 inch of MIL-B-543.

3.3.7 Clips, end. The end clips shall conform to type I, class 1, sizes 5/8 and 1 inch of MIL-C-496.

3.3.8 Fasteners, snap. The snap fasteners shall conform to style 2, finish 2, button 24 line size, size 1 of MIL-F-10884.

* 3.3.9 Rivets. The solid belt rivets with burrs shall conform to type I, class 2, grade A or F, size No. 6 of FF-R-556. The length shall be such as to insure a secure clinch.

3.4 Construction. The construction shall conform in all respects to the drawings listed in section 2 and as specified herein.

3.4.1 Stitching. All stitching, except bartacking, shall conform to type 301, 6 to 8 stitches per inch of FED-STD-751. Thread breaks in stitching shall be overstitched not less than 1 inch at each break. Stitching ends shall be overstitched not less than 1 inch except where ends are turned under in a hem, held down by other stitching, or where stitching is performed automatically. When stitch patterns such as box, box with cross-stitch, "W" stitching or straight line tacking are performed automatically, at least three or more tying, overlapping or backstitches shall be used to secure the ends of stitching.

3.4.1.1 Bartacking shall be 5/8 inch $\pm$ 1/16 inch in length with 1/8 inch bight and shall contain 28 stitches. Bartacking shall be free of thread breaks and loose stitching.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:53Z
Check the source to verify that this is the current version before use.

3.4.1.2 Skipped stitches. Two or more skipped stitches shall be overstitched not less than 1 inch on each side of the defective area. Skipped stitches noted during inspection shall be repaired as directed for thread breaks.

3.4.2 Setting of end clips. The webbing shall be inserted the full depth of the clip. The clips shall be securely attached without cutting the webbing and the webbing shall be flat at the point of entrance.

3.4.3 Setting of snap fasteners. A hole shall be punched prior to inserting the male or female part of the snap fastener, it shall be smaller than the outside diameter of the fastener tube so that the tube must be forced through the hole. The fasteners shall be securely clinched without cutting the material.

3.4.4 Setting of rivets. Rivets shall be securely set and neatly headed.

3.5 Marking.

3.5.1 Identification. Identification marking conforming to type IV, class 5 of DDD-L-20 shall be located on all size rolls in such a manner as to be clearly visible when roll is in a closed condition.

3.5.2 Pocket and content. The pocket and content marking, where required shall be as specified in the applicable specification sheet.

3.6 Workmanship. Cloth components shall be clean and free of holes, cuts, tears or cloth defects such as smashes, weak places, broken or missing yarns. Webbing and tape shall contain no frayed or scalloped edges. Thread tension shall be maintained so that there will be no loose stitching and seam allowances shall be maintained with seams properly sewed so that no runoffs, pleats, twists, puckers or open seams shall result. Care shall be taken in sewing so that there shall be no needle chews. All thread ends shall be trimmed. Metal components shall be free of burrs, sharp edges and corroded areas, and shall not be broken or malformed.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:53Z
Check the source to verify that this is the current version before use.

* 4.2 First article inspection. When required (see 6.2), examination of the first article shall made of a completely fabricated roll for all end item inspection provisions of this specification.

4.3 Inspection. Sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105, unless otherwise indicated hereinafter.

* 4.3.1 Component and material inspection. In accordance with 4.1, above components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

* 4.3.2 In-process inspection. Examination shall be made of the following operations to establish conformance to specified requirements. Whenever nonconformance is noted, correction shall be made to the items affected and to the operation.

a. Cut dimensions of tape, webbing, and pocket pieces are as specified
b. Location of stitching of pocket pieces are as specified
c. Holes for snap fastener installation shall be prepunched conforming to size requirement (see 3.4.3).

4.3.3 End product inspection. The lot shall consist of all completely fabricated rolls of one type offered for inspection at one time. The sample unit shall be one completely fabricated roll. The inspection levels and acceptable quality levels (AQL's) shall be as specified in 4.3.3.3.

* 4.3.3.1 Visual examination. Visual examination shall be made of the completely fabricated roll for the defects in table I.

TABLE I. Classification of defects for visual characteristics

Examine	Defect	Classification Major	Minor A	Minor B
Fabric	Any smash, weak place, broken or missing yarns, multiple floats or open place clearly visible at normal inspection distance (approximately 3 feet)	X		
	Shade bar or fine or coarse filling bar		X	
	Hole (except drill hole), cut, or tear	X		
	Exposed drill hole; i.e., not covered by attached parts			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:53Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects for visual characteristics (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Webbing	Edge frayed or scalloped	X		
Hardware	Broken	X		
	Malformed - fails to perform intended function	X		
	Malformed - but will perform intended function		X	
	Corroded area			X
	Burr or sharp edge	X		
End clips	Not securely clinched; webbing not flat at point of insertion			X
	Clinched excessively tight, cutting webbing		X	
Snap fasteners	Any fastener not functioning properly; i.e., fails to snap closed, provide a secure closure, or to open freely	X		
	Improper or insecure clinching	X		
	Clinched excessively tight, cutting surrounding material	X		
	Clinched loosely, permitting components to rotate freely in the hole of the material	X		
	Incorrect style	X		
	NOTE: Incomplete roll of the end of the button or eyelet tube is evidence of improper and insecure clinching. Fasteners evidencing incomplete roll will separate in use.			
	NOTE: Fasteners shall be snapped and unsnapped twice to determine weather parts of fastener separate freely and also affect a secure closure.			
Rivets	Insecurely clinched so that rivets may become disengaged		X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:53Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects for visual characteristics (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Seams and stitching	Open seams on stitch type 301:			
	- 1/2 inch or less			X
	- more than 1/2 inch, but not more than 1 inch		X	
	- more than 1 inch	X		
	Run-offs (see open seams)			
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped stitches or run-offs occur. On double stitched seams, a seam shall be considered open when either one or both sides of the seam are open.			
	Any raw edge			X
	NOTE: Raw edges not securely caught in stitching shall be classified as open seams.			
	Thread breaks:			
	- overstitched less than 1 inch			X
	NOTE: Thread breaks not overstitched shall be classified as open seams.			
	Skipped stitches:			
	- not overstitched as specified			X
	NOTE: Skipped stitches not overstitched shall be classified as open seams.			
	Needle chews		X	
Seam and stitch type	Wrong seam or stitch type	X		
Stitch tension	Loose, resulting in a loosely exposed top or bobbin thread			X
	Tight, resulting in excessive tightness or puckering of fabric		X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:53Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects for visual characteristics (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Stitches per inch	One stitch less than minimum specified		X	
	Two or more stitches less than minimum specified	X		
	One or more stitches in excess of minimum specified			X
	NOTE: Variation in the number of stitches per inch, caused by the operator's speeding up the machine and pulling the fabric in order to sew over heavy seams or heavy places or in turning corners shall be classified as follows: a. Within the minor "A" defect classification - minor "B" defect b. Within the minor "B" defect classification - no defect			
Stitching margin	Not as specified			X
Stitching ends	Overstitched less than 1 inch (except where ends are held down by other stitching, turned under in a hem or where stitching is performed automatically)			X
	Secured with less than three tying, overlapping or backstitches when automatic stitching is performed			X
Box stitching	Incomplete:			
	- one end row of stitching omitted		X	
	- two end rows of stitching omitted	X		
	- any other row of stitching omitted	X		
Seams	Badly pleated or puckered		X	
Hems	Twisted or pleated			X
	Constructed with a partial turnunder when a double turnunder is required	X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:53Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects for visual characteristics (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Reinforcements	Improperly applied, causing excessive fullness or reinforcements or reinforced parts			X
	Not stitched to reinforced parts on all sides or not caught in seams or stitching of reinforced parts, single ply construction when double ply is required		X	
Components and assembly	Any component or required operation omitted (unless otherwise classified)	X		
	Any part or component not fabricated of applicable referenced material	X		
Markings; Identification	Omitted, incorrect, illegible, or misplaced, or size characters not as specified			X
Pocket and content (when applicable)	Omitted, incorrect, incompleted or otherwise not as specified			X
Cleanness	Grease or oil stains; thread ends not trimmed throughout			X

4.3.3.2 Dimensional examination. Overall dimensions of the roll not within the specified tolerances shall be classified as a defect. Location and component dimensions over or under specified dimensions by more than 1/2 inch shall be classified as a defect.

4.3.3.3 Inspection levels and AQL's. The inspection levels and AQL's, expressed in terms of defects per hundred units, shall be as follows:

Examination	Inspection level	AQL's
For defects applicable to 4.3.3.1	II	2.5 Major 6.5 Major and minor A defects 15.0 Totals
For defects applicable to 4.3.3.2	S-3	4.0 (one class)

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:53Z
Check the source to verify that this is the currentversion before use.

4.3.4 Inspection of preparation for delivery requirement. An inspection shall be made to determine that packaging and packing and marking requirements are in compliance with section 5. Defects shall be as listed in table II. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. Defects of closure listed below shall be inspected on shipping containers fully prepared for delivery. The lot shall be the number of shipping containers offered for inspection at one time. The inspection level shall be S-2 with an AQL of 2.5, expressed in terms of defects per hundred units.

TABLE II. Inspection of preparation for delivery

Examine	Defect
Marking	Omitted, incorrect, illegible, or improper size, location, sequence or method of application
Materials	Any component missing or damaged
Contents	Number per container not as required
Weight	Net weight of contents exceed requirements

4.3.4.1 Inspection of shipping containers. When shipping containers are required to be in accordance with PPP-B-636, inspection for defects in closure, waterproofing and reinforcing shall be in accordance with the appendix of the container specification.

* 5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. Each roll shall be folded or rolled and buckled or tied, as applicable.

* 5.1.2 Level C. Rolls shall be packaged to afford adequate protection against damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

* 5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

* 5.2.1 Level A. Rolls, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V3s or V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CT, class weather-resistant, variety DW, grade V15c of PPP-B-636. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of the container specification. The weight of contents of each V3s or V2s shipping container shall not exceed 40 pounds and 65 pounds, respectively.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:53Z
Check the source to verify that this is the current version before use.

* 5.2.2 Level B. Rolls, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF, variety SW, or type SF, class domestic, of PPP-B-636. When specified (see 6.2), the inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 200 of PPP-B-636. Closure shall be in accordance with method II of the appendix of PPP-B-636. The weight of contents of each shipping container shall not exceed 65 pounds. When specified (see 6.2), the shipping container shall be V3c, V3s, or V4s fabricated and closed in accordance with PPP-B-636.

5.2.3 Level C. Rolls, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

* 5.3 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with FED-STD-123 or MIL-STD-129 as applicable.

6. NOTES

6.1 Intended use. The tool rolls covered by this specification are used to contain various tool sets and to protect these tools from damage and the elements when not in use.

* 6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification and applicable specification sheet (see 1.2).
(b) When first article is required (see 3.2, 4.2 and 6.3).
(c) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
(d) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2).
(e) When box liners are required for level B packing (see 5.2.2).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of ASPR 7-104.55. The first article should be a preproduction sample, initial production item or other specific item described under the definition of a first article in the ASPR. The contracting officer should specify the appropriate type of first article and the number of units to be furnished and should include specific instructions in all procurement instruments, regarding arrangements for inspection and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:53Z
Check the source to verify that this is the current version before use.

* 6.4 For access to a standard shade sample of thread, address the Defense Personnel Support Center, Philadelphia, PA 19101.

* 6.5 Supersession and deletion data. Specification sheets MIL-R-45804/1 thru MIL-R-45804/12 cover sizes 1, 6, 9 and 11 thru 19 as specified in MIL-R-45804C, MIL-R-45804/13 covers size 20 as specified in GGG-R-615.

* 6.6 The margins of this document have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Air Force - 84

Review activities:

Army - WC, MD

User activities:

Army - EL, ME

Preparing activity:

Army - GL

Project No. 5140-0061

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:53Z
Check the source to verify that this is the current version before use.

SPECIFIED MIL *:8:66:

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL	OMB Approval No. 22-R255

INSTRUCTIONS. The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-R-45804D - ROLLS, TOOLS AND ACCESSORIES; GENERAL SPECIFICATION FOR

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:53Z
Check the source to verify that this is the current version before use.

o in accordance with the applicable cost basis maximum rates for