[INCH-POUND]
A-A-51123B
December 4, 1996
SUPERSEDING
A-A-51123A
January 27, 1988

COMMERCIAL ITEM DESCRIPTION

VISES, MACHINE TABLE, BENCH AND MACHINE TABLE

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE

1.1 Scope. This commercial item description (CID) covers heavy, duty bench and machine table vises.

1.2 Intended use. Bench and machine table vises covered by this CID are intended for use in a production environment.

2. CLASSIFICATION

2.1 Classification. Vises shall be of the following types and sizes listed in tables I through IV. The type and size to be furnished shall be as specified (see 7.2).

Type: Type I - Machine table, toolmaker's vise (table I).
Type II - Machine table, drill press vise (table II).
Type III - Machine table, quick-action vise (table III).
Type IV - Machine table and bench mounting vise with swivel base (table IV).

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: Defense Supply Center Richmond, ATTN: DSCR-VBD, 8000 Jefferson Davis Highway, Richmond, VA 23297-5610.

AMSC N/A FSC 3460
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

TABLE I. Type I, machine table, toolmaker's vise.

Size	Jaw width (in.)	Jaw depth (in.)	Jaw opening (in.)
1	1-1/2	1	1-5/8
2	2-3/8	1-1/2	2-1/4
3	2-1/2	1-1/2	2-1/8
4	3	1-1/4	3
5	4	1-3/4	4

TABLE II. Type II, machine table, drill press vise.

Size	Jaw width (in.)	Jaw depth (in.)	Jaw opening (in.)
1	1-1/2	1	1-1/2
2	3	1-1/2	3
3	3	1-1/2	4
4	4	1-3/4	4-1/2
5	6	2	6

TABLE III. Type III, machine table, quick-action vise.

Size	Jaw width (in.)	Jaw depth (in.)	Jaw opening (in.)
1	3	1-1/2	3
2	4	1-1/2	4-3/4
3	6	2	6
4	8	3	10

TABLE IV. Type IV, machine table and bench mounting vise.

Size	Jaw width (in.)	Jaw depth (in.)	Jaw opening (in.)
1	2-7/16	1-1/2	2-1/2
2	4	1-1/4	4
3	6	2	6
4	8	2	7-1/2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

3. SALIENT CHARACTERISTICS

3.1 General requirements. The vise shall be new and one of the manufacturer's standard commercial designs. The vise shall consist of a body with a fixed jaw, a sliding jaw and a vise screw with a handle. The vise body, fixed jaw and sliding jaw shall be of cast iron or steel. The vise screw shall be of screw stock having not less than 60,000 pounds per square inch (psi) yield strength and not less than 70,000 psi tensile strength. All parts shall be free of defects and blemishes which may effect the serviceability and appearance of the vise. All surfaces shall be smooth and free of sharp edges.

3.2 Type I, machine table, toolmaker's vise. The two sides of a type I vise shall be parallel to each other and parallel to the inside surface of the body jaw to within 0.0002 in. The two sides shall be square with the inside of the slide surface bottom and back of the body jaw.

3.3 Type II, machine table, drill press vise. Unless otherwise specified (see 7.2), the base of the body of a type II vise shall contain a minimum of two bolt slots for mounting purposes.

3.4 Type III, machine table, quick-action vise. The body of a type III vise shall have a slot with serrations or a taper for the attachment of a nut to provide for quick action in opening and closing the vise jaws. Unless otherwise specified (see 7.2), the base of the body of a type III vise shall contain a minimum of two bolt slots for mounting purposes.

3.5 Type IV, machine table and bench mounting vise with swivel base. The type IV vise shall be provided with a detachable, bench mounted, swivel base. The swivel base shall rotate not less than 360 degrees in a plane parallel to the mounting surface. Unless otherwise specified (see 7.2), the swivel base shall contain a minimum of two bolt slots for mounting purposes. If required (see 7.2), the swivel base shall have graduated markings in inch-pound or dual (inch-pound and metric) units 360 degrees in a plane parallel to the mounting surface.

4. REGULATORY REQUIREMENTS

4.1 Recycled, recovered, or environmentally preferable materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Environmental protection. The item shall meet all applicable Environmental Protection Agency restrictions in effect on the date of the contract. These regulations apply to the emission of materials hazardous to the environment or the user's health and shall be met during the manufacturing, service, transportation, storage, and operation/use of the item.

5. QUALITY ASSURANCE PROVISIONS

5.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

6. PACKAGING

6.1 Packaging requirements. Preservation, packaging, packing and marking shall be as specified (see 7.2).

7. NOTES

7.1 Source of documents.

7.1.1 Government documents. Copies of Military and Federal documents may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

7.2 Ordering data. Acquisition documents must specify the following:

a. Title, number, and date of this document.
b. Type and size required (see 2.1).
c. Mounting bolt slots, if different (see 3.3, 3.4 and 3.5).
d. Graduated markings, if required (see 3.5).
e. Packaging requirements, if different (see 6.1).

7.3 Part identification number (PIN). The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.

AA51123 - XX

- Size: (See Tables I, II, III, or IV.)
- Type:
  - A - Type I (Machine table, toolmaker's vise)
  - B - Type II (Machine table, drill press vise)
  - C - Type III (Machine table, quick-action vise)
  - D - Type IV (Machine table/bench mounting vise w/swivel base)
- CID number

MILITARY INTERESTS:

Custodians
Army - AL
Air Force - 99

Reviewers
Air Force - 84

PREPARING ACTIVITY:
DLA-GS

(Project 3460-0173)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.