A-A-51124
22 June 1984

COMMERCIAL ITEM DESCRIPTION

ADAPTER, DRILL CHUCK, MOTOR SHAFT

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification GGG-C-350b.

This description covers motor shaft adapters with a straight hole suitable for mounting a drill chuck onto a motor shaft. One adapter end will have a straight shaft, the opposite adapter end is tapered to conform to the tapered mount hole of the chuck for which it is procured.

Salient characteristics.

Size. The size of adapters covered by this description shall be as listed below. The size adapter to be furnished under a specific procurement shall be as specified in the contract or order.

Size 1	-	1/2 inch hole diameter	-	2 Jacobs taper
Size 2	-	1/2 inch hole diameter	-	3 Jacobs taper
Size 3	-	1/2 inch hole diameter	-	6 Jacobs taper
Size 4	-	1/2 inch hole diameter	-	33 Jacobs taper

Material. All adapters shall be made from a high grade steel and shall be soft throughout.

Set screw. The adapter shall contain a headless set screw to secure the adapter upon the motor shaft.

Markings. Each adapter shall be permanently marked with the manufacturer's name, model number, shaft hole diameter, and taper number.

Finish. Surfaces shall be smoothly ground, free from wheel and chatter marks, or other imperfections which may affect their accuracy, appearance, or serviceability.

Concentricity. Each adapter shall be ground concentric within 0.001 inch total indicator reading.

FSC 3460

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

Measurement system. All dimensions in this commercial item description are given in the English system of measurement. These dimensions can be converted to Metric system of equivalents by the use of ANSI/IEEE 268 for Department of Defense use or FED-STD-376 for Civil Agency use.

Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any inspections set forth in this CID where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Acceptance inspection. The supplier shall randomly select the number of samples specified in table I that is applicable to the quantity of items being pruchased. Each sample shall be visually inspected, measured, and tested, by the supplier, to determine conformance with the salient characteristics specified herein. Any sample failing to meet these requirements shall be considered a defective item. If the number of defective items equals, or is less than the quantity specified under "Acceptance, number defective" column in table I, the supplier shall replace the defective samples with acceptable items and the entire lot shall be considered acceptable for shipment. If the number of defective samples equals or exceeds the quantity specified in the "Rejection, number defective" column of table I, the entire lot shall be considered defective and unsuitable for acceptance.

TABLE I. Sampling plan.

Quantity of items being purchased	Sample size	Acceptance, number defective	Rejection, number defective
2 to 8	2	0	1
9 to 15	3	0	1
16 to 25	5	0	1
26 to 50	8	0	1
51 to 90	13	1	2
91 to 150	20	2	3
151 to 280	32	3	4
281 to 500	50	5	6

Concentricity test. Each of the sample adapters selected in accordance with table I shall be checked for concentricity specified herein.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:51Z
Check the source to verify that this is the current version before use.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practical.

Preservation, packaging, packing, labeling and marking. Unless otherwise specified in the contract or order, preservation, packaging, packing, labeling and marking shall be in accordance with ASTM D-3951. When specified in the contract or order, preservation, packaging, packing, labeling and marking shall be in accordance with Federal Specification PPP-T-1150, level as specified.

Notes. Purchaser should specify the quantity and size adapters required for specific procurements.

MILITARY INTEREST:

Custodians
Army - AL
Air Force - 99

Review activities
Air Force - 84
DLA - GS, DH

User activity
Navy - YD

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY

DLA - IP

Project Number 3460-0109

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.